

RENSHAPE® HIGH PERFORMANCE SEALER US

Version 1.0 Revision Date: 05/07/2015 MSDS Number: 400001009031

GHS Label element

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H225 Highly flammable liquid and vapour.
 H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H360 May damage fertility or the unborn child.
 H370 Causes damage to organs (Central nervous system, Liver, Kidney, Bladder, Cardio-vascular system, Nervous system, optic nerve, spleen).
 H372 Causes damage to organs (Central nervous system, Eyes) through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ eye protection/ face protection.
 P281 Use personal protective equipment as required.
Response:
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
 P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304 + P340 + P311 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

RENSHAP[®] HIGH PERFORMANCE SEALER US

Version Revision Date: MSDS Number:
1.0 05/07/2015 400001009031

to do. Continue rinsing.
P307 + P311 IF exposed: Call a POISON CENTER or doctor/physician.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute oral toxicity: 12 %

The following percentage of the mixture consists of ingredient(s) with unknown acute dermal toxicity: 12 %

The following percentage of the mixture consists of ingredient(s) with unknown acute inhalation toxicity: 12 %

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 12 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Methanol	67-56-1	30 - 60
Benzene, methyl-	108-88-3	13 - 30
Solvent naphtha (petroleum), light aliph.	64742-89-8	13 - 30
2-Propanol, 1-butoxy-	5131-66-8	3 - 7

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
Consult a physician.

If inhaled : Consult a physician after significant exposure.
If unconscious place in recovery position and seek medical advice.



RENSHAPE® HIGH PERFORMANCE SEALER US

Version	Revision Date:	MSDS Number:
1.0	05/07/2015	400001009031

- | | | |
|---|---|--|
| In case of skin contact | : | If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : | Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : | Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |
| Most important symptoms and effects, both acute and delayed | : | None known. |

SECTION 5. FIRE-FIGHTING MEASURES

- | | | |
|--|---|---|
| Suitable extinguishing media | : | No data is available on the product itself. |
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during fire fighting | : | Do not allow run-off from fire fighting to enter drains or water courses.

Do not use a solid water stream as it may scatter and spread fire.
Cool closed containers exposed to fire with water spray. |
| Hazardous combustion products | : | No data is available on the product itself.

No data is available on the product itself. |
| Specific extinguishing methods | : | No data is available on the product itself. |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for fire-fighters | : | Wear self-contained breathing apparatus for firefighting if necessary.

In the event of fire, wear self-contained breathing apparatus. |



RENSHAPE® HIGH PERFORMANCE SEALER US

Version	Revision Date:	MSDS Number:
1.0	05/07/2015	400001009031

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.
Ensure adequate ventilation. |
| Environmental precautions | : | Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : | Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal. |

SECTION 7. HANDLING AND STORAGE

- | | | |
|---|---|---|
| Advice on protection against fire and explosion | : | Normal measures for preventive fire protection.

Keep away from heat and sources of ignition. |
| Advice on safe handling | : | Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Keep away from heat. |
| Conditions for safe storage | : | Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards. |
| Materials to avoid | : | Strong acids

Strong bases

Strong oxidizing agents |

RENSHAPE® HIGH PERFORMANCE SEALER US

Version Revision Date: MSDS Number:
1.0 05/07/2015 400001009031

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		STEL	250 ppm 325 mg/m3	OSHA P0
Benzene, methyl-	108-88-3	TWA	200 ppm 260 mg/m3	OSHA P0
		TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
Solvent naphtha (petroleum), light aliph.	64742-89-8	Peak	500 ppm	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0

Personal protective equipment

Respiratory protection : In the case of vapor formation use a respirator with an approved filter.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Solvent-resistant gloves (butyl-rubber)
Nitrile rubber
10 - 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

RENSHAPE® HIGH PERFORMANCE SEALER US

Version	Revision Date:	MSDS Number:
1.0	05/07/2015	400001009031

- Wear face-shield and protective suit for abnormal processing problems.
Safety glasses
Ensure that eyewash stations and safety showers are close to the workstation location.
- Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Protective measures : Wear suitable protective equipment.
Avoid contact with skin.
When using do not eat, drink or smoke.
- Hygiene measures : Avoid contact with skin, eyes and clothing.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and immediately after handling the product.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : clear
light yellow
- Odor : solvent
- Odor Threshold : No data is available on the product itself.
- pH : No data is available on the product itself.
- Boiling point : 66 °C
- Flash point : 3 °C
Method: Tag closed cup, closed cup
- Evaporation rate : No data is available on the product itself.
- Flammability (solid, gas) : No data is available on the product itself.
- Upper explosion limit : No data is available on the product itself.
- Lower explosion limit : No data is available on the product itself.
- Vapor pressure : No data is available on the product itself.
- Relative vapor density : No data is available on the product itself.



RENShape® HIGH PERFORMANCE SEALER US

Version	Revision Date:	MSDS Number:
1.0	05/07/2015	400001009031

Relative density	: 0.84
Density	: 0.84 g/cm ³
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.
Autoignition temperature	: No data is available on the product itself.
Thermal decomposition	: No data is available on the product itself.
Viscosity	: No data is available on the product itself.
Self-Accelerating decomposition temperature (SADT)	: No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available
	Extremes of temperature and direct sunlight.
Hazardous decomposition products	: Carbon oxides
	Burning produces obnoxious and toxic fumes.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	: No data is available on the product itself.
Acute toxicity	
Acute oral toxicity - Product	: Acute toxicity estimate : 200 mg/kg Method: Calculation method
	Acute toxicity estimate : 199.45 mg/kg Method: Calculation method
Acute inhalation toxicity - Product	: Acute toxicity estimate: 6 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method



RENSHAPE® HIGH PERFORMANCE SEALER US

Version	Revision Date:	MSDS Number:
1.0	05/07/2015	400001009031

Acute toxicity estimate: 6 mg/l
 Exposure time: 4 h
 Test atmosphere: vapor
 Method: Calculation method

Acute dermal toxicity - Product : Acute toxicity estimate : 600 mg/kg
 Method: Calculation method

Acute toxicity estimate : 600 mg/kg
 Method: Calculation method

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitization**Ingredients:**

Methanol:
 Routes of exposure: Skin
 Species: Guinea pig
 Method: OECD Test Guideline 406
 Result: Does not cause skin sensitization.

Benzene, methyl-:
 Routes of exposure: Skin
 Species: Guinea pig
 Method: Directive 67/548/EEC, Annex V, B.6.
 Result: Does not cause skin sensitization.

2-Propanol, 1-butoxy-:
 Routes of exposure: Skin
 Species: Guinea pig
 Method: OECD Test Guideline 406
 Result: Does not cause skin sensitization.

Assessment: No data available

Germ cell mutagenicity**Ingredients:**

Methanol:
 Genotoxicity in vitro : Concentration: 15.8 - 63.3 mg/ml
 Metabolic activation: with and without metabolic activation



RENSHAPE® HIGH PERFORMANCE SEALER US

Version Revision Date: MSDS Number:
1.0 05/07/2015 400001009031

Method: OECD Test Guideline 476
Result: negative

Concentration: 5 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Concentration: ca 40 mg/ml
Metabolic activation: negative
Result: negative

Benzene, methyl-:
Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

2-Propanol, 1-butoxy-:
Genotoxicity in vitro : Concentration: 6000 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Concentration: 5 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Concentration: 500 - 5000 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Ingredients:

Methanol:
Genotoxicity in vivo : Application Route: Intraperitoneal injection
Dose: 1920 - 4480 mg/kg
Method: OECD Test Guideline 474
Result: negative

Benzene, methyl-:
Genotoxicity in vivo : Application Route: Intraperitoneal injection
Method: OPPTS 870.5385
Result: negative

Carcinogenicity**Ingredients:**

Methanol:
Species: Rat, (male and female)
Application Route: Inhalation
Exposure time: 24 month(s)
Dose: >= 1300 mg/m³
Frequency of Treatment: 20 hour
Method: OECD Test Guideline 453



RENShape® HIGH PERFORMANCE SEALER US

Version	Revision Date:	MSDS Number:
1.0	05/07/2015	400001009031

Result: negative

Species: Mouse, (male and female)
 Application Route: Inhalation
 Exposure time: 18 month(s)
 Dose: 13 - 1300 mg/m³
 Frequency of Treatment: 19 hour
 Method: OECD Test Guideline 453
 Result: negative

Benzene, methyl-:
 Species: Rat, (male and female)
 Application Route: Inhalation
 Exposure time: 103 weeks
 Dose: 4522 mg/m³
 Frequency of Treatment: 6.5 hour
 Method: OECD Test Guideline 453
 Result: negative
 Target Organs: Respiratory Tract

Target Organs: Kidney

2-Propanol, 1-butoxy-:
 Species: Rat, (male and female)
 Application Route: Inhalation
 Exposure time: 24 month(s)
 Dose: 3000 ppm
 Frequency of Treatment: 5 daily
 Method: OECD Test Guideline 453
 Result: negative

Carcinogenicity - Assessment : No data available

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Ingredients:**

Methanol:
 Effects on fertility : Species: Rat, male and female
 Application Route: Inhalation



RENSHAPE® HIGH PERFORMANCE SEALER US

Version	Revision Date:	MSDS Number:
1.0	05/07/2015	400001009031

Method: OECD Test Guideline 416

Species: Monkey, female
Application Route: InhalationSpecies: Mouse, male
Application Route: Oral

Benzene, methyl-:

Species: Rat, male and female
Application Route: Inhalation
Method: OECD Test Guideline 416

2-Propanol, 1-butoxy-:

Species: Rat, male and female
Application Route: Inhalation
Method: OECD Test Guideline 416**Ingredients:**

Methanol:

Effects on fetal development : Species: Monkey
Application Route: Inhalation
General Toxicity Maternal: NOAEL (No observed adverse effect level): 2,390 mg/m³
Result: No teratogenic effects.

Benzene, methyl-:

Species: Rat, female
Application Route: Inhalation
General Toxicity Maternal: NOAEL (No observed adverse effect level): 2,812 mg/m³
Method: Skin Sensitization
Result: No teratogenic effects.

2-Propanol, 1-butoxy-:

Species: Rat, female
Application Route: Dermal
General Toxicity Maternal: NOAEL (No observed adverse effect level): 880 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects.

Reproductive toxicity - Assessment : No data available

STOT-single exposure**Ingredients:**

Benzene, methyl-:

Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

RENSHAPE® HIGH PERFORMANCE SEALER US

Version Revision Date: MSDS Number:
1.0 05/07/2015 400001009031

STOT-repeated exposure**Ingredients:**

Benzene, methyl-:

Target Organs: Liver, Lungs, Kidney

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Repeated dose toxicity**Ingredients:**

Methanol:

Species: Monkey

NOEC: 13 mg/m³

Test atmosphere: vapor

Exposure time: 5,040 h

Number of exposures: 21 h

Benzene, methyl-:

Species: Rat, male and female

Lowest Observed Effect Concentration: 625 mg/kg, 600 ppm

Application Route: Ingestion

Test atmosphere: vapor

Exposure time: 13 Weeks

Number of exposures: 6 d

Method: OECD Test Guideline 453

2-Propanol, 1-butoxy-:

Species: Rat, male and female

NOEC: 350 mg/kg, > 700 ppm

Application Route: Ingestion

Test atmosphere: vapor

Exposure time: 2 Weeks

Number of exposures: 7 d

Method: OECD Test Guideline 412

Species: Rat, male and female

NOAEL (No observed adverse effect level): 880 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks

Number of exposures: 5 d

Method: Subchronic toxicity

Repeated dose toxicity - : No data available
Assessment

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available



RENSHAPE® HIGH PERFORMANCE SEALER US

Version	Revision Date:	MSDS Number:
1.0	05/07/2015	400001009031

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:**

Methanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l
Exposure time: 96 h
Test Type: flow-through test
Test substance: Fresh water

Benzene, methyl-:

Toxicity to fish : LC50: 5.5 mg/l
Exposure time: 96 h
Test Type: flow-through test
Test substance: Fresh water

2-Propanol, 1-butoxy-:

Toxicity to fish : LC50: 560 - 1,000 mg/l
Exposure time: 96 h

Ingredients:

Methanol:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test



RENSHAPE® HIGH PERFORMANCE SEALER US

Version Revision Date: MSDS Number:
1.0 05/07/2015 400001009031

Test substance: Fresh water
Method: DIN 38412

Benzene, methyl-:
Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (Water flea)): 3.78 mg/l
Exposure time: 48 h
Test Type: Other guidelines
Test substance: Fresh water
Method: Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids

2-Propanol, 1-butoxy-:
Toxicity to daphnia and other aquatic invertebrates : EC50: > 1,000 mg/l
Exposure time: 48 h

Ingredients:

Methanol:
Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): ca. 22,000 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : No data available

Ingredients:

Benzene, methyl-:
Toxicity to fish (Chronic toxicity) : NOEC: 1.39 mg/l
Exposure time: 40 d
Test Type: flow-through test
Test substance: Fresh water

Ingredients:

Benzene, methyl-:
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (Water flea)): 0.74 mg/l
Exposure time: 7 d
Test Type: Other guidelines
Test substance: Fresh water
Method: Daphnid Chronic Toxicity Test

M-Factor (Chronic aquatic toxicity) : No data available

Ingredients:

Methanol:
Toxicity to bacteria : IC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 209



RENSHAP® HIGH PERFORMANCE SEALER US

Version	Revision Date:	MSDS Number:
1.0	05/07/2015	400001009031

Toxicity to soil dwelling organisms : No data available

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial organisms : No data available

Ecotoxicology Assessment
Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Further information

The following percentage of the mixture consists of ingredient(s) with unknown hazards to the aquatic environment: 12 %

Persistence and degradability**Ingredients:****Methanol:**

Biodegradability : Inoculum: Marine water
Result: Readily biodegradable.
Biodegradation: 69 - 97 %
Exposure time: 5 - 20 d

Benzene, methyl-:

Biodegradability : Inoculum: Sewage (STP effluent)
Concentration: 10 mg/l
Result: Readily biodegradable.
Biodegradation: 81 %
Exposure time: 5 d

2-Propanol, 1-butoxy-:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 60 %
Exposure time: 28 d

Biochemical Oxygen Demand (BOD) : No data available

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available



RENSHAPE® HIGH PERFORMANCE SEALER US

Version	Revision Date:	MSDS Number:
1.0	05/07/2015	400001009031

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

Stability in water : No data available

Ingredients:

Methanol:
Photodegradation : Test Type: Air
Rate constant: 0.0093
Rate constant: 50 %

Impact on Sewage Treatment : No data available

Bioaccumulative potential**Ingredients:**

Methanol:
Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): < 10
Exposure time: 3 d
Test substance: Fresh water

2-Propanol, 1-butoxy-:
Bioaccumulation : Bioconcentration factor (BCF): 99

Ingredients:

Methanol:
Partition coefficient: n-octanol/water : log Pow: -0.77

Benzene, methyl-:
Partition coefficient: n-octanol/water : log Pow: 2.73 (20 °C)
pH: 7

Mobility in soil

Mobility : No data available

Ingredients:

Benzene, methyl-:
Distribution among environmental compartments : Koc: 34 - 120. Method: OECD Test Guideline 312
2-Propanol, 1-butoxy-:
Distribution among environmental compartments : Koc: 0 - 50.
Stability in soil : No data available

Other adverse effects

RENSHAPE® HIGH PERFORMANCE SEALER US

Version	Revision Date:	MSDS Number:
1.0	05/07/2015	400001009031

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

Adsorbed organic bound halogens (AOX) : No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Not applicable

Additional ecological information - Product : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

Global warming potential (GWP) : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International Regulation****IATA**


UN/ID No.	: UN 1992
Proper shipping name	: Flammable liquid, toxic, n.o.s. (METHANOL, TOLUENE)
Class	: 3
Subsidiary risk	: 6.1
Packing group	: II



RENSHAP® HIGH PERFORMANCE SEALER US

Version 1.0 Revision Date: 05/07/2015 MSDS Number: 400001009031

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Revision Date : 05/07/2015

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE. THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.

RENSHAP[®] HIGH PERFORMANCE SEALER US

Version	Revision Date:	MSDS Number:
1.0	05/07/2015	400001009031
