



## Mono-Coat® RM-1910RP

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

### SECTION 1. IDENTIFICATION

Product name : Mono-Coat® RM-1910RP

Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : Chem-Trend LP  
1445 W McPherson Park Dr  
PO Box 860, Howell MI 48844-0860  
United States  
+1 517 546 4520

E-mail address of person responsible for the SDS : SDS-NA@chemtrend.com

Emergency telephone number : +1 517 545 7070

#### Recommended use of the chemical and restrictions on use

Recommended use : Primers

Restrictions on use : For industrial use only.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Reproductive toxicity : Category 1B

Specific target organ toxicity - single exposure : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)



**Mono-Coat® RM-1910RP**

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

Aspiration hazard : Category 1

**GHS label elements**

Hazard pictograms :   

Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.  
Harmful if swallowed.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May damage fertility or the unborn child.  
Causes damage to organs.

Precautionary statements : **Prevention:**  
Obtain special instructions before use.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
IF exposed or concerned: Call a POISON CENTER/ doctor.  
Do NOT induce vomiting.  
In case of fire: Use alcohol-resistant foam, carbon dioxide or water mist to extinguish.

**Storage:**  
Store in a well-ventilated place. Keep cool.  
Store locked up.

**Disposal:**  
Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture



**Mono-Coat® RM-1910RP**

Version 2.0	Revision Date: 2024-07-15	Date of last issue: 2023-03-04 Date of first issue: 2023-03-04	Print Date: 2024-09-26
----------------	------------------------------	---	---------------------------

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Benzene, 1,2-dimethyl-	o-xylene	95-47-6	Trade secret ( $\geq 10 - < 30$ *)
Naphtha (petroleum), light alkylate	Naphtha (petroleum), light alkylate; Low boiling point modified naphtha	64741-66-8	Trade secret ( $\geq 10 - < 30$ *)
Methanol	methanol	67-56-1	Trade secret ( $\geq 5 - < 10$ *)
3-butoxypropan-2-ol	3-butoxypropan-2-ol	5131-66-8	Trade secret ( $\geq 1 - < 5$ *)
dibutyltin dilaurate	dibutyltin dilaurate	77-58-7	Trade secret ( $\geq 0.1 - < 1$ *)

\* Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- If inhaled : Call a physician or poison control centre immediately.  
Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
Seek medical advice.
- If swallowed : Move the victim to fresh air.  
If accidentally swallowed obtain immediate medical attention.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
Do NOT induce vomiting.



**Mono-Coat® RM-1910RP**

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

Rinse mouth with water.  
Never give anything by mouth to an unconscious person.  
Aspiration hazard if swallowed - can enter lungs and cause damage.

Most important symptoms and effects, both acute and delayed : Aspiration may cause pulmonary oedema and pneumonitis.  
Central nervous system depression  
Can be absorbed through skin.  
Risk of product entering the lungs on vomiting after ingestion.  
Health injuries may be delayed.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema

Notes to physician : Treat symptomatically.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not let product enter drains.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides  
Metal oxides

Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.  
Exposure to decomposition products may be a hazard to health.



**Mono-Coat® RM-1910RP**

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Do not breathe vapours or spray mist.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Non-sparking tools should be used.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Keep away from heat and sources of ignition.
- Advice on safe handling : Use only in an area containing explosion proof equipment.  
Do not use in areas without adequate ventilation.  
Do not breathe vapours or spray mist.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash hands and face before breaks and immediately after handling the product.  
Ensure all equipment is electrically grounded before beginning transfer operations.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.  
Do not ingest.  
Do not use sparking tools.  
Do not enter areas where used or stored until adequately ventilated.  
Do not repack.  
Do not re-use empty containers.  
These safety instructions also apply to empty packaging which

**Mono-Coat® RM-1910RP**

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

may still contain product residues.  
Keep container closed when not in use.

Conditions for safe storage : Store in original container.  
Keep container closed when not in use.  
Keep in a cool place away from oxidizing agents.  
Keep in a dry, cool and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store in accordance with the particular national regulations.  
Keep in properly labelled containers.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Benzene, 1,2-dimethyl-	95-47-6	TWA	100 ppm 434 mg/m3	CA AB OEL (2009-04-30)
		STEL	150 ppm 651 mg/m3	CA AB OEL (2009-04-30)
		TWAEV	100 ppm 434 mg/m3	CA QC OEL (2020-03-11)
		STEV	150 ppm 651 mg/m3	CA QC OEL (2020-03-11)
		TWA	100 ppm	CA BC OEL (2007-07-06)
		STEL	150 ppm	CA BC OEL (2007-07-06)
		TWA	20 ppm	ACGIH (2023-01-01)
Naphtha (petroleum), light alkylate	64741-66-8	TWA (Mist)	5 mg/m3	CA AB OEL (2009-04-30)
		STEL (Mist)	10 mg/m3	CA AB OEL (2009-04-30)
Methanol	67-56-1	TWA	200 ppm 262 mg/m3	CA AB OEL (2007-01-01)
		STEL	250 ppm 328 mg/m3	CA AB OEL (2007-01-01)
		TWA	200 ppm	CA BC OEL (2006-11-29)
		STEL	250 ppm	CA BC OEL (2006-11-29)
		STEV	250 ppm 328 mg/m3	CA QC OEL (2006-12-29)
		TWAEV	200 ppm	CA QC OEL

**Mono-Coat® RM-1910RP**

Version 2.0      Revision Date: 2024-07-15      Date of last issue: 2023-03-04      Date of first issue: 2023-03-04      Print Date: 2024-09-26

			262 mg/m3	(2006-12-29)
		TWA	200 ppm	ACGIH (2013-03-01)
		STEL	250 ppm	ACGIH (2013-03-01)
dibutyltin dilaurate	77-58-7	TWA	0.1 mg/m3 (Tin)	CA AB OEL (2007-01-01)
		STEL	0.2 mg/m3 (Tin)	CA AB OEL (2007-01-01)
		TWAEV	0.1 mg/m3 (Tin)	CA QC OEL (2006-12-29)
		STEV	0.2 mg/m3 (Tin)	CA QC OEL (2006-12-29)
		TWA	0.1 mg/m3 (Tin)	CA BC OEL (2006-11-29)
		STEL	0.2 mg/m3 (Tin)	CA BC OEL (2006-11-29)
		TWA	0.1 mg/m3 (Tin)	CA ON OEL (2010-11-05)
		TWA	0.1 mg/m3 (Tin)	ACGIH (2013-03-01)
		STEL	0.2 mg/m3 (Tin)	ACGIH (2013-03-01)

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Benzene, 1,2-dimethyl-	95-47-6	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI (2023-01-01)
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI (2007-01-01)

**Engineering measures** : Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.



**Mono-Coat® RM-1910RP**

Version 2.0	Revision Date: 2024-07-15	Date of last issue: 2023-03-04 Date of first issue: 2023-03-04	Print Date: 2024-09-26
----------------	------------------------------	---	---------------------------

Hand protection  
Material : Nitrile rubber  
Break through time : > 10 min  
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid (20 °C )

Colour : colourless

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/range : No data available

Boiling point/boiling range : 61 °C

Flash point : -2 °C

Method: Tag open cup



# SAFETY DATA SHEET

- CA



DISTRIBUTED BY  
Freeman Mfg. & Supply Co.  
www.FreemanSupply.com



## Mono-Coat® RM-1910RP

Version 2.0	Revision Date: 2024-07-15	Date of last issue: 2023-03-04 Date of first issue: 2023-03-04	Print Date: 2024-09-26
----------------	------------------------------	---	---------------------------

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : 0.84 (20 °C)  
Reference substance: Water  
The value is calculated

Bulk density : No data available

Solubility(ies)

    Water solubility : insoluble

    Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

    Viscosity, dynamic : No data available

    Viscosity, kinematic : < 20.5 mm<sup>2</sup>/s ( 40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

**Mono-Coat® RM-1910RP**

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.  
Strong sunlight for prolonged periods.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : >150 °C small quantities of formaldehyde may be formed.

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

**Product:**

Acute oral toxicity : Remarks: Effects due to ingestion may include:  
Harmful if swallowed.

Symptoms: Central nervous system depression

Acute toxicity estimate: 1,599 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:  
Local irritation, Respiratory disorders, Dizziness, Drowsiness,  
Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Remarks: Respiration of solvent vapour may cause dizziness.  
Harmful by inhalation.  
Toxic by inhalation.  
Irritating to respiratory system.

Acute dermal toxicity : Symptoms: Redness, Local irritation

Acute toxicity estimate: > 2,000 mg/kg  
Method: Calculation method

**Components:**

**|| Benzene, 1,2-dimethyl-**



**Mono-Coat® RM-1910RP**

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

Acute oral toxicity : LD50 Oral (Rat, male): 6,602 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10 - 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 1,000 - 2,000 mg/kg

**|| Naphtha (petroleum), light alkylate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

**|| Methanol:**

Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): 131.25 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

**|| 3-butoxypropan-2-ol:**

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

**|| dibutyltin dilaurate:**

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

**Skin corrosion/irritation**

**Product:**

Remarks : Irritating to skin.

**Components:**

**|| Benzene, 1,2-dimethyl-:**

Result : Skin irritation

**|| Naphtha (petroleum), light alkylate:**

Result : Skin irritation

**|| 3-butoxypropan-2-ol:**



**Mono-Coat® RM-1910RP**

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

Result : Skin irritation

**Serious eye damage/eye irritation**

**Product:**

Remarks : Irritating to eyes.

**Components:**

**|| Benzene, 1,2-dimethyl-:**

Result : Eye irritation

**|| 3-butoxypropan-2-ol:**

Result : Eye irritation

**|| dibutyltin dilaurate:**

Result : Eye irritation

**Respiratory or skin sensitisation**

**Product:**

Remarks : This information is not available.

**Components:**

**|| dibutyltin dilaurate:**

Result : May cause sensitisation by skin contact.

**Germ cell mutagenicity**

**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Components:**

**|| dibutyltin dilaurate:**

Germ cell mutagenicity - Assessment : In vitro tests showed mutagenic effects

**Carcinogenicity**

**Product:**

Remarks : No data available

**Mono-Coat® RM-1910RP**

Version 2.0	Revision Date: 2024-07-15	Date of last issue: 2023-03-04 Date of first issue: 2023-03-04	Print Date: 2024-09-26
----------------	------------------------------	---	---------------------------

**Reproductive toxicity**

**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

**Components:**

**|| dibutyltin dilaurate:**

Reproductive toxicity - Assessment : - Fertility -  
Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

**STOT - single exposure**

**Product:**

Remarks : No data available

**Components:**

**|| Benzene, 1,2-dimethyl-:**

Assessment : May cause respiratory irritation.

**|| Naphtha (petroleum), light alkylate:**

Assessment : May cause drowsiness or dizziness.

**|| Methanol:**

Assessment : Causes damage to organs.

**|| dibutyltin dilaurate:**

Assessment : Causes damage to organs.

**STOT - repeated exposure**

**Product:**

Remarks : No data available

**Components:**

**|| dibutyltin dilaurate:**

Exposure routes : Inhalation  
Assessment : Causes damage to organs through prolonged or repeated exposure.



**Mono-Coat® RM-1910RP**

Version 2.0	Revision Date: 2024-07-15	Date of last issue: 2023-03-04 Date of first issue: 2023-03-04	Print Date: 2024-09-26
----------------	------------------------------	---	---------------------------

**Repeated dose toxicity**

**Product:**

Remarks : This information is not available.

**Aspiration toxicity**

**Product:**

May be fatal if swallowed and enters airways.

**Components:**

**Benzene, 1,2-dimethyl-:**  
May be fatal if swallowed and enters airways.

**Naphtha (petroleum), light alkylate:**  
May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks : Risks of irreversible effects after a single exposure.  
Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.  
Possible risk of irreversible effects.  
Danger of very serious irreversible effects.

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available



**Mono-Coat® RM-1910RP**

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

**Components:**

**|| Benzene, 1,2-dimethyl-:**

**Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**|| Naphtha (petroleum), light alkylate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 18.4 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.4 mg/l  
Exposure time: 48 h

**|| dibutyltin dilaurate:**

M-Factor (Acute aquatic toxicity) : 1

**Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**Persistence and degradability**

**Product:**

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

**Components:**

**|| Benzene, 1,2-dimethyl-:**

Biodegradability : Result: Not readily biodegradable.

**|| Naphtha (petroleum), light alkylate:**

Biodegradability : Result: Not readily biodegradable.



**Mono-Coat® RM-1910RP**

Version 2.0	Revision Date: 2024-07-15	Date of last issue: 2023-03-04 Date of first issue: 2023-03-04	Print Date: 2024-09-26
----------------	------------------------------	---	---------------------------

**Methanol:**  
Biodegradability : Result: Readily biodegradable.

**3-butoxypropan-2-ol:**  
Biodegradability : Result: Readily biodegradable.

**dibutyltin dilaurate:**  
Biodegradability : Result: Not readily biodegradable.

**Bioaccumulative potential**

**Product:**

Bioaccumulation : Remarks: No data available

**Components:**

**Benzene, 1,2-dimethyl-:**  
Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Partition coefficient: n-octanol/water : log Pow: 3.12

**Naphtha (petroleum), light alkylate:**  
Bioaccumulation : Bioconcentration factor (BCF): 105

Partition coefficient: n-octanol/water : log Pow: 3.52

**Methanol:**  
Bioaccumulation : Bioconcentration factor (BCF): 1.0

**3-butoxypropan-2-ol:**  
Bioaccumulation : Bioconcentration factor (BCF): < 100

Partition coefficient: n-octanol/water : log Pow: 1.2





**Mono-Coat® RM-1910RP**

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

**|| dibutyltin dilaurate:**

Bioaccumulation : Bioconcentration factor (BCF): 31

Partition coefficient: n-octanol/water : Pow: ca. 3

**Mobility in soil**

**Product:**

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

**Other adverse effects**

**Product:**

Additional ecological information : Toxic to aquatic life with long lasting effects.

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Dispose of waste product or used containers according to local regulations.

---

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**UNRTDG**

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(o-xylene, hexamethyldisiloxane)  
Class : 3

# SAFETY DATA SHEET

- CA



DISTRIBUTED BY  
Freeman Mfg. & Supply Co.  
www.FreemanSupply.com



## Mono-Coat® RM-1910RP

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

Packing group : II  
Labels : 3

### IATA-DGR

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(o-xylene, hexamethyldisiloxane)  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

### IMDG-Code

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(o-xylene, hexamethyldisiloxane)  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### TDG

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(o-xylene, hexamethyldisiloxane)  
Class : 3  
Packing group : II  
Labels : 3  
ERG Code : 128  
Marine pollutant : yes

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All substances listed as active on the TSCA inventory

**Mono-Coat® RM-1910RP**

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

**Canadian lists**

No substances are subject to a Significant New Activity Notification.

**SECTION 16. OTHER INFORMATION**

**Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for

# SAFETY DATA SHEET

- CA



DISTRIBUTED BY  
Freeman Mfg. & Supply Co.  
www.FreemanSupply.com



## Mono-Coat® RM-1910RP

Version	Revision Date:	Date of last issue: 2023-03-04	Print Date:
2.0	2024-07-15	Date of first issue: 2023-03-04	2024-09-26

Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 2024-07-15  
Date format : mm/dd/yyyy

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.