



Clay Modeling Products  
Since 1892, the finest name in modeling clay

Chavant, Inc.  
5043 Industrial Road  
Farmingdale, NJ 07727

Phone: 1-800-CHAVANT  
Fax: (732) 751-1982  
Internet: <http://www.chavant.com>  
E-mail: [mail@chavant.com](mailto:mail@chavant.com)

### MATERIAL SAFETY DATA SHEET

March 7, 2010

#### HAZARD RATING

	FLAMMABILITY		<u>HAZARD RATING</u>
TOXICITY		REACTIVITY	N 4 - EXTREME F 3 - HIGH P 2 - MODERATE A 1 - SLIGHT 0 - INSIGNIFICANT
	SPECIAL		

#### SECTION 1. PRODUCT IDENTIFICATION

TRADE NAMES: CM-50, CM-70, DaVinci, H-525, I-305, I-307, J-88, J-525, Professional Plasteline

CHEMICAL NAME: Sulfur-Based Modeling Clay

EMERGENCY PHONE: 1-800-242-8268  
1-732-751-0003

EMERGENCY FAX: 1-732-751-1982

#### SECTION 2. HAZARDOUS INGREDIENT INFORMATION

This product is not hazardous as defined in 29 CFR1900.1200. The composition of this clay is a trade secret as allowed by 29 CFR 1910. 1200-48. In the event of a medical emergency, compositional information will be provided to a physician or nurse.

Product labeling conforms to ASTM D-4236 (no special label required).

---

### SECTION 3. PHYSICAL AND CHEMICAL DATA

---

Appearance and Odor: Brown or green, pliable solid, varying degree of odor.

Specific Gravity: Varies between 1.47 and 1.76 g/cm<sup>3</sup> depending on formula.

Solubility in Water: Negligible ( <1% )

Evaporation Rate: N/A

Vapor Pressure: N/A

Vapor Density: N/A

Melting Point: 180 - 200 °F

---

### SECTION 4. HEALTH INFORMATION AND PROTECTION

---

#### NATURE OF HAZARD

EYE CONTACT: Direct contact may irritate but will not injure eye tissue.

SKIN CONTACT: Clay is regularly used with no skin protection. Hypersensitive users may experience slight irritation.

INHALATION: N/A

INGESTION: May induce laxative effects.

#### FIRST AID

EYE CONTACT: Flush with water.

SKIN CONTACT: Modeling clay is normally used with no skin protection. If irritation appears, it is an allergic reaction and use should be discontinued.

INHALATION: Normally not required.

INGESTION: Normally not required.

---

### SECTION 5. FIRE AND EXPLOSION HAZARD

---

FLASHPOINT: > 200 °F.

FLAMMABLE LIMITS: N/A

SPECIAL FIRE FIGHTING INFORMATION: Firefighters should use self-contained breathing apparatus to avoid exposure to smoke and vapor. A component, SULFUR, often burns in air to form Sulfur Dioxide.

