



Clay Modeling Products  
Since 1892, the finest name in modeling clay

Chavant, Inc.  
5043 Industrial Road  
Farmingdale, NJ 07727

1-800-CHAVANT  
Fax: (732) 842-3621  
Internet: <http://www.chavant.com>  
E-mail: [mail@chavant.com](mailto:mail@chavant.com)

### MATERIAL SAFETY DATA SHEET

March 7, 2010

#### HAZARD RATING

	FLAMMABILITY			<u>HAZARD RATING</u>
TOXICITY		REACTIVITY		N 4 - EXTREME
	SPECIAL			F 3 - HIGH
				P 2 - MODERATE
				A 1 - SLIGHT
				0 - INSIGNIFICANT

#### SECTION 1. PRODUCT IDENTIFICATION

TRADE NAME: Le Beau Touché, Le Beau Touché HM, NSP, P40, Y2 Klay

CHEMICAL NAME: Sulfur-Free Modeling Clay

EMERGENCY PHONE: 1-800-242-8268  
1-732-751-0003

EMERGENCY FAX: 1-732-751-1982

#### SECTION 2. HAZARDOUS INGREDIENT INFORMATION

This product is not hazardous as defined in 29 CFR1900.1200. The composition of this clay is a trade secret as allowed by 29 CFR 1910. 1200-48. In the event of a medical emergency, compositional information will be provided to a physician or nurse.

Product labeling conforms to ASTM D-4236 (no special label required).



---

SECTION 3.            PHYSICAL AND CHEMICAL DATA

---

Appearance and Odor:    Gray-Green, Brown, Dark brown, slight odor.

Specific Gravity:        Varies between 1.05 – 1.65 g/cm<sup>3</sup>, depending on formula

Solubility in Water:    Negligible ( <1% )

Evaporation Rate:      N/A

Vapor Pressure:        N/A

Vapor Density:         N/A

Melting Point:         180 °F

---

SECTION 4.            HEALTH INFORMATION AND PROTECTION

---

NATURE OF HAZARD

EYE CONTACT:         Direct contact may irritate but will not injure eye tissue.

SKIN CONTACT:        Clay is regularly used with no skin protection.

INHALATION:          N/A

INGESTION:            May induce laxative effects.

FIRST AID

EYE CONTACT:         Flush with water.

SKIN CONTACT:        Modeling clay is normally used with no skin protection. If irritation appears, it is an allergic reaction and use should be discontinued.

INHALATION:          Normally not required.

INGESTION:            Normally not required.

---

SECTION 5.            FIRE AND EXPLOSION HAZARD

---

FLASHPOINT:            > 300 °F.

FLAMMABLE LIMITS:    N/A

SPECIAL FIRE FIGHTING INFORMATION:    Firefighters should use self-contained breathing apparatus to avoid exposure to smoke.

