

Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17

SECTION 1. IDENTIFICATION

Product name : Chemlease® 5029

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Chem-Trend LP
1445 W McPherson Park Dr
PO Box 860, Howell MI 48844-0860
United States
+1 517 546 4520

E-mail address of person responsible for the SDS : SDS-NA@chemtrend.com
Emergency telephone number : +1 517 545 7070

Recommended use of the chemical and restrictions on use

Recommended use : Release agent

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 3
Skin irritation : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :   

Signal word : Danger

Hazard statements : Flammable liquid and vapour.
May be fatal if swallowed and enters airways.

Chemlease® 5029

Version 1.0	Revision Date: 2023-04-21	Date of last issue: - Date of first issue: 2023-04-21	Print Date: 2023-05-17
----------------	------------------------------	--	---------------------------

Causes skin irritation.
May cause drowsiness or dizziness.

Precautionary statements :

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting.

In case of fire: Use alcohol-resistant foam, carbon dioxide or water mist to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated light	Distillates (petroleum), hydro- treated light; Kerosine — unspecified	64742-47-8	Trade secret** ($\geq 30 - < 60$ *)
Light aliphatic naphtha	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	64742-49-0	Trade secret** ($\geq 30 - < 60$ *)

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17

- If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
In case of contact, immediately flush skin with plenty of water.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.
- Most important symptoms and effects, both acute and delayed : Central nervous system depression
Can be absorbed through skin.
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Causes skin irritation.
Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Aspiration may cause pulmonary oedema and pneumonitis.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not let product enter drains.
Container may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17

- Hazardous combustion products : Carbon oxides
- Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
Exposure to decomposition products may be a hazard to health.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Use personal protective equipment.
Remove all sources of ignition.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Non-sparking tools should be used.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Keep away from heat and sources of ignition.
- Advice on safe handling : Use only in an area containing explosion proof equipment.
Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after

Chemlease® 5029

Version 1.0	Revision Date: 2023-04-21	Date of last issue: - Date of first issue: 2023-04-21	Print Date: 2023-05-17
----------------	------------------------------	--	---------------------------

handling the product.
Ensure all equipment is electrically grounded before beginning transfer operations.
Do not use sparking tools.
Do not enter areas where used or stored until adequately ventilated.

Conditions for safe storage : Store in original container.
Keep container closed when not in use.
Keep in a cool place away from oxidizing agents.
Keep in a dry, cool and well-ventilated place.
Do not store together with oxidizing and self-igniting products.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Store in accordance with the particular national regulations.
Keep in properly labelled containers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m ³ (total hydrocarbon vapor)	CA BC OEL (2006-11-29)
		TWA	200 mg/m ³ (total hydrocarbon vapor)	CA AB OEL (2009-04-30)
		TWA (Mist)	5 mg/m ³	CA AB OEL (2009-04-30)
		STEL (Mist)	10 mg/m ³	CA AB OEL (2009-04-30)
		TWAEV (Mist)	5 mg/m ³	CA QC OEL (2012-11-28)
		STEV (Mist)	10 mg/m ³	CA QC OEL (2012-11-28)
		TWA	525 mg/m ³	CA ON OEL (2010-11-05)
Light aliphatic naphtha	64742-49-0	TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH (2010-03-01)
		TWA (Mist)	5 mg/m ³	CA AB OEL (2009-04-30)
		STEL (Mist)	10 mg/m ³	CA AB OEL (2009-04-30)
		TWAEV	5 mg/m ³	CA QC OEL

Chemlease® 5029

Version 1.0 Revision Date: 2023-04-21 Date of last issue: - Print Date: 2023-05-17
Date of first issue: 2023-04-21

		(Mist)		(2012-11-28)
		STEV (Mist)	10 mg/m3	CA QC OEL (2012-11-28)
Paraffin waxes and Hydrocarbon waxes	8002-74-2	TWA (Fumes)	2 mg/m3	CA BC OEL (2012-04-20)
		TWA (Fumes)	2 mg/m3	CA AB OEL (2009-04-30)
		TWAEV (Fumes)	2 mg/m3	CA QC OEL (2012-11-28)
		TWA (Fumes)	2 mg/m3	ACGIH (2010-03-01)

Engineering measures : Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Protective gloves The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : white

Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : Not applicable

Melting point/range : No data available

Boiling point/boiling range : 121 °C

Flash point : 24 °C
Method: Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 14.6654 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0.77 (20 °C)
Reference substance: Water
The value is calculated

Bulk density : No data available

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20.5 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:
Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.
Symptoms: Inhalation may provoke the following symptoms:,
Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17

Components:

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Light aliphatic naphtha:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Light aliphatic naphtha:

Result : Skin irritation

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17

STOT - single exposure

Product:

Remarks : No data available

Components:

Distillates (petroleum), hydrotreated light:

Exposure routes : Inhalation
Assessment : May cause drowsiness or dizziness.

Light aliphatic naphtha:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Product:

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

Distillates (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Light aliphatic naphtha:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Distillates (petroleum), hydrotreated light:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Light aliphatic naphtha:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17

Components:

Distillates (petroleum), hydrotreated light:

Biodegradability : Result: rapidly biodegradable

Light aliphatic naphtha:

Biodegradability : Remarks: No data available

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

Distillates (petroleum), hydrotreated light:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

Light aliphatic naphtha:

Bioaccumulation : Bioconcentration factor (BCF): 10 - 2,500

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

Other adverse effects

Product:

Additional ecological information : No information on ecology is available.

Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
- Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of waste product or used containers according to local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

- UN number : UN 3295
Proper shipping name : HYDROCARBONS, LIQUID, N.O.S.
Class : 3
Packing group : III
Labels : 3

IATA-DGR

- UN/ID No. : UN 3295
Proper shipping name : Hydrocarbons, liquid, n.o.s.
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

- UN number : UN 3295
Proper shipping name : HYDROCARBONS, LIQUID, N.O.S.
(Light aliphatic naphtha)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

TDG

- UN number : UN 3295

Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17

Proper shipping name : HYDROCARBONS, LIQUID, N.O.S.

Class : 3
Packing group : III
Labels : 3
ERG Code : 128
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All substances listed as active on the TSCA inventory

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.

CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

ACGIH / TWA : 8-hour, time-weighted average

CA AB OEL / TWA : 8-hour Occupational exposure limit

CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average

CA ON OEL / TWA : Time-Weighted Average Limit (TWA)

CA QC OEL / TWA EV : Time-weighted average exposure value

CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -

Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17

Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 2023-04-21
Date format : mm/dd/yyyy

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

SAFETY DATA SHEET
- CA

 DISTRIBUTED BY
Freeman Mfg. & Supply Co.
www.FreemanSupply.com



Chemlease® 5029

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	2023-04-21	Date of first issue: 2023-04-21	2023-05-17
