



# MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING	
Telephone numbers:	(517) 546-4520
Manufacturer/Supplier:	CHEM-TREND LP P.O. BOX 860 HOWELL, MI 48844-0860
Product Name:	Chemwax 500

2. HAZARDS IDENTIFICATION	
Physical State:	Liquid
Appearance	Liquid
Color:	Off-white
Odor	mild
Emergency Overview:	DANGER: FLAMMABLE!
Principle Routes of Exposure:	Skin, eyes, respiratory tract, gastrointestinal tract

3. COMPOSITION/INFORMATION ON INGREDIENTS		
Components	CAS-No.	Weight %
Light aliphatic naphtha	-	90 - 100%
Wax blend	-	1 - 5%

4. FIRST AID MEASURES	
Skin contact:	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Eye contact:	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Inhalation:	Move to fresh air. If symptoms persist, call a physician.
Ingestion:	Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. Aspiration may cause pulmonary oedema and pneumonitis. Call a physician or poison control center immediately.
Aggravated Medical Conditions:	No information available.
Notes to physician:	No information available.

## Chemwax 500

### 5. FIRE-FIGHTING MEASURES

<b>Flash point:</b>	19 °F , -7°C (Pensky-Martens, ASTM D 93, ISO 1523, ISO 2719, DIN 51 755, DIN 51758)
<b>Flame extension test, inches (aerosol products only):</b>	Not applicable, no information available.
<b>Suitable extinguishing media:</b>	Carbon dioxide (CO2). Dry chemical. Foam. Do not use a direct stream of water..
<b>Unusual hazards:</b>	Flammable.
<b>Special protective equipment for fire-fighters:</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear
<b>Specific methods:</b>	Standard procedure for chemical fires.
<b>Explosive properties:</b>	No information available.

### 6. ACCIDENTAL RELEASE MEASURES

#### Methods for cleaning up:

<b>Small spills:</b>	Take precautionary measures against static discharges. Soak up with inert absorbent material and dispose of as hazardous waste.
<b>Large spills:</b>	Take precautionary measures against static discharges. Pick up and transfer to properly labelled containers.

### 7. HANDLING AND STORAGE

#### Handling:

**Technical measures/precautions** Ensure adequate ventilation. Take precautionary measures against static discharges.

**Safe handling advice:** Handle in accordance with good industrial hygiene and safety practice.  
Normal measures for preventive fire protection  
Take precautionary measures against static discharges.  
Keep away from open flames, hot surfaces and sources of ignition  
Bond and ground containers during transfer of material.  
Do not puncture empty containers.  
Do not re-use empty containers for other materials.

#### Storage:

**Technical measures/storage conditions:** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep product and empty container away from open flames, hot surfaces and sources of ignition. Store at temperatures not exceeding 110°F.

**Incompatible products:** Strong oxidizing agents.

**Other precautions:** None

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Components	CAS-No.	ACGIH TWA:	OSHA - TWA:	OSHA - Skin Notations	OSHA Z3 Mineral Dusts
Light aliphatic naphtha	-	-	-	-	-
Wax blend	-	-	-	-	-

**Engineering measures:** Ensure adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

**Personal Protective Equipment**

- Respiratory protection:** In case of insufficient ventilation wear suitable respiratory equipment.
- Hand protection:** Impervious gloves
- Eye protection:** Tightly fitting safety goggles or safety glasses with side-shields
- Skin and body protection:** Lightweight protective clothing. Usual safety precautions while handling the product will provide adequate protection against this potential effect.

## Chemwax 500

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Initial boiling point:</b>	200 °F , 93 °C
<b>Specific gravity:</b>	0.70
<b>Bulk density (lb/gal):</b>	5.84
<b>Vapor pressure (mm Hg, 20 °C (68 °F)):</b>	No information available.
<b>Vapor density (Air = 1.0)</b>	>1
<b>Evaporation rate:</b>	<1 (n-butyl acetate = 1)
<b>Volatiles content (%):</b>	90 - 100 %
<b>Water solubility:</b>	Insoluble
<b>pH of concentrate:</b>	Not applicable.
<b>Melting point range:</b>	Not applicable
<b>Flash point:</b>	19 °F , -7°C (Pensky-Martens, ASTM D 93, ISO 1523, ISO 2719, DIN 51 755, DIN 51758)
<b>Flammability limits in air:</b>	Percent by volume

Components	CAS-No.	Lower (%):	Upper (%):
Light aliphatic naphtha	-	0.9	6.0

### 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable.
<b>Conditions to avoid:</b>	Keep away from open flames, hot surfaces and sources of ignition.
<b>Materials to avoid:</b>	Strong oxidizing agents
<b>Hazardous decomposition products:</b>	Carbon oxides.
<b>Polymerization:</b>	Hazardous polymerization does not occur.

## Chemwax 500

### 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

##### Component Information:

Components	CAS-No.	LD50 Oral	LD50 Dermal	LC50 Inhalation (Vapor)
Light aliphatic naphtha	-	5000 mg/kg (mouse)	3000 mg/kg (rabbit)	-
Wax blend	-	-	-	-

#### Acute effects

**Product contains proprietary ingredients. Health hazards are listed below.**

##### Skin contact:

Prolonged contact may defat skin, causing irritation and/or dermatitis.

##### Eye contact:

Contact with eyes may cause irritation.

##### Inhalation:

High levels above the TLV cause stupor, headache, nausea, dizziness, unconsciousness, and may produce adverse effects on vision.

##### Ingestion:

Ingestion may cause gastrointestinal irritation, nausea, and diarrhea. Material entering lungs during swallowing or vomiting causes lung inflammation and other lung injury.

##### Sensitization:

No information available.

##### Other effects:

No information available.

#### Chronic effects

##### Carcinogenic effects:

Components	CAS-No.	NTP:	IARC:	OSHA:
Light aliphatic naphtha	-	No	No	No
Wax blend	-	No	No	No

##### Mutagenic effects:

No information available.

##### Reproductive toxicity:

No information available.

##### Target Organ Effects:

No information available.

### 12. ECOLOGICAL INFORMATION

**Ecotoxicity:** No data available.

### 13. DISPOSAL CONSIDERATIONS

**Method(s) of disposal:** Dispose of in accordance with local, state, and federal regulations.

**US EPA Waste number:** D001 because of its ignitability if the product is disposed of in its original form.

**Chemwax 500****14. TRANSPORT INFORMATION**

**IMDG - Marine Pollutants** This product does not contain marine pollutants as classified by the International Maritime Organization.

**Emergency Response Guidebook (ERG) No:** 128

<b>Mode of Transportation:</b>	<b>UN/NA ID No:</b>	<b>Proper shipping name:</b>	<b>Technical name</b>	<b>Hazard Class:</b>		<b>Packing group:</b>
DOT - Non-Bulk	UN1993	Flammable liquids, n.o.s.	(Contains Light aliphatic naphtha )	3		II
DOT - Bulk	UN1993	Flammable liquids, n.o.s.	(Contains Light aliphatic naphtha )	3		II
Canadian TDG	UN1993	Flammable liquid, n.o.s.	(Contains Light aliphatic naphtha )	3		II
ICAO/IATA	UN1993	Flammable liquid, n.o.s.	(Contains Light aliphatic naphtha )	3		II
IMO/IMDG	UN1993	Flammable liquid, n.o.s.	(Contains Light aliphatic naphtha )	3		II

**15. REGULATORY INFORMATION****Federal Regulations**

OSHA Hazardous Chemical: Yes

**SARA Title III****CERCLA/SARA (304) Hazardous Substances and RQs**

Components	CAS-No.	Weight %	RQ
Light aliphatic naphtha	-	90 - 100%	-
Wax blend	-	1 - 5%	-

**SARA (302) Extremely Hazardous Substances and RQs**

Components	CAS-No.	Weight %	TPQ
Light aliphatic naphtha	-	90 - 100%	-
Wax blend	-	1 - 5%	-

**SARA (311/312) Classification:**

**Acute health hazard:** Yes  
**Chronic health hazard:** No  
**Fire:** Yes  
**Sudden Release of Pressure:** No  
**Reactive:** No

**SARA (313) Toxic Chemicals**

Components	CAS-No.	Weight %	SARA (313) List
Light aliphatic naphtha	-	90 - 100%	Not Listed
Wax blend	-	1 - 5%	Not Listed

**International Inventories**

<b>Australia:</b>	All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).
<b>Canada:</b>	This product complies with DSL.
<b>China:</b>	This product complies with CLECS.
<b>Europe:</b>	This product complies with EINECS.
<b>Japan:</b>	This product complies with ENCS/MITI.
<b>Korea:</b>	Listed on ECL.
<b>New Zealand:</b>	This product complies with NZIoC.
<b>Philippines:</b>	This product complies with PICCS.
<b>United States:</b>	This product complies with TSCA.

**16. OTHER INFORMATION****Hazardous Material Information System (USA):**

**Health** 1      **Flammability:** 3      **Physical hazard:** 0      **Personal Protection code:** H

**National Fire Protection Association (USA):**

**Health:** 1      **Flammability:** 3      **Instability:** 0      **Special Hazards:** None/Not available

All revisions are marked with one or more asterisks (\*)

**Prepared by:** Karen M. Kuroda

**Revision number:** 0

**Revision date:** 03/23/2011

**Review date:** 12/12/2011

**Print date:** 12/12/2011

**Disclaimer**

*Information presented herein has been compiled from information provided to us by our suppliers and other sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or the use of any product in violation of any patent or in violation of any law or regulation. It is the users' responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.*