

1. Product and company identification

Product identifier

Trade name: Resin Infusion Products

Knitflow 110, Knitflow 150, PVC Tube, FlowPeel 160-37P16-ESG, Dahltexx SP-2, Dahltexx SP-3, FlowRunner KF160, Vac-Brake, Vac-Brake Pro, Flowstrip PP4, Flowstrip PP4 Max, Dahlvac RC Vacuum Hose, Flowlease 160-PP200, PP200, Dahlvac MB80, Breatherflow 20, Dahlpac MC79, Tube mesh, SpiralMesh, Flowstrip, Greenflow 75, Greenflow 185, Knitflow 160, Knitflow 105 HT, Resinflow 100, Resinflow 60, Resinflow 20, Resinflow 90HT, Flowlease 160-37P16, Flowlease 75-37P16, Flowlease Blue, OF313, OF500, OF750, OF1000, OF625V, Resintrak, Vactrak, Tac-Strip, VAC-RIC LT, VAC-RIC HT, RIC, RIC HT, RIA, polyethylene and nylon tubing, , polyethylene and nylon spiral tubing, nylon fittings (NTF, NEF, NCF), Sil-tube, HTRIL-S59, Infusion valve, Hose clamps A & B, Flowrunner PP2

Relevant identified uses of the substance or mixture and uses advised against

General use: Article: Resin distribution media and auxiliaries
For industrial purposes only

Details of the supplier of the safety data sheet

Company name:

Airtech International, Inc.
5700 Skylab Road
Huntington Beach, CA 92647
E-mail: airtech@airtechintl.com
Website: www.airtechonline.com
Telephone: +1 714.899.8100
Department responsible for information:
Telephone: +1 714.899.8100
E-mail: airtech@airtechintl.com

Airtech Europe Sarl
Zone industrielle Haneboesch
L-4562 Differdange
Luxembourg
Website: www.airtech.lu
Telephone: +352 582.282
Department responsible for information:
Telephone: +352 582.282
E-mail: sales@airtech.lu

Tygavac Advanced Materials Ltd.
The Causeway
Broadway Business Park
Chadderton, Oldham
OL9 9XD United Kingdom
Website: www.tygavac.co.uk
Telephone: +44 161.947.1610
Department responsible for information:
Telephone: +44 161.947.1610
E-mail: sales@tygavac.co.uk

Airtech Asia Ltd.
No. 161 of Anyuan Rd
Chagugang County
Wuqing District
301721, Tianjin, P.R. China
Website: www.airtech.asia
Telephone: +86 22 8862 9800
Telefax: +86 22 8862 9900
Department responsible for information:
Telephone: +86 22 8862 9800
E-mail: airtech.asia@airtechasia.com.cn

Emergency phone number

CHEMTREC EMERGENCY PHONE:
Within USA/Canada: 1-(800)424-9300
International: +1 703-741-5970

2. Hazards identification

Emergency overview

Appearance:	Form: solid Color: varying
Odor:	odorless
Classification:	Article not subject to hazard labelling or classification.

Regulatory status

This material is not considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200).

Hazards not otherwise classified

Toxic fumes may be emitted at elevated temperatures. Do not breathe vapor. Processing, e.g. by cutting, sawing or grinding, can produce particles and dust. Avoid inhalation of dusts, as even inert dusts may functionally affect respiratory organs.
see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterization: Article: Thermoplastic, Silicone, Fiberglass, Metal

4. First aid measures

In case of inhalation:	In case of inhalation of decomposition products, affected person should be moved into fresh air and kept still. If the casualty has difficulty breathing, call a doctor immediately.
Following skin contact:	After contact with molten product, cool skin area rapidly with cold water. Do not peel solidified product off the skin. Seek medical attention.
After eye contact:	In the event of irritation from processing vapors: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. In case of troubles or persistent symptoms, consult an ophthalmologist.
After swallowing:	Not a probable route of exposure. In the case of the formation of dust: Rinse mouth. Seek medical treatment in case of troubles.

Most important symptoms/effects, acute and delayed

In case of inhalation:
Inhalation of dust may cause irritation of the respiratory system. Overheating released mist or vapors can irritate the respiratory tracts.
Other symptoms: Cough, respiratory complaints, dizziness, nausea, vomiting.
After contact with skin: The melted product can cause severe burns.
After eye contact:
Process vapors can irritate the eyes. Dust contact with the eyes can lead to mechanical irritation.

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:

No data available

Auto-ignition temperature: No data available

Suitable extinguishing media:

Water spray jet, dry chemical powder, foam, carbon dioxide

Extinguishing media which must not be used for safety reasons:

Full water jet.

Specific hazards arising from the chemical

This material is combustible, but will not ignite readily. Toxic fumes may be emitted at elevated temperatures.

In case of fire may be liberated: Caprolactam, nitrogen oxides (NO_x), amines, carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information:

Seal off endangered area. Cool endangered containers with water spray and, if possible, remove from danger zone. Use a water fog to control vapors. Do not breathe fumes. Do not allow fire water to penetrate into surface or ground water.

6. Accidental release measures

Personal precautions:

Handle in accordance with good industrial hygiene and safety practice.

At processing: Avoid the formation of aerosol/vapors. Avoid generation of dust. Avoid inhalation and contact with skin and eyes. Wear appropriate protective equipment. Keep unprotected people away. Ensure adequate ventilation, especially in confined areas.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains.

Methods for clean-up:

Take up mechanically, placing in appropriate containers for disposal. Dispose of waste according to applicable legislation.

7. Handling and storage

Handling

Advices on safe handling:

Handle in accordance with good industrial hygiene and safety practice.

At processing: Provide adequate ventilation, and local exhaust as needed. Avoid the formation of aerosol/vapors. Avoid generation of dust. Avoid inhalation and contact with skin and eyes. Wear appropriate protective equipment. Keep unprotected people away. When using do not eat, drink or smoke.

Precautions against fire and explosion:

Take standard precautions to prevent fire.

Storage

Requirements for storerooms and containers:

Keep in a cool place. Keep container dry. Protect from direct sunlight. Keep away from incompatible materials. Store at room temperature.

Hints on joint storage:

Incompatible materials: Strong bases, strong acids, strong oxidizing agents.

Keep away from food and drinks.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

Type	Limit value
USA: ACGIH: TWA	10 mg/m ³ (Dust limit value, inhalable fraction)
USA: ACGIH: TWA	3 mg/m ³ (Dust limit value, respirable fraction)
USA: OSHA: TWA	15 mg/m ³ (Dust limit value, inhalable fraction)
USA: OSHA: TWA	5 mg/m ³ (Dust limit value, respirable fraction)

Engineering controls

Provide good ventilation and/or an exhaust system in the work area.

In case of development of vapors or dust (at processing): Use local exhaust.

See also information in chapter 7, section storage.

Personal protection equipment (PPE)

Eye/face protection: At processing (recommended): Safety glasses in accordance with OSHA 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection: At processing (recommended): Wear suitable protective clothing.

Recommendation:

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Glove material: nitrile rubber (0.11 mm)

Breakthrough time: 480 min.

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Respiratory protection: Respiratory protection is not necessary if room is well ventilated.

At processing:

When vapors form, use respiratory protection. The filter class must be suitable for the maximum contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

General hygiene considerations:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and after work. When using do not eat, drink or smoke.

At processing:

Avoid contact with skin, eyes, and clothing. Do not breathe vapors. Do not breathe dust.

Environmental exposure controls

Refer to 6.: Section "Environmental precautions".

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:	Form: solid Color: varying
Odor:	odorless
Odor threshold:	No data available
pH:	No data available

Melting point/freezing point:	212 - 500 °F
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	No data available
Evaporation rate:	No data available
Flammability:	This material is combustible, but will not ignite readily.
Explosion limits:	No data available
Vapor pressure:	No data available
Vapor density:	No data available
Density:	No data available
Water solubility:	at 68 °F: insoluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Thermal decomposition:	No data available
Additional information:	No data available

10. Stability and reactivity

Reactivity:	Refer to section: Possibility of hazardous reactions.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions:	No dangerous reactions with proper and specified storage and handling
Conditions to avoid:	Keep away from heat. Protect from direct sunlight. Avoid generation of dust. Avoid the formation of aerosol/vapors.
Incompatible materials:	Strong acids, strong oxidizing agents.
Hazardous decomposition products:	Caprolactam, nitrogen oxides (NO _x), amines, carbon monoxide and carbon dioxide
Thermal decomposition:	No data available

11. Toxicological information

Toxicological tests

Toxicological effects:	Acute toxicity (oral): Lack of data. Acute toxicity (dermal): Lack of data. Acute toxicity (inhalative): Lack of data. Skin corrosion/irritation: Lack of data. Serious eye damage/irritation: Lack of data. Sensitisation to the respiratory tract: Lack of data. Skin sensitisation: Lack of data. Germ cell mutagenicity/Genotoxicity: Lack of data. Carcinogenicity: Lack of data. Reproductive toxicity: Lack of data. Effects on or via lactation: Lack of data. Specific target organ toxicity (single exposure): Lack of data. Specific target organ toxicity (repeated exposure): Lack of data. Aspiration hazard: Lack of data.
Other information:	Toxic fumes may be emitted at elevated temperatures. Processing, e.g. by cutting, sawing or grinding, can produce particles and dust. Dust may irritate airways and cause bronchitis symptoms. Information about Caprolactam: Harmful if swallowed. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

Symptoms

In case of inhalation:
Inhalation of dust may cause irritation of the respiratory system. Overheating released mist or vapors can irritate the respiratory tracts.
Other symptoms: Cough, respiratory complaints, dizziness, nausea, vomiting.
After contact with skin: The melted product can cause severe burns.
After eye contact:
Process vapors can irritate the eyes. Dust contact with the eyes can lead to mechanical irritation.

12. Ecological information

Ecotoxicity

Effects in sewage plants: The insoluble part can be precipitated mechanically in suitable sewage treatment plants.

Further details: No data available

Mobility in soil

No data available

Persistence and degradability

Further details: Product is not biodegradable.

Additional ecological information

General information: Do not allow to penetrate into soil, waterbodies or drains.

13. Disposal considerations

Product

Recommendation: Dispose of waste according to applicable legislation. Recycling or special waste incineration.

Package

Recommendation: Dispose of waste according to applicable legislation. Non-contaminated packages may be recycled.

14. Transport information

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:

Not restricted

Transport hazard class(es)

ADR/RID, IMDG, IATA-DGR:

not applicable

Packing group

ADR/RID, IMDG, IATA-DGR:

not applicable

Environmental hazards

Marine pollutant:

no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

USA: Department of Transportation (DOT)

Proper shipping name:

Not restricted

Sea transport (IMDG)

Proper shipping name:

Not restricted

Marine pollutant:

no

Air transport (IATA)

Proper shipping name:

Not restricted

Further information

No dangerous good in sense of these transport regulations.

15. Regulatory information

National regulations - U.S. Federal Regulations

This product is an article as defined by TSCA regulations, and is exempt from TSCA inventory listing requirements.

National regulations - Great Britain

Hazchem-Code: -

16. Other information

Hazard rating systems:



NFPA Hazard Rating:

Health: 1 (Slight)

Fire: 1 (Slight)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 1 (Slight)

Flammability: 1 (Slight)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS: Chemical Abstracts Service

CFR: Code of Federal Regulations

CLP: Classification, Labelling and Packaging

DMEL: Derived minimal effect level

DNEL: Derived no-effect level

EC: European Community

EN: European Standard

EQ: Excepted quantities

IATA: International Air Transport Association

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

IMDG Code: International Maritime Dangerous Goods Code

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OSHA: Occupational Safety and Health Administration

PBT: Persistent, bioaccumulative and toxic

PNEC: Predicted no-effect concentration

RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail

TRGS: Technical Rules for Hazardous Substances

TSCA: Toxic Substance Control Act

vPvB: Very persistent and very bioaccumulative

Reason of change: Changes in section 1: Changes of product list

Department issuing data sheet

Contact person: see section 1: Department responsible for information

This data sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, and which additional precautions may be necessary. All health and safety information contained in this data sheet should be provided to your employees and customers. It is your responsibility to develop appropriate workplace instructions and training programs for employees.

As the conditions and methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. All statements or suggestions are made without warranty, expressed or implied, regarding accuracy of information, the hazards connected with the use of the product or the results to be obtained from the use thereof.