

Material Safety Data Sheet

Freeman 801 Resin

Date of Preparation: October 25, 2010

Section 1 Chemical Product and Company Identification

Product/Chemical Name: Freeman 801 Resin
Chemical Family: Epoxy Resin
CAS Number: N/A
Other Designations: N/A
General Use: N/A
Manufacturer: Freeman Manufacturing and Supply Company, 1101 Moore Road, Avon, OH 44011
Phone (440) 934-1902, FAX (440) 934-7200, Hours of Operation 8-5,
Emergency phone number 1-800-424-9300

HMIS	
H	2
F	2
R	1
PPE Sec.8.	

Section 2 Composition/Information on Ingredients

Ingredient Name	CAS Number
Butyl Glycidyl Ether	2426-08-6
Bisphenol A Epoxy Resin	25068-38-6

Ingredient	OSHA		ACGIH	
	PEL	STEL	TLV	STEL
Butyl Glycidyl Ether	50 ppm	none estab.	25 ppm	none estab.
Bisphenol A Epoxy Resin	none estab.	none estab.	none estab.	none estab.

Section 3 Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Combustible. Causes eye, and skin irritation. May cause skin sensitization.

Potential Health Effects

Primary Entry Routes: Skin; Inhalation from heated vapors.

Acute Effects:

Inhalation: Irritates the respiratory tract.

Eye: Causes irritation

Skin: Causes irritation May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.

Medical Conditions Aggravated by Long-Term Exposure: Skin and eye conditions.

Carcinogenicity: IARC, NTP, and OSHA do not list any component as carcinogenic

Section 4 First Aid Measures

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen and/or artificial respiration.

Eye Contact: Flush with plenty of water for 15 minutes and get medical attention.


Skin Contact: Wash thoroughly with soap and water. Remove contaminated clothing and launder before reuse.
Destroy contaminated shoes.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person, Get medical attention.

Freeman 801 Resin

Section 5 Fire Fighting Measures

Flash Point: 171°F (77 °C)
Flash Point Method: PMCC
LEL: Not established
UEL: Not established
Extinguishing Media: CO₂, or dry chemical
Unsuitable Media: Water or foam may cause frothing.
Fire-Fighting Equipment: Use self-contained breathing apparatus.
Fire and Explosion Hazards: Decomposition and combustion products may be toxic.



Section 6 Accidental Release Measures

Spill /Leak Procedures: Stop spill at source. Dike area and contain. Clean up remainder with absorbent materials such as sand or vermiculite. Mop up and dispose of.

Section 7 Handling and Storage

Handling & Storage: Use with adequate ventilation. Avoid prolonged breathing of vapor. Avoid prolonged or repeated contact with skin. Wear safety goggles or face shield. Wear gloves, apron and footwear impervious to this material. Wash clothing before reuse. Store at ambient temperatures. . Keep container tightly closed and upright when not in use to prevent leakage.

Section 8 Exposure Controls/Personal Protection

Ventilation: Local exhaust recommended. General mechanical is acceptable. Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2).
Respiratory Protection: Use a NIOSH approved respirator when vapor/mist exposure is likely.
Eye Protection: Wear splash-proof chemical goggles.
Skin Protection: Wear impermeable gloves.
Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.
Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 Physical and Chemical Properties

Appearance and Odor: Pourable gray liquid, mild odor	Water Solubility: Negligible
Vapor Pressure: 1.1 mm Hg at 77 °F (25 °C)	Boiling Point: >200°F (> 93°C)
Vapor Density (Air=1): Not determined	% Volatile: Negligible
Specific Gravity (H₂O=1, at 4 °C): 1.73	Evaporation Rate: Not determined
	pH: Not determined

Section 10 Stability and Reactivity

Stability: Stable.
Conditions to Avoid: Excessive heat for prolonged period.
Chemical Incompatibilities: Strong oxidizing agents, acids and bases
Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.
Hazardous Polymerization: Will not occur. Avoid inadvertent mixture with epoxy curing agents.

Freeman 801 Resin

Section 11 Toxicological Information

Acute Inhalation Exposure Effects: Respiratory irritant.
Skin Irritation: Irritant.
Eye Irritation: Irritant.
Sensitization: Possible in susceptible individuals.
Carcinogenicity: IARC, NTP, and OSHA do not list any component as carcinogenic

Section 12 Ecological Information

No Known evidence of adverse effects from available information

Section 13 Disposal Considerations

Disposal: Use safety containers for disposal. Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations

Section 14 Transport Information

DOT Transportation Data (49 CFR 172.101):

Shipping Name: Environmentally hazardous substance, liquid, n.o.s.
Technical Shipping Name (if n.o.s) Bisphenol A epoxy resin
Hazard Class: 9
ID No.: UN 3082
Packing Group: III
Label: Marine Pollutant

Note: Under 49 CFR 171.4 (c) NONBULK shipments of marine pollutants are not regulated for transport by motor vehicles, rail cars or aircraft. NONBULK shipments of marine pollutants are regulated when transported by vessel (ship).

Section 15 Regulatory Information

US Federal Regulations:

OSHA (Occupational Safety and Health Act): This Material Safety Data Sheet has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

RCRA (Resource Conservation and Recovery Act): Not a hazardous waste under RCRA (40 CFR 261).

SARA Toxic Chemical (40 CFR 372.65): This product contains the following toxic chemical subject to the reporting requirements of Section 313 of SARA Title III of 1986 and of 40 CFR 372.

Aluminum (CAS # 7429-90-5) 45% by weight

TSCA Inventory Status: All ingredients listed on TSCA inventory requirements.

State Regulations: California Proposition 65: Butyl glycidyl ether (CAS # 2426-08-6) is listed as a developmental or reproductive hazard.

State Lists:

Calcium Carbonate (CAS Number: 1317-65-3), Aluminum (CAS # 7429-90-5) , and Butyl glycidyl ether(CAS # 2426-08-6) are on the following state Right to Know Lists: Pennsylvania, New Jersey

Freeman 801 Resin

Section 16 Other Information

Disclaimer: The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.

Material Safety Data Sheet

Freeman 801 Hardener

Date of Preparation: January 28, 2010

Section 1 Chemical Product and Company Identification

Product/Chemical Name: Freeman 801 Hardener

Chemical Family: Amine

CAS Number: N/A

Other Designations: N/A

General Use: N/A

Manufacturer: Freeman Manufacturing and Supply Company, 1101 Moore Road, Avon, OH 44011
Phone (440) 934-1902, FAX (440) 934-7200, Hours of Operation 8-5,
Emergency phone number 1-800-424-9300

HMIS	
H	3
F	1
R	0
PPE Sec.8.	

Section 2 Composition/Information on Ingredients

Ingredient Name	CAS Number
Tetraethylenepentamine	112-57-2
2,4,6-Tris (Dimethylaminomethyl) phenol	90-72-2
Polyaminoamide	68953-36-6

Ingredient	OSHA		ACGIH	
	PEL	STEL	TLV	STEL
Tetraethylenepentamine	none estab.	none estab.	none estab.	none estab.
2,4,6-Tris (Dimethylaminomethyl) phenol	none estab.	none estab.	none estab.	none estab.
Polyaminoamide	none estab.	none estab.	none estab.	none estab.

Section 3 Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Corrosive-Causes skin and eye burns. May cause allergic skin reaction

Potential Health Effects

Primary Entry Routes: Skin; Inhalation from heated vapors.

Acute Effects:

Inhalation: Vapor is irritating to the upper respiratory system and mucous membranes.

Eye: Product can cause severe eye irritation, swelling and/or chemical burn.

Skin: Skin contact may result in irritation or chemical burn.

Medical Conditions Aggravated by Long-Term Exposure: Skin and eye conditions.

Chronic Effects: N/A

Carcinogenicity: IARC, NTP, and OSHA do not list any components as carcinogens.

Section 4 First Aid Measures

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen and/or artificial respiration.

Eye Contact: Flush with plenty of water for 15 minutes and get medical attention.

Skin Contact: Wash thoroughly with soap and water. Remove contaminated clothing and launder before reuse.
Destroy contaminated shoes.

Ingestion: If conscious, give 2-4 glasses of water to drink. Do not induce vomiting. Get medical attention.

Freeman 801 Hardener

Section 5 Fire Fighting Measures

Flash Point: 225°F (107°C)

Flash Point Method: PMCC


LEL: Not established

UEL: Not established

Extinguishing Media: Foam, water, CO₂, or dry chemical

Fire-Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Decomposition and combustion products may be toxic.



Section 6 Accidental Release Measures

Spill /Leak Procedures: Stop spill at source. Dike area and contain. Clean up remainder with absorbent materials such as sand or vermiculite. Mop up and dispose of.

Section 7 Handling and Storage

Handling & Storage: Use with adequate ventilation. Avoid breathing of vapor. Avoid prolonged or repeated contact with skin. Wear safety goggles or face shield. Wear gloves, apron and footwear impervious to this material. Wash clothing before reuse. Store at ambient temperatures. . Keep container tightly closed and upright when not in use to prevent leakage.

Section 8 Exposure Controls/Personal Protection

Ventilation: Local exhaust recommended. General mechanical is acceptable. Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2).

Respiratory Protection: Use a NIOSH approved respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Skin Protection: Wear impermeable gloves.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 Physical and Chemical Properties

Appearance and Odor: Amber liquid, faint ammonical odor

Vapor Pressure: < 1 mm Hg @ 70°F

Vapor Density (Air=1): Not determined

Specific Gravity (H₂O=1, at 4 °C): 0.96

Water Solubility: Slight

Boiling Point: Not determined

% Volatile: Negligible

Evaporation Rate: Not determined

pH: Not determined

Section 10 Stability and Reactivity

Stability: Stable.

Conditions to Avoid: Excessive heat for prolonged period.

Chemical Incompatibilities: Strong oxidizing agents, acids and bases

Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

Hazardous Polymerization: Will not occur. Avoid inadvertent mixing with epoxy resins

Freeman 801 Hardener

Section 11 Toxicological Information

Skin Irritation: Corrosive. Causes burns.

Eye Irritation: Corrosive. Causes burns

Sensitization: Possible in susceptible individuals.

Carcinogenicity: IARC, NTP, and OSHA do not list any components as carcinogens.

Section 12 Ecological Information

No Known evidence of adverse effects from available information

Section 13 Disposal Considerations

Disposal: Use safety containers for disposal. Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations

Section 14 Transport Information

DOT Transportation Data (49 CFR 172.101):

Shipping Name: Polyamines, liquid, corrosive, N.O.S.

Technical Shipping Name (If n.o.s.): Tetraethylenepentamine,
Aliphatic polyaminoamide

Hazard Class: 8

ID No.: UN 2735

Packing Group: PG III

Label: Corrosive

Section 15 Regulatory Information

US Federal Regulations:

OSHA (Occupational Safety and Health Act): This Material Safety Data Sheet has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

RCRA (Resource Conservation and Recovery Act): Not a hazardous waste under RCRA (40 CFR 261).

SARA 311/312 Codes:

SARA Toxic Chemical (40 CFR 372.65): This product contains the following toxic chemical subject to the reporting requirements of Section 313 of SARA Title III of 1986 and of 40 CFR 372.

None

TSCA Inventory Status: All ingredients listed on TSCA inventory requirements.

State Regulations:

CA Proposition: No component listed

Tetraethylenepentamine (112-57-2) is listed on the New Jersey and Pennsylvania Right to Know Lists.

Section 16 Other Information

Disclaimer: The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.