

Freeman 925 Part A (Resin)

Section 1 Identification

Product Name

Freeman 925 Epoxy Casting Resin Part A (Resin)

Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Epoxy Mixture - For Industrial Use Only

Details of the supplier of the Safety Data Sheet

Freeman Manufacturing & Supply Company 1101 Moore Road, Avon, OH 44011 USA

Telephone: (440) 934-1902

Email: contactus@freemansupply.com

24 Hour emergency telephone number: CHEMTREC (800) 424-9300

Section 2 Hazards Identification

Classification in accordance with 29 CFR 1910.1200 (OSHA HCS)

Eye Irritation, Category 2A Skin Irritation, Category 2 Skin Sensitization, Category 1 Acute Toxicity, Oral, Category 4

Specific Target Organ Toxicity (Single Exposure) (Respiratory Tract Irritation), Category 3

GHS Label Elements



Warning

Hazard Statements

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H317 - May cause an allergic skin reaction.

H302 - Harmful if swallowed.

H335 – May cause respiratory irritation.

Precautionary Statements

Prevention: Do not eat, drink or smoke when using this product. Wash hands and face thoroughly after handling. Wear protective gloves/protective clothing. Wear eye and face protection. Avoid breathing dust, fume, gas, mist, vapors or spray. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace.

Response: If swallowed rinse mouth. Call poison center or doctor if you feel unwell.

If on skin wash with plenty of soap and water. If irritation or rash occurs, get medical advice/attention. Take off contaminated clothing & wash before reuse.

If in eyes rinse cautiously with water for several minutes while holding eye lid(s) open. Remove contact lenses, if present and easy to do and continue rising. If eye irritation persists get medical advice/attention.

If inhalation occurs, remove person to fresh air and get medical advice/attention if ill or concerned.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and container to an appropriate waste site in accordance with local and national regulations.



Freeman 925 Part A (Resin)

Section 3 Composition/Information on Ingredients

Ingredient Name	CAS Number	Concentration
Epoxy Resin	25068-38-6	<50%
Diglycidyl Ether	17557-23-2	<10%
Aluminum	7429-90-5	<30%
Glass, Oxide Chemicals	65997-17-3	>10%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4 First-Aid Measures

Inhalation: Move person to fresh air; if you feel unwell, get medical attention.

Skin contact: Immediately wash with soap and plenty of water. Remove contaminated clothing and wash before reuse. Seek medical attention if irritation/rash occurs.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses if easy to do and continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed: Rinse mouth. Call poison center or doctor if you feel unwell.

Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects.

Indication of any immediate medical attention and special treatment required

Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

Section 5 Fire-Fighting Measures

Extinguishing Media

Suitable agents: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam or alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams or protein foams may function, but will be less effective. Water fog, applied gently may be used as a blanket for fire extinguishment.

Unsuitable agents: Do not use direct water stream, may spread fire.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

Decomposition products may include the following materials: carbon dioxide, carbon monoxide, or halogenated compounds.

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.



Freeman 925 Part A (Resin)

Section 6 Accidental Release Measures

Environmental precautions

Avoid release to the environment. Prevent entry into sewer systems or bodies of water.

Methods and materials for containment and clean-up

Move containers from spill area. Absorb with an inert dry material until it appears dry. Adding an absorbent material does not remove a physical, health, or environmental hazard. Place in an appropriate waste disposal container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/ international regulations. For larger spills, dispose of via a licensed waste disposal contractor. Remove residual with soap and hot water. Solvents are not recommended for clean-up unless the recommended exposure guidelines and safe handling practices for the specific solvent are followed.

Section 7 Handling and Storage

Precautions for safe handling

For industrial/occupational use only. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (e.g. Chlorine, chromic acid etc.)

Conditions for safe storage

For safe storage, store at or below 72°F (22°C). Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Store locked up.

Section 8 Exposure Controls/Personal Protection

Components with workplace control parameters

None

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits.

Personal Protective Equipment (PPE)

Eye protection: Wear safety glasses equipped with side shields, or chemical goggles if splashing is possible. **Hand Protection:** The glove material has to be impermeable and resistant to the product/the substance/the preparation. Due to missing tests no recommendation to the glove material can be given. Contaminated gloves should be replaced.

Body Protection: Prevent skin contact when handling material. Wear protective clothing.

Respiratory Protection: The need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist prefilter should be used.

Safety Stations

Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

General Hygienic Practices

Avoid breathing vapor or mist. Avoid contamination of food, beverages, or smoking materials. Wash thoroughly after handling, and before eating, drinking or smoking. Remove contaminated clothing promptly and clean thoroughly before reuse.



Freeman 925 Part A (Resin)

Section 9 Physical and Chemical Properties

Appearance Opaque black thick liquid

Odor Mild

Odor ThresholdNo data availablepHNo data availableMelting PointNo data available

VOC Content None

>204°C (>400°F) **Boiling Point Flash Point** >149°C (>300°F) **Evaporation Rate** No data available Flammability (solid, gas) No data available **Upper/lower flammability** No data available **Vapor Pressure** No data available Vapor density No data available Relative Density at 72°F 14.4 lb./gal

Specific Gravity 1.73 **Water Solubility** Slight

Coefficient: n-octanol/ waterNo data availableAuto-ignition temperatureNo data availableViscosityNo data available

Explosive PropertiesNoneOxidizing PropertiesNonePercents Volatile0%

Section 10 Stability and Reactivity

Reactivity

No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

In normal storage hazardous reaction will not occur, reacts with amines.

Conditions to avoid

Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately.

Failure to observe this precaution may result in excessive heat build-up causing exotherm.

Incompatible materials

Keep away from strong oxidizing agents. Avoid contact with Acids, Bases or unintended contact with amines.

Hazardous decomposition products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons and undetermined organics.

Section 11 Toxicological Information

Relevant routes of exposure

Skin, Inhalation, Eyes and Ingestion

Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. Adverse symptoms may include the following: respiratory tract irritation/coughing.

Skin contact: This product may cause irritation to the skin. May cause an allergic skin reaction. Adverse symptoms may include the following: irritation, redness or rash



Freeman 925 Part A (Resin)

Section 11 Toxicological Information

Eye contact: This product may cause serious eye irritation. Adverse symptoms may include the following: pain, irritation, watering or redness.

Ingestion: Irritating to mouth, throat and stomach. Adverse symptoms: No specific data.

Potential Chronic Effects

Immediate effects of short-term exposure: Not available Delayed effects of short-term exposure: Not available Immediate effects of long-term exposure: Not available Delayed effects of long-term exposure: Not available

Section 12 Ecological Information

Aquatic or Other Organisms Toxicity: No further relevant information available.

Information about elimination (Persistence and Degradability): No further relevant information available.

Bioaccumulation: No further relevant information available. **Mobility in soil:** No further relevant information available.

Other Adverse Effects: No known significant effects or critical hazards.

Section 13 Disposal Considerations

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers retain some product residue. Avoid spilled material and/or runoff with contact in soil, waterways, drains and sewers.

Section 14 Transport Information

DOT / TDG / IMDG / IATA

Not Regulated

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Section 15 Regulatory Information

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (SARA)

Sections 311 and 312 (Emergency Planning and Community Right-to-Know Act of 1986): See Section 2 **Section 313:** This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Date of Preparation: August 25, 2023 Page 5 of 6



Freeman 925 Part A (Resin)

Section 15 Regulatory Information

US State Regulations

Pennsylvania Worker and Community Right-To-Know Act: To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

Inventories

US TSCA Inventory (TSCA): All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16 Other Information

Disclaimer

The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole

remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.

Date of Initial Release: January 24, 2007 Date of Previous Revision: February 7, 2019



Freeman 925 Part B (Hardener)

Section 1 Identification

Product identifiers

Product name: Freeman 925 High-Temperature Hardener Part B (Hardener) Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Epoxy Casting Hardener - For Industrial Use Only

Details of the supplier of the safety data sheet

Freeman Manufacturing & Supply Company 1101 Moore Road, Avon, OH 44011 USA

Telephone: (440) 934-1902

Email: contactus@freemansupply.com

24 Hour emergency telephone number: CHEMTREC (800) 424-9300

Section 2 Hazards Identification

Classification in accordance with 29 CFR 1910.1200 (OSHA HCS)

Skin Corrosion/Irritation, Category 2 Eye Damage/Irritation, Category 2A Skin Sensitization, Category 1

Acute Toxicity, Oral, Category 4

Specific Target Organ Toxicity, Single Exposure (Respiratory tract irritation), Category 3

GHS Label Elements



Warning

Hazard Statements

H319 - Causes serious eye irritation.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H302 - Harmful if swallowed.

H335 - May cause respiratory irritation.

Precautionary Statements

Prevention: Do not eat, drink or smoke when using this product. Wash hands and face thoroughly after handling. Wear protective gloves/protective clothing. Wear eye and face protection. Avoid breathing dust, fume, gas, mist, vapors or spray. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace.

Response: If swallowed rinse mouth. Call poison center or doctor if you feel unwell.

If on skin wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

If in eyes rinse continuously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. If eye irritation persists: Get medical advice/attention.

If inhalation occurs, remove person to fresh air and get medical advice/attention if ill or concerned.

Storage: Store in a well-ventilated place. Keep cool. Keep container tightly closed when not in use.

Disposal: Dispose of contents and container to an appropriate waste site in accordance with local and national regulations.



Freeman 925 Part B (Hardener)

Section 3 Composition/Information on Ingredients

Ingredient Name	CAS Number
Diglycidyl Ether	17557-23-2
Diamine	68479-98-1
Safety Adducted Amine	140-31-8

There are no additional ingredients present, which within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4 First Aid Measures

Inhalation: Move person into fresh air. Get medical attention if you feel unwell.

Skin contact: Immediately wash off with soap and plenty of water. Remove contaminated clothing and wash before reuse. Get medical attention if symptoms occur.

Eye contact: Flush eyes with water for at least 15 minutes. Remove contact lenses if easy to do and continue rinsing. Get medical attention if irritation develops.

If Swallowed: Rinse mouth. Call poison center or doctor if you feel unwell.

Most important symptoms and effects, both acute and delayed

See Section 11 Information on toxicological effects

Indication of any immediate medical attention and special treatment required

Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

Section 5 Fire-Fighting Measures

Extinguishing Media

Suitable agents: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam or alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams or protein foams may function, but will be less effective. Water fog, applied gently may be used as a blanket for fire extinguishment.

Unsuitable agents: Do not use direct water stream, may spread fire.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur, and the container may burst.

Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide, carbon monoxide, or halogenated compounds.

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.



Freeman 925 Part B (Hardener)

Section 6 Accidental Release Measures

Environmental precautions

Avoid release to the environment. Prevent entry into sewer systems or bodies of water.

Methods and materials for containment and clean-up

Move containers from spill area. Absorb with an inert dry material until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Place in an appropriate waste disposal container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/ international regulations. For larger spills, dispose of via a licensed waste disposal contractor. Remove residual with soap and hot water. Solvents are not recommended for clean-up unless the recommended exposure guidelines and safe handling practices for the specific solvent are followed.

Section 7 Handling and Storage

Precautions for safe handling

For industrial/occupational use only. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (e.g., Chlorine, chromic acid etc.)

Conditions for safe storage, including any incompatibilities

For safe storage, store at or below 72°F (22°C). Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Store locked up.

Section 8 Exposure Controls/Personal Protection

Components with workplace control parameters

None

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits.

Personal Protective Equipment (PPE)

Eye Protection: Wear safety glasses equipped with side shields, or chemical goggles if splashing is possible. **Hand Protection:** The glove material must be impermeable and resistant to the product/the substance/the preparation. Due to missing tests no recommendation to the glove material can be given. Contaminated gloves should be replaced.

Body Protection: Prevent skin contact when handling material.

Respiratory Protection: The need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist prefilter should be used.

Safety Stations

Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

General Hygienic Practices

Avoid breathing vapor or mist. Avoid contamination of food, beverages, or smoking materials. Wash thoroughly after handling, and before eating, drinking or smoking. Remove contaminated clothing promptly and clean thoroughly before reuse.



Freeman 925 Part B (Hardener)

Section 9 Physical and Chemical Properties

Appearance Amber liquid

Odor Slight

Odor ThresholdNo data availablepHNo data availableMelting PointNo data available

VOC Content None

Boiling pointNo data availableFlash Point>126°C (>260°F)Evaporation rateNo data availableFlammability (solid, gas)No data availableUpper/lower flammabilityNo data available

Vapor pressure<1 mm Hg</th>Vapor density>5.04Relative density at 72°F8.57 lb./gal

Specific gravity 1.03 **Water Solubility** Slight

Coefficient: n-octanol/ waterNo data availableAuto-ignition temperatureNo data availableViscosityNo data available

Explosive PropertiesNoneOxidizing PropertiesNonePercent Solids100%Percent Volatiles0%

Section 10 Stability and Reactivity

Reactivity

No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

In normal storage hazardous reaction will not occur, reacts with amines.

Conditions to avoid

Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately. Failure to observe this precaution may result in excessive heat build-up causing exotherm.

Incompatible materials

Keep away from strong oxidizing agents. Avoid contact with Acids, Bases or unintended contact with amines.

Hazardous decomposition products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons and undetermined organics.

Section 11 Toxicological Information

Relevant routes of exposure

Skin, Inhalation, Eyes and Ingestion

Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. Adverse symptoms may include the following: respiratory tract irritation/coughing.



Freeman 925 Part B (Hardener)

Section 11 Toxicological Information

Skin contact: This product may cause irritation to the skin. May cause an allergic skin reaction. Adverse symptoms may include the following: irritation, redness or rash

Eye contact: This product may cause serious eye irritation. Adverse symptoms may include the following: pain, irritation, watering or redness.

Ingestion: Irritating to mouth, throat and stomach. Adverse symptoms: No specific data.

Potential Chronic Effects

Immediate effects of short-term exposure: Not available Delayed effects of short-term exposure: Not available Immediate effects of long-term exposure: Not available Delayed effects of long-term exposure: Not available

Section 12 Ecological Information

Aquatic or Other Organisms Toxicity: No further relevant information available.

Information about elimination (Persistence and Degradability): No further relevant information available.

Bioaccumulation: No further relevant information available. **Mobility in soil:** No further relevant information available.

Other Adverse Effects: No known significant effects or critical hazards.

Section 13 Disposal Considerations

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers retain some product residue. Avoid spilled material and/or runoff with contact in soil, waterways, drains and sewers.

Section 14 Transport Information

DOT / TDG / IMDG / IATA

Not Regulated

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Section 15 Regulatory Information

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Date of Preparation: August 25, 2023 Page 5 of 6



Freeman 925 Part B (Hardener)

Section 15 Regulatory Information

Superfund Amendments and Reauthorization Act of 1986 Title III (SARA)

Sections 311 and 312 (Emergency Planning and Community Right-to-Know Act of 1986): See Section 2 **Section 313:** This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Worker and Community Right-To-Know Act: To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65: This product does not contain any chemicals known to the State of California to cause cancer or birth defects or any other reproductive harm.

Inventories

US TSCA Inventory (TSCA): All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16 Other Information

Disclaimer

The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole

remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.

Date of Initial Release: January 3, 2007 Date of Previous Revision: January 3, 2023