

SAFFTY DATA SHFFT

This safety data sheet was created pursuant to the requirements of: 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)
Canada Hazardous Products Regulations (SOR/2015-17)

Revision date 05-Aug-2022 Revision Number 3

1. Identification

Product identifier

Product Name CAB-O-SIL® M-5 Untreated Fumed Silica

Other means of identification

Product Code(s) M5

Synonyms Silicon Dioxide, Synthetic Amorphous Silica, Pyrogenic (Fumed) Amorphous Silica

Recommended use of the chemical and restrictions on use

Recommended use Various, Rheological control, Flow agent, Anti-caking agent, Anti-blocking agent, Anti-settling agent,

Spray aid, Thickening agent, Carrier, Viscosity control agent, Glossing or matting agent, Chemical intermediate, Stabilization agent, Filler, Reinforcing agent in: Coatings, Adhesives and/or sealants, Silicone Elastomer, Rubber products, suspension, dispersion, Batteries, Cosmetics, Inks and toners,

Paints, Hygiene and sanitary products, Other

Restrictions on use None known.

Details of the supplier of the safety data sheet

Cabot Business & Technology Center Cabot Corporation

157 Concord Road 4400 North Point Parkway

Billerica, Massachusetts Suite 200

01821 Alpharetta, Georgia

United States 30022 Tel: +1 978 663 3455 United S

Fax: +1 678 297 1245

Emergency telephone number

Emergency Telephone US: CHEMTREC: 1-800-424-9300 or +1-703-527-3887

International CHEMTREC: +1 703-741-5970 or +1-703-527-3887

2. Hazard(s) identification

Classification

This product is not considered hazardous by either the US 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) or the Canadian Workplace Hazardous Material Information System (WHMIS 2015)

Label elements

Signal word None

Hazard statements

None

Precautionary statements

None

Other information

May cause mechanical irritation. Dust may be irritating to respiratory tract.

3. Composition/information on ingredients

Substance

Synonyms Silicon Dioxide, Synthetic Amorphous Silica, Pyrogenic (Fumed) Amorphous Silica

Chemical name	CAS No	Weight-%	Hazardous Material	Date HMIRA filed and
			Information Review Act	date exemption granted
			registry number (HMIRA	(if applicable)
			registry #)	
Synthetic Amorphous, Pyrogenic Silica	112945-52-5	> 99.9	-	-

Additional information

Regulatory information is found under the general silica: CAS RN 7631-86-9

The hyphen (-) means "not applicable".

4. First-aid measures

Description of first aid measures

Inhalation If cough, shortness of breath or other breathing problems occur, move to fresh air. Seek medical

attention if symptoms persist. If necessary, restore normal breathing through standard first aid

measures.

Eye contact In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention if symptoms occur.

Skin contact Wash skin with soap and water. Get medical attention if symptoms occur.

Ingestion Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an

unconscious person.

Most important symptoms and effects, both acute and delayed

Symptoms See Section 11 for additional Toxicological Information.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable Extinguishing Media Silica is non-combustible, therefore no extinguishing media needs to be identified.

Unsuitable extinguishing media None.

Specific hazards arising from the chemical None.

Hazardous combustion products None

Explosion data

Revision date 05-Aug-2022

Sensitivity to mechanical impact Sensitivity to static discharge

None

This material is an inorganic dust and will not create nor support conditions that would result in a dust explosion or fire. Take precautionary measures against static discharges. Avoid generation of dust. All metal parts of the mixing and processing equipment must be earthed/grounded. Ensure all equipment is electrically earthed/grounded before beginning transfer operations.

Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid generation of dust. Ensure adequate ventilation. Use personal protective equipment as

required. See section 8.

Environmental precautions

Environmental precautions Local authorities should be advised if significant spillages cannot be contained. See Section 12 for

additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Contain spilled product on land, if possible. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Clean up promptly by vacuum. Use of a vacuum with high efficiency particulate air (HEPA) filtration

is recommended. Do not create a dust cloud by using a brush or compressed air. Pick up and

transfer to properly labeled containers. See section 13.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Avoid contact with skin and eyes. Avoid generation of dust. Do not breathe dust. Provide

appropriate local exhaust ventilation at machinery and at places where dust can be generated. Do

not create a dust cloud by using a brush or compressed air.

Take precautionary measures against static discharges. All metal parts of the mixing and processing equipment must be earthed/grounded. Ensure all equipment is electrically earthed/grounded before beginning transfer operations. Fine dust is capable of penetrating electrical equipment and

may cause electrical shorts.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Do not store together with volatile

chemicals as they may be adsorbed onto product. Store at ambient conditions. Keep in properly

labeled containers.

8. Exposure controls/personal protection

Control parameters

Exposure Limits The table below is a summary. Please see the specific legislation for complete information.

Chemical name	Amorphous Silica	
	7631-86-9	
OSHA PEL	(vacated) TWA: 6 mg/m ³	
Chemical name	Dust, or particulates not otherwise specified	

	RR-00072-6	
ACGIH TLV	TWA: 10 mg/m ³ inhalable particles, recommended	
	TWA: 3 mg/m³ respirable particles, recommended	
OSHA PEL	TWA: 15 mg/m³ total dust; 5 mg/m³ respirable fraction	
	(vacated) TWA: 15 mg/m³ total dust; 5 mg/m³ respirable fraction	
Alberta	TWA: 10 mg/m³ total; 3 mg/m³ respirable	
British Columbia	TWA: 10 mg/m³ total dust; 3 mg/m³ respirable fraction	
Ontario	TWA: 10 mg/m³ inhalable fraction; 3 mg/m³ respirable fraction	
Quebec	TWA: 10 mg/m³ total dust	

Other information In its facilities globally, Cabot Corporation manages silica to the Germany TRGS 900 occupational

exposure limit of 4 mg/m³, TWA, Inhalable fraction.

Appropriate engineering controls

Engineering controls Ensure adequate ventilation to maintain exposures below occupational limits. Provide appropriate

local exhaust ventilation at machinery and at places where dust can be generated. Ensure that

eyewash stations and safety showers are close to the workstation location.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves to prevent soiling of hands. Use protective barrier cream before handling

the product.

Skin and body protection Wear suitable protective clothing. Wash contaminated clothing before reuse. Contaminated work

clothing should not be allowed out of the workplace.

Respiratory protection Approved respirator may be necessary if local exhaust ventilation is not adequate.

Environmental exposure controls In accordance with all local legislation and permit requirements as applicable for dusts.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Solid
Appearance Powder
Color white
Odor None

Odor threshold Not applicable

Property
pHValues
3.6 - 4.5Remarks • Method
In-house testing

Melting point / freezing point 1700 °C NIOSH Pocket Guide to Chemical Hazards
Boiling point / boiling range 2230 °C NIOSH Pocket Guide to Chemical Hazards

Flash point Not combustible Evaporation rate Not applicable

Flammability (solid, gas)

Not flammable. Product resists ignition and does not

promote flame spread

Flammability Limit in Air

Vapor pressure

Relative vapor density

Relative density

2.2

Not applicable

Not applicable

2.2

@ 20 °C

Water solubility Soluble According to OECD 105, enhanced

Solubility(ies) No data available
Partition coefficient Not applicable

Revision date 05-Aug-2022

Autoignition temperature Not applicable Not applicable Decomposition temperature Kinematic viscosity Not applicable Not applicable Dynamic viscosity

Other information

Explosive properties Oxidizing properties **Bulk density**

Non-explosible

No Oxidizing properties

30-150 kg/m³ DIN/ISO 787:11

10. Stability and reactivity

Reactivity Not reactive. Substance is an inert inorganic solid.

Chemical stability Stable under normal conditions. Stable under recommended storage conditions.

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to avoid None known.

Incompatible materials None known

Hazardous decomposition products None known

Toxicological information

Acute toxicity

> 5000 mg/kg (rat). No deaths occurred and no signs of toxicity were seen during the Oral LD50

observation periods after single oral administration of silica(OECD 401).

Dermal LD50 > 2000 mg/kg (rabbit). Very slight transient erythema in one animal. No signs of systemic or

organ toxicity (OECD 402).

Inhalation LC50 Due to the product's physical characteristics, no suitable testing procedure is available.

Skin corrosion/irritation Primary irritation index = 0/8 @ 24 hr. Not classified as an irritant (OECD 404).

Draize score 1.0/110 @ 24 hr. Not classified as an irritant in rabbit studies (OECD 405). High dust Serious eye damage/eye irritation

concentrations may cause mechanical irritation.

No experimental animal data are available. No cases of sensitization in humans have been Respiratory or skin sensitization

reported.

Not mutagenic in AMES Test. Negative in the unscheduled DNA synthesis assay. Negative in the Germ cell mutagenicity

chromosome aberration test in Chinese hamster ovary (CHO) cells.

No evidence of carcinogenicity was observed in multiple animal species following repeated oral or Carcinogenicity

inhalation exposure to amorphous silica. Similarly, epidemiology studies show no evidence of

carcinogenicity in workers who manufacture amorphous silica.

Reproductive toxicity No effects on reproductive organs or fetal development have been reported in animal toxicity

studies.

STOT - single exposure Based on available data, specific target organ toxicity is not expected after single oral, single

inhalation, or single dermal exposure.

Revision date 05-Aug-2022

STOT - repeated exposure Repeated dose toxicity: oral (rat), 2 weeks to 6 months, no significant treatment-related adverse

effects at doses of up to 8% silica in the diet.

Repeated dose toxicity: inhalation (rat), 13 weeks, Lowest Observed Effect Level (LOEL) = 1.3 mg/m³

based on mild reversible effects in the lungs.

Repeated dose toxicity: inhalation (rat), 90 days, LOEL = 1 mg/m³ based on reversible effects in the

lungs and effects in the nasal cavity.

Repeated dose toxicity using SAS 400 m2/g: inhalation (rat), 90 days, fully reversible inflammation related to clearance processes following recovery period. NOAEC (lung) based on histopathology

and inflammatory marker is 5 mg/m³

Based on available data, a STOT-RE classification is not warranted.

Target organ effects Lungs

Aspiration hazard Based on industrial experience and available data, no aspiration hazard is expected.

Other adverse effects No information available.

12. Ecological information

Ecotoxicity Fish (Brachydanio rerio) LC50 (96 h): > 10,000 mg/l; (Method: OECD 203).

No acute toxicity to Daphnia with EL and EL50 ranging from >1000 to 10,000 mg/L (OECD 202).

Persistence and degradability The methods for determining biodegradability are not applicable to inorganic substances.

Bioaccumulation Not expected due to physicochemical properties of the substance.

Mobility Not expected to migrate.

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with federal, state and local regulations. Dispose of waste in accordance

with environmental legislation.

Contaminated packaging Dispose of contents/container in accordance with local, regional, national, and international

regulations as applicable.

US EPA Waste Number Unused product is not a hazardous waste under U.S. RCRA, 40 CFR 261

14. Transport information

DOT Not regulated

<u>TDG</u> Not regulated

MEX Not regulated

ICAO (air) Not regulated

IATA Not regulated

IMDG Not regulated

RID Not regulated

ADR Not regulated

<u>ADN</u> Not regulated

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

TSCA Complies

Chemical name	CAS No	US TSCA Inventory listing	US TSCA inactive/active designation
Synthetic Amorphous, Pyrogenic Silica	112945-52-5	Present	Active

DSL/NDSL Complies Complies **EINECS/ELINCS** Complies **ENCS** Complies **IECSC KECL** Complies **PICCS** Complies Complies AICS Complies **TCSI** NZIoC Complies

Note:

Regulatory information is found under the general silica: CAS RN 7631-86-9

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

TCSI - Taiwan Chemical Substance Inventory

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

TSCA Section 12(b) Export Regulations

This product does not contain any components that are subject to TSCA 12(b) Export Notification.

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

Clean Air Act Amendments of 1990 (CAA, Section 112, 40 CFR 82)

This product does not contain any components listed as a Hazardous Air Pollutant, Flammable Substance, Toxic Substance, or Class 1 or 2 Ozone Depletor.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Synthetic Amorphous, Pyrogenic	-	X	Х
Silica			
112945-52-5			

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

Key literature references and sources for data used to compile the SDS

NIOSH Pocket Guide to Chemical Hazards, September 2005. "Silica, amorphous". DHHS (NIOSH) Publication No. 2005-149. National Technical Information Service, Springfield, VA. p. 277

Prepared By Cabot Corporation - Safety, Health and Environmental Affairs.

Revision date 05-Aug-2022

Revision Note Revisions to Section(s) 8, 11

Disclaimer

The information set forth is based on information that Cabot Corporation believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and Cabot assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede

All names annotated with the ® or ™ symbol are trademarks of the Cabot Corporation or its affiliates

End of Safety Data Sheet