

P.O. Box 4980
The Woodlands, TX 77387-4980

8 am to 5 pm Phone: (800) 257-5547
24-Hour Emergency Phone: (800) 328-8501
International Emergency Phone: (409) 727-0831
Asia Pacific Emergency Phone: (65) 6336-6011

Effective Date: 1/14/10


Material Safety Data Sheet

MSDS No: 6061

1. PRODUCT IDENTIFICATION

Trade Name: RenGel 3260

Chemical Family: Epoxy



NFPA RATING

Health:	2
Flammability:	2
Reactivity:	0
Personal Protection:	

HMIS RATING

Synonyms:
RP 3260 Resin

Intended Use or Product Type: Blue, abrasion resistant surface coat resin

2. COMPOSITION / INFORMATION ON INGREDIENTS

O S H A	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS				CARCINOGEN STATUS			
			ACGIH		OSHA		MFR.	IARC	NTP	OSHA
			TWA	STEL	PEL	STEL				
*	2426-08-6	Oxirane, (Butoxymethyl)- Common Name: Butyl glycidyl ether Concentration: 1.00 - 5.00 % by wt	25 ppm	NE	50 ppm	NE	Table Z1A TWA 25 ppm	NR	NR	NR
*	25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane Common Name: Bisphenol A diglycidyl ether polymer Concentration: 30.00 - 60.00 % by wt	NE	NE	NE	NE	NE	NR	NR	NR
	1345-05-7	Lithopone Concentration: 10.00 - 30.00 % by wt	NE	NE	NE	NE	NE	NR	NR	NR
	409-21-2	Silicon Carbide (SIC) Concentration: 30.00 - 60.00 % by wt	10 mg/m3	NE	5 mg/m3	NE	NE	NR	NR	NR

NE = Not Established NR = Not Reviewed * = OSHA Hazardous Ingredient

3. HAZARDS IDENTIFICATION

Emergency Overview: Combustible. Causes skin and eye irritation. May cause allergic skin and respiratory reactions.



Effective Date: 1/14/10

Primary Route(s) of Entry: Dermal; heated product may produce inhalable vapors.

Carcinogenicity (NTP, IARC, OSHA): This product contains carbon black which is classified as a carcinogen by IARC (2B, possibly carcinogenic to humans) and NIOSH.

Chronic: Butyl Glycidyl Ether (BGE) may have effects on central nervous and reproductive systems.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Skin: Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes. Seek immediate medical attention.

Inhalation: Remove to fresh air. Seek immediate medical attention.

Eyes: Immediately flush eyes with water for at least 15 minutes. Seek immediate medical attention.

Overexposure Effects: Skin and eye irritation and allergic skin and respiratory reactions.

Medical Conditions Aggravated by Exposure: Skin and eye conditions.

Additional Information: Referral to a physician is recommended if there is any question about the seriousness of any injury.

5. FIRE FIGHTING MEASURES

Flash Point: 170°F (77 °C)

Flash Point Method Used: PMCC

Flammable Limits in Air (Lower - % by volume): Not established

Flammable Limits in Air (Upper - % by volume): Not established

Fire Fighting Extinguishing Media: Carbon dioxide, dry chemical, foam, water.

Fire Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Decomposition and combustion products may be toxic.

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Remove spillage by absorbing in absorbent material.

7. HANDLING AND STORAGE

Signal Word: Warning!

Effective Date: 1/14/10

Precautions: Combustible. Keep away from heat and flame. Can cause skin irritation, eye irritation, allergic respiratory reaction, and allergic skin reaction. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated breathing of vapor or mist. Keep container closed when not in use. Use with adequate ventilation. Wash thoroughly after handling.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Skin Protection: Wear impermeable gloves.

Respiratory Protection: Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Engineering Controls: General mechanical and local exhaust in accordance with ACGIH recommendations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Blue Opaque
Odor:	Slight Ethereal
Physical State:	Liquid
Solubility in Water:	Insoluble
Vapor Pressure:	9.57 mm Hg at 55°C (131 °F)
Specific Gravity:	1.88 - 1.96 (water = 1)
Boiling Point:	Not Determined
Melting Point:	Not Determined
Evaporation Rate:	Not Determined
Density:	Not Determined
Vapor Density:	Not Determined
VOC:	42.97 g/L
pH:	Not Determined
Coefficient of water/oil:	Not Determined

Percent Volatile: Not determined.

10. STABILITY AND REACTIVITY

Conditions to Avoid: Excessive heat for prolonged periods of time.

Stability: Stable.

Incompatibility: Strong oxidizers, acids and bases.

Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Effective Date: 1/14/10

Acute Oral Effects (LD50): Unspecified**Acute Dermal Toxicity (LD50):** For Butyl Glycidyl Ether (BGE): > 2150 mg/kg (rabbits) [from RTECS]**Inhalation Toxicity (LC50):** for Butyl Glycidyl Ether (BGE): 1030 ppm/8 hour**Sensitization:** May cause allergic skin reaction and respiratory sensitivity in some people.**Skin Irritation:** Irritant.**Eye Irritation:** Irritant.**Reproduction:** Inhalation of Butyl Glycidyl Ether (38, 75, 150 or 300 ppm [0.20, 0.40, 0.799, or 1.60 g/m³] for 7 hours per day, 5 days per week for 10 weeks produced atrophic testes in 4 of 5 surviving rats at 300 ppm, very small testes in 1 of 10 rats at 150 ppm, and slightly patch atrophy of the testes in 1 of 10 rats at 75 ppm.**Mutagenicity:** Butyl glycidyl ether (BGE) was found to be mutagenic in a number of in vitro tests. In vivo studies have shown mixed mutagenic results.**Sub-Chronic:** Diglycidyl ether of bisphenol A, applied to the skin of rats five times per week for approximately 13 weeks, caused no apparent systemic toxicity with the exception of decreased body weight and body weight gain.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

14. TRANSPORT INFORMATION

DOT: Non-Bulk

Proper Shipping Name:	Environmentally hazardous substance, liquid, n.o.s.
Technical Shipping Name (If n.o.s.):	Bisphenol A epoxy resin
Hazard Class:	9
ID Number:	UN 3082
Packing Group:	PG III
Marine Pollutant:	Marine Pollutant

IATA: Non-Bulk

Proper Shipping Name:	Environmentally hazardous substance, liquid, n.o.s.
Technical Shipping Name (If n.o.s.):	Bisphenol A epoxy resin
Hazard Class:	9
ID Number:	UN 3082
Packing Group:	PG III
Marine Pollutant:	Marine Pollutant

IMDG: Non-Bulk

Proper Shipping Name:	Environmentally hazardous substance, liquid, n.o.s.
Technical Shipping Name (If n.o.s.):	Bisphenol A epoxy resin
Hazard Class:	9
ID Number:	UN 3082

Effective Date: 1/14/10

Packing Group:	PG III
Marine Pollutant:	Marine Pollutant
TDG: Non-Bulk	
Proper Shipping Name:	Environmentally hazardous substance, liquid, n.o.s.
Technical Shipping Name (If n.o.s.):	Bisphenol A epoxy resin
Hazard Class:	9
ID Number:	UN 3082
Packing Group:	PG III
Marine Pollutant:	Marine Pollutant

Department of Transportation: Under 49 CFR 171.4 (c) NONBULK shipments of marine pollutants are not regulated for transport by motor vehicles, rail cars or aircraft. NONBULK shipments of marine pollutants are regulated when transported by vessel (ship).

15. REGULATORY INFORMATION

US Federal Regulations:

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261).

SARA Title III: Section 313 Toxic Chemical List (TCL): This product does not contain any chemicals for routine annual toxic chemical release reporting under Section 313 (40 CFR 372).

TSCA Section 8(b) - Inventory Status: All chemical components of this product are in compliance with TSCA inventory requirements.

TSCA Section 12(b) - Export Notification: This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.

International Regulations:

Canadian Inventory Status: This product contains only chemicals that are currently listed on the Canadian Domestic Substance List.

Canadian WHMIS: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. B3 D2A D2B

European Inventory Status (EINECS): This product contains one or more chemicals currently not on the European Inventory of Existing Commercial Chemical Substances (EINECS) or Pre-market notified.

Japanese Inventory Status: This product contains only chemicals currently listed on the Japanese Ministry of International Trade and Industry List of Existing and New Chemical Substances.

State Regulations:

California Proposition 65: This product does not contain any chemicals currently on the California list of Known Carcinogens and Reproductive Toxins.

Effective Date: 1/14/10

Pennsylvania Right-to-Know: The following is required composition information:

Chemical Name: Silicon Carbide (SiC)
CAS Number: 409-21-2
Comment: Hazardous Substance

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane
Common Name: Bisphenol A diglycidyl ether polymer
CAS Number: 25068-38-6
Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: Lithopone
CAS Number: 1345-05-7
Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: Oxirane, (Butoxymethyl)-
Common Name: Butyl glycidyl ether
CAS Number: 2426-08-6
Comment: Hazardous Substance

16. OTHER INFORMATION

MSDS No:	6061
Reason Issued:	1/10 update DOT
Approved By:	Matt Austin
Title:	EHS Chemist

Other Information: WLW/T (W10022530)

Disclaimer: The information and recommendations contained herein are based upon tests in controlled laboratory conditions, are believed to be correct, and are provided for the sole purpose of hazard communication as part of Huntsman's product safety program. This product has not been tested for, and therefore is not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for any such uses.

The information and recommendations contained herein are not intended to constitute performance information concerning the product, which is available in separate technical data sheets available from Huntsman upon request. Users are urged, and are urged to urge others who may come in contact with the product, to obtain and consult data sheets prior to purchase, use, transportation or storage of the product.

HUNTSMAN MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY, QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED TO REIMBURSEMENT OF BUYER'S PURCHASE PRICE, OR IN HUNTSMAN'S DISCRETION REPLACEMENT, OF THE PRODUCT IN RESPECT OF WHICH SUCH CLAIM IS MADE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED BY LEGAL NOTICES IN TECHNICAL DATA SHEETS, PRODUCT LITERATURE, AND/OR SALE DOCUMENTS. The foregoing DISCLAIMERS and LIMITATION OF LIABILITY supercede inconsistent or contradictory provisions in Buyer's documents.

USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENTAL AGENCY TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.

Effective Date: 1/14/10

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.



P.O. Box 4980
The Woodlands, TX 77387-4980

8 am to 5 pm Phone: (800) 257-5547
24-Hour Emergency Phone: (800) 328-8501
International Emergency Phone: (409) 727-0831
Asia Pacific Emergency Phone: (65) 6336-6011

Effective Date: 10/3/08


Material Safety Data Sheet

MSDS No: 6060

1. PRODUCT IDENTIFICATION

Trade Name: Ren 3260

Chemical Family: Amine



NFPA RATING

Health:	3*
Flammability:	1
Reactivity:	0
Personal Protection:	

HMIS RATING

Synonyms:

RP 3260 Hardener

Intended Use or Product Type: Surface coat and casting hardener

2. COMPOSITION / INFORMATION ON INGREDIENTS

O S H A	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS				CARCINOGEN STATUS			
			ACGIH		OSHA		MFR.	IARC	NTP	OSHA
			TWA	STEL	PEL	STEL				
*	111-40-0	1,2-Ethanediamine, N-(2-aminoethyl)- Diethylenetriamine Common Name: Concentration 15.00 - 40.00 % by wt	1 ppm	NE	NE	NE	NE	NR	NR	NR
*	68610-56-0	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane, diethylenetriamine-terminated Amine adduct Common Name: Concentration 15.00 - 40.00 % by wt	NE	NE	NE	NE	NE	NR	NR	NR
*	80-05-7	Phenol, 4,4'-(1-methylethylidene)bis- Common Name: Concentration 10.00 - 30.00 % by wt	NE	NE	NE	NE	TLV 5 mg/m3	NR	NR	NR

NE = Not Established NR = Not Reviewed * = OSHA Hazardous Ingredient

3. HAZARDS IDENTIFICATION

Emergency Overview: Corrosive - causes skin and eye burns. Can cause allergic respiratory reaction and allergic skin reaction. Can be harmful if absorbed through skin and may be harmful if swallowed.



Primary Route(s) of Entry: Dermal; heated product may produce inhalable vapors.

Acute Exposure: Corrosive. Causes skin and eye burns.

Chronic: Overexposure may have effects on developing fetus.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Skin: Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes. Seek immediate medical attention.

Inhalation: Remove to fresh air. Seek immediate medical attention.

Eyes: Immediately flush eyes with water for at least 15 minutes. Seek immediate medical attention.

Overexposure Effects: Corrosive - causes skin and eye burns. Can cause allergic respiratory reaction and allergic skin reaction. Can be harmful if absorbed through skin and may be harmful if swallowed.

Medical Conditions Aggravated by Exposure: Skin, eye and pulmonary conditions.

Additional Information: Referral to a physician is recommended if there is any question about the seriousness of any injury.

5. FIRE FIGHTING MEASURES

Flash Point:	> 250°F (> 121 °C)
Flash Point Method Used:	PMCC
Flammable Limits in Air (Lower - % by volume):	Not established
Flammable Limits in Air (Upper - % by volume):	Not established

Fire Fighting Extinguishing Media: Carbon dioxide, dry chemical, foam, water.

Fire Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Decomposition and combustion products may be toxic.

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Remove spillage by absorbing in absorbent material.

7. HANDLING AND STORAGE

Signal Word: Danger!

Effective Date: 10/3/08

Precautions: Corrosive - causes skin and eye burns. Can cause allergic respiratory reaction and allergic skin reaction. Can be harmful if absorbed through skin and may be harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid breathing vapor or mist. Avoid tasting or swallowing. Keep container closed when not in use. Use with adequate ventilation. Wash thoroughly after handling. Notice! Overexposure may have effects on developing fetus.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Skin Protection: Wear impermeable gloves.

Respiratory Protection: Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Engineering Controls: General mechanical and local exhaust in accordance with ACGIH recommendations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Amber
Odor:	Ammonia
Physical State:	Clear liquid
Solubility in Water:	Slight
Vapor Pressure:	< 2.34 mm Hg at 70°C (158 °F)
Specific Gravity:	1.06 - 1.09 (water = 1)
Boiling Point:	> 400°F (> 204 °C)
Melting Point:	Not Determined
Evaporation Rate:	Not Determined
Density:	Not Determined
Vapor Density:	Not Determined
VOC:	405 g/L
pH:	Not Determined
Coefficient of water/oil:	Not Determined

Percent Volatile: Not determined.

10. STABILITY AND REACTIVITY

Conditions to Avoid: Excessive heat for prolonged periods of time.

Stability: Stable.

Incompatibility: Strong oxidizers, acids and bases.

Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Effective Date: 10/3/08

Acute Oral Effects (LD50): Component(s) are slightly toxic, 500 - 5000 mg/kg (rat).
Diethylenetriamine= 1080 - 2330 mg/kg (rat)

Acute Dermal Toxicity (LD50): Component(s) are toxic, 200 - 1000 mg/kg (rabbit).
Diethylenetriamine= 672 - 1240 mg/kg (rabbit)

Sensitization: May cause allergic skin reaction and respiratory sensitivity in some people.

Skin Irritation: Corrosive.

Eye Irritation: Corrosive.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

14. TRANSPORT INFORMATION

DOT: Non-Bulk

Proper Shipping Name:	Diethylenetriamine Mixture
Hazard Class:	8
ID Number:	UN 2079
Packing Group:	PG II
Label:	Corrosive

IATA:

Proper Shipping Name:	Diethylenetriamine Mixture
Hazard Class:	8
ID Number:	UN 2079
Packing Group:	PG II
Label:	Corrosive

IMDG: Non-Bulk

Proper Shipping Name:	Diethylenetriamine Mixture
Hazard Class:	8
ID Number:	UN 2079
Packing Group:	PG II
Label:	Corrosive

TDG: Non-Bulk

Proper Shipping Name:	Diethylenetriamine Mixture
Hazard Class:	8
ID Number:	UN 2079
Packing Group:	PG II
Label:	Corrosive

15. REGULATORY INFORMATION

Effective Date: 10/3/08

US Federal Regulations:

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261) but handle with care due to corrosive effect on skin and eyes.

SARA Title III: Section 313 Toxic Chemical List (TCL): This product contains a toxic chemical(s) for routine annual toxic chemical release reporting under section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this material.

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-

Common Name: Bisphenol A

Percent in Composition: 10 - 30 % by wt

Comment:

TSCA Section 8(b) - Inventory Status: All chemical components of this product are in compliance with TSCA inventory requirements.

TSCA Section 12(b) - Export Notification: This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.

International Regulations:

Canadian Inventory Status: This product contains only chemicals that are currently listed on the Canadian Domestic Substance List.

Canadian WHMIS: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. D1B D2A D2B E

State Regulations:

California Proposition 65: This product does not contain any chemicals currently on the California list of Known Carcinogens and Reproductive Toxins.

Pennsylvania Right-to-Know: The following is required composition information:

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane, diethylenetriamine-terminated

Common Name: Amine adduct

CAS Number: 68610-56-0

Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: 1,2-Ethanediamine, N-(2-aminoethyl)-

Common Name: Diethylenetriamine

CAS Number: 111-40-0

Comment: Hazardous Substance

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-

Common Name: Bisphenol A

CAS Number: 80-05-7

Effective Date: 10/3/08

Comment: Environmental Hazardous Substance

16. OTHER INFORMATION

MSDS No: 6060
Approved By: Dianne Blessing
Title: EH&S Specialist

Disclaimer: The information and recommendations contained herein are based upon tests in controlled laboratory conditions, are believed to be correct, and are provided for the sole purpose of hazard communication as part of Huntsman's product safety program. This product has not been tested for, and therefore is not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for any such uses.

The information and recommendations contained herein are not intended to constitute performance information concerning the product, which is available in separate technical data sheets available from Huntsman upon request. Users are urged, and are urged to urge others who may come in contact with the product, to obtain and consult data sheets prior to purchase, use, transportation or storage of the product.

HUNTSMAN MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY, QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED TO REIMBURSEMENT OF BUYER'S PURCHASE PRICE, OR IN HUNTSMAN'S DISCRETION REPLACEMENT, OF THE PRODUCT IN RESPECT OF WHICH SUCH CLAIM IS MADE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED BY LEGAL NOTICES IN TECHNICAL DATA SHEETS, PRODUCT LITERATURE, AND/OR SALE DOCUMENTS. The foregoing DISCLAIMERS and LIMITATION OF LIABILITY supercede inconsistent or contradictory provisions in Buyer's documents.

USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENTAL AGENCY TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.