



Product Name:

Por-A-Foam, Polyol Side A

I. Basic Information:


Supplier: PUMA Polymers

Address: 2003 Curtain Pole Rd, P.O. Box 5413

City, ST Zip: Chattanooga, TN 37406

Emergency Phone: 423-697-0499

Transportation Emergency Phone: Chem-trec 1-800-424-9300



Chemical State: [X] Liquid [] Gas [] Solid Chemical Type: [] Pure [X] Mixture

II. Ingredients:

Table with 10 columns: CAS No., Chemical Name, % Range, EHS, NTP, IARC, SUB Z, SARA 313, OSHA PEL, ACGIH TLV, Other Limits. Lists ingredients like 1,4-diazabicyclo[2.2.2]octane, Diethyl-N,N-bis(2-hydroxyethyl) aminomethyl phosphonate, etc.

III. Hazardous Identification:

Hazard Category: ACUTE

Hazardous Identification Information:

Warning!

Amber liquid with a slight ammoniacal odor.

Contact may cause skin and eye irritation.

IV. First Aid Measures:

Route(s) of Entry: Inhalation, Ingestion, Skin and Eye contact.

Health Hazards (Acute and Chronic):

Acute (Short-Term)

Contact may cause skin and eye irritation.

Signs and Symptoms:

Skin and eye irritation.

Medical Conditions Generally Aggravated by Exposure: None known

Emergency and First Aid Procedures:

SKIN CONTACT: Remove contaminated clothing and wash affected area with isopropyl alcohol followed by soap and water.

EYE CONTACT: Flush eyes with water for at least 15 minutes and contact a physician.

INGESTION: Do NOT induce vomiting. Take 1-2 glasses of water and contact a physician. Do not give anything by mouth to an unconscious person.

INHALATION: Remove person to fresh air. If person is not breathing give mouth-to-mouth resuscitation and contact a physician.





Material Safety Data Sheet **No. 116908**

Page 2 of 3

Printed:

06/01/2009

Last Update:

04/04/2008

Product Name:

Por-A-Foam, Polyol Side A

Other Health Warnings

Wash hands thoroughly after handling this material, before eating, smoking, etc.

V. Fire Fighting Measures:

Flash Point: 395°F **Lower Explosive Limit:** NE **Upper Explosive Limit:** NE

Fire Extinguishing Media:

Foam, water fog, carbon dioxide or dry chemical extinguishers.

Special Fire Fighting Procedures:

Firefighters should wear a self-contained breathing apparatus and protective clothing to guard against incompletely combusted carbon products.

Unusual Fire and Explosion:

None known

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Cover liquid with an absorbent material (sawdust, vermiculite or wet sand). After the material is absorbed scoop up and place in containers for disposal.

VII. Handling and Storage:

Precautions to be Taken:

Store in a cool, dry place in tightly sealed containers. Protect from heat and moisture contamination.

Other Precautions:

Avoid contact with skin and eyes. Avoid ingestion.

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

Local Exhaust: Provide mechanical (general) and/or local exhaust ventilation to control airborne levels.

Personal Protective Equipment:

RESPIRATORY PROTECTION: None needed at normal temperatures. Use a self-contained breathing apparatus under emergency conditions.

PROTECTIVE GLOVES: Impervious rubber gloves.

EYE PROTECTION: Wear safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: An apron or suitable clothing to prevent skin contact.

IX. Physical and Chemical Properties:

Boiling Point: NE **Melting Point:** NA **Evaporation Rate:** NA

Vapor Pressure (mm Hg.): NE **Vapor Density (AIR = 1):** NA

Solubility In Water: Soluble

Appearance and Odor: Amber liquid, low odor.

Other Information: VOLATILITY @75°F: Very Low
PERCENT VOLATILE BY VOLUME(%): Negligible
SPECIFIC GRAVITY: 1.1

X. Stability and Reactivity:

Stability:

Stable

Incompatibility (Materials to Avoid):

Strong oxidizers and alkalis. Under wet, alkaline conditions may partially hydrolyze slowly and nonviolently to form an acidic material.





Product Name:

Por-A-Foam, Polyol Side A

Decomposition/By Products:

Incompletely burned carbon products, carbon monoxide and carbon dioxide, phosphoric acid. Nitrogen and phosphorous oxides.

Hazardous Polymerization:

Will not occur

XI. Toxicological Information:

None available

XII. Ecological Information:

None available

XIII. Disposal Considerations:

Waste must be disposed of in accordance with federal, state and local environmental regulations. Incinerate or bury in a licensed facility. Containers may be disposed of or reclaimed in a routine manner.

XIV. Transport Information:

Not regulated by DOT

XV. Regulatory Information:

TSCA Inventory Status: This product, or its components, are listed on, or are exempt from the Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

SARA 313 INFORMATION: This product does not contain substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

XVI. Other Information:

In this document the following abbreviations were used:

NA: Not Applicable NE: Not Established





Material Safety Data Sheet

No. 117908

Page 1 of 4

Printed:

06/01/2009

Last Update:

04/04/2008

Product Name:

Por-A-Foam, Iso Side B

I. Basic Information:


Supplier: PUMA Polymers

Address: 2003 Curtain Pole Rd, P.O. Box 5413

City, ST Zip: Chattanooga, TN 37406

Emergency Phone: 423-697-0499

Transportation Emergency Phone: Chem-trec 1-800-424-9300



Chemical State: Liquid Gas Solid Chemical Type: Pure Mixture

II. Ingredients:

CAS No.	Chemical Name	% Range	EHS	NTP	IARC	SUB Z	SARA 313	OSHA PEL	ACGIH TLV	Other Limits
2644740	Diphenylmethane Diisocyanate (MDI) Mixed isomers	1-5								
101688	4,4' - Diphenylmethane Diisocyanate (MDI)	35-45					X	0.02 ppm	0.005 ppm	NE
9016879	Polymeric MDI	40-55					X	NE	NE	NE

III. Hazardous Identification:

Hazard Category: ACUTE CHRONIC REACTIVE

Hazardous Identification Information:

Warning!

Contains 4,4' -Diphenylmethane Diisocyanate (4,4'-MDI)

Brown liquid with a musty odor.

May cause eye, skin and respiratory tract irritation.

IV. First Aid Measures:

Route(s) of Entry: Inhalation, Ingestion, Skin and Eye contact.

Health Hazards (Acute and Chronic):

Acute (Short-Term)

Inhalation of vapors may cause irritation of the mucous membranes in the respiratory tract, running nose and sore throat. Contact may cause slight irritation of the skin and eyes (tearing).

Chronic (Delayed)

Repeated or prolonged inhalation of MDI vapors above the TLV of 0.02 ppm can cause immediate or delayed respiratory sensitization and asthma-like conditions. Prolonged skin contact can cause reddening, swelling or skin sensitization in susceptible individuals.

Signs and Symptoms:

Skin, eye and respiratory tract irritation.

Medical Conditions Generally Aggravated by Exposure: Prolonged skin contact can cause reddening, swelling or skin sensitization

Emergency and First Aid Procedures:





Material Safety Data Sheet **No. 117908**

Page 2 of 4

Printed:

06/01/2009

Last Update:

04/04/2008

Product Name:

Por-A-Foam, Iso Side B

SKIN CONTACT: Remove contaminated clothing and wash affected area with isopropyl alcohol followed by soap and water.

EYE CONTACT: Flush eyes with water for at least 15 minutes and contact a physician.

INGESTION: Do NOT induce vomiting. Do not give anything by mouth to an unconscious person.

INHALATION: Remove person to fresh air. If person is not breathing give mouth-to-mouth resuscitation and contact a physician.

Other Health Warnings

Due to the low volatility of MDI vapors, high exposures are not anticipated unless the material is overheated or sprayed as an aerosol in the air.

V. Fire Fighting Measures:

Flash Point: 390°F **Lower Explosive Limit:** NE **Upper Explosive Limit:** NE

Fire Extinguishing Media:

Foam, carbon dioxide, dry chemical and Halon 1211. If water is used, it should be used in very large quantities.

Special Fire Fighting Procedures:

Firefighters should wear a full face positive pressure self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion:

Contamination of isocyanates with water releases carbon dioxide which may result in a dangerous amount of pressure build-up in closed containers. Do NOT reseal contaminated containers. Personnel must be evacuated. Use cold water to cool fire exposed containers.

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Cover liquid with an absorbent material (sawdust, vermiculite or wet sand). After the material is absorbed scoop up and place in containers. Treat material with the prepared decontamination solution and leave the container open in a well ventilated area for 48 hours. Spill area should also be decontaminated with the following decontamination solution: 90% water, 2% detergent and 8% concentrated ammonia or sodium carbonate.

VII. Handling and Storage:

Precautions to be Taken:

Store in tightly closed containers at 50-100°F in a dry ventilated area away from sources of heat, moisture and incompatibles. Do NOT reseal containers if water contamination is suspected.

Other Precautions:

Avoid contact with skin and eyes. Avoid breathing vapors.

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

Local Exhaust: Provide mechanical (general) and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

Personal Protective Equipment:

RESPIRATORY PROTECTION: None needed at normal temperatures. Use a self-contained breathing apparatus for high concentrations and under emergency conditions.

PROTECTIVE GLOVES: Impervious rubber gloves.

EYE PROTECTION: Wear safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: An apron or suitable clothing to prevent skin contact.





Product Name:

Por-A-Foam, Iso Side B

IX. Physical and Chemical Properties:

Boiling Point: >406°F Melting Point: < 32 F Evaporation Rate: NE
Vapor Pressure (mm Hg.): < 0.00001 Vapor Density (AIR = 1): NE
Solubility In Water: Reacts slowly to liberate CO2 gas
Appearance and Odor: Light yellow; slight musty odor
Other Information: VOLATILITY @75°F: Very Low
PERCENT VOLATILE BY VOLUME(%): Negligible
SPECIFIC GRAVITY @ 77°F: 1.2

X. Stability and Reactivity:

Stability:

Stable

Incompatibility (Materials to Avoid):

Water, acids, bases, alcohols, amines and other materials which react with isocyanates.

Decomposition/By Products:

High temperatures and burning conditions may release isocyanate vapors, carbon dioxide, carbon monoxide, nitrogen oxide and traces of hydrogen cyanide.

Hazardous Polymerization:

Hazardous polymerization may occur. Temperatures above 170°F will accelerate reactions with water. Polymerization may occur above 350°F.

XI. Toxicological Information:

None Available

XII. Ecological Information:

None Available

XIII. Disposal Considerations:

Neutralized waste must be disposed of in accordance with federal, state and local environmental control regulations. Incineration is the preferred method.

XIV. Transport Information:

Contains Diphenylmethane-4,4'-diisocyanate (MDI).
Single containers less than 11,111 lbs are not regulated.
Single containers with > 11,111 lbs are regulated as:
Other Regulated Substances, Liquid, N.O.S Diphenylmethane-4,4'-diisocyanate (MDI)
Class 9
UN 3082
PG III


XV. Regulatory Information:

TSCA Inventory Status: This product, or its components, are listed on, or are exempt from the Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

SARA 313 INFORMATION: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372:

CHEMICAL NAME	CAS NUMBER	CONCENTRATION
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	35-45 %

SARA HAZARD CATEGORY: This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:





Material Safety Data Sheet

No. 117908

Page 4 of 4

Printed:

06/01/2009

Last Update:

04/04/2008

Product Name:

Por-A-Foam, Iso Side B

An immediate health hazard; A delayed health hazard; A reactive hazard

XVI. Other Information:

In this document the following abbreviations were used:

NA: Not Applicable NE: Not Established

