

# Material Safety Data Sheet

Freeman 1035T Part A

MSDS No.

Date of Preparation: January 3, 2007

Revision:

## Section 1 - Chemical Product and Company Identification

**Product/Chemical Name:** Freeman 1035T Part A

**Chemical Family:** Isocyanate

**CAS Number:** N/A

**Other Designations:** N/A

**General Use:** Polyurethane Elastomer

**Manufacturer:** Freeman Manufacturing and Supply Company, 1101 Moore Road, Avon, OH 44011,  
Phone (440)934-1902, FAX (440)934-7200, Hours of Operation 8-5, Emergency Phone Number 800-424-9300

**HMIS**

**H** 2

**F** 1

**R** 1

**PPE**†

†Sec. 8

### ☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Irritant, possible sensitizer

## Section 2 - Composition / Information on Ingredients

Ingredient Name	CAS Number	% wt
Polyurethane Prepolymer	-	95 - 100
Bis (2-ethylhexyl) phthalate	117-81-7	0 - 5
2,4 Toluene Diisocyanate	584-84-9	< 1.0
2,6 Toluene Diisocyanate	91-08-7	< 1.0

Ingredient	OSHA PEL		OSHA PEL	
	TWA	STEL	TWA	STEL
Polyurethane Prepolymer	none estab.	none estab.	none estab.	none estab.
Bis (2-ethylhexyl) phthalate	5 mg/m3	none estab.	5 mg/m3	none estab.
2,4 Toluene Diisocyanate	0.005 ppm	none estab.	0.005 ppm	none estab.
2,6 Toluene Diisocyanate	0.005 ppm	none estab.	0.005 ppm	none estab.

## Section 3 - Physical and Chemical Properties

**Physical State:** Liquid

**Appearance and Odor:** Clear yellow viscous liquid

**Odor:** sharp pungent odor

**Viscosity:** 4500-5500 cps

**Vapor Pressure:** None (Polymeric Resin)

**Vapor Density (Air=1):** >1

**Specific Gravity (H<sub>2</sub>O=1, at 4 °C):** 1.04

**pH:** N/A

**Water Solubility:** Negligible

**Boiling Point:** None (Polymeric Resin)

**Freezing/Melting Point:** None (Polymeric Resin)

**% Volatile:** Nil

**Evaporation Rate:** Not Applicable

## Section 4 - Fire-Fighting Measures

**Flash Point:** >270°F (>132°C)

**Flash Point Method:** TOC

**Burning Rate:** Not established

**Autoignition Temperature:** Not established

**LEL:** Not established

**UEL:** Not established

**Flammability Classification:** Non-Flammable

**Extinguishing Media:** Water Fog, Dry Chemical, and Carbon Dioxide Foam


**Unusual Fire or Explosion Hazards:** Hazardous decomposition products may be formed. Avoid water contamination in closed containers or confined areas as exothermic heat and carbon dioxide can evolve.

**Hazardous Combustion Products:** N/A

**Fire-Fighting Instructions:** Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.

**Fire-Fighting Equipment:** Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

NFPA



## Section 5 - Stability and Reactivity

**Stability:** This product is stable at room temperature in closed containers under normal storage and handling conditions.

**Polymerization:** Hazardous polymerization can occur.

**Chemical Incompatibilities:** Strong bases, water, amines, alcohols

**Conditions to Avoid:** Avoid contamination with water and other materials that react with Isocyanates.

**Hazardous Decomposition Products:** Toluene diisocyanate vapors, hydrogen cyanide gas, oxides of nitrogen, carbon monoxide and carbon dioxide.

## Section 6 - Health Hazard Information

### Potential Health Effects

**Primary Entry Routes:** Inhalation and Dermal

**Target Organs:** Lungs

#### Acute Effects

**Inhalation:** Vapors cause irritation to respiratory tract and pulmonary edema can occur after a serious vapor exposure; pulmonary sensitization can occur in some individuals leading to asthma-like spasms of the bronchial tubes and difficulty in breathing; recent studies indicate overexposure with chronic lung impairment.

**Eye:** May cause irritation, redness, tearing, and blur vision. Prolonged vapor contact may cause conjunctivitis.

**Skin:** Contact will cause irritation, reddening, swelling, rash, scaling, or blistering. Prolonged or repeated contact can cause moderate dermatitis.

**Ingestion:** May have corrosive effects on the linings of the mouth and stomach: symptoms can include sore throat, abdominal pain, nausea, vomiting and diarrhea.

**Carcinogenicity:** IARC and NTP list Toluene Diisocyanate as a suspected carcinogen.

**Medical Conditions Aggravated by Long-Term Exposure:** Asthma, bronchitis, and emphysema, skin allergies, eczema.

### Emergency and First Aid Procedures

**Inhalation:** Remove sources(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately. Asthma-like symptoms may develop immediately or be delayed several hours.

**Eye Contact:** Flush eyes with plenty of water. If irritation persists, seek medical attention.

**Skin Contact:** In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse: seek medical attention if rash develops.

**Ingestion:** Do not induce vomiting unless instructed by a physician. Contact physician immediately.

*After first aid, get appropriate in-plant, paramedic, or community medical support.*

## Section 7 - Spill, Leak, and Disposal Procedures

**Spill /Leak Procedures:** Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.

**Containment:** For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

**Regulatory Requirements:** Follow applicable OSHA regulations (29 CFR 1910.120).

**Disposal:** Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

**Disposal Regulatory Requirements:** This material contains a hazardous constituent as identified in RCRA, Title 40 CFR 261, Appendix VIII and must be disposed of in accordance with applicable Federal, state, and local regulations.

#### Toxicological Information:

**Eye Effects:** Irritation

**Skin Effects:** Irritation

**Carcinogenicity:** IARC and NTP list Toluene Diisocyanate as a suspected carcinogen

**Ecological Information:** None established

#### EPA Regulations:

**RCRA Hazardous Waste Number:** Not listed (40 CFR 261.33)

**CERCLA Hazardous Substance** (40 CFR 302.4) listed specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112:

<u>Chemical Name</u>	<u>RQ</u>	<u>% Reportable Component</u>
Toluene diisocyanate (mixed isomers)	100 lbs.	<1.0

**SARA Toxic Chemical** (40 CFR 372.65):

<u>Chemical Name</u>	<u>CAS #</u>	<u>% by Weight</u>
Toluene diisocyanate (mixed isomers)	26471-62-5	<1.0

SARA EHS (Extremely Hazardous Substance) (40 CFR 355):

Chemical Name	CAS #	% by Weight
Toluene diisocyanate (mixed isomers)	26471-62-5	<1.0

**TSCA Inventory Status (40 CFR710):** All components of this formulation are listed in the TSCA Inventory.

**State Regulations:**

California Proposition 65: This product contains toluene diisocyanate and Bis (2-ethylhexyl) phthalate, which in the State of California have found to cause cancer, birth defects or other reproductive harm.

2,4 Toluene Diisocyanate (CAS # 584-84-9) and 2,6 Toluene Diisocyanate (CAS # 91-08-7) are found on the New Jersey, Pennsylvania and Massachusetts Right to Know Lists

Bis (2-ethylhexyl) phthalate (CAS # 117-81-7) is found on the New Jersey, Pennsylvania and Massachusetts Right to Know Lists.

## Section 8 - Exposure Controls / Personal Protection

**Engineering Controls:**

**Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**Administrative Controls:**

**Respiratory Protection:** Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA.

**Protective Clothing/Equipment:** Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

**Safety Stations:** Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

**Contaminated Equipment:** Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

## Section 9 - Special Precautions and Comments

**Handling Precautions:** Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Avoid moisture contamination. Reseal partial containers. Use good general housekeeping procedures.

**Storage Requirements:** Store in cool, dry, well-ventilated area.

### DOT Transportation Data (49 CFR 172.101): Not Classified

**Disclaimer:** The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.