

Material Safety Data Sheet

Freeman 917 Hardener

Date of Preparation: January 3, 2007

Revision:

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Freeman 917 Hardener

Chemical Family: Amine

CAS Number: N/A

Other Designations: N/A

Intended Use or Product Type: Heat resistant hardener

Manufacturer: Freeman Manufacturing and Supply Company, 1101 Moore Road, Avon, OH 44011,
Phone (440)934-1902, FAX (440)934-7200, Hours of Operation 8-5, Emergency Phone Number 800-424-9300

HMIS

H 3

F 1

R 0

PPE†

†Sec. 8

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Corrosive – causes skin and eye burns. Can cause allergic respiratory reaction and allergic skin reaction.
Can be harmful if absorbed through skin and may be harmful if swallowed.

Section 2 - Composition / Information on Ingredients

Ingredient Name	CAS Number
* Triethylenetetramine	112-24-3
* m-Xylenediamine	1477-55-0
*: 1-Methylimidazole	616-47-7
* MXDA/TMD/DGEBA Adduct	68738-77-2

* = OSHA Hazardous Ingredient

Ingredient	OSHA		ACGIH	
	PEL	STEL	TWA	STEL
Triethylenetetramine	none estab.	none estab.	none estab.	none estab.
m-Xylenediamine	none estab.	none estab.	none estab.	0.1 mg/m3
1-Methylimidazole	none estab.	none estab.	none estab.	none estab.
MXDA/TMD/DGEBA Adduct	none estab.	none estab.	none estab.	none estab.

Section 3 - Physical and Chemical Properties

Physical State: Liquid

Appearance and Odor: Blue thin liquid; amine odor.

Vapor Pressure: 0.0009 mm Hg at 68 °F (20 °C)

Vapor Density (Air=1): Not determined

Specific Gravity (H₂O=1, at 4 °C): 1.04

pH: Not determined

Water Solubility: Moderate

VOC: 51.992 g/L

% Volatile: Negligible

Evaporation Rate: Not determined

Boiling Point: >400°F (>204°C)

Section 4 - Fire-Fighting Measures

Flash Point: >200 °F (>93 °C)

Flash Point Method: Estimated

LEL: Not established


UEL: Not established

Extinguishing Media: Carbon dioxide, dry chemical, foam, water.

Fire-Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Decomposition and combustion products may be toxic.

NFPA



Section 5 - Stability and Reactivity

Stability: Stable

Conditions to Avoid: Excessive heat for prolonged periods of time.

Incompatibility: Strong oxidizers, acids, and bases

Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

Hazardous Polymerization: Will not occur.

Section 6 - Health Hazard Information

Potential Health Effects

Primary Entry Routes: Dermal: heated product may produce inhalable vapors.

Acute Exposure: Corrosive. Causes skin and eye burns.

Chronic: Possible mutagen.

Overexposure Effects: Corrosive – causes skin and eye burns. Can cause allergic respiratory reaction and allergic skin reaction. Can be harmful if absorbed through skin and may be harmful if swallowed.

Medical Conditions Aggravated by Exposure: Skin, eye and pulmonary conditions.

Additional Information: Referral to a physician is recommended if there is any question about the seriousness of any injury.

Emergency and First Aid Procedures

Inhalation: Remove to fresh air. Call a physician.

Eye: Immediately flush eyes with water for at least 15 minutes. Call a physician.

Skin: Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes.

Ingestion: If conscious, give 2-4 glasses of water to drink. Do not induce vomiting. Call a physician.

Section 7 - Spill, Leak, and Disposal Procedures

Accidental Release Measures: Remove spillage by absorbing in absorbent material.

Waste Disposal Method: Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

Toxicological Information:

Acute Oral Effects (LD50) Triethylenetetramine = 2500-4340 mg/kg (rat)

Acute Dermal Toxicity (LD50): Triethylenetetramine = 550-800 mg/kg (rabbit)

Sensitization: May cause allergic skin reaction and respiratory sensitivity in some people.

Skin Irritation: Corrosive. Causes burns.

Eye Irritation: Corrosive. Causes burns.

Ecological Information: N/A

Regulatory Information:

US Federal Regulations:

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazardous Communication Standard 29 CFR 1910,1200. This product is considered to be a hazardous chemical under that standard.

Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261) but handle with care due to corrosive effect on skin and eyes.

SARA Title III: Section 313 Toxic Chemical List (TCL): This product does not contain any chemicals for routine annual toxic chemical release reporting under Section 313 (40 CFR 372).

TSCA Section 8b- Inventory Status: All chemical components of this product are in compliance with TSCA inventory requirements.

TSCA Section 12b- Export Notification: This product does not contain any chemicals that are subject to a Section 12b export notification.

Revision:

Freeman 917 Hardener

State Regulations:

California Proposition 65: This product does not contain any chemicals currently on the California list of Known Carcinogens and Reproductive Toxins.

Triethylenetetramine (CAS # 112-24-3) is on the New Jersey and Pennsylvania Right to Know Lists

m-Xylenediamine (CAS # 1477-55-0) is on the New Jersey and Pennsylvania Right to Know Lists

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: General mechanical and local exhaust in accordance with ACGIH recommendations.

Respiratory Protection: Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Skin Protection: Wear impermeable gloves.

Section 9 - Special Precautions and Comments

Handling and Storage:

Signal Word: Danger!

Precautions: Corrosive – causes skin and eye burns. Can cause allergic respiratory reaction and allergic skin reaction. Can be harmful if absorbed through skin and may be harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid breathing vapor or mist. Avoid tasting or swallowing. Keep container closed when not in use. Use with adequate ventilation. Wash thoroughly after handling. Notice! Possible mutagen.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

DOT Transportation Data (49 CFR 172.101):

Shipping Name: Polyamines, liquid, corrosive, n.o.s.

Technical Shipping Name:

Triethylene tetramine,
Metaxylenediamine

Hazard Class: 8

ID No.: UN 2735

Packing Group: PG III

Label: Corrosive

Packaging Authorizations

a) Exceptions:

b) Non-bulk Packaging: X

c) Bulk Packaging:

Quantity Limitations

a) Passenger, Aircraft, or Railcar:

b) Cargo Aircraft Only:

Vessel Stowage Requirements

a) Vessel Stowage:

b) Other:

Prepared By:

Revision Notes:

Disclaimer: The following supersedes Buyer’s documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer’s sole remedy and Seller’s sole liability for any claims shall be Buyer’s purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.