

Material Safety Data Sheet

Freeman NO. 60 Pattern Coating

Date of Preparation: January 3, 2007

Revision:

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Freeman NO. 60 Pattern Coating

Chemical Family: Solvent

CAS Number: N/A

Other Designations: N/A

General Use: N/A

Manufacturer: Freeman Manufacturing and Supply Company, Avon, OH 44011, Phone (440) 934-1902, FAX (440) 934-7200, Hours of Operation (8-5), Emergency phone number 1-800-424-9300.

HMIS

H 2

F 3

R 0

PPE†

†Sec. 8

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Flammable, Inhalation, Irritant

Section 2 - Composition / Information on Ingredients

Ingredient Name	CAS Number	% wt or % vol
n-Butyl Acetate	123-86-4	15-25
Methyl Isobutyl Ketone	108-10-1	5-15
Isopropyl Acetate	108-21-4	<5
Butyl Benzyl Phthalate	85-68-7	<5
Anhyd. Isopropyl Alcohol	67-63-0	<5
VM&P Naphtha	64742-89-8	<5
Methyl Ethyl Ketone	78-93-3	<5
Xylene	1330-20-7	<5
Amyl Acetate	628-63-7	<1
n-Butyl Alcohol	71-36-3	<1
Ethyl Benzene	100-41-4	<1

Ingredient	OSHA		ACGIH		Vapor Pressure
	PEL	STEL	TLV	STEL	
n-Butyl Acetate	150 ppm	None estab.	150 ppm	None estab.	13.0 mm Hg @ 68°F
Methyl Isobutyl Ketone	100 ppm	None estab.	50 ppm	None estab.	16.0 mm Hg @ 68°F
Isopropyl Acetate	250 ppm	None estab.	250 ppm	None estab.	47.0 mm Hg @ 68°F
Butyl Benzyl Phthalate	5 mg/m ³	None estab.	5 mg/m ³	None estab.	N/A
Isopropyl Alcohol	400 ppm	None estab.	400 ppm	None estab.	33.0 mm Hg @ 68°F
VM&P Naphtha	300 ppm	None estab.	300 ppm	None estab.	10.2 mm Hg @ 68°F
Methyl Ethyl Ketone	200 ppm	None estab.	200 ppm	None estab.	78.0 mm Hg @ 68°F
Xylene	100 ppm	None estab.	50 ppm	None estab.	14.2 mm Hg @ 100°F
Amyl Acetate	100 ppm	None estab.	100 ppm	None estab.	4.0 mm Hg @ 68°F
n- Butyl Alcohol	100 ppm	None estab.	50 ppm	None estab.	4.4 mm Hg @ 68°F
Ethyl Benzene	100 ppm	None estab.	100 ppm	None estab.	7.1 mm Hg @ 68°F

Section 3 - Physical and Chemical Properties

Appearance and Odor: Gray liquid, Strong Solvent

Coating V.O.C.: 4.49 lb/gal

Material V.O.C.: 4.49 lb/gal

Specific Gravity (H₂O=1, at 4 °C): 1.26

Water Solubility: Negligible


Boiling Range: 175°F-464°F

Evaporation Rate: Slower than Ether

Vapor Density (Air=1): Heavier than air.

Section 4 - Fire-Fighting Measures

Flash Point: 23°F (-5°C)
Flash Point Method: TCC
LEL: 0.9% v/v
UEL: 20 % v/v
Extinguishing Media: Foam, CO₂, dry chemical



Unusual Fire and Explosion Hazards: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Do not apply to hot surfaces.

Fire-Fighting Instructions: Water spray may be ineffective. Use fog nozzles. Cool fire exposed containers with water.

Section 5 - Stability and Reactivity

Stability: Stable under recommended handling and storage conditions.

Conditions to Avoid: High temperatures

Incompatibility (Materials to Avoid): N/A

Hazardous Decomposition Products: May produce hazardous fumes when heated. Carbon monoxide, oxides of nitrogen.

Hazardous Polymerization: Will not occur.

Section 6 - Health Hazard Information

Potential Health Effects

Inhalation: Anesthetic. Irritation of the respiratory tract or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness, or coma.

Skin and Eye Contact: Primary irritation.

Skin: Prolonged or repeated exposure to this material may cause redness and burning, during, and cracking of the skin and dermatitis. Person with pre-existing skin disorders may be more susceptible.

Ingestion: Do not induce vomiting. Consult a physician or poison control center.

Health Hazards (Acute and Chronic): Pre-existing heart disorders may be aggravated by exposure to this material.

Carcinogenicity: IARC, NTP, and OSHA do not any component as carcinogenic. Contains very low levels of Benzene as an impurity of Xylene. Benzene is classified by the State of California as a cancer hazard.

Medical Conditions Aggravated by Long-Term Exposure: Any medical condition, allergy, or sensitization can become worse upon exposure.

Emergency and First Aid Procedures

Inhalation: Remove from exposure. Restore breathing. Keep warm and quiet. Notify a physician.

Eyes: Flush immediately with large amounts of water for 15 minutes. See a physician.

Skin: Wash affected areas thoroughly with soap and water. Remove contaminated clothing.

Ingestion: Do not induce vomiting. Consult a physician or poison control center.

Section 7 - Spill, Leak, and Disposal Procedures

Spill/Leak Procedures: Remove all sources of ignition. Ventilate area. Remove with inert absorbent and non-sparking tools.

Disposal: Disposal in accordance with local, state, and federal regulation. Incinerate in approved facility. Do not incinerate closed containers. Emptied containers may retain hazardous residue and explosive vapors. Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

State Regulations:

California Proposition 65: Contains - Benzene, butyl benzyl phthalate, xylene and ethyl benzene

Materials on the New Jersey Right to Know List: Amyl acetate, methyl isobutyl ketone, butyl benzyl phthalate, isopropyl acetate, n-butyl acetate, isopropyl alcohol, methyl ethyl ketone, isobutyl alcohol, xylene, ethyl benzene and talc (CAS # 14807-96-6)

Revision:

Freeman NO. 60 Pattern Coating

Materials on the Pennsylvania Right to Know List: Amyl acetate, methyl isobutyl ketone, butyl benzyl phthalate, isopropyl acetate, n-butyl acetate, isopropyl alcohol, methyl ethyl ketone,; isobutyl alcohol, xylene, ethyl benzene and talc (CAS # 14807-96-6)

Materials on the Massachusetts Right to Know List: Amyl acetate, methyl isobutyl ketone, butyl benzyl phthalate isopropyl acetate, n-butyl acetate, isopropyl alcohol, methyl ethyl ketone, isobutyl alcohol, xylene and ethyl benzene

Regulatory Information:

TSCA Inventory Status: All ingredients listed on TSCA Inventory.

Section 8 - Exposure Controls / Personal Protection

Ventilation: In restricted ventilation areas use Bureau of Mines approved chemical mechanical filters designed to remove a combination of particulate and gas/vapor. In confined areas use Bureau of Mines approved air line type respirator.
Respiratory Protection: In outdoor or open areas use Bureau of Mines approved mechanical filter respirator to remove solid air borne particles of overspray during spray application.
Protective Gloves: Wear resistant gloves such as: Natural rubber, or neoprene.
Eye Protection: Chemical splash goggles in compliance with OSHA regulation.
Other Protective Clothing or Equipment: To prevent repeated or prolonged skin contact, wear impervious clothing and boots.
Work/Hygienic Practices: Wash hands before eating or using the washrooms, smoke in smoking areas only.

Section 9 - Special Precautions and Comments

Handling and Storage:
Handling Precautions: Ground containers when pouring. Avoid free fall of liquid in excess of a few inches. Do not flame cut, braze or weld.
Storage Requirements: Do not store above 120°F. Store large quantities in building designed and protected for storage of NFPA Class Liquids.

DOT Transportation Data (49 CFR 172.101):

Shipping Name: Paint Flammable Liquid 3	Packaging Authorizations	Quantity Limitations
Shipping Symbols:	a) Exceptions:	a) Passenger, Aircraft, or Railcar:
Hazard Class: 3	b) Non-bulk Packaging:	b) Cargo Aircraft Only:
ID No.: UN 1263	c) Bulk Packaging:	Vessel Stowage Requirements
Packing Group: II		a) Vessel Stowage:
Label: Flammable Liquid		b) Other:
Special Provisions (172.102):		

Prepared By:
Revision Notes:

Disclaimer: The following supersedes Buyer’s documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer’s sole remedy and Seller’s sole liability for any claims shall be Buyer’s purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.