

Material Safety Data Sheet

Freeman Repro Ultra Light A Side

Date of Preparation: January 3, 2007

Revision:

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Freeman Repro Ultra Light A Side

Chemical Family: Polyol

CAS Number: N/A

Other Designations: N/A

General Use: N/A

Manufacturer: Freeman Manufacturing and Supply Company, 1101 Moore Road, Avon, OH 44011, Phone (440)934-1902, FAX (440) 934-7200, Hours of Operation 8-5, Emergency Phone 800-424-9300.

HMIS

H 1

F 2

R 0

PPE†

†Sec. 8

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Combustible. Causes eye, skin, and respiratory irritations.

Section 2 - Composition / Information on Ingredients

Ingredient Name	CAS Number
Urethane Polyol	Proprietary
Aromatic Solvent	Blend

Ingredient	OSHA		ACGIH		Vapor Pressure
	PEL	STEL	TLV	STEL	
Urethane Polyol	none estab.	none estab.	none estab.	none estab.	N/A
Aromatic Solvent	100 ppm	none estab.	25 ppm	none estab.	1.7 mm Hg @ 68°F

Section 3 - Physical and Chemical Properties

Appearance and Odor: Off-White liquid, mild odor

Vapor Pressure: Not determined

Vapor Density (Air=1): Not determined

VOC Content: 0.9 lbs/gal

Specific Gravity (H₂O=1, at 4 °C): 0.59

Water Solubility: Slight

Boiling Point: Not determined

% Volatile: 20-25%

Evaporation Rate: Not determined

pH: Not determined

Section 4 - Fire-Fighting Measures

Flash Point: 150 °F (66°C)

Flash Point Method: SETA

LEL: Not established


UEL: Not established

Extinguishing Media: Foam, water, CO₂, or dry chemical

Fire-Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Decomposition and combustion products may be toxic.

NFPA



Section 5 - Stability and Reactivity

Stability: Stable.

Conditions to Avoid: Contamination with materials containing active NCO compounds, excessive heat for prolonged period.

Chemical Incompatibilities: Strong oxidizing agents, acids, metal-organic compounds.

Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

Hazardous Polymerization: Will not occur. Avoid inadvertent mixture of A and B parts.

Section 6 - Health Hazard Information

Potential Health Effects

Primary Entry Routes: Skin; Inhalation from heated vapors.

Acute Effects:

Inhalation: Irritates the respiratory tract

Eye: Causes irritation

Skin: Causes irritation

Ingestion: Swallowing can cause abdominal irritation, nausea, vomiting, and diarrhea.

Medical Conditions Aggravated by Long-Term Exposure: Persons with severe skin problems should avoid use.

Chronic Effects: No known chronic effects associated with this material.

Carcinogenicity: IARC, NTP, and OSHA do not list any component as carcinogenic.

Emergency and First Aid Procedures

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen and/or artificial respiration.

Eye Contact: Flush with plenty of water for 15 minutes and get medical attention.

Skin Contact: Wash thoroughly with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes.

Ingestion: If conscious, give 2-4 glasses of water to drink. Do not induce vomiting. Get medical attention.

Section 7 - Spill, Leak, and Disposal Procedures

Spill /Leak Procedures: Stop spill at source. Dike area and contain. Clean up remainder with absorbent materials such as sand or vermiculite. Mop up and dispose of.

Disposal: Dispose of in safety containers as a solid water material. Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Ecological Information: N/A

Toxicology Information:

Acute Inhalation Exposure Effects: Respiratory irritant.

Skin Irritation: Irritant.

Eye Irritation: Irritant.

Regulatory Information:

US Federal Regulations:

OSHA (Occupational Safety and Health Act): This Material Safety Data Sheet has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

RCRA (Resource Conservation and Recovery Act): Not a hazardous waste under RCRA (40 CFR 261).

SARA 311/312 Codes: Acute Health, Fire.

SARA Toxic Chemical (40 CFR 372.65): This product contains the following toxic chemical subject to the reporting requirements of Section 313 of SARA Title III of 1986 and of 40 CFR 372.

Xylenes	CAS # 1330-20-7	< 0.5 %
Naphthalene	CAS # 91-20-3	< 0.5 %

TSCA Inventory Status: All ingredients listed on TSCA inventory requirements.

Revision:

Freeman Ultra Repro Light A Side

State Regulations: CA Proposition 65: Naphthalene (CAS # 91-20-3) is listed as a cancer hazard. Contain small amounts of xylene (CAS # 1330-20-7) and naphthalene (CAS # 91-20-3) which is on the New Jersey, Pennsylvania and Massachusetts Right to Know lists.

Section 8 - Exposure Controls / Personal Protection

Ventilation: Local exhaust recommended. General mechanical is acceptable. Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2).

Respiratory Protection: Use a NIOSH approved respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Skin Protection: Wear impermeable gloves.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Special Precautions and Comments

Handling & Storage: Use with adequate ventilation. Avoid prolonged breathing of vapor. Avoid prolonged or repeated contact with skin. Wear safety goggles or face shield. Wear gloves, apron and footwear impervious to this material. Wash clothing before reuse. Store at ambient temperatures or below 90 F. When resealing cans, use a nitrogen purge (Magic Blanket). Keep container tightly closed and upright when not in use to prevent leakage.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

DOT Transportation Data (49 CFR 172.101):

Shipping Name: Liquid Plastic,
N.O.I., Non-Regulated

Shipping Symbols:

Hazard Class:

ID No.:

Packing Group:

Label:

Special Provisions (172.102):

Packaging Authorizations

a) Exceptions:

b) Non-bulk Packaging:

c) Bulk Packaging:

Quantity Limitations

a) Passenger, Aircraft, or Railcar:

b) Cargo Aircraft Only:

Vessel Stowage Requirements

a) Vessel Stowage:

b) Other:

Prepared By:

Revision Notes:

Disclaimer: The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.

Material Safety Data Sheet

Freeman Repro Ultra Light B Side

Date of Preparation: January 3, 2007

Revision:

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Freeman Repro Ultra Light B Side

Chemical Family: Isocyanate

CAS Number: N/A

Other Designations: N/A

General Use: Polyurethane

Manufacturer: Freeman Manufacturing and Supply Company, 1101 Moore Road, Avon, OH 44011 Phone (440) 934-1902, FAX (440) 934-7200, Hours of Operation 8-5, Emergency phone number 1-800-424-9300.

HMIS

H 3

F 2

R 1

PPE†

†Sec. 8

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Can cause eye, skin, and respiratory tract irritation; Can cause allergic respiratory reaction, and allergic skin reaction. Can be harmful if inhaled.

Section 2 - Composition / Information on Ingredients

Ingredient Name	CAS Number
Diphenylmethane Diisocyanate (mixed isomers)	26447-40-5
Polymeric Diphenylmethane Diisocyanate	9016-87-9
4,4'-Diphenylmethane Diisocyanate	101-68-8
Aromatic Solvent	Blend

Ingredient	OSHA		ACGIH		Vapor Pressure
	PEL	STEL	TLV	STEL	
Polymeric Diphenylmethane Diisocyanate	none estab.	none estab.	none estab.	none estab.	N/A
4,4'-Diphenylmethane Diisocyanate	0.02 ppm	none estab.	0.005 ppm	none estab.	N/A
Diphenylmethane Diisocyanate (mixed isomers)	none estab.	none estab.	none estab.	none estab.	N/A
Aromatic Solvent	100 ppm	none estab.	25 ppm	none estab.	1.7 mm Hg @ 68°F

Section 3 - Physical and Chemical Properties

Appearance and Odor: Tan liquid; mild odor

Odor Threshold: N/A

Vapor Pressure: Not Established

Vapor Density (Air=1): >1.0

VOC Content: 1.25 lbs/gal

Specific Gravity (H₂O=1, at 4 °C): 0.900

pH: N/A

Water Solubility: Reacts with water

Other Solubilities: N/A

Boiling Point: 350 F

Freezing/Melting Point: N/A

% Volatile: 20-25%

Evaporation Rate: N/A

Section 4 - Fire-Fighting Measures

Flash Point: 150 °F (66°C)

Flash Point Method: SETA


Burning Rate: N/A

Autoignition Temperature: Not established

LEL: N/E

UEL: N/E

NFPA



Flammability Classification: N/A

Extinguishing Media: Foam, water, CO₂, dry chemical.

Unusual Fire or Explosion Hazards: Combustible! Keep containers tightly closed. Isolate from oxidizers, heat, and open flame. At temperatures greater than 400°F material can polymerize and decompose which can cause pressure build-up in closed containers. Container rupture is possible. Use cold water to cool fire-exposed container.

Hazardous Combustion Products: Carbon monoxide, oxides of nitrogen, traces of HCN, MDI vapors or aerosols.

Fire-Fighting Instructions: Firefighters must be equipped with self-contained breathing apparatus and turnout gear. Water spray may be ineffective on fire but can protect fire fighters and cool closed containers. Use fog nozzles if water is used. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

Section 5 - Stability and Reactivity

Stability: Freeman Repro Ultra Light B Side is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization can occur. Avoid contact with moisture or other material, which react with isocyanates. May occur at temperatures above 400° F (204° C).

Chemical Incompatibilities: Water, alcohols, strong oxidizing agents, strong bases, acids, metal-organic compounds.

Conditions to Avoid: Contamination with water and polyols. Avoid prolonged heating over 160F or storing below 75F.

Hazardous Decomposition Products: Thermal oxidative decomposition of Freeman Repro Ultra Light B Side can produce CO, NO, traces of HCN, MDI vapors or aerosols.

Section 6 - Health Hazard Information

Potential Health Effects

Primary Entry Routes: Inhalation from heated vapors and skin from liquids

Target Organs: N/A

Acute Effects

Inhalation: Irritation to eyes, skin, and respiratory tract. May cause asthmatic-like symptoms.

Eye: Eye irritation may include tearing, reddening, and swelling.

Skin: Skin irritation may include reddening, swelling, rash, scaling or blistering, and in some cases, skin sensitization.

Ingestion: Can result in irritation and corrosive action in the mouth, stomach tissue and digestive tract. Symptoms can include sore throat, abdominal pain, nausea, vomiting and diarrhea.

Medical Conditions Aggravated by Long-Term Exposure: Asthma, other respiratory disorders (bronchitis, emphysema, bronchial hyperactivity) skin allergies, eczema.

Chronic Effects

Inhalation: As a result of previous repeated overexposures, certain individuals develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. These symptoms, which can include chest tightness, wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed (up to several hours after exposure). Sensitization can either be temporary or permanent.

Eye: None found.

Skin: Prolonged contact can cause reddening, swelling, rash, scaling, blistering, and in some cases, skin sensitization. Individuals who have skin sensitization can develop these symptoms from contact with liquid or vapors.

Ingestion: None found.

Carcinogenicity: IARC, NTP, and OSHA do not list any component as carcinogenic.

Emergency and First Aid Procedures

Inhalation: Move to an area free from risk of further exposure. Administer oxygen and/or artificial respiration as needed. Call a physician.

Eye Contact: Flush with plenty of water for at least 15 minutes, holding eyelids open all the time. Get medical attention

Skin Contact: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

Ingestion: Do not induce vomiting! Give one to two cups of milk or water to drink. Do not give anything by mouth to an unconscious person. Consult a physician.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Note to Physicians: N/A

Section 7 - Spill, Leak, and Disposal Procedures

Spill /Leak Procedures: Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment including respiratory equipment during clean up. Clean up remainder with absorbent materials such as sand or vermiculite. Mop up and dispose of.

Containment: For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

Cleanup: N/A

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Disposal: Dispose in safety containers as a solid waste material according to federal, state, and local environmental control regulations. Incineration is the preferred method. Contact your supplier or a licensed contractor for detailed recommendations.

Disposal Regulatory Requirements: N/A

Container Cleaning and Disposal: N/A

Ecological Information: N/A

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification (40 CFR 261.): Not classified

CERCLA Hazardous Substance (40 CFR 302.4) listed/unlisted specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112

CERCLA Reportable Quantity (RQ) kg

SARA 311/312 Codes: Immediate Health Hazard; Delayed Health Hazard.

SARA Toxic Chemical (40 CFR 372.65): This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of SARA TITLE III and 40 CFR 372:

Polymeric Diphenylmethane Diisocyanate	CAS # 9016-87-9	15.0 – 20.0 %
4, 4' Diphenylmethane Diisocyanate	CAS # 101-68-8	8.0 – 10.0 %
Xylenes	CAS # 1330-20-7	< 0.5 %
Naphthalene	CAS # 91-20-3	< 0.5 %

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed, Threshold Planning Quantity (TPQ)

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed

OSHA Specifically Regulated Substance (29CFR 1910.)

State Regulations: CA Proposition 65 Naphthalene (CAS # 91-20-3) is listed as a cancer hazard.

Contains small amounts of xylene (CAS # 1330-20-7) and naphthalene (CAS # 91-20-3) which are on the New Jersey, Pennsylvania and Massachusetts Right to Know lists.

4, 4' Diphenylmethane Diisocyanate (CAS # 101-68-8) is found on the New Jersey and Pennsylvania Right to Know Lists

Other Regulatory Information:

TSCA Inventory Status: All ingredients listed on TSCA Inventory.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: N/A

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Respiratory Protection: For isocyanates, an organic respirator can provide protection at less than the TLV. For exposures beyond the TLV, a supplied air respirator is recommended. Conditions that may create exposures above TLV are spray applications, material being heated above 125 F or use in poorly ventilated areas. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA

Protective Clothing/Equipment: Wear chemically protective permeation resistant gloves (butyl rubber, nitrile, polyvinyl alcohol), boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Special Precautions and Comments

Handling & Storage: Store at ambient temperatures or below 90°F. Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected. When resealing cans use a nitrogen purge (Magic Blanket). Causes irritation if inhaled and can cause skin irritation, eye irritation, allergic respiratory reaction, and allergic skin reaction. Avoid contact with skin and eyes. Do not breathe vapors. This material can produce asthmatic sensitization upon either single inhalation exposure to a relatively high concentration or upon repeated inhalation exposures to lower concentrations.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

DOT Transportation Data (49 CFR 172.101):

Shipping Name: Liquid Plastic
N.O.I., Non-Regulated

Shipping Symbols:

Hazard Class:

ID No.:

Packing Group:

Label:

Special Provisions (172.102):

Packaging Authorizations

a) Exceptions:

b) Non-bulk Packaging:

c) Bulk Packaging:

Quantity Limitations

a) Passenger, Aircraft, or Railcar:

b) Cargo Aircraft Only:

Vessel Stowage Requirements

a) Vessel Stowage:

b) Other:

Prepared By:

Revision Notes:

Disclaimer: The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.