

MSDS - Material Safety Data Sheet**Product Name: Por-A-Mold, S-333 Prepol**

MSDS No.: 032902


I. Basic Information:

Manufacturer: Synair Corporation

DISTRIBUTED BY FREEMAN MFG & SUPPLY CO. 800-321-8511

Transportation Emergency Phone: Chem-trec 1-800-424-9300

Last Update: 05/13/2002

Chemical State: Liquid Gas SolidChemical Type: Pure Mixture

3		Health
1		Flammability
1		Reactivity
C		Pers. Protection

II. Ingredients:

CAS No.	Chemical Name	% Range	EHS	NTP	IARC	SUB Z	SARA 313	OSHA PEL	ACGIH TLV	Other Limits
26447405	Diphenylmethane Diisocyanate (MDI)	6-13					X	0.02 ppm	0.005 ppm	NE
	Isocyanate Terminated Prreopolymer	55-60						NE	NE	NE
	Parrafinic and Naphthenic Petroleum Blend	16-20						NE	NE	NE
	Petroleum Hydrocarbon	8-12			X			NE	5.0 mg/m3	NE
26471625	Toluenediisocyanate (mixed isomers)	2-4		X			X	0.02 ppm	0.005 ppm	NE

III. Hazardous Identification:**Hazard Category:**
 Acute Chronic Fire Pressure Reactive
Hazardous Identification Information:

Warning!

Brown liquid with a characteristic odor.

Inhalation of vapors may cause respiratory tract irritation. Contact with skin and eyes may cause irritation.

This product contains petroleum oils similar to the ones categorized by IARC as causing skin cancer in mice after prolonged and repeated contact. Any potential hazard can be minimized by using the recommended protective equipment.

IV. First Aid Measures:**Route(s) of Entry:**

Inhalation, Ingestion, Skin and Eye contact.

Health Hazards (Acute and Chronic):

Acute (Short-Term)

Contact may cause slight irritation of the skin and eyes (tearing). Inhalation of vapors may cause irritation of the mucous membranes in the respiratory tract, running nose and sore throat.

MSDS - Material Safety Data Sheet

Product Name: *Por-A-Mold, S-333 Prepol*

MSDS No.: 032902

Chronic (Delayed)

Prolonged skin contact can cause reddening, swelling or skin sensitization in susceptible individuals.

Repeated or prolonged inhalation of TDI and MDI vapors above the TLV of 0.02 ppm can cause immediate or delayed respiratory sensitization and asthma-like conditions.

Signs and Symptoms:

Skin, eye and respiratory tract irritation.

Medical Conditions Generally Aggravated by Exposure:

Repeated skin contact may cause skin sensitization.

Prolonged inhalation of vapors may cause respiratory sensitization in susceptible individuals.

Emergency and First Aid Procedures:

SKIN CONTACT: Remove contaminated clothing and wash affected area with isopropyl alcohol followed by soap and water.

EYE CONTACT: Flush eyes with water for at least 15 minutes and contact a physician.

INGESTION: Do NOT induce vomiting and contact a physician. Do NOT give anything by mouth to an unconscious person.

INHALATION: Remove person to fresh air. If person is not breathing give mouth-to-mouth resuscitation and contact a physician.

Other Health Warnings:

In an NTP study, TDI was carcinogenic when given to rats and mice at maximum tolerated doses. TDI was carcinogenic to rats in a two-year inhalation study.

V. Fire Fighting Measures:

Flash Point:	440°F	Lower Explosive Limit:	NE	Upper Explosive Limit:	NE
---------------------	-------	-------------------------------	----	-------------------------------	----

Fire Extinguishing Media: Foam, water fog, carbon dioxide or dry chemical extinguishers.

Special Fire Fighting Procedures:

Firefighters should wear a self-contained breathing apparatus and protective clothing.

Unusual Fire and Explosion:

Contamination of isocyanates with water releases carbon dioxide which may result in a dangerous amount of pressure build-up in closed containers. Do NOT reseal contaminated containers. Personnel must be evacuated. Use cold water to cool fire exposed containers.

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Cover liquid with an absorbent material (sawdust, vermiculite or wet sand). After the material is absorbed scoop up and place in open containers. Treat material with the prepared decontamination solution and leave the container open in a well ventilated area for 48 hours. Spill area should also be decontaminated with the following decontamination solution: 90% water, 2% detergent and 8% concentrated ammonia or sodium carbonate.

VII. Handling and Storage:

Precautions to be Taken:

Store in tightly closed containers in a cool, dry area away from sources of heat, moisture and incompatibles.

Other Precautions:

This product contains petroleum oils similar to the ones categorized by IARC as causing skin cancer in mice after prolonged and repeated contact. Any potential hazard can be minimized by using recommended protective equipment.

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

Local Exhaust: Provide mechanical (general) and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

MSDS - Material Safety Data Sheet

Product Name: *Por-A-Mold, S-333 Prepol*

MSDS No.: 032902

Personal Protective Equipment:

RESPIRATORY PROTECTION: None needed at normal temperatures. Use a self-contained breathing apparatus under emergency conditions.

PROTECTIVE GLOVES: Impervious rubber gloves.

EYE PROTECTION: Wear safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: An apron or suitable clothing to prevent skin contact.

IX. Physical and Chemical Properties:

Boiling Point:	>400°F	Melting Point:	NA	Evaporation Rate:	<1
Vapor Pressure (mm Hg.):	NE	Vapor Density (AIR = 1):	>1		
Solubility In Water:	Reacts slowly to liberate CO2 gas				
Appearance and Odor:	Brown liquid; characteristic odor				
Other Information:	VOLATILITY @75°F: Very low				
	PERCENT VOLATILE BY VOLUME(%): Negligible				
	SPECIFIC GRAVITY: 1.082				

X. Stability and Reactivity:

Stability:

Stable

Incompatibility (Materials to Avoid):

Water, bases, oxidizers, and amines.

Decomposition/By Products:

Carbon dioxide, carbon monoxide, TDI vapors, MDI vapors, traces of HCN and oxides of nitrogen.

Hazardous Polymerization:

May occur at temperatures above 400°F.

XI. Toxicological Information:

None Available

XII. Ecological Information:

None Available

XIII. Disposal Considerations:

Neutralized waste must be disposed of in accordance with federal, state and local environmental control regulations. Incineration is the preferred method.

XIV. Transport Information:

Plastic Liquid Resin Material
Item 156240
DOT Shipping Class 60
Non-Hazardous

MSDS - Material Safety Data Sheet

Product Name: *Por-A-Mold, S-333 Prepol*

MSDS No.: 032902

XV. Regulatory Information:

Toluene Diisocyanate CAS# 26471-62-5 contains 2,4 Toluene Diisocyanate CAS# 584-84-9 and 2,6 Toluene Diisocyanate CAS# 91-08-7.

Diphenylmethane Diisocyanate (MDI) CAS# 26447-40-5 contains Methylene Bisphenyl Isocyanate CAS# 101-68-8.

SARA 313 INFORMATION: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372:

CHEMICAL NAME	CAS NUMBER	CONCENTRATION
2,4 Toluene Diisocyanate	584-84-9	<1%
2,6 Toluene Diisocyanate	91-08-7	<1%
Methylene Bisphenyl Isocyanate	101-68-8	2-6%

SARA HAZARD CATEGORY: This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

An immediate health hazard
A delayed health hazard
A reactive hazard

XVI. Other Information:

In this document the following abbreviations were used:

NA: Not Applicable
NE: Not Established