

Distributed by Freeman Mfg & Supply Co.
800.321.8511 www.freemansupply.com

24-Hour Emergency Phone: (800) 328-8501

Effective Date: 1/22/07


Material Safety Data Sheet

MSDS No: 6062

1. PRODUCT IDENTIFICATION

Trade Name: Ren 3261

Chemical Family: Amine



NFPA RATING

Health:	3*
Flammability:	1
Reactivity:	0
Personal Protection:	

HMIS RATING

Synonyms:

RP 3261 Hardener

Intended Use or Product Type: Surface coat and casting hardener

2. COMPOSITION / INFORMATION ON INGREDIENTS

O S H A	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS				CARCINOGEN STATUS			
			ACGIH		OSHA		MFR.	IARC	NTP	OSHA
			TWA	STEL	PEL	STEL				
*	111-40-0 Common Name:	1,2-Ethanediamine, N-(2-aminoethyl)-Diethylenetriamine	1 ppm	NE	NE	NE	NE	NR	NR	NR
*	68610-56-0 Common Name:	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane, diethylenetriamine-terminated Amine adduct	NE	NE	NE	NE	NE	NR	NR	NR
*	80-05-7 Common Name:	Phenol, 4,4'-(1-methylethylidene)bis- Bisphenol A	NE	NE	NE	NE	TLV 5 mg/m3	NR	NR	NR

NE = Not Established NR = Not Reviewed * = OSHA Hazardous Ingredient

3. HAZARDS IDENTIFICATION

Emergency Overview: Corrosive - causes skin and eye burns. Can cause allergic respiratory reaction and allergic skin reaction. Can be harmful if absorbed through skin and may be harmful if swallowed.

Effective Date: 1/22/07

Primary Route(s) of Entry: Dermal; heated product may produce inhalable vapors.

Acute Exposure: Corrosive. Causes skin and eye burns.

Chronic: Overexposure may have effects on developing fetus.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Skin: Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes. Seek immediate medical attention.

Inhalation: Remove to fresh air. Seek immediate medical attention.

Eyes: Immediately flush eyes with water for at least 15 minutes. Seek immediate medical attention.

Overexposure Effects: Corrosive - causes skin and eye burns. Can cause allergic respiratory reaction and allergic skin reaction. Can be harmful if absorbed through skin and may be harmful if swallowed.

Medical Conditions Aggravated by Exposure: Skin, eye and pulmonary conditions.

Additional Information: Referral to a physician is recommended if there is any question about the seriousness of any injury.

5. FIRE FIGHTING MEASURES

Flash Point:	> 250°F (> 121 °C)
Flash Point Method Used:	PMCC
Flammable Limits in Air (Lower - % by volume):	Not established
Flammable Limits in Air (Upper - % by volume):	Not established

Fire Fighting Extinguishing Media: Carbon dioxide, dry chemical, foam, water.

Fire Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Decomposition and combustion products may be toxic.

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Remove spillage by absorbing in absorbent material. Avoid contact.

7. HANDLING AND STORAGE

Signal Word: Danger!

Precautions: Corrosive - causes skin and eye burns. Can cause allergic respiratory reaction and allergic skin reaction. Can be harmful if absorbed through skin and may be harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid breathing

Effective Date: 1/22/07

vapor or mist. Avoid tasting or swallowing. Keep container closed when not in use. Use with adequate ventilation. Wash thoroughly after handling. Notice! Overexposure may have effects on developing fetus.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Skin Protection: Impermeable gloves and protective clothing.

Respiratory Protection: Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely.

Eye Protection: Full face shield.

Engineering Controls: General mechanical and local exhaust in accordance with ACGIH recommendations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear
Color:	Amber
Odor:	Ammonia
Physical State:	Liquid
Solubility in Water:	Slight
Vapor Pressure:	< 2.34 mm Hg at 70°C (158 °F)
Specific Gravity:	1.06 - 1.09 (water = 1)
Boiling Point:	> 400°F (> 204 °C)
Evaporation Rate:	Not Determined
Vapor Density:	Not Determined
pH:	10.2

Percent Volatile: Less than 1%.

10. STABILITY AND REACTIVITY

Conditions to Avoid: Excessive heat for prolonged periods of time.

Stability: Stable.

Incompatibility: Strong oxidizing agents, acids, metal-organic compounds.

Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute Oral Effects (LD50): Component(s) are slightly toxic, 500 - 5000 mg/kg (rat).

Diethylenetriamine= 1080 - 2330 mg/kg (rat)

Acute Dermal Toxicity (LD50): Component(s) are toxic, 200 - 1000 mg/kg (rabbit).

Diethylenetriamine= 672 - 1240 mg/kg (rabbit)

Effective Date: 1/22/07

Sensitization: May cause allergic skin reaction and respiratory sensitivity in some people.

Skin Irritation: Corrosive. Causes burns.

Eye Irritation: Corrosive. Causes burns.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

14. TRANSPORT INFORMATION

DOT: Non-Bulk

Proper Shipping Name:	Diethylenetriamine Mixture
Hazard Class:	8
ID Number:	UN 2079
Packing Group:	PG II
Label:	Corrosive

15. REGULATORY INFORMATION

US Federal Regulations:

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261) but handle with care due to corrosive effect on skin and eyes.

SARA Title III: Section 313 Toxic Chemical List (TCL): This product contains a toxic chemical(s) for routine annual toxic chemical release reporting under section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this material.

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-

Common Name: Bisphenol A

Percent in Composition: 25 % by wt

Comment:

TSCA Section 8(b) - Inventory Status: All chemical components of this product are in compliance with TSCA inventory requirements.

TSCA Section 12(b) - Export Notification: This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.

Effective Date: 1/22/07

State Regulations:

California Proposition 65: This product does not contain any chemicals currently on the California list of Known Carcinogens and Reproductive Toxins.

Pennsylvania Right-to-Know: The following is required composition information:

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane, diethylenetriamine-terminated
Common Name: Amine adduct
CAS Number: 68610-56-0
Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: 1,2-Ethanediamine, N-(2-aminoethyl)-
Common Name: Diethylenetriamine
CAS Number: 111-40-0
Comment: Hazardous Substance

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-
Common Name: Bisphenol A
CAS Number: 80-05-7
Comment: Environmental Hazardous Substance

16. OTHER INFORMATION

MSDS No: 6062
Approved By: Dianne Blessing
Title: EH&S Specialist

Disclaimer: The information and recommendations contained herein are based upon tests in controlled laboratory conditions, are believed to be correct, and are provided for the sole purpose of hazard communication as part of Huntsman's product safety program. This product has not been tested for, and therefore is not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for any such uses.

The information and recommendations contained herein are not intended to constitute performance information concerning the product, which is available in separate technical data sheets available from Huntsman upon request. Users are urged, and are urged to urge others who may come in contact with the product, to obtain and consult data sheets prior to purchase, use, transportation or storage of the product.

HUNTSMAN MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY, QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED TO REIMBURSEMENT OF BUYER'S PURCHASE PRICE, OR IN HUNTSMAN'S DISCRETION REPLACEMENT, OF THE PRODUCT IN RESPECT OF WHICH SUCH CLAIM IS MADE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED BY LEGAL NOTICES IN TECHNICAL DATA SHEETS, PRODUCT LITERATURE, AND/OR SALE DOCUMENTS. The foregoing DISCLAIMERS and LIMITATION OF LIABILITY supercede inconsistent or contradictory provisions in Buyer's documents.

USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENTAL AGENCY TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.

Effective Date: 1/22/07

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.