


**DISTRIBUTED BY FREEMAN MFG & SUPPLY CO. 800-321-8511**

24-Hour Emergency Phone: 1-888-354-3323

**Effective Date:** 10/12/04**Material Safety Data Sheet**

MSDS No: 6065

**1. PRODUCT IDENTIFICATION****Trade Name:** RenCast 3262**Chemical Family:** Epoxy

NFPA RATING

<b>Health:</b>	<b>2</b>
<b>Flammability:</b>	<b>2</b>
<b>Reactivity:</b>	<b>1</b>
<b>Personal Protection:</b>	

HMIS RATING

**Synonyms:**

RP 3262 Resin

**Intended Use or Product Type:**

Casting resin

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

O S H A	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS				MFR.	CARCINOGEN STATUS		
			ACGIH		OSHA			IARC	NTP	OSHA
			TWA	STEL	PEL	STEL				
*	2426-08-6	Oxirane, (Butoxymethyl)-  Common Name: Butyl glycidyl ether	25 ppm	NE	50 ppm	NE	Table Z1A TWA 25 ppm	NR	NR	NR
*	25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane Common Name: Bisphenol A diglycidyl ether polymer	NE	NE	NE	NE	NE	NR	NR	NR

\* = OSHA Hazardous Ingredient

**3. HAZARDS IDENTIFICATION****Emergency Overview:** Combustible. Causes skin and eye irritation. May cause allergic skin and respiratory reactions.**Primary Route(s) of Entry:** Dermal; heated product may produce inhalable vapors.

---

Effective Date: 10/12/04

---

#### **4. FIRST AID MEASURES**

**Ingestion:** If conscious, give 2 - 4 glasses of water to drink. Do not induce vomiting. Call a physician.

**Skin:** Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes.

**Inhalation:** Remove to fresh air. Call a physician.

**Eyes:** Immediately flush eyes with water for at least 15 minutes. Call a physician.

**Overexposure Effects:** Causes skin and eye irritation. May cause allergic skin and respiratory reactions.

**Medical Conditions Aggravated by Exposure:** Skin, eye and pulmonary conditions.

**Additional Information:** Referral to a physician is recommended if there is any question about the seriousness of any injury.

#### **5. FIRE FIGHTING MEASURES**

**Flash Point:** 160°F (71 °C)

**Flash Point Method Used:** PMCC

**Flammable Limits in Air (Lower - % by volume):** Not established

**Flammable Limits in Air (Upper - % by volume):** Not established

**Fire Fighting Extinguishing Media:** Carbon dioxide, dry chemical, foam.

**Fire Fighting Equipment:** Use self-contained breathing apparatus.

**Fire and Explosion Hazards:** Decomposition and combustion products may be toxic.

#### **6. ACCIDENTAL RELEASE MEASURES**

**Accidental Release Measures:** Remove spillage by absorbing in absorbent material.

#### **7. HANDLING AND STORAGE**

**Signal Word:** Warning!

**Precautions:** Combustible. Keep away from heat and flame. Can cause skin irritation, eye irritation, allergic respiratory reaction, and allergic skin reaction. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated breathing of vapor or mist. Keep container closed when not in use. Use with adequate ventilation. Wash thoroughly after handling.

**Other Handling Information:** Nuisance dust may be generated when sanding or sawing cured material.

#### **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Skin Protection:** Wear impermeable gloves.

**Respiratory Protection:** Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely.

---

**Effective Date:** 10/12/04

---

**Eye Protection:** Wear splash-proof chemical goggles.

**Engineering Controls:** General mechanical and local exhaust in accordance with ACGIH recommendations.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Color:</b>	Grey
<b>Odor:</b>	Slight Ethereal
<b>Physical State:</b>	Pourable Liquid
<b>Solubility in Water:</b>	Insoluble
<b>Vapor Pressure:</b>	4.84 mm Hg at 54°C (129 °F)
<b>Specific Gravity:</b>	1.71 - 1.75 (water = 1)
<b>Boiling Point:</b>	> 300°F (> 149 °C)
<b>Evaporation Rate:</b>	Not Determined
<b>Vapor Density:</b>	Not Determined
<b>pH:</b>	Not Determined

**Percent Volatile:** Negligible.

## **10. STABILITY AND REACTIVITY**

**Conditions to Avoid:** Excessive heat for prolonged periods of time.

**Stability:** Stable.

**Incompatibility:** Strong oxidizers, acids and bases.

**Hazardous Decomposition Products:** Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

**Hazardous Polymerization:** Will not occur.

## **11. TOXICOLOGICAL INFORMATION**

**Sensitization:** May cause allergic skin reaction and respiratory sensitivity in some people.

**Skin Irritation:** Irritant.

**Eye Irritation:** Irritant.

## **12. ECOLOGICAL INFORMATION**

## **13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

## **14. TRANSPORT INFORMATION**

---

**Effective Date:** 10/12/04

---

**DOT: Non-Bulk****Proper Shipping Name:**

Resin compounds, N.O.I.

**Department of Transportation:** Not regulated as a hazardous material by the U.S. Dept. of Transportation (DOT) 49 CFR 172.101 hazardous materials table.**15. REGULATORY INFORMATION****US Federal Regulations:****Occupational Safety and Health Act (OSHA):** This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.**Resource Conservation and Recovery Act (RCRA):** Not a hazardous waste under RCRA (40 CFR 261).**SARA Title III: Section 313 Toxic Chemical List (TCL):** This product contains a toxic chemical(s) for routine annual toxic chemical release reporting under section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this material.

Chemical Name: Aluminum

Percent in Composition: 57 % by wt

Comment:

**TSCA Section 8(b) - Inventory Status:** All chemical components of this product are in compliance with TSCA inventory requirements.**TSCA Section 12(b) - Export Notification:** This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.**State Regulations:****California Proposition 65:** This product does not contain any chemicals currently on the California list of Known Carcinogens and Reproductive Toxins.**Pennsylvania Right-to-Know:** The following is required composition information:

Chemical Name: Aluminum

CAS Number: 7429-90-5

Comment: Environmental Hazardous Substance

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane

Common Name: Bisphenol A diglycidyl ether polymer

CAS Number: 25068-38-6

Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: Oxirane, (Butoxymethyl)-

Common Name: Butyl glycidyl ether

CAS Number: 2426-08-6

Comment: Hazardous Substance

---

**Effective Date:** 10/12/04

---

Chemical Name: Magnesium oxide  
Common Name: Calcined brucite  
CAS Number: 1309-48-4  
Comment: Hazardous Substance

## **16. OTHER INFORMATION**

**MSDS No:** 6065  
**Approved By:** Dianne Blessing  
**Title:** EH&S Specialist

**Disclaimer:** The information and recommendations contained herein are based upon tests in controlled laboratory conditions, are believed to be correct, and are provided for the sole purpose of hazard communication as part of Huntsman's product safety program. This product has not been tested for, and therefore is not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for any such uses.

The information and recommendations contained herein are not intended to constitute performance information concerning the product, which is available in separate technical data sheets available from Huntsman upon request. Users are urged, and are urged to urge others who may come in contact with the product, to obtain and consult data sheets prior to purchase, use, transportation or storage of the product.

HUNTSMAN MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY, QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED TO REIMBURSEMENT OF BUYER'S PURCHASE PRICE, OR IN HUNTSMAN'S DISCRETION REPLACEMENT, OF THE PRODUCT IN RESPECT OF WHICH SUCH CLAIM IS MADE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED BY LEGAL NOTICES IN TECHNICAL DATA SHEETS, PRODUCT LITERATURE AND/OR SALE DOCUMENTS. The foregoing DISCLAIMERS and LIMITATION OF LIABILITY supercede inconsistent or contradictory provisions in Buyer's documents.

USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENTAL AGENCY TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.