

Distributed by Freeman Mfg & Supply Co.
800.321.8511 www.freemansupply.com

24-Hour Emergency Phone: (800) 328-8501

Effective Date: 3/30/07


Material Safety Data Sheet

MSDS No: 11255

1. PRODUCT IDENTIFICATION

Trade Name: RenCast 4037

Chemical Family: Epoxy



NFPA RATING

Health:	2
Flammability:	1
Reactivity:	0
Personal Protection:	

HMIS RATING

Synonyms:

DT 177-147 Resin
RP 4037 Resin

Intended Use or Product Type: High heat casting system resin

2. COMPOSITION / INFORMATION ON INGREDIENTS

O S H A	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS				CARCINOGEN STATUS			
			ACGIH		OSHA		MFR.	IARC	NTP	OSHA
			TWA	STEL	PEL	STEL				
*	2425-79-8	Oxirane, 2,2'-[1,4-Butanediylbis(Oxymethylene)]bis-Butanediol diglycidyl ether Common Name: Concentration 1.00 - 5.00 % by wt	NE	NE	NE	NE	NE	NR	NR	NR
*	25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane Bisphenol A diglycidyl ether polymer Common Name: Concentration 10.00 - 30.00 % by wt	NE	NE	NE	NE	NE	NR	NR	NR
*	28064-14-4	Phenol, polymer with formaldehyde, glycidyl ether Epoxy Phenol Novolac Common Name: Concentration 7.00 - 13.00 % by wt	NE	NE	NE	NE	NE	NR	NR	NR

* = OSHA Hazardous Ingredient

3. HAZARDS IDENTIFICATION

Emergency Overview: Can cause skin irritation, eye irritation, and allergic skin reaction. May be harmful if absorbed through skin or if swallowed.

Effective Date: 3/30/07

Primary Route(s) of Entry: Dermal; heated product may produce inhalable vapors.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Skin: Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes. Seek immediate medical attention.

Inhalation: Remove to fresh air. Seek immediate medical attention.

Eyes: Immediately flush eyes with water for at least 15 minutes. Seek immediate medical attention.

Overexposure Effects: Can cause skin irritation, eye irritation, and allergic skin reaction. May be harmful if absorbed through skin or if swallowed.

Medical Conditions Aggravated by Exposure: Skin and eye conditions.

Additional Information: Referral to a physician is recommended if there is any question about the seriousness of any injury.

5. FIRE FIGHTING MEASURES

Flash Point:	> 300°F (> 149 °C)
Flash Point Method Used:	PMCC
Flammable Limits in Air (Lower - % by volume):	Not established
Flammable Limits in Air (Upper - % by volume):	Not established

Fire Fighting Extinguishing Media: Carbon dioxide, dry chemical, foam, water.

Fire Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Decomposition and combustion products may be toxic.

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Remove spillage by absorbing in absorbent material.

7. HANDLING AND STORAGE

Signal Word: Warning!

Precautions: Can cause skin irritation, eye irritation, and allergic skin reaction. May be harmful if absorbed through skin or if swallowed. Avoid contact with eyes, skin, and clothing. Avoid tasting or swallowing. Wash thoroughly after handling.

Effective Date: 3/30/07

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Skin Protection: Wear impermeable gloves.

Respiratory Protection: Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Engineering Controls: General mechanical and local exhaust in accordance with ACGIH recommendations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Grey
Odor:	Slight
Physical State:	Liquid
Solubility in Water:	Negligible
Vapor Pressure:	0.0073 mm Hg at 80°C (176 °F)
Specific Gravity:	1.73 - 1.78 (water = 1)
Boiling Point:	> 350°F (> 177 °C)
Evaporation Rate:	Not Determined
Vapor Density:	Not Determined
VOC:	0 g/L
pH:	Not Determined
Coefficient of water/oil:	Not Determined

Percent Volatile: Negligible.

10. STABILITY AND REACTIVITY

Conditions to Avoid: Excessive heat for prolonged periods of time.

Stability: Stable.

Incompatibility: Strong oxidizers, acids and bases.

Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute Oral Effects (LD50): Component(s) are slightly toxic, 500 - 5000 mg/kg (rat).

Butanediol diglycidyl ether= 1134 mg/kg (rat)

Acute Dermal Toxicity (LD50): Component(s) are slightly toxic, 1000 - 2000 mg/kg (rabbit).

Butanediol diglycidyl ether= 1130 mg/kg (rabbit)

Sensitization: Possible in susceptible individuals.

Effective Date: 3/30/07

Carcinogenicity: Based on several dermal studies in mice, IARC had concluded in 1999 that diglycidyl ether of bisphenol A is not classifiable as a human carcinogen (Group 3) and has limited evidence of carcinogenicity in animals.

Skin Irritation: Irritant.

Eye Irritation: Irritant.

Reproduction: For diglycidyl ether of bisphenol A- There were no treatment-related histologic changes noted nor effects on reproductive performance in rats at any oral dose tested.

Teratogenicity: For diglycidyl ether of bisphenol A- No adverse effects on embryonic or fetal development was observed in rabbits after dermal exposure.

Mutagenicity: For diglycidyl ether of bisphenol A- In vitro tests showed mutagenic effects which were not observed with in vivo tests.

Sub-Chronic: Diglycidyl ether of bisphenol A, applied to the skin of rats five times per week for approximately 13 weeks, caused no apparent systemic toxicity with the exception of decreased body weight and body weight gain.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

14. TRANSPORT INFORMATION

DOT: Non-Bulk

Proper Shipping Name: Resin compounds, N.O.I.

IATA: Non-Bulk

Proper Shipping Name: Not Regulated

IMDG: Non-Bulk

Proper Shipping Name: Not Regulated

TDG: Non-Bulk

Proper Shipping Name: Not Regulated

Department of Transportation: Not regulated as a hazardous material by the U.S. Dept. of Transportation (DOT) 49 CFR 172.101 hazardous materials table.

15. REGULATORY INFORMATION

US Federal Regulations:

Occupational Safety and Health Act (OSHA): This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261).

Effective Date: 3/30/07

SARA Title III: Section 313 Toxic Chemical List (TCL): This product contains a toxic chemical(s) for routine annual toxic chemical release reporting under section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this material.

Chemical Name: Aluminum
Percent in Composition: 31.6 % by wt
Comment:

TSCA Section 8(b) - Inventory Status: All chemical components of this product are in compliance with TSCA inventory requirements.

TSCA Section 12(b) - Export Notification: This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.

International Regulations:

Canadian Inventory Status: This product contains components which are included on the Domestic Substances List (DSL) and the Non-Domestic Substances List (NDSL).

Canadian WHMIS: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. D2B

State Regulations:

California Proposition 65: The following is required composition information. This product contains the following chemical(s) which are currently listed on the California list of Known Carcinogens and Reproductive Toxins:

Chemical Name: Oxirane, (phenoxymethyl)-
Common Name: Phenyl glycidyl ether
CAS Number: 122-60-1
Percent in Composition: 0.0001 % by wt
Comment: Warning! This chemical is known to the State of California to cause cancer.

Pennsylvania Right-to-Know: The following is required composition information:

Chemical Name: Aluminum
CAS Number: 7429-90-5
Comment: Environmental Hazardous Substance

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane
Common Name: Bisphenol A diglycidyl ether polymer
CAS Number: 25068-38-6
Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: Limestone
Common Name: Calcium carbonate
CAS Number: 1317-65-3
Comment: Hazardous Substance

Chemical Name: Phenol, polymer with formaldehyde, glycidyl ether
Common Name: Epoxy Phenol Novolac
CAS Number: 28064-14-4
Comment: Not on Pennsylvania Hazardous Substance List

Effective Date: 3/30/07

Chemical Name: Aluminum hydroxide
Common Name: Hydrated Alumina
CAS Number: 21645-51-2
Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: Oxirane, 2,2'-[1,4-Butanediylbis(Oxymethylene)]bis-
Common Name: Butanediol diglycidyl ether
CAS Number: 2425-79-8
Comment: Not on Pennsylvania Hazardous Substance List

16. OTHER INFORMATION

MSDS No: 11255
Approved By: Dianne Blessing
Title: EH&S Specialist

Disclaimer: The information and recommendations contained herein are based upon tests in controlled laboratory conditions, are believed to be correct, and are provided for the sole purpose of hazard communication as part of Huntsman's product safety program. This product has not been tested for, and therefore is not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for any such uses.

The information and recommendations contained herein are not intended to constitute performance information concerning the product, which is available in separate technical data sheets available from Huntsman upon request. Users are urged, and are urged to urge others who may come in contact with the product, to obtain and consult data sheets prior to purchase, use, transportation or storage of the product.

HUNTSMAN MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY, QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED TO REIMBURSEMENT OF BUYER'S PURCHASE PRICE, OR IN HUNTSMAN'S DISCRETION REPLACEMENT, OF THE PRODUCT IN RESPECT OF WHICH SUCH CLAIM IS MADE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED BY LEGAL NOTICES IN TECHNICAL DATA SHEETS, PRODUCT LITERATURE, AND/OR SALE DOCUMENTS. The foregoing DISCLAIMERS and LIMITATION OF LIABILITY supercede inconsistent or contradictory provisions in Buyer's documents.

USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENTAL AGENCY TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.

