

DISTRIBUTED BY FREEMAN MFG & SUPPLY CO.
800-321-8511 www.freemansupply.com

Effective Date: 12/8/04


Material Safety Data Sheet

MSDS No: 31796

1. PRODUCT IDENTIFICATION

Trade Name: Ren 8236 Medium

Chemical Family: Amine



NFPA RATING

Health:	3*
Flammability:	1
Reactivity:	0
Personal Protection:	

HMIS RATING

Synonyms:

RP 8236 Medium Hardener

Intended Use or Product Type:

High-temp aluminum filled casting hardener

2. COMPOSITION / INFORMATION ON INGREDIENTS

O S H A	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS				CARCINOGEN STATUS			
			ACGIH		OSHA		MFR.	IARC	NTP	OSHA
			TWA	STEL	PEL	STEL				
*	111-40-0	1,2-Ethanediamine, N-(2-aminoethyl)- Diethylenetriamine Common Name:	1 ppm	NE	NE	NE	NE	NR	NR	NR
*	1477-55-0	1,3-Benzenedimethanamine m-Xylenediamine Common Name:	NE	0.1 mg/m3	NE	NE	NE	NR	NR	NR
*	2855-13-2	Cyclohexanemethanamine, 5-Amino-1,3,3-Trimethyl- Isophorone diamine Common Name:	NE	NE	NE	NE	NE	NR	NR	NR
*	68479-98-1	Benzenediamine, ar,ar-diethyl-ar-methyl- Diethyltoluenediamine Common Name:	NE	NE	NE	NE	NE	NR	NR	NR
*	80-05-7	Phenol, 4,4'-(1-methylethylidene)bis- Bisphenol A Common Name:	NE	NE	NE	NE	TLV 5 mg/m3	NR	NR	NR
*	63548	Polymer of Benzenediamine, AR,AR-Diethyl-AR-Methyl and Phenol, Polymer with Formaldehyde, Glycidyl Ether Amine adduct Common	NE	NE	NE	NE	NE	NR	NR	NR

Effective Date: 12/8/04

Name:									
-------	--	--	--	--	--	--	--	--	--

NE = Not Established NR = Not Reviewed * = OSHA Hazardous Ingredient

3. HAZARDS IDENTIFICATION

Emergency Overview: Corrosive - Causes skin and eye burns. Harmful if swallowed or if absorbed through skin. May cause allergic skin and respiratory reactions.

Primary Route(s) of Entry: Dermal; heated product may produce inhalable vapors.

Acute Exposure: Corrosive. Causes skin and eye burns.

Chronic: Overexposure may have effects on developing fetus.

4. FIRST AID MEASURES

Ingestion: If conscious, give 2 - 4 glasses of water to drink. Do not induce vomiting. Call a physician.

Skin: Immediately wash with soap and water. Remove contaminated clothing and laundry before reuse. Destroy contaminated shoes.

Inhalation: Remove to fresh air. Call a physician.

Eyes: Immediately flush eyes with water for at least 15 minutes. Call a physician.

Overexposure Effects: Corrosive - causes skin and eye burns. Harmful if swallowed or if absorbed through skin. May cause allergic skin and respiratory reactions.

Medical Conditions Aggravated by Exposure: Skin, eye and pulmonary conditions.

Additional Information: Referral to a physician is recommended if there is any question about the seriousness of any injury.

5. FIRE FIGHTING MEASURES

Flash Point: > 200°F (> 93 °C)

Flash Point Method Used: Estimated

Flammable Limits in Air (Lower - % by volume): Not established

Flammable Limits in Air (Upper - % by volume): Not established

Fire Fighting Extinguishing Media: Carbon dioxide, dry chemical, foam, water.

Fire Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Decomposition and combustion products may be toxic.

Effective Date: 12/8/04

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Remove spillage by absorbing in absorbent material.

7. HANDLING AND STORAGE

Signal Word: Danger!

Precautions: Corrosive. Causes skin and eye burns. Harmful if swallowed or if absorbed through skin. May cause allergic skin and respiratory reactions. Do not get in eyes, on skin, on clothing. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Notice! Overexposure may have effects on developing fetus.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Skin Protection: Wear impermeable gloves.

Respiratory Protection: Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Engineering Controls: General mechanical and local exhaust in accordance with ACGIH recommendations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Brown
Odor:	Amine
Physical State:	Liquid
Solubility in Water:	Slight
Vapor Pressure:	> 0.1 mm Hg at 25°C (77 °F)
Specific Gravity:	1.01 (water = 1)
Boiling Point:	Not Determined
Evaporation Rate:	Not Determined
Vapor Density:	Not Determined
pH:	Not Determined

Percent Volatile: Negligible.

10. STABILITY AND REACTIVITY

Conditions to Avoid: Excessive heat for prolonged periods of time.

Stability: Stable.

Incompatibility: Strong oxidizers, acids and bases.

Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

Hazardous Polymerization: Will not occur.

Effective Date: 12/8/04

11. TOXICOLOGICAL INFORMATION**Acute Oral Effects (LD50):** Component(s) are toxic, 50 - 500 mg/kg (rat).

Diethylenetriamine= 1080 - 2330 mg/kg (rat)

Acute Dermal Toxicity (LD50): Component(s) are toxic, 200 - 1000 mg/kg (rabbit).

Diethylenetriamine= 672 - 1240 mg/kg (rabbit)

Sensitization: May cause allergic skin reaction and respiratory sensitivity in some people.**Skin Irritation:** Corrosive. Causes burns.**Eye Irritation:** Corrosive. Causes burns.**12. ECOLOGICAL INFORMATION****13. DISPOSAL CONSIDERATIONS****Waste Disposal Method:** Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.**14. TRANSPORT INFORMATION****DOT: Non-Bulk****Proper Shipping Name:**

Polyamines, liquid, corrosive, N.O.S.

Technical Shipping Name (If n.o.s.):

Metaxylenediamine, Diethylene triamine

Hazard Class:

8

ID Number:

UN 2735

Packing Group:

PG II

Label:

Corrosive

15. REGULATORY INFORMATION**US Federal Regulations:****Occupational Safety and Health Act (OSHA):** This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.**Resource Conservation and Recovery Act (RCRA):** Not a hazardous waste under RCRA (40 CFR 261) but handle with care due to corrosive effect on skin and eyes.**SARA Title III: Section 313 Toxic Chemical List (TCL):** This product contains a toxic chemical(s) for routine annual toxic chemical release reporting under section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this material.

Effective Date: 12/8/04

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-
Common Name: Bisphenol A
Percent in Composition: 1.998 % by wt
Comment:

TSCA Section 8(b) - Inventory Status: All chemical components of this product are in compliance with TSCA inventory requirements.

TSCA Section 12(b) - Export Notification: This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.

State Regulations:

California Proposition 65: This product does not contain any chemicals currently on the California list of Known Carcinogens and Reproductive Toxins.

Pennsylvania Right-to-Know: The following is required composition information:

Chemical Name: Benzenediamine, ar,ar-diethyl-ar-methyl-
Common Name: Diethyltoluenediamine
CAS Number: 68479-98-1
Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: Cyclohexanemethanamine, 5-Amino-1,3,3-Trimethyl-
Common Name: Isophorone diamine
CAS Number: 2855-13-2
Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: Polymer of Benzenediamine, AR,AR-Diethyl-AR-Methyl and Phenol, Polymer with Formaldehyde, Glycidyl Ether
Common Name: Amine adduct
CAS Number: 63548
Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: 1,3-Benzenedimethanamine
Common Name: m-Xylenediamine
CAS Number: 1477-55-0
Comment: Hazardous Substance

Chemical Name: 1,2-Ethanediamine, N-(2-aminoethyl)-
Common Name: Diethylenetriamine
CAS Number: 111-40-0
Comment: Hazardous Substance

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-
Common Name: Bisphenol A
CAS Number: 80-05-7
Comment: Environmental Hazardous Substance

16. OTHER INFORMATION

MSDS No: 31796
Approved By: Dianne Blessing

Effective Date: 12/8/04

Title: EH&S Specialist

Disclaimer: The information and recommendations contained herein are based upon tests in controlled laboratory conditions, are believed to be correct, and are provided for the sole purpose of hazard communication as part of Huntsman's product safety program. This product has not been tested for, and therefore is not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for any such uses.

The information and recommendations contained herein are not intended to constitute performance information concerning the product, which is available in separate technical data sheets available from Huntsman upon request. Users are urged, and are urged to urge others who may come in contact with the product, to obtain and consult data sheets prior to purchase, use, transportation or storage of the product.

HUNTSMAN MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY, QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED TO REIMBURSEMENT OF BUYER'S PURCHASE PRICE, OR IN HUNTSMAN'S DISCRETION REPLACEMENT, OF THE PRODUCT IN RESPECT OF WHICH SUCH CLAIM IS MADE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED BY LEGAL NOTICES IN TECHNICAL DATA SHEETS, PRODUCT LITERATURE AND/OR SALE DOCUMENTS. The foregoing DISCLAIMERS and LIMITATION OF LIABILITY supercede inconsistent or contradictory provisions in Buyer's documents.

USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENTAL AGENCY TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.