

Distributed by Freeman Mfg & Supply Co.
800-321-8511 www.freemansupply.com

24-Hour Emergency Phone: 1-888-354-3323

Effective Date: 12/7/04


Material Safety Data Sheet

MSDS No: 6080

1. PRODUCT IDENTIFICATION

Trade Name: RP 40 Aluminum Shot

Chemical Family: Aluminum Metal



NFPA RATING

Health:	1
Flammability:	1
Reactivity:	1
Personal Protection:	

HMIS RATING

Intended Use or Product Type: Aluminum alloy filler (shot)

2. COMPOSITION / INFORMATION ON INGREDIENTS

O S H A	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS				CARCINOGEN STATUS			
			ACGIH		OSHA		MFR.	IARC	NTP	OSHA
			TWA	STEL	PEL	STEL				
*	7429-90-5	Aluminum	2 mg/m3	NE	5 mg/m3	NE	NE	NR	NR	NR

NE = Not Established NR = Not Reviewed * = OSHA Hazardous Ingredient

3. HAZARDS IDENTIFICATION

Emergency Overview: Dust hazard. In accord with good industrial practice, handle with due care.

Primary Route(s) of Entry: Dermal or inhalation

4. FIRST AID MEASURES

Ingestion: If conscious, give 2 - 4 glasses of water to drink. Do not induce vomiting. Call a physician.

Skin: Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes.

Inhalation: Remove to fresh air. Call a physician.

Eyes: Immediately flush eyes with water for at least 15 minutes. Call a physician.

Overexposure Effects: Aluminum is practically inert with little degree of toxicity.

Effective Date: 12/7/04

Medical Conditions Aggravated by Exposure: Skin and eye conditions.

Additional Information: Referral to a physician is recommended if there is any question about the seriousness of any injury.

5. FIRE FIGHTING MEASURES

Flash Point:	Not Applicable
Flash Point Method Used:	Not Applicable
Flammable Limits in Air (Lower - % by volume):	Not established
Flammable Limits in Air (Upper - % by volume):	Not established

Fire Fighting Extinguishing Media: Carbon dioxide, dry chemical, foam.

Fire Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Aluminum dust can be ignited by static discharge.

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Sweep up into approved disposal container. Thoroughly vacuum area. Do not create dusty condition.

7. HANDLING AND STORAGE

Signal Word: Caution!

Precautions: Dust hazard. Avoid dusty conditions. Avoid breathing dust. Use with adequate ventilation. Use normal industrial hygiene practices. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Skin Protection: Wear canvas gloves as a standard handling procedure.

Respiratory Protection: Use NIOSH approved dust mask, if required during machining.

Eye Protection: Wear safety glasses to protect against dust particles during machining.

Engineering Controls: General mechanical and local exhaust in accordance with ACGIH recommendations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Aluminum Shot ~ 3/16" Diameter
Odor:	No Odor
Physical State:	Solid
Solubility in Water:	Insoluble
Vapor Pressure:	Not Determined

Effective Date: 12/7/04

Specific Gravity: 2.5 - 2.9
Boiling Point: Not Determined
Evaporation Rate: Not Determined
Vapor Density: Not Determined
pH: Not Determined

Percent Volatile: 0%

10. STABILITY AND REACTIVITY

Conditions to Avoid: Contact with water, acids or foreign materials.

Stability: Stable.

Incompatibility: Water, acids, alkalies and oxidizing agents

Hazardous Decomposition Products: Hydrogen - generated by reaction with acids, bases or water

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Eye Irritation: Dust due to machining may cause irritation.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

14. TRANSPORT INFORMATION

DOT: Non-Bulk

Proper Shipping Name: Aluminum scrap, n.o.i.

Department of Transportation: Not regulated as a hazardous material by the U.S. Dept. of Transportation (DOT) 49 CFR 172.101 hazardous materials table.

15. REGULATORY INFORMATION

US Federal Regulations:

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

Effective Date: 12/7/04

Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261).

SARA Title III: Section 313 Toxic Chemical List (TCL): This product contains a toxic chemical(s) for routine annual toxic chemical release reporting under section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this material.

Chemical Name: Aluminum

Percent in Composition: 100 % by wt

Comment:

TSCA Section 8(b) - Inventory Status: All chemical components of this product are in compliance with TSCA inventory requirements.

TSCA Section 12(b) - Export Notification: This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.

State Regulations:

California Proposition 65: This product does not contain any chemicals currently on the California list of Known Carcinogens and Reproductive Toxins.

Pennsylvania Right-to-Know: The following is required composition information:

Chemical Name: Aluminum

CAS Number: 7429-90-5

Comment: Environmental Hazardous Substance

16. OTHER INFORMATION

MSDS No:	6080
Approved By:	Dianne Blessing
Title:	EH&S Specialist

Disclaimer: The information and recommendations contained herein are based upon tests in controlled laboratory conditions, are believed to be correct, and are provided for the sole purpose of hazard communication as part of Huntsman's product safety program. This product has not been tested for, and therefore is not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for any such uses.

The information and recommendations contained herein are not intended to constitute performance information concerning the product, which is available in separate technical data sheets available from Huntsman upon request. Users are urged, and are urged to urge others who may come in contact with the product, to obtain and consult data sheets prior to purchase, use, transportation or storage of the product.

HUNTSMAN MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY, QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED TO REIMBURSEMENT OF BUYER'S PURCHASE PRICE, OR IN HUNTSMAN'S DISCRETION REPLACEMENT, OF THE PRODUCT IN RESPECT OF WHICH SUCH CLAIM IS MADE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED BY LEGAL NOTICES IN TECHNICAL DATA SHEETS, PRODUCT LITERATURE AND/OR SALE DOCUMENTS. The foregoing DISCLAIMERS and LIMITATION OF LIABILITY supercede inconsistent or contradictory provisions in Buyer's documents.

Effective Date: 12/7/04

USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENTAL AGENCY TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.