Distributed by Freeman Mfg & Supply Co. 800.321.8511 www.freemansupply.com



24-Hour Emergency Phone: (800) 328-8501

Effective Date: 4/17/06 Material Safety Data Sheet

MSDS No: 6759

1. PRODUCT IDENTIFICATION

Trade Name: RenLease 79-2

Chemical Family: Organic solvent and propellant

2 4 0

Health: 2
Flammability: 4
Reactivity: 0
Personal Protection:

NFPA RATING

HMIS RATING

Synonyms: RP 79-2

Intended Use or Product Type:

Release agent

2. COMPOSITION / INFORMATION ON INGREDIENTS

O S	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS					CARCINOGEN STATUS		
H			ACGIH		OSHA		MFR.	IARC	NTP	OSHA
A			TWA	STEL	PEL	STEL				
*	142-82-5	Heptane	400	500	500	500	NE	NR	NR	NR
			ppm	ppm	ppm	ppm				
*	67-63-0	2-Propanol	200	400	400	500	NE	NR	NR	NR
	Common Name:	Isopropyl alcohol	ppm	ppm	ppm	ppm				
*	68476-86-8 Common Name:	Petroleum Gases, Liquefied, Sweetened Propane/isobutane blend	NE	NE	NE	NE	NE	NR	NR	NR

* = OSHA Hazardous Ingredient

3. HAZARDS IDENTIFICATION

Emergency Overview: Extremely flammable. Contents under pressure. Vapor or gas reduces oxygen available for breathing. Misuse by concentrating and inhaling the contents can be harmful or fatal. May cause mild irritation if inhaled and may cause mild skin and eye irritation.

Primary Route(s) of Entry: Dermal; heated product may produce inhalable vapors.

Printed: 9/18/2006 Page 1 of 6

Effective Date: 4/17/06

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Skin: Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes. Seek immediate medical attention.

Inhalation: Remove to fresh air. Seek immediate medical attention.

Eyes: Immediately flush eyes with water for at least 15 minutes. Seek immediate medical attention.

Overexposure Effects: May cause mild irritation if inhaled and may cause mild skin and eye irritation.

Medical Conditions Aggravated by Exposure: Skin, eye and pulmonary conditions.

Additional Information: Referral to a physician is recommended if there is any question about the seriousness of any injury.

5. FIRE FIGHTING MEASURES

Flash Point: -156°F (-104 °C)

Flash Point Method Used: PMCC

Flammable Limits in Air (Lower - % by volume): 1 - 2 For Component Flammable Limits in Air (Upper - % by volume): 9.5 - 12 For Component

Fire Fighting Extinguishing Media: Carbon dioxide, dry chemical, foam, water.

Fire Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Aerosols may burst if exposed to temperatures above 120 degrees F. Contents of aerosol can are under pressure. Decomposition and combustion products may be toxic.

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Eliminate all sources of ignition. Vapors are heavier than air and may spread long distances or collect in low spots. Remove spillage by absorbing in absorbent material.

7. HANDLING AND STORAGE

Signal Word: Danger!

Precautions: Extremely flammable. Contents under pressure. Vapor or gas reduces oxygen available for breathing. Keep away from heat, sparks, and flame. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120F (49C). Do not enter storage areas unless adequately ventilated. Store indoors out of direct sunlight. Keep container closed when not in use. Use with adequate ventilation. Misuse by concentrating and inhaling the contents can be harmful or fatal. May cause mild irritation if inhaled and may cause mild skin and eye irritation. Avoid breathing vapor or mist. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

Printed: 9/18/2006 Page 2 of 6

Effective Date: 4/17/06

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Skin Protection: Wear impermeable gloves.

Respiratory Protection: Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Engineering Controls: General mechanical and local exhaust in accordance with ACGIH recommendations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color: Clear

Odor: Characteristic Solvent

Physical State: Thin Liquid

Solubility in Water: Nil

Vapor Pressure: 70 mm Hg
Specific Gravity: 0.67 (water = 1)

Boiling Point: -209°F (-134 °C) (initial)

Freezing Point: Not Evaluated

Evaporation Rate: > 1 (n-Butyl acetate = 1)

Vapor Density:> 1 (Air = 1)pH:Not DeterminedCoefficient of water/oil:Not Determined

Percent Volatile: 95 - 99

10. STABILITY AND REACTIVITY

Conditions to Avoid: Keep aerosols away from direct sunlight and other heat sources. Reacts with aluminum above 49 degrees C.

Stability: Stable.

Incompatibility: Nitric acid and sulfuric acids, strong oxidizers, aldehydes, halogens and halogen compounds.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and fluorine compounds.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute Inhalation Exposure Effects: Mild respiratory irritant.

Skin Irritation: Mild irritant.

Eye Irritation: Mild irritant.

12. ECOLOGICAL INFORMATION

Printed: 9/18/2006 Page 3 of 6

Effective Date: 4/17/06

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

14. TRANSPORT INFORMATION

DOT: Non-Bulk

Proper Shipping Name:

Consumer commodity, orm-d

Department of Transportation: Not regulated as a hazardous material by the U.S. Dept. of Transportation (DOT) 49 CFR 172.101 hazardous materials table.

15. REGULATORY INFORMATION

US Federal Regulations:

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

Resource Conservation and Recovery Act (RCRA): D 001 ignitable.

SARA Title III: Section 313 Toxic Chemical List (TCL): This product contains a toxic chemical(s) for routine annual toxic chemical release reporting under section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this material.

Chemical Name: 2-Propanol Common Name: Isopropyl alcohol Percent in Composition: 4 % by wt

Comment:

TSCA Section 8(b) - Inventory Status: All chemical components of this product are in compliance with TSCA inventory requirements.

TSCA Section 12(b) - Export Notification: This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.

International Regulations:

Canadian WHMIS: A B5

State Regulations:

California Proposition 65: This product does not contain any chemicals currently on the California list of Known Carcinogens and Reproductive Toxins.

Pennsylvania Right-to-Know: The following is required composition information:

Printed: 9/18/2006 Page 4 of 6

Effective Date: 4/17/06

Chemical Name: Petroleum Gases, Liquefied, Sweetened

Common Name: Propane/isobutane blend

CAS Number: 68476-86-8

Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: Heptane CAS Number: 142-82-5

Comment: Hazardous Substance

Chemical Name: Non-hazardous release blend

CAS Number: Confidential

Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: 2-Propanol Common Name: Isopropyl alcohol

CAS Number: 67-63-0

Comment: Environmental Hazardous Substance

16. OTHER INFORMATION

MSDS No: 6759

Approved By: Dianne Blessing Title: EH&S Specialist

Disclaimer: The information and recommendations contained herein are based upon tests in controlled laboratory conditions, are believed to be correct, and are provided for the sole purpose of hazard communication as part of Huntsman's product safety program. This product has not been tested for, and therefore is not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for any such uses.

The information and recommendations contained herein are not intended to constitute performance information concerning the product, which is available in separate technical data sheets available from Huntsman upon request. Users are urged, and are urged to urge others who may come in contact with the product, to obtain and consult data sheets prior to purchase, use, transportation or storage of the product.

HUNTSMAN MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY, QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED TO REIMBURSEMENT OF BUYER'S PURCHASE PRICE, OR IN HUNTSMAN'S DISCRETION REPLACEMENT, OF THE PRODUCT IN RESPECT OF WHICH SUCH CLAIM IS MADE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED BY LEGAL NOTICES IN TECHNICAL DATA SHEETS, PRODUCT LITERATURE, AND/OR SALE DOCUMENTS. The foregoing DISCLAIMERS and LIMITATION OF LIABILITY supercede inconsistent or contradictory provisions in Buyer's documents.

USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENTAL AGENCY TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS,

Printed: 9/18/2006 Page 5 of 6 Effective Date: 4/17/06

WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.

Page 6 of 6 Printed: 9/18/2006