

P.O. Box 4980
The Woodlands, TX 77387-4980

8 am to 5 pm Phone: (800) 257-5547
24-Hour Emergency Phone: (800) 328-8501
International Emergency Phone: (409) 727-0831
Asia Pacific Emergency Phone: (65) 6336-6011

Effective Date: 6/5/08


Material Safety Data Sheet

MSDS No: 6763

1. PRODUCT IDENTIFICATION

Trade Name: RenLease 803

Chemical Family: Wax dispersion in hydrocarbon solvent



NFPA RATING

Health:	2*
Flammability:	2
Reactivity:	0
Personal Protection:	

HMIS RATING

Synonyms:
RP 803

Intended Use or Product Type: Release agent

2. COMPOSITION / INFORMATION ON INGREDIENTS

O S H A	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS				CARCINOGEN STATUS			
			ACGIH		OSHA		MFR.	IARC	NTP	OSHA
			TWA	STEL	PEL	STEL				
*	8052-41-3	Stoddard Solvent	100 ppm	NE	500 ppm	NE	NE	NR	NR	NR
	Common Name: Concentration	Aliphatic petroleum distillates 60.00 - 100.00 % by wt								

* = OSHA Hazardous Ingredient

3. HAZARDS IDENTIFICATION

Emergency Overview: Combustible. Causes eye, skin, and respiratory irritations. May cause allergic skin reaction.

Primary Route(s) of Entry: Dermal; heated product may produce inhalable vapors.

Chronic: Overexposure may have effects on kidney and nervous system.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Effective Date: 6/5/08

Skin: Immediately wash with soap and water. Remove contaminated clothing and laundry before reuse. Destroy contaminated shoes. Seek immediate medical attention.

Inhalation: Remove to fresh air. Seek immediate medical attention.

Eyes: Immediately flush eyes with water for at least 15 minutes. Seek immediate medical attention.

Overexposure Effects: Causes eye, skin, and respiratory irritations. May cause allergic skin reaction.

Medical Conditions Aggravated by Exposure: Skin, eye and pulmonary conditions.

Additional Information: Referral to a physician is recommended if there is any question about the seriousness of any injury.

5. FIRE FIGHTING MEASURES

Flash Point:	103°F (39 °C)
Flash Point Method Used:	PMCC
Flammable Limits in Air (Lower - % by volume):	1 %
Flammable Limits in Air (Upper - % by volume):	6 %

Fire Fighting Extinguishing Media: Carbon dioxide, dry chemical, foam, water.

Fire Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Decomposition and combustion products may be toxic.

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Remove spillage by absorbing in absorbent material.

7. HANDLING AND STORAGE

Signal Word: Warning!

Precautions: Combustible. Keep away from heat and flame. Causes eye, skin, and respiratory irritations. May cause allergic skin reaction. Avoid contact with eyes, skin, and clothing. Avoid breathing vapor or mist. Avoid breathing vapor or mist. Avoid prolonged or repeated contact with skin. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Overexposure may have effects on kidney and nervous system.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Skin Protection: Wear impermeable gloves.

Respiratory Protection: Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Effective Date: 6/5/08

Engineering Controls: General mechanical and local exhaust in accordance with ACGIH recommendations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Off White
Odor:	Naphtha odor
Physical State:	Liquid
Solubility in Water:	Insoluble
Vapor Pressure:	0.6 mm Hg at 20°C (68 °F) For Component
Specific Gravity:	0.78 - 0.8 (water = 1)
Boiling Point:	~ 318°F (~ 159 °C)
Melting Point:	Not Determined
Evaporation Rate:	< 1 (ether = 1)
Density:	Not Determined
Bulk Density:	6.59 lb/gal
Vapor Density:	> 1 (Air = 1)
pH:	Not Determined
Coefficient of water/oil:	Not Determined

Percent Volatile: 80 - 90

10. STABILITY AND REACTIVITY

Conditions to Avoid: Excessive heat for prolonged periods of time.

Stability: Stable.

Incompatibility: Strong oxidizers, acids and bases.

Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute Inhalation Exposure Effects: Respiratory irritant.

Sensitization: Possible in susceptible individuals.

Skin Irritation: Irritant.

Eye Irritation: Irritant.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

Effective Date: 6/5/08

14. TRANSPORT INFORMATION**DOT: Non-Bulk**

Proper Shipping Name: Petroleum distillates, n.o.s.
Technical Shipping Name (If n.o.s.): Hydrocarbon naphtha
Hazard Class: 3
ID Number: UN 1268
Packing Group: PG III
Label: Flammable liquid

IATA: Non-Bulk

Proper Shipping Name: Petroleum distillates, n.o.s.
Technical Shipping Name (If n.o.s.): Hydrocarbon naphtha
Hazard Class: 3
ID Number: UN 1268
Packing Group: PG III
Label: Flammable liquid

IMDG: Non-Bulk

Proper Shipping Name: Petroleum distillates, n.o.s.
Technical Shipping Name (If n.o.s.): Hydrocarbon naphtha
Hazard Class: 3
ID Number: UN 1268
Packing Group: PG III
Label: Flammable liquid

TDG: Non-Bulk

Proper Shipping Name: Petroleum distillates, n.o.s.
Technical Shipping Name (If n.o.s.): Hydrocarbon naphtha
Hazard Class: 3
ID Number: UN 1268
Packing Group: PG III
Label: Flammable liquid

15. REGULATORY INFORMATION**US Federal Regulations:**

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

Resource Conservation and Recovery Act (RCRA): D 001 ignitable.

SARA Title III: Section 313 Toxic Chemical List (TCL): This product does not contain any chemicals for routine annual toxic chemical release reporting under Section 313 (40 CFR 372).

TSCA Section 8(b) - Inventory Status: All chemical components of this product are in compliance with TSCA inventory requirements.

TSCA Section 12(b) - Export Notification: This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.

Effective Date: 6/5/08

International Regulations:

Canadian Inventory Status: This product contains only chemicals that are currently listed on the Canadian Domestic Substance List.

Canadian WHMIS: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. B3 D2B

State Regulations:

California Proposition 65: This product does not contain any chemicals currently on the California list of Known Carcinogens and Reproductive Toxins.

Pennsylvania Right-to-Know: The following is required composition information:

Chemical Name: Stoddard Solvent
Common Name: Aliphatic petroleum distillates
CAS Number: 8052-41-3
Comment: Hazardous Substance

Chemical Name: Synthetic waxes
CAS Number: Confidential
Comment: Not on Pennsylvania Hazardous Substance List

16. OTHER INFORMATION

MSDS No:	6763
Approved By:	Dianne Blessing
Title:	EH&S Specialist

Disclaimer: The information and recommendations contained herein are based upon tests in controlled laboratory conditions, are believed to be correct, and are provided for the sole purpose of hazard communication as part of Huntsman's product safety program. This product has not been tested for, and therefore is not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for any such uses.

The information and recommendations contained herein are not intended to constitute performance information concerning the product, which is available in separate technical data sheets available from Huntsman upon request. Users are urged, and are urged to urge others who may come in contact with the product, to obtain and consult data sheets prior to purchase, use, transportation or storage of the product.

HUNTSMAN MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY, QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED TO REIMBURSEMENT OF BUYER'S PURCHASE PRICE, OR IN HUNTSMAN'S DISCRETION REPLACEMENT, OF THE PRODUCT IN RESPECT OF WHICH SUCH CLAIM IS MADE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED BY LEGAL NOTICES IN TECHNICAL DATA SHEETS, PRODUCT LITERATURE, AND/OR SALE DOCUMENTS. The foregoing DISCLAIMERS and LIMITATION OF LIABILITY supercede inconsistent or contradictory provisions in Buyer's documents.

USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENTAL AGENCY TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.

Effective Date: 6/5/08

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.