

4917 Dawn Avenue
East Lansing, MI 48823-5691


8am to 5pm Phone: (517) 351-5900
24-Hour Emergency Phone: 1-888-354-3323

Effective Date: 11/11/04**Material Safety Data Sheet**

MSDS No: 31772

1. PRODUCT IDENTIFICATION**Trade Name:** RenPIM 6486 Slow Polyol**Chemical Family:** Polyol**Synonyms:**

RP 6486 Slow Hardener

Intended Use or Product Type: Polyurethane

NFPA RATING

Health:	2*
Flammability:	1
Reactivity:	0
Personal Protection:	

HMIS RATING

2. COMPOSITION / INFORMATION ON INGREDIENTS

O S H A	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS				CARCINOGEN STATUS			
			ACGIH		OSHA		MFR.	IARC	NTP	OSHA
			TWA	STEL	PEL	STEL				
*	8002-26-4	Tall Oil	NE	NE	NE	NE	NE	NR	NR	NR
*	102093-68-5	1,3-Benzenediamine, 4-Methyl-2,6-bis(Methylthio) Di-(methylthio) toluenediamine Common Name:	NE	NE	NE	NE	NE	NR	NR	NR
*	104983-85-9	1,3-Benzenediamine, 2-Methyl-4,6-bis(Methylthio)- Di-(methylthio) toluenediamine Common Name:	NE	NE	NE	NE	NE	NR	NR	NR

* = OSHA Hazardous Ingredient

3. HAZARDS IDENTIFICATION

Emergency Overview: Can cause skin irritation, eye irritation, and allergic skin reaction. May be harmful if swallowed.

Primary Route(s) of Entry: Dermal; heated product may produce inhalable vapors.

Chronic: Overexposure may have effects on kidney and liver.

Diocyl adipate (DOA) was tested by the National Toxicology Program/National Cancer Institute (NCI/NTP) in a lifetime feeding study in rats and mice. It was reported that extremely high doses of DOA caused an increased incidence of liver tumors in female mice. Male mice and both male and female rats did not show this response. Previous long-term feeding studies with DOA in rats and dogs did not detect tumors. Thus, interpretation of the NTP/NCI bioassay results has proved difficult.

Effective Date: 11/11/04

4. FIRST AID MEASURES

Ingestion: If conscious, give 2 - 4 glasses of water to drink. Do not induce vomiting. Call a physician.

Skin: Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes.

Inhalation: Remove to fresh air. Call a physician.

Eyes: Immediately flush eyes with water for at least 15 minutes. Call a physician.

Overexposure Effects: Can cause skin irritation, eye irritation, and allergic skin reaction. May be harmful if swallowed.

Medical Conditions Aggravated by Exposure: Skin and eye conditions.

Additional Information: Referral to a physician is recommended if there is any question about the seriousness of any injury.

5. FIRE FIGHTING MEASURES

Flash Point: > 210°F (> 99 °C)

Flash Point Method Used: PMCC

Flammable Limits in Air (Lower - % by volume): Not established

Flammable Limits in Air (Upper - % by volume): Not established

Fire Fighting Extinguishing Media: Carbon dioxide, dry chemical, foam, water.

Fire Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Decomposition and combustion products may be toxic.

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Remove spillage by absorbing in absorbent material.

7. HANDLING AND STORAGE

Signal Word: Warning!

Precautions: Can cause skin irritation, eye irritation, and allergic skin reaction. May be harmful if swallowed. Avoid contact with eyes, skin, and clothing. Avoid tasting or swallowing. Wash thoroughly after handling. Notice! Overexposure may have effects on kidney and liver.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Effective Date: 11/11/04

Skin Protection: Wear impermeable gloves.

Respiratory Protection: Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Engineering Controls: General mechanical and local exhaust in accordance with ACGIH recommendations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Dark Green/Amber
Odor:	Characteristic
Physical State:	Liquid
Solubility in Water:	Slight
Vapor Pressure:	Not Determined
Specific Gravity:	1.12 (water = 1)
Boiling Point:	Not Determined
Evaporation Rate:	Not Determined
Vapor Density:	Not Determined
pH:	Not Determined

Percent Volatile: Negligible.

10. STABILITY AND REACTIVITY

Conditions to Avoid: Excessive heat for prolonged periods of time.

Stability: Stable.

Incompatibility: Strong oxidizers, acids and bases.

Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute Oral Effects (LD50): Component(s) are slightly toxic, 500 - 5000 mg/kg (rat).

Sensitization: Possible in susceptible individuals.

Skin Irritation: Irritant.

Eye Irritation: Irritant.

Sub-Chronic: Butyl benzyl phthalate (BBP) produced liver necrosis and pancreatic lesions at a dose of approximately 675 mg/kg/day and 275 mg/kg/day, respectively, during a 90-day oral administration study with rats. The no observable effect levels (NOEL) were approximately 275 and 110 mg/kg/day, respectively.

Effective Date: 11/11/04

12. ECOLOGICAL INFORMATION**13. DISPOSAL CONSIDERATIONS**

Waste Disposal Method: Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

14. TRANSPORT INFORMATION**DOT: Non-Bulk**

Proper Shipping Name: Resin compounds, N.O.I.

Department of Transportation: Not regulated as a hazardous material by the U.S. Dept. of Transportation (DOT) 49 CFR 172.101 hazardous materials table.

15. REGULATORY INFORMATION**US Federal Regulations:**

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261).

SARA Title III: Section 313 Toxic Chemical List (TCL): This product does not contain any chemicals for routine annual toxic chemical release reporting under Section 313 (40 CFR 372).

TSCA Section 8(b) - Inventory Status: All chemical components of this product are in compliance with TSCA inventory requirements.

TSCA Section 12(b) - Export Notification: This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.

State Regulations:

California Proposition 65: This product does not contain any chemicals currently on the California list of Known Carcinogens and Reproductive Toxins.

Pennsylvania Right-to-Know: The following is required composition information:

Chemical Name: 1,3-Benzenediamine, 4-Methyl-2,6-bis(Methylthio)

Common Name: Di-(methylthio) toluenediamine

CAS Number: 102093-68-5

Comment: Not on Pennsylvania Hazardous Substance List

Effective Date: 11/11/04

Chemical Name: 1,2- Benzenedicarboxylic acid, butyl phenylmethyl ester
Common Name: Butyl benzyl phthalate
CAS Number: 85-68-7
Comment: Environmental Hazardous Substance

Chemical Name: Hexanedioic acid, bis(2-ethylhexyl) ester
Common Name: Dioctyl adipate
CAS Number: 103-23-1
Comment: Environmental Hazardous Substance

Chemical Name: 1,3-Benzenediamine, 2-Methyl-4,6-bis(Methylthio)-
Common Name: Di-(methylthio) toluenediamine
CAS Number: 104983-85-9
Comment: Not on Pennsylvania Hazardous Substance List

16. OTHER INFORMATION

MSDS No: 31772
Approved By: Dianne Blessing
Title: EH&S Specialist

Disclaimer: The information and recommendations contained herein are based upon tests in controlled laboratory conditions, are believed to be correct, and are provided for the sole purpose of hazard communication as part of Huntsman's product safety program. This product has not been tested for, and therefore is not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for any such uses.

The information and recommendations contained herein are not intended to constitute performance information concerning the product, which is available in separate technical data sheets available from Huntsman upon request. Users are urged, and are urged to urge others who may come in contact with the product, to obtain and consult data sheets prior to purchase, use, transportation or storage of the product.

HUNTSMAN MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY, QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED TO REIMBURSEMENT OF BUYER'S PURCHASE PRICE, OR IN HUNTSMAN'S DISCRETION REPLACEMENT, OF THE PRODUCT IN RESPECT OF WHICH SUCH CLAIM IS MADE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED BY LEGAL NOTICES IN TECHNICAL DATA SHEETS, PRODUCT LITERATURE AND/OR SALE DOCUMENTS. The foregoing DISCLAIMERS and LIMITATION OF LIABILITY supercede inconsistent or contradictory provisions in Buyer's documents.

USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENTAL AGENCY TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.