

Distributed by Freeman Mfg & Supply Co.  
800-321-8511 www.freemansupply.com

24-Hour Emergency Phone: 1-888-354-3323

Effective Date: 1/20/04


Material Safety Data Sheet

MSDS No: 34632

**1. PRODUCT IDENTIFICATION**

Trade Name: RenCast 6492

Chemical Family: Isocyanate



NFPA RATING

Health:	2*
Flammability:	1
Reactivity:	1
Personal Protection:	

HMIS RATING

Intended Use or Product Type: Polyurethane resin

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

O S H A	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS				CARCINOGEN STATUS			
			ACGIH		OSHA		MFR.	IARC	NTP	OSHA
			TWA	STEL	PEL	STEL				
*	101-68-8	Benzene, 1,1'-Methylenebis[4-Isocyanato-MDI Common Name:	0.005 ppm	NE	0.02 ppm	NE	NE	NR	NR	NR
*	25686-28-6	Benzene, 1,1'-Methylenebis[4-Isocyanato-, Homopolymer Modified MDI Common Name:	NE	NE	NE	NE	NE	NR	NR	NR
*	26447-40-5	Benzene, 1,1'-Methylenebis[Isocyanato-Diphenylmethane diisocyanate Common Name:	NE	NE	NE	NE	NE	NR	NR	NR
*	115-96-8	Ethanol, 2-Chloro-, Phosphate (3:1) Chlorinated phosphate ester Common Name:	NE	NE	NE	NE	NE	NR	NR	NR

NE = Not Established NR = Not Reviewed \* = OSHA Hazardous Ingredient

**3. HAZARDS IDENTIFICATION**

**Emergency Overview:** Causes irritation if inhaled and can cause skin irritation, eye irritation, allergic respiratory reaction, and allergic skin reaction. Can be harmful if swallowed.

**Primary Route(s) of Entry:** Dermal; heated product may produce inhalable vapors.

Effective Date: 1/20/04

#### **4. FIRST AID MEASURES**

**Ingestion:** If conscious, give 2 - 4 glasses of water to drink. Do not induce vomiting. Call a physician.

**Skin:** Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes.

**Inhalation:** Remove to fresh air. Call a physician.

**Eyes:** Immediately flush eyes with water for at least 15 minutes. Call a physician.

**Overexposure Effects:** Contact with liquid causes eye and skin irritation. If inhaled causes breathlessness, chest discomfort, and reduced pulmonary function. May cause allergic skin and respiratory reactions in some individuals, leading to asthma type spasms of the bronchial tubes and difficulty in breathing. Ingestion (ethanol, 2 chloro, phosphate) can cause harm to the central nervous system.

**Medical Conditions Aggravated by Exposure:** Persons with asthmatic-type conditions, chronic bronchitis, other chronic respiratory diseases, eye conditions or recurrent skin eczema or sensitization should be excluded from working with isocyanates.

**Additional Information:** Referral to a physician is recommended if there is any question about the seriousness of any injury.

#### **5. FIRE FIGHTING MEASURES**

**Flash Point:** > 350°F (> 177 °C)

**Flash Point Method Used:** PMCC

**Flammable Limits in Air (Lower - % by volume):** Not established

**Flammable Limits in Air (Upper - % by volume):** Not established

**Fire Fighting Extinguishing Media:** Carbon dioxide, dry chemical, foam, water.

**Fire Fighting Equipment:** Use self-contained breathing apparatus.

**Fire and Explosion Hazards:** Decomposition and combustion products may be toxic.

#### **6. ACCIDENTAL RELEASE MEASURES**

**Accidental Release Measures:** Remove spillage by absorbing in absorbent material.

#### **7. HANDLING AND STORAGE**

**Signal Word:** Warning!

**Precautions:** Causes irritation if inhaled and can cause skin irritation, eye irritation, allergic respiratory reaction, and allergic skin reaction. Can be harmful if swallowed. Avoid breathing vapor or mist. Avoid contact with eyes, skin, and clothing. Avoid tasting or swallowing. Keep container closed when not in use. Use with adequate ventilation. Wash thoroughly after handling.

**Other Handling Information:** Nuisance dust may be generated when sanding or sawing cured material.

#### **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Effective Date: 1/20/04

**Skin Protection:** Wear impermeable gloves.

**Respiratory Protection:** If a person is concerned with exposure to isocyanates, an organic respirator can provide protection at less than the TLV. It is not a requirement at an exposure level less than the TLV. For exposures in excess of the TLV, an air supplied respirator would be required. Conditions that may create exposures above the TLV are spray applications, the material being strongly heated in excess of 125F before application, or the use of material in poorly ventilated areas.

**Eye Protection:** Wear splash-proof chemical goggles.

**Engineering Controls:** General mechanical and local exhaust in accordance with ACGIH recommendations.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Color:</b>	Amber
<b>Physical State:</b>	Liquid
<b>Solubility in Water:</b>	Reacts with water
<b>Vapor Pressure:</b>	0.0002 mm Hg at 25°C (77 °F)
<b>Specific Gravity:</b>	1.22 - 1.24 (water = 1)
<b>Boiling Point:</b>	Not Determined
<b>Evaporation Rate:</b>	Not Determined
<b>Vapor Density:</b>	> 1 (Air = 1)
<b>pH:</b>	Not Determined

**Percent Volatile:** Negligible.

## **10. STABILITY AND REACTIVITY**

**Conditions to Avoid:** Excessive heat for prolonged periods of time.

**Stability:** Stable.

**Incompatibility:** Strong oxidizers, acids and bases.

**Hazardous Decomposition Products:** Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

**Hazardous Polymerization:** Will not occur.

## **11. TOXICOLOGICAL INFORMATION**

**Acute Oral Effects (LD50):** Component(s) are slightly toxic, 500 - 5000 mg/kg (rat).  
Ethanol, 2-chloro-, phosphate (3:1)= 550 mg/kg (rat)

**Acute Inhalation Exposure Effects:** Respiratory irritant.

**Sensitization:** May cause allergic skin reaction and respiratory sensitivity in some people.

**Skin Irritation:** Irritant.

**Eye Irritation:** Irritant.

Effective Date: 1/20/04

**12. ECOLOGICAL INFORMATION****13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

**14. TRANSPORT INFORMATION****DOT: Non-Bulk****Proper Shipping Name:** Resin compounds, N.O.I.

**Department of Transportation:** Not regulated as a hazardous material by the U.S. Dept. of Transportation (DOT) 49 CFR 172.101 hazardous materials table.

**15. REGULATORY INFORMATION****US Federal Regulations:**

**Occupational Safety and Health Act (OSHA):** This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

**Resource Conservation and Recovery Act (RCRA):** Not specifically listed as hazardous waste under RCRA (40 CFR 261). However, it is strongly recommended that compound be treated as a hazardous waste and disposed of accordingly.

**SARA Title III: Section 313 Toxic Chemical List (TCL):** This product contains a toxic chemical(s) for routine annual toxic chemical release reporting under section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this material.

Chemical Name: Benzene, 1,1'-Methylenebis[4-Isocyanato-

Common Name: MDI

Percent in Composition: 67.5 % by wt

Comment:

**TSCA Section 8(b) - Inventory Status:** Chemical components listed on TSCA Inventory.

**TSCA Section 12(b) - Export Notification:** This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.

**State Regulations:**

**Pennsylvania Right-to-Know:** The following is required composition information:

Chemical Name: Benzene, 1,1'-Methylenebis[4-Isocyanato-

Common Name: MDI

CAS Number: 101-68-8

Comment: Environmental Hazardous Substance

---

**Effective Date: 1/20/04**

---

Chemical Name: 1,1'-Methylenebis(4-Isocyanatobenzene) Homopolymer  
Common Name: Modified MDI  
CAS Number: 25686-28-6  
Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: Ethanol, 2-Chloro-, Phosphate (3:1)  
Common Name: Chlorinated phosphate ester  
CAS Number: 115-96-8  
Comment: Not on Pennsylvania Hazardous Substance List

## **16. OTHER INFORMATION**

**MSDS No:** 34632  
**Approved By:** Dianne Blessing  
**Title:** EH&S Specialist

**Disclaimer:** The following supercedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict liability, tort or contract arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled or lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.