



DIRECCION : VALLE DE COLCURA S/N LOTA VIII Región  
 CASILLA : 51, Lota, Chile  
 TELEFONOS : 41 - 878000  
 FAX : 41 - 878001

**DISTRIBUTED BY FREEMAN MFG & SUPPLY CO.**  
 800-321-8511 [www.freemansupply.com](http://www.freemansupply.com)

<b>MATERIAL SAFETY DATA SHEET</b>			
<b>CAS NUMBER: None</b>	<b>Common Name: PSF OVERLAID PLYWOOD</b>		
<b>PRODUCTS IDENTIFICATION</b>	<p><b>SYNONYMS:</b> Phenolic Surface Film Overlaid Plywood for Concrete Forming.</p> <p><b>DESCRIPTION:</b> Layers of wood vanner bonded together with phenolic resins Overlaid with sheets of Medium Density Paper topped with a Phenolic Resin impregnated surface film.</p>		
<b>HAZARDOUS INGREDIENTS</b>	<p><b>COMPONENTS:</b> Wood Dust Free Fomaldehyde</p> <p><b>CAS NUMBER:</b> Wood Dust - None Free Formaldehyde 50-00-0</p> <p><b>PERCENTAGE:</b> Wood Dust - Variable Free Formaldehyde -&gt; 01%</p>		
<b>HEALTH EFFECTS INFORMATION</b>	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; vertical-align: top;"> <p style="text-align: center;"><b>WOOD DUST</b></p> <p><b>EXPOSURE OSHA PEL - None</b>  <b>LIMIT: ACGIH YLV - Softwood 5 mg/M3</b>                      8 hour TWA                      10 mg/M3 Stel                      Hardwood a mg/M3                      8 hour TWA</p> <p><b>EYE CONTACT:</b> Wood dust may cause eye irritation. Formaldehyde gas may cuses temporary irritation to eye tissue.</p> <p><b>INHALATION:</b> Wood dust may cause nasal obstruction. Formaldehyde gas may cause headaches, sneezing, shortness of breath and may cause sensitization in susceptible individuals. Formaldeyde is listed as an "A" carcinogen.</p> </td> <td style="width: 50%; vertical-align: top; border-left: 1px solid black; border-right: 1px solid black;"> <p style="text-align: center;"><b>UREA FORMALDEHYDE</b></p> <p>1 ppm TWQ, 2ppm STEL 1 ppm</p> </td> </tr> </table>	<p style="text-align: center;"><b>WOOD DUST</b></p> <p><b>EXPOSURE OSHA PEL - None</b>  <b>LIMIT: ACGIH YLV - Softwood 5 mg/M3</b>                      8 hour TWA                      10 mg/M3 Stel                      Hardwood a mg/M3                      8 hour TWA</p> <p><b>EYE CONTACT:</b> Wood dust may cause eye irritation. Formaldehyde gas may cuses temporary irritation to eye tissue.</p> <p><b>INHALATION:</b> Wood dust may cause nasal obstruction. Formaldehyde gas may cause headaches, sneezing, shortness of breath and may cause sensitization in susceptible individuals. Formaldeyde is listed as an "A" carcinogen.</p>	<p style="text-align: center;"><b>UREA FORMALDEHYDE</b></p> <p>1 ppm TWQ, 2ppm STEL 1 ppm</p>
<p style="text-align: center;"><b>WOOD DUST</b></p> <p><b>EXPOSURE OSHA PEL - None</b>  <b>LIMIT: ACGIH YLV - Softwood 5 mg/M3</b>                      8 hour TWA                      10 mg/M3 Stel                      Hardwood a mg/M3                      8 hour TWA</p> <p><b>EYE CONTACT:</b> Wood dust may cause eye irritation. Formaldehyde gas may cuses temporary irritation to eye tissue.</p> <p><b>INHALATION:</b> Wood dust may cause nasal obstruction. Formaldehyde gas may cause headaches, sneezing, shortness of breath and may cause sensitization in susceptible individuals. Formaldeyde is listed as an "A" carcinogen.</p>	<p style="text-align: center;"><b>UREA FORMALDEHYDE</b></p> <p>1 ppm TWQ, 2ppm STEL 1 ppm</p>		
<b>EMERGENCY AND FIRST AID</b>	<p><b>EYES:</b> Remove to fresh air, flush with water.</p> <p><b>INHALATION:</b> Remeve to fresh air.</p> <p><b>INGESTION:</b> Not applicable</p>		