



# MATERIAL SAFETY DATA SHEET

## Lab-metal

### 1. Product And Company Identification

**Supplier**

Alvin Products, Inc. a division of Dampney Co. Inc.  
85 Paris Street, Everett, MA 02149

Telephone Number: 617-389-2805

FAX Number: 617-389-0484

E-Mail: sales@alvinproducts.com

Web Site: www.alvinproducts.com

**Distributor**

Freeman Mfg & Supply Co.  
1101 Moore Rd  
Avon, OH 44011

Telephone Number: 800-321-8511

FAX Number: 440-934-7200

Web site: www.freemansupply.com

**Supplier Emergency Contacts & Phone Number**

Chemtrec (24-hrs): 800-424-9300

Issue Date: 10/01/2005

Product Name: Lab-metal

CAS Number: NE

MSDS Number: 750

Product Code: 10100, 10101, 10102, 10103, 10104, 10105, 12201

**Product/Material Uses**

Used to repair and fill holes, surface defects, dents, and rough or porous areas on metal parts. Seals seams and joints in sheet metal. Builds up worn metal surfaces.

### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
POWDERED ALUMINUM	7429-90-5	43 - 57
BARIUM SULFATE	7727-43-7	20 - 30
METHYL ETHYL KETONE	78-93-3	5 - 10
TOLUENE	108-88-3	5 - 10

### EMERGENCY OVERVIEW

**WARNING: FLAMMABLE LIQUID AND VAPOR.** Contains powdered aluminum, barium sulfate, toluol, and methyl ethyl ketone. USE ONLY WITH ADEQUATE VENTILATION.

Vapor Harmful - may affect the brain or nervous system, causing dizziness, headache, or nausea. Causes eye, skin, nose and throat irritation. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks and open flame. Vapors may cause flash fire. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not cut open or reuse container. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with skin and eyes.

**KEEP CAN TIGHTLY CLOSED - STORE IN COOL PLACE.**

**KEEP OUT OF REACH OF CHILDREN.**

# MATERIAL SAFETY DATA SHEET

## Lab-metal

### 3. Hazards Identification

#### Primary Routes(s) Of Entry

Inhalation, Skin absorption, Skin contact, Eye contact

#### Eye Hazards

Direct contact and exposure to vapors is irritating to mucous membranes and the eyes, possibly causing stinging, tearing, redness and swelling of the eyes. Direct eye contact with product or high vapor concentrations may cause possible corneal damage.

#### Skin Hazards

Contact may cause mild to moderate skin and mucous membrane irritation. Prolonged skin contact may defat the skin and produce dermatitis. Possible symptoms include redness, burning, drying and cracking of the skin.

Absorption of this material through the skin is possible. But it is unlikely that harmful amounts will be absorbed from a single, brief exposure. Absorption of large amounts from prolonged exposure may produce central nervous system depression and effects similar to those from inhalation.

#### Ingestion Hazards

Accidental swallowing of minute amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. Aspiration into the lungs after swallowing or vomiting can result in lung inflammation, lung injury and even death due to chemical pneumonia, respiratory failure and cardiac arrest.

Ingestion may also cause irritation of the gastrointestinal tract and other systemic effects from absorption. Possible symptoms could include: nausea, vomiting, diarrhea, central nervous system depression (dizziness, drowsiness, weakness, fatigue, headache, unconsciousness), muscle weakness, loss of coordination, coma, confusion, or possibly death.

#### Inhalation Hazards

Inhalation of low vapor concentrations under normal conditions of handling is not likely to cause harmful effects. Inhalation of high concentrations for brief periods may cause irritation to the nose, throat and lungs, and central nervous system effects.

Prolonged or intentional exposure may lead to the damage of many organ systems, including the central and peripheral nervous system, vision, hearing, liver, kidneys, lungs, heart and blood. Symptoms may include: headache, dizziness, drowsiness, loss of coordination, fatigue, headache, irritation, nausea, vomiting, sleep disturbance, and mental confusion. Overexposures to components of this product have been associated with cardiac sensitization.

Product contains aluminum powder. Short exposures to high concentrations of dust during filling, grinding and sanding of dry product may cause coughing and mild temporary irritation.

#### Chronic/Carcinogenicity Effects

This material is not expected to cause cancer in humans.

#### Conditions Aggravated By Exposure

Individuals with diseases of the nervous system, respiratory tract, skin, heart, liver, and kidneys should avoid or limit exposure. Those persons susceptible to dermatitis should limit skin contact.

### 4. First Aid Measures

#### Eye

In case of eye contact, blot away excess chemical from around the eyes. Hold eyelids apart and immediately flush eyes with plenty of luke warm, gently flowing water for at least 15 minutes. Get medical attention.

# MATERIAL SAFETY DATA SHEET

## Lab-metal

### 4. First Aid Measures - Continued

#### **Skin**

Remove contaminated clothing and shoes. Wash affected areas with soap and water. Get medical attention immediately if irritation (redness, rash, blistering) develops. Wash clothing before reuse.

#### **Ingestion**

If swallowed, DO NOT INDUCE VOMITING unless directed to do so by medical personnel. CALL A PHYSICIAN OR THE POISON CONTROL CENTER IMMEDIATELY.

If the victim stops breathing: Wipe away any remaining materials off the lips. Clear the airway and administer artificial respiration.

If the victim is conscious: Have the person rinse his/her mouth several times with cold water and spit out. Lean the person forward to reduce risk of aspiration. Have the person drink 8 to 10 oz. of water to dilute. If possible, give a mixture of 2 tablespoons of activated charcoal with water to drink. Repeat administration of water. Keep the person warm and quiet. Never give anything by mouth to an unconscious victim or a person losing consciousness.

#### **Inhalation**

Remove the person away from exposure to fresh air. Keep the victim warm and quiet. Support breathing as necessary. Administer cardiopulmonary resuscitation if pulse has stopped. Get medical attention immediately.

#### **Note To Physician**

Inhalation of high concentrations of this product, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. This material is an aspiration hazard. The potential danger from aspiration must be weighed against possible oral toxicity.

### 5. Fire Fighting Measures

#### **Fire And Explosion Hazards**

FLAMMABLE. DO NOT USE NEAR FIRE OR FLAME. Vapor may cause flash fire.

Vapors may accumulate in confined spaces (e.g., pits, sumps, sewers) and inadequately ventilated areas. Vapors may travel to areas (rooms) away from worksite before igniting/flashing back to vapor source.

Do not reuse container. Keep away from heat, sparks, open flame and other ignition sources. In the presence of an ignition source, containers containing residual flammable vapors may explode causing serious injury or death. Do not cut open or apply heat sources to containers.

#### **Extinguishing Media**

Fire-fighting foam, carbon dioxide, dry chemical. Water spray may be used to cool fire exposed containers.

#### **Fire Fighting Instructions**

Fire fighters should wear self-contained breathing apparatus and full protective gear. Avoid breathing vapors, gases and fumes. If safe to do so, shut off all gas pilot lights and electrical (spark or hot-wire) igniters and other sources of ignition. Water can be used to cool and protect exposed material.

### 6. Accidental Release Measures

Eliminate all ignition sources. Provide maximum dilution or explosion-proof exhaust ventilation. Avoid release to the environment. For large spills, use fire fighting foam or water spray to disperse vapors.

Use appropriate personal protective equipment. Contain and pickup spilled material using spark-resistant tools. Absorb any residual solvent with inert material (e.g. sand, vermiculite) or other flammable solvent absorbing materials. Collect and dispose using approved waste containers.

# MATERIAL SAFETY DATA SHEET

## Lab-metal

### 7. Handling And Storage

#### Handling And Storage Precautions

Keep out of reach of children. Keep containers tightly closed. Use only with adequate ventilation. Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors, and static electricity). Protect from temperature extremes and direct sunlight. Do not reuse or cut open empty containers.

Avoid exposure to vapor. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

#### Work/Hygienic Practices

Use good personal hygiene. Wash thoroughly with soap and water after handling.

### 8. Exposure Controls/Personal Protection

#### Engineering Controls

Use with adequate general and local exhaust ventilation to maintain air concentrations below recognized exposure limits.

#### Eye/Face Protection

Safety glasses with side shields or goggles.

#### Skin Protection

Chemical-resistant gloves made of Teflon or Viton are recommended. PVA or butyl rubber gloves may also be used for short-term work involving limited contact. Note: PVA should not be used when contact with water is expected. Consult your glove manufacturer for additional chemical resistance information and glove limitations.

#### Respiratory Protection

None normally required when used with adequate ventilation. In case of inadequate ventilation, use a NIOSH-approved respirator for organic vapors when applying product. A 95-series particulate respirator should be used when filing, grinding, or sanding.

Engineering controls should be implemented preferentially to reduce exposures. The level of respiratory protection needed should be based on the required protection factor after evaluating chemical exposures using appropriate industrial hygiene monitoring and/or OSHA guidance. Use self-contained breathing apparatus (SCBA) for fires and large spill cleanup.

#### Ingredient(s) - Exposure Limits

##### POWDERED ALUMINUM

ACGIH TLV-TWA: 10 mg/m<sup>3</sup>

OSHA PEL-TWA: 15 mg/m<sup>3</sup> (total dust)

OSHA PEL-TWA: 5 mg/m<sup>3</sup> (respirable dust)

##### BARIUM SULFATE

ACGIH TLV-TWA: 10 mg/m<sup>3</sup>

OSHA PEL-TWA: 15 mg/m<sup>3</sup> (total dust)

OSHA PEL-TWA: 5 mg/m<sup>3</sup> (respirable dust)

##### METHYL ETHYL KETONE

ACGIH TLV-TWA: 200 ppm

ACGIH TLV-STEL: 300 ppm

OSHA PEL-TWA: 200 ppm

##### TOLUENE

ACGIH TLV-TWA: 50 ppm (Skin)

OSHA PEL-CEILING: 300 ppm

OSHA PEL-PEAK: 500 ppm (10-min)

OSHA PEL-TWA: 200 ppm

# MATERIAL SAFETY DATA SHEET

## Lab-metal

### 9. Physical And Chemical Properties

#### Appearance

A gray or aluminum-gray colored semi-solid

#### Odor

A characteristic solvent odor

**Chemical Type:** Mixture

**Physical State:** Liquid

**Boiling Point:** 175 to 231 °F

**Specific Gravity:** 1.77 g/ml (14.75 lbs/gal)

**Percent Volatiles:** 20

**Percent VOCs:** 10

**Vapor Density:** > 1

**Solubility:** negligible to slight in water

**Viscosity:** > 1,000,000 CPS

**Evaporation Rate:** slower than ethyl ether

### 10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will Not Occur

#### Conditions To Avoid (Stability)

Avoid contact with heat, spark, open flame or other source of ignition. Do not reuse or cut open empty container.

#### Incompatible Materials

Avoid contact with strong oxidizing agents (e.g., sulfuric acid, nitric acid), reducing agents, acids, alkalis and aliphatic amines. May attack some rubber and plastics.

#### Hazardous Decomposition Products

Thermal oxidation (i.e., "burning") may produce decomposition products of carbon and nitrogen. Burning at extreme temperatures may produce oxides of aluminum and barium.

### 11. Toxicological Information

#### Subchronic (Target Organ Effects)

Long-term exposures may be harmful to the nervous system, lungs, kidneys, liver, heart and blood.

A link between aluminum exposure and neurological diseases, such as Alzheimer's disease, has been suggested.

#### Chronic/Carcinogenicity

Neither the product overall nor any of its ingredients are known to be listed as potentially carcinogenic by NTP, IARC, OSHA or ACGIH.

#### Teratogenicity (Birth Defects)

Components of this product have been toxic to the embryo and fetus of laboratory animals at doses toxic to the mother, and have caused birth defects when dosed orally. The significance of animal data to human exposure is unknown. Prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans.

Human studies have also suggested a link between exposure to organic solvents with increased occurrence of miscarriages or birth defects in children. However, in the majority of cases, there was simultaneous exposure to a variety of solvents.

#### Reproductive Effects

Disruption of menstrual function has been reported from exposure to toluene.

# MATERIAL SAFETY DATA SHEET

## Lab-metal

### 12. Ecological Information

Protect drains, sewers, and waterways. Product may be moderately toxic to aquatic organisms on an acute basis.

### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Dispose of unused or spill cleanup material as hazardous waste. Do not reuse empty containers.

#### RCRA Information

Unused, unsolidified waste material may meet the RCRA characteristics for Ignitable (DOO1) waste.

### 14. Transport Information

#### Proper Shipping Name

Paint (Limit Quantity ORM-D)

#### Hazard Class

3

#### DOT Identification Number

UN1263

#### DOT Shipping Label

Flammable

Certain quantities of the product packaged for ground transportation may qualify for categorization under Consumer Commodity ORM-D and/or Limited Quantity exemptions. Consult the manufacturer and/or DOT regulations.

#### DOT (Pictograms)



#### TDG - Canada (Pictograms)



### 15. Regulatory Information

#### U.S. Regulatory Information

Toxic Substance Control Act (TSCA): All ingredients of this product are listed on the TSCA Chemical Substance Inventory.

#### SARA Hazard Classes

Acute Health Hazard  
Chronic Health Hazard  
Fire Hazard

#### Ingredient(s) - U.S. Regulatory Information

POWDERED ALUMINUM  
SARA Title III - Section 313 Form "R"/TRI Reportable Chemical  
METHYL ETHYL KETONE  
SARA Title III - Section 313 Form "R"/TRI Reportable Chemical  
TOLUENE  
SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

# MATERIAL SAFETY DATA SHEET

## Lab-metal

### 15. Regulatory Information - Continued

#### State Regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects, or other reproductive harm.

#### Ingredient(s) - State Regulations

##### POWDERED ALUMINUM

New Jersey - Workplace Hazard  
New Jersey - Environmental Hazard  
Pennsylvania - Workplace Hazard  
Pennsylvania - Environmental Hazard  
Massachusetts - Hazardous Substance  
New York City - Hazardous Substance

##### BARIUM SULFATE

New Jersey - Workplace Hazard

##### METHYL ETHYL KETONE

New Jersey - Workplace Hazard  
New Jersey - Environmental Hazard  
New Jersey - Special Hazard  
Pennsylvania - Workplace Hazard  
Pennsylvania - Environmental Hazard  
Massachusetts - Hazardous Substance  
New York City - Hazardous Substance

##### TOLUENE

New Jersey - Workplace Hazard  
New Jersey - Environmental Hazard  
New Jersey - Special Hazard  
Pennsylvania - Workplace Hazard  
Pennsylvania - Environmental Hazard  
California - Proposition 65  
Massachusetts - Hazardous Substance  
New York City - Hazardous Substance

#### Canadian Regulatory Information

Class B2 - Division 2: Flammable Liquid  
Class D2 - Division 2: Materials Causing Other Toxic Effects

#### Ingredient(s) - Canadian Regulatory Information

##### METHYL ETHYL KETONE

WHMIS - Ingredient Disclosure List

##### TOLUENE

WHMIS - Ingredient Disclosure List

#### European Union (EU) Regulatory Information

European Union Risk Phrases -  
R11 - Highly Flammable  
R36/37/38 - Irritating to skin, eye and respiratory system

European Union Safety Phrases -  
S2 - Keep out of reach of children  
S7 - Keep container tightly closed  
S9 - Keep container in a well-ventilated place  
S16 - Keep away from sources of ignition - no smoking

# MATERIAL SAFETY DATA SHEET

## Lab-metal

### 15. Regulatory Information - Continued


#### European Union (EU) Regulatory Information - Continued

S29 - Do not empty into drains  
S33 - Take precautionary measures against static discharges  
S51 - Use only in well ventilated areas

#### WHMIS - Canada (Pictograms)



#### NFPA



#### HMIS

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	B

### 16. Other Information

#### Reference Documentation

The following were the primary references used in the creation of this MSDS:

- \* U.S. National Library of Medicine Hazardous Substance Databank (HSDB) - aluminum, toluene, acetone
- \* Canadian Centre for Occupational Health & Safety (CCINFO) MSDS Database - aluminum, toluene, acetone
- \* Guide to Occupational Exposure Values, ACGIH 2002
- \* Quick Selection Guide to Chemical Protective Clothing
- \* Fire Protection Guide on Hazardous Materials
- \* Rapid Guide to Chemical Incompatibilities, 1997
- \* Toluene MSDS (Ashland, 8/3/99)

#### Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

Alvin Products, Inc.

Printed Using MSDS Generator™ 2000