



Distributed By -
FREEMAN Mfg. & Supply Co.
 1101 MOORE ROAD
 AVON, OHIO 44011-1011 (800) 321-8511

MATERIAL SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

THIS MATERIAL SAFETY DATA SHEET IS AVAILABLE IN SPANISH UPON REQUEST.

LOS DATOS DE SEGURIDAD DEL PRODUCTO PUEDEN OBTENERSE EN ESPANOL SI LO REQUIERE.

PRODUCT NAME : WOOD DOUGH -ALL COLORS
 UPC NUMBER : 11008, 21141, 21142, 21143, 21144, 21146, 21147, 21151, 21152, 21161, 21162, 21166, 21167, 21171, 21172, 21176, 21177, 21181, 21186, 99940, 99941
 PRODUCT USE/CLASS : Wood Dough
 MSDS NUMBER : 10504

MANUFACTURER:
 DAP INC.
 P.O. BOX 277
 DAYTON, OH 45401-0277

24 HOUR EMERGENCY:
 TRANSPORTATION: 1-800-535-5053
 MEDICAL(U.S.) : 1-800-327-3874

PREPARE DATE: 02/06/96
 REVISION NO.: 13
 REVISION DATE: 02/01/97

GENERAL INFORMATION:
 DAP INC.: 1-800-543-3840

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

| ITEM | CHEMICAL NAME | CAS NUMBER | WT/WT % RANGE |
|------|---------------------|------------|---------------|
| 01 | Isopropanol | | |
| 02 | Acetone | 67-63-0 | 5.0-10.0 % |
| 03 | Methyl ethyl ketone | 67-64-1 | 10.0-15.0 % |
| 04 | Naphtha | 78-93-3 | 5.0-10.0 % |
| 05 | Dibutyl phthalate | 8030-30-6 | 5.0-10.0 % |
| 06 | Cellulose nitrate | 84-74-2 | 1.0-5.0 % |
| | | 9004-70-0 | 5.0-10.0 % |

EXPOSURE LIMITS

| ITEM | ACGIH | | OSHA | | COMPANY TLV-TWA | SKIN |
|------|---------|----------|---------|-------------|-----------------|------|
| | TLV-TWA | TLV-STEL | PEL-TWA | PEL-CEILING | | |
| 01 | 400 ppm | 500 ppm | 400 ppm | N.E. | N.E. | NO |
| 02 | 750 ppm | 1000 ppm | 750 ppm | N.E. | N.E. | NO |
| 03 | 200 ppm | 300 ppm | 200 ppm | N.E. | N.E. | NO |
| 04 | 300 ppm | N.E. | 300 ppm | N.E. | N.E. | NO |
| 05 | 5 ppm | N.E. | 5 mg/m3 | N.E. | N.E. | NO |
| 06 | N.E. | N.E. | N.E. | N.E. | N.E. | NO |

Product Name: WOOD DOUGH -ALL COLORS
Revision Date: 02/01/97

Page 2

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

(See Section 16 for abbreviation legend)

Remaining ingredients are not considered hazardous per the OSHA Hazard Communication Standard.

Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); limits may vary between states.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: DANGER! Extremely flammable liquid and vapor. Vapor harmful. Harmful or fatal if swallowed. Removal of this product after use will result in the generation of dust. If dry-sanded, exposure to dust may result in build-up of material in eyes, ears, nose, and mouth which may cause irritation.

POTENTIAL HEALTH EFFECTS:

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May cause skin irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: Vapor harmful if inhaled.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed. If ingested this product may cause vomiting, diarrhea, and depressed respiration.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Reports have associated permanent brain and nervous system damage with prolonged and repeated occupational overexposure to solvents. Prolonged or repeated contact with skin can cause defatting of the skin which may lead to dermatitis. Inhalation of dust may result in pulmonary and respiratory damages.

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY CONTACT: None known.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INHALATION

SECTION 4 - FIRST AID MEASURES

EYE CONTACT: Flush with large quantities of water until irritation subsides.

SKIN CONTACT: Wash with soap and water.

INHALATION: Remove to fresh air.

INGESTION: DO NOT INDUCE VOMITING.

Product Name: WOOD DOUGH -ALL COLORS
Revision Date: 02/01/97

SECTION 4 - FIRST AID MEASURES

COMMENTS: Call Medical in Section 1 if irritation or complications arise from any above exposures.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: <20 F
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: N.A.
UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: N.E.

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extremely Flammable. Material will readily ignite at room temperatures. Containers may explode if exposed to extreme heat. Eliminate sources of ignition: heat, electrical equipment, sparks, and flames. Do not put in contact with oxidizing or caustic materials.

SPECIAL FIREFIGHTING PROCEDURES: Full protective equipment, including self-contained breathing apparatus, is recommended to protect from combustion products. Cool exposed containers with water.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Scrape up dried material and place into containers.

SECTION 7 - HANDLING AND STORAGE

HANDLING INFORMATION: KEEP OUT OF REACH OF CHILDREN. Avoid skin and eye contact. Avoid breathing vapors. Use only in a well ventilated area.

STORAGE INFORMATION: Store away from caustics and oxidizers. Keep containers tightly closed when not in use. Keep containers from excessive heat and freezing. Do not store at temperatures above 120 degrees F.

OTHER PRECAUTIONS: Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal. Do not take internally.

Product Name: WOOD DOUGH -ALL COLORS

Revision Date: 02/01/97

Page 4

 SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide sufficient mechanical ventilation (local or general exhaust) to maintain exposure below PEL and TLV. Vapors are heavier than air and will collect in low areas. Check all low areas (basements, sumps, etc.) for vapor before entering. Provide eyewash and solvent impervious apron if body contact may occur.

RESPIRATORY PROTECTION: If 8 hour exposure limit or value is exceeded for any component, use an approved NIOSH/OSHA respirator. Consult your safety equipment supplier and the OSHA regulation, 29 CFR 1910.134 for respirator requirements. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

EYE PROTECTION: Goggles or safety glasses with side shields.

SKIN PROTECTION: Solvent impervious gloves.

OTHER PROTECTIVE EQUIPMENT: Provide eyewash and solvent impervious apron if body contact may occur.

HYGIENIC PRACTICES: Wash contaminated clothing before reuse. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area.

 SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|-------------------|---------------------|-------------------|------------------------------|
| BOILING RANGE | : N.E. | VAPOR DENSITY | : Is heavier than air |
| ODOR | : Strong solvent | | |
| APPEARANCE | : Wood paste | EVAPORATION RATE: | Is faster than Butyl Acetate |
| SOLUBILITY IN H2O | : Negligible | | |
| SPECIFIC GRAVITY | : 1.1901 | | |
| VAPOR PRESSURE | : 185 mm Hg @ 68 F. | | |
| PHYSICAL STATE | : Paste | | |

(See Section 16 for abbreviation legend)

 SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Strong oxidizers and caustics.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e. CO_x, NO_x

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

(Continued on Page 5)

Product Name: WOOD DOUGH -ALL COLORS
Revision Date: 02/01/97

Page 5

SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

SECTION 12 - ECOLOGICAL INFORMATION

No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE MANAGEMENT/DISPOSAL: Recycle or incinerate at an EPA approved facility or dispose in compliance with Federal, State, and local regulations. Do not reuse empty containers. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

EPA WASTE CODE - If discarded (40 CFR 261): D001- Ignitable

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Flammable Liquid, N.O.S.(Contains acetone)

(Consumer Commodityx)

DOT HAZARD CLASS: 3(ORM-Dx)

DOT UN/NA NUMBER: UN 1993(NONEx) PACKING GROUP: III(NONEx)

* For containers of 1 gallon or less

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

Product Name: WOOD DOUGH -ALL COLORS
Revision Date: 02/01/97

SECTION 15 - REGULATORY INFORMATION

| CHEMICAL NAME | CAS NUMBER | WT/WT % RANGE |
|---------------------|------------|---------------|
| Isopropanol | 67-63-0 | 5.0-10.0 % |
| Methyl ethyl ketone | 78-93-3 | 5.0-10.0 % |
| Dibutyl phthalate | 84-74-2 | 1.0-5.0 % |

TOXIC SUBSTANCES CONTROL ACT:
This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

| CHEMICAL NAME | CAS NUMBER |
|---------------|------------|
| None. | |

NEW JERSEY RIGHT-TO-KNOW:
The following materials are non-hazardous, but are among the top five components in this product:

| CHEMICAL NAME | CAS NUMBER |
|---------------|-------------------|
| Wood Fibers | TSRN-618608-5067P |
| Gypsum | TSRN-618608-5066P |

PENNSYLVANIA RIGHT-TO-KNOW:
The following non-hazardous ingredients are present in the product at greater than 3%:

| CHEMICAL NAME | CAS NUMBER |
|-------------------|-------------|
| Wood Fibers | proprietary |
| Castor oil | proprietary |
| Proprietary resin | proprietary |
| Gypsum | proprietary |

CALIFORNIA PROPOSITION 65:
WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

| CHEMICAL NAME | CAS NUMBER |
|---|------------|
| No Proposition 65 chemicals are known to exist in this product. | |

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

WHMIS RATINGS - HEALTH: 2 FLAMMABILITY: 3 REACTIVITY: 0

Product Name: WOOD DOUGH -ALL COLORS
Revision Date: 02/01/97

SECTION 16 - OTHER INFORMATION

PREVIOUS MSDS REVISION DATE: 07/18/95

VOC less water, less exempt solvent: 345-355 gm/l(29.0-30.0%)where acetone is exempt.
VOC material: 275-285 gm/l(23.0-24.0%) where acetone is exempt.

- LEGEND:
- ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
 - N.A. - NOT APPLICABLE
 - N.E. - NOT ESTABLISHED
 - PEL - PERMISSIBLE EXPOSURE LIMIT
 - NTP - NATIONAL TOXICOLOGY PROGRAM
 - SARA - SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986
 - STEL - SHORT TERM EXPOSURE LIMIT
 - TLV - THRESHOLD LIMIT VALUE(8 HR. TIME WEIGHTED AVERAGE OR TWA)
 - VOC - VOLATILE ORGANIC COMPOUND
 - NJRTK - NEW JERSEY RIGHT TO KNOW LAW
 - N.D. - NOT DETERMINED

Supersedes MSDS# 10504 Revision 12

This data is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.
