



9411 Corsair Road Frankfort, IL 60423 1-800-552-0299 Phone 1-815-464-5650 Fax

**EMERGENCY PHONE 1-800-255-3924** 

# TECHNICAL DATA SHEETS 42TL THREADLOCKER

### **Description:**

ADVANCED PERFORMANCE SERIES THREADLOCKER 42TL is a thixotropic anaerobic compounds formulated to cure rapidly and reliably on most "as received" fasteners. They give predictable lubricity on assembly.

#### **Physical Properties:**

**Uncured State:** 

Viscosity: 1200CPS Color. Blue

Operating Temperature Range: - 65 to 350° F Cure Speed 20% Fix (1) 10-30 minutes Bolt Treating Range: 1/4 to 3/4 inch (6 - 20 MM)

Toxicity: Low Specific Gravity: 1.05 Corrosivity: None

> MIL (S-46163-A) Type II Grade N

Cured State:

Shear Strength (2) 800 Lb/in. (5.5 MPa)

Resin: Solid Polyacrylate

Color: Blue

## **Typical Applications:**

LOCKING AND SEALING

Hydraulic Line Fittings

Vacuum cleaner bell housing screws

Hydraulic pistons nuts

**Rocker Nuts** 

Oil pressure switch assembly Construction equipment bolts

Bulldozers track bolts

Railroad bolts on wear plates

Typewriter screws

Carburetor adjusting screws

Machinery Keys

# Engineering Excellence

For technical information and support call 1-800-552-0299 or visit our website at



