



Distributed By  
 Freeman Manufacturing & Supply Co.  
[www.freemansupply.com](http://www.freemansupply.com) 800-321-8511

## DATA SHEET

Page 18  
 2-28-97

### AIRTECH 1050

Silicone Rubber, Cured and Unsupported

Thermovac® Elastomeric Vacuum Bagging Materials

#### Description:

The Thermovac® grade silicone rubber is a proprietary formulation that offers high reversion resistance and strength. It is designed to provide superior performance in composite lamination systems for vacuum/autoclave and vacuum/hydraulic curing. Any silicone rubber has the potential to transfer. Silicone transfer investigation should be done by the user.

<u>Available Forms:</u>	Thickness:	.040" (1.02mm) - .060" (1.52mm)
	Width:	48" (122cm) ± .25 (6.4mm) usable material (edges untrimmed)
	Finish:	Glossy
	State:	Cured
	Form:	25 LYD Roll (22.9m)
	Color:	Red

Note: Rolls may contain one unbonded splice with a minimum length of 5 yards (4.6m). An additional yard will be added to a spliced roll at no additional cost on full roll orders.

#### Physical Properties:

<u>Property</u>	<u>Test Method</u>	<u>Value</u>
Durometer	ASTM-D2240, Shore A	50
Tear, lbs/in.	ASTM-D624, Die B (75°F) (212°F)	250 200
Tensile, psi	ASTM-D412, Die A	1400
Elongation %	ASTM-D412, Die A	700
100% Modulus, psi		300
300% Modulus, psi		250
Temperature Use Range		600°F
Coefficient of Thermal Expansion	in/in/°F (75°F-350°F)	1.6 x 10 <sup>-4</sup>
Compression Set	ASTM-D395, Method B 22 hrs. 350°F	28%
Volumetric Expansion	in/in/°F (75°F-350°F)	5 x 10 <sup>-4</sup>
Thermal Conductivity	ASTM-F433 325°F BTU-in./FT <sup>2</sup> hr.°F	1.8

CATALOG POSITION: **RUBBER**



As the conditions or methods of use are beyond our control, Airtech International, Inc. does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech International, Inc. disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use.

WE COVER THE WORLD WITH HIGH TEMPERATURE FILM