



## DATA SHEET

### AIRHOLD 1 CBS

#### High Temperature Double-Backed Holding Tape

#### Description

**Airhold 1 CBS** is an all-purpose, high temperature double-backed holding tape. **Airhold 1 CBS** is a one mil polyester film coated on both sides with a non-silicone adhesive.

#### Application

**Airhold 1 CBS** is designed to hold secondary bonded details, release plies, release films and breathers in place during layup and vacuum bagging operations. **Airhold 1 CBS** is also ideal for holding down low density honeycomb and foam core during machining operations. **Airhold 1 CBS** leaves very little residue which can be removed with common shop solvents. **Airhold 1 CBS** can also be used to replace aerosol contact adhesives and works well on inclined tool surfaces.

Material Characteristics	
Carrier Type:	Polyester
Adhesive Type:	Acrylic
Total Thickness, in (μ):	.0035 (90)
Film Thickness, in (μ):	.0005 (13)
Adhesive Thickness, in (μ):	.0025 (65)
Adhesion oz/in-width (N/cm-width):	40 (4.4)
Elongation, %:	25
Maximum Recommended Use Temperature, °F (°C.):	400 (204)
Color:	Clear
Available Sizes:	1/2" (1.27cm) x 36 yards (33m)
	1" (2.54cm) x 36 yards (33m)
	2" (5.08cm) x 36 yards (33m)
Shelf Life:	1 year when stored at 72°F (22°C).

#### CATALOG POSITION: PRESSURE SENSITIVE TAPES

As the conditions or methods of use are beyond our control, Airtech International, Inc. does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech International, Inc. disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes.

**MORE THAN A MANUFACTURER...A TECHNICAL PARTNER!**

