

Data Sheet

AIRTAC 2 IMPROVED

Spray contact adhesive for temporary bonding

DESCRIPTION

Airtac 2 Improved is a mist spray rubber adhesive designed for temporary bonds. Airtac 2 Improved can be used on materials needing extra tack for placement on vertical or difficult surface areas. This product is ideally suited for tool shop applications such as temporary placement of details and pattern fabrication. Resin infusion process rely on Airtac 2 Improved for holding plies in place until resin infusion is completed. Airtac 2 Improved meets many of the low VOC state restrictions for aerosol products.

BENEFITS

- Excellent tack holds dry materials for faster vacuum bagging.
- More accurate material placement for infusion setups and better quality laminates.
- Less toxic for safer application.

TECHNICAL DATA

Solvent characteristics

Non CFC

Shelf life

12 months from date of shipment
when stored at 72°F (22°C)

VOC

< 25%

SIZES

Packaging Type	Content Weight
12 cans per case	18.04 oz (511 g)

APPLICATION

- Make sure spray distance to the part is minimum 12 in (30 cm).
- After spraying Airtac 2 Improved, wait at least 10 seconds to give solvent the possibility to evaporate.



NOTES

- Consult SDS prior to use.

Last updated : 2020-03-03

Catalog position : [Resin infusion products](#)