

Page 3 10 December 2004

### DATA SHEET

## FLASHBREAKER<sup>®</sup> 1R, 2R and 5R

### All Purpose Pressure Sensitive Tape with a Non-Silicone Adhesive

#### **Description**

**Flashbreaker**<sup>®</sup> (**R**) **Tapes** are high temperature / high tensile strength polyester films coated with a pressure sensitive rubber based adhesive.

#### Application

**Flashbreaker**<sup>®</sup> **1R, 2R and 5R** are our rubber adhesive based, polyester pressure sensitive tapes. These tapes hold down vacuum bagging materials and TC wires on metal or composite parts and tooling. These tapes are designed for use in sensitive areas where silicone adhesives are not permitted. **Flashbreaker**<sup>®</sup> **2R and 5R** are used in more extreme environments where extra strength is needed.

Material Characteristics	Flashbreaker <sup>®</sup> 1R	Flashbreaker <sup>®</sup> 2R	Flashbreaker <mark>.</mark> ®5R
Carrier Type:	Polyester	Polyester	Polyester
Adhesive Type:	Rubber	Rubber	Rubber
Total Thickness, in (µ):	.003 (75)	.004 (100)	.007 (175)
Film Thickness, in (µ):	.001 (25)	.002 (50)	.005 (125)
Adhesive Thickness, in (µ):	.002 (50)	.002 (50)	.002 (50)
Adhesion oz/in-width (N/cm-width):	15 (1.6)	15 (1.6)	15 (1.6)
Elongation, %:	90	110	150
Maximum Recommended Use Temperature, °F (°C):	400 (204)	400 (204)	400 (204)
Color:	Green	Green	Green
Standard Sizes(1):	1" (2.54cm) x 72 yards (66m)	1" (2.54cm) x 72 yards (66m)	1" (2.54cm) x 36 yards (33m)
	2" (5.08cm) x 72 yards (66m)	2" (5.08cm) x 72 yards (66m)	2" (5.08cm) x 36 yards (33m)
Shelf Life:	1 year when stored at 72°F (22°C)		

#### 1) Other widths available.

# CATALOG POSITION: PRESSURE SENSITIVE TAPES



As the conditions or methods of use are beyond our control, Airtech International, Inc. does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech International, Inc. disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use. The information contained herein represents typical properties and should not be used for specification purposes.

MORE THAN A MANUFACTURER...A TECHNICAL PARTNER!



Distributed by Freeman Manufacturing & Supply Co. www.freemansupply.com (800) 321-8511 **FREEMAN**