

CORPORATE HEADQUARTERS 5700 Skylab Road Huntington Beach, CA 92647 PHONE: (714) 899-8100 FAX: (714) 899-8179 Internet: www.airtechonline.com e-mail: airtech@airtechintl.com

> Page 8B January 29, 2004

DATA SHEET

TAC-STRIP

Dry Fabric Placement Tape

Description

Tac-Strip is a fiberglass fabric mesh tape coated on both sides with a "high tack" pressure sensitive adhesive. **Tac-Strip** is designed to hold dry fabrics in place as required when using resin infusion, resin transfer molding, and other processes requiring dry fabric layup. **Tac-Strip** has the added advantage of being very clean when compared to spray adhesives commonly used for ply placement.

Physical Properties Fabric Type Thickness Adhesive Type

Roll Size 1 inch x 295 feet (2.54cm x 90m) 2 inch x 295 feet (5.08cm x 90m) Fiberglass .008" ± .002" Acrylic

<u>Case Size</u> 72 rolls/case 36 rolls/case

Shelf life one year from date of shipment when stored at 72°F (22°C).



CATALOG POSITION: MISCELLANEOUS



As the conditions or methods of use are beyond our control, Airtech International, Inc. does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech International, Inc. disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use.