

DATA SHEET
VACUUM BAG SEALANT TAPE MATERIAL CHARACTERISTICS

<u>Product</u>	<u>Color</u>	<u>Base Material</u>	<u>Composition (% Solids)</u>	<u>Maximum Use Temp.</u>	<u>Standard* Sizes (L x W x L)</u>	<u>Rolls Per Case</u>
GS-95	Dark Grey	Synthetic Rubber	100%	225°F (107°C)	1/8" x 1/2" x 25'*	40
GS-100	Reddish Brown	Synthetic Rubber	100%	375°F (191°C)	1/8" x 1/2" x 25'*	40
AT-200Y	Yellow	Synthetic Rubber	100%	400°F (204°F)	1/8" x 1/2" x 25'*	40
GS-213	Off-White	Synthetic Rubber	100%	400°F (204°C)	1/8" x 1/2" x 25' 1/8" x 3/4" x 25'	40 28
GS-333	Black	Synthetic Rubber	100%	400°F (204°C)	1/8" x 1/2" x 25'*	40
GS-213-3	Light Green	Synthetic Rubber	100%	450°F (232°C)	1/8" x 1/2" x 25' 1/8" x 3/4" x 25'	32 20
GS-43MR	Off-White	Synthetic Rubber	100%	450°F (232°C)	1/8" x 1/2" x 25' 1/8" x 3/4" x 25'	40 28
GS-580B	Black	Silicone	100%	600°F (316°C)	1/8" x 1/2" x 25'	40
AVBS 750	Brown	Silicone	100%	752°F (400°C)	3mm x 18mm x 10m	4
A-800-3G	Light Green	Silicone	100%	800°F (427°C)	1/8" x 1/2" x 25'*	40

* 3/4" width available on special order.

** Shelf life - 12 months from date of manufacture when stored at 72°F (22°C)

CATALOG POSITION: VACUUM BAG SEALANT TAPES



As the conditions or methods of use are beyond our control, Airtech International, Inc. does not assume any responsibility for the performance of this material for any particular use. The material is sold "as is". Airtech International, Inc. disclaims, and buyer waives, any and all implied warranties, including without limitation the implied warranties of merchantability and of fitness for particular use.

WE COVER THE WORLD WITH HIGH TEMPERATURE FILM