



Rapid Patch Urethane Repair Material

Description

Rapid Patch Urethane Repair Material offers a quick (15 minutes) and economical means of repairing urethane molds and pattern equipment. Rapid Patch is also a strong adhesive and provides for a secure bond on various plastics and tooling boards. This black material is formulated with an easy to use 1:1 mix ratio. The Rapid Patch repair kit comes complete with two 5 oz tubes, mixing sticks, and instructions.



Freeman Mfg.
& Supply Co.
1101 Moore Rd
Avon, OH 44011

Phone 800 321 8511
Fax 440 934 7200

www.freemansupply.com

www.freemanwax.com

Application Instructions

1. Dispense equal lengths of catalyst and base onto a suitable mixing pad.
2. Mix catalyst and base with mixing stick until color is uniform.
3. Apply Rapid Patch to surface in need of repair.
4. Allow Rapid Patch to harden for approximately 15 minutes.
5. Sand and finish surface as required.

Ordering Information

Part Number	Description	Net Wt.
054279	Rapid Patch Rigid 10 oz kit	0.644

Physical and mechanical properties of tooling plastics herein reported are typical after a full cure of seven (7) days at room temperature or equivalent. Designated mix ratios must be adhered to for desired results.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT

Freeman Mfg. & Supply Co.

1101 Moore Rd.
Avon, Ohio 44011
www.freemansupply.com
800-321-8511