

**Advanced Materials****RenLease<sup>®</sup> 803-1 All-Purpose Parting Agent**

---

**DESCRIPTION:**

RenLease<sup>®</sup> 803-1 agent is an all-purpose, wax-based parting agent. It provides an exceptionally thin film which assures accurate pick-up of minute detail. RenLease<sup>®</sup> 803-1 agent contains a small amount of silicone to facilitate release properties. If a non-silicone containing wax is needed, use RenLease<sup>®</sup> 805-1 agent. Maximum service temperature is 250°F (121°C).

---

**DIRECTION:**

Mix thoroughly before using. RenLease<sup>®</sup> 803-1 agent may be sprayed, brushed or applied with a cloth without pre-waxing (except on plaster and sheet wax).

**Spray Applications**

Add mineral spirits until desired consistency is obtained to accommodate available spray equipment (recommend 10%). Apply up to three coats. Polish each coat before applying next coat, to remove excess from corners and minute detail areas.

**Brush of Cloth Applications**

Use RenLease<sup>®</sup> 803-1 agent from the container. Apply at least three coats directly to surface with brush or clean cloth. Polish each coat before adding the next coat.

**Plaster Applications**

When used on plaster, first apply Ren<sup>®</sup> 802 Plaster Sealer to seal pores and eliminate absorption. Do not use a water soluble parting agent on plasters.

---

**HANDLING :****RenLease<sup>®</sup> 803-1 agent**

Stir well before use. This material will separate.

Work in a well ventilated area and use clean, dry tools for mixing and applying. For two component system, combine the resin and hardener according to mix ratio. Mix together thoroughly and use immediately after mixing. Material temperature should not be below 65°F (18°C) when mixing.

---

**PACKAGING:**

This product is available in the following package size(s):

**Quart can (1.65#), or by the case (6 quarts) (9.9#), or 5-gallon pail (33.12#)**

Please call Customer Service (800-367-8793) for price and availability.

---

**STORAGE :**

RenLease<sup>®</sup> 803-1 agent should be stored in a dry place, in the sealed original container, at temperatures between +2°C and +40°C (+35.6°F and 104°F). Under these storage conditions, the shelf life is 2 years. The product should not be exposed to direct sunlight.

---

**PRECAUTIONARY STATEMENT :**

Huntsman Advanced Materials Americas LLC maintains up-to-date Material Safety Data Sheets (MSDS) on all of its products. These sheets contain pertinent information that you may need to protect your employees and customers against any known health or safety hazards associated with our products. Users should review the latest MSDS to determine possible health hazards and appropriate precautions to implement prior to using this material.

**First Aid!**

Refer to MSDS as mentioned above.

**KEEP OUT OF REACH OF CHILDREN  
FOR PROFESSIONAL**

---

**IMPORTANT LEGAL NOTICE**

Huntsman Advanced Materials warrants only that its products meet the specifications agreed with the user. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications.

The manufacture of materials is the subject of granted patents and patent applications; freedom to operate patented processes is not implied by this publication.

WHILE ALL THE INFORMATION AND RECOMMENDATIONS IN THIS PUBLICATION ARE, TO THE BEST OF HUNTSMAN ADVANCED MATERIAL'S KNOWLEDGE, INFORMATION AND BELIEF, ACCURATE AT THE DATE OF PUBLICATION, nothing herein is to be construed as a warranty, whether express or implied, including but without limitation, as to merchantability or fitness for a particular purpose. In all cases, it is the responsibility of the user to determine the applicability of such information and recommendations and the suitability of any product for its own particular purpose.

The behavior of the products referred to in this publication in manufacturing processes and their suitability in any given end-use environment are dependent upon various conditions such as chemical compatibility, temperature, and other variables, which are not known to Huntsman Advanced Materials. It is the responsibility of the user to evaluate the manufacturing circumstances and the final product under actual end-use requirements and to adequately advise and warn purchasers and users thereof.

Products may be toxic and require special precautions in handling. The user should obtain Safety Data Sheets from Huntsman Advanced Materials containing detailed information on toxicity, together with proper shipping, handling and storage procedures, and should comply with all applicable safety and environmental standards.

Hazards, toxicity and behavior of the products may differ when used with other materials and are dependent on manufacturing circumstances or other processes. Such hazards, toxicity and behavior should be determined by the user and made known to handlers, processors and end users.

Except where explicitly agreed otherwise, the sale of products referred to in this publication is subject to the general terms and conditions of sale of Huntsman Advanced Materials LLC or of its affiliated companies including without limitation, Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials Americas Inc., and Huntsman Advanced Materials (Hong Kong) Ltd.

Huntsman Advanced Materials is an international business unit of Huntsman Corporation. Huntsman Advanced Materials trades through Huntsman affiliated companies in different countries including but not limited to Huntsman Advanced Materials LLC in the USA and Huntsman Advanced Materials (Europe) BVBA in Europe.

Ren and RenLease are registered trademarks of Huntsman Corporation or an affiliate thereof in one or more, but not all, countries.

Copyright © 2011 Huntsman Corporation or an affiliate thereof. All rights reserved.

Main Offices :

**Huntsman Corporation**  
10003 Woodloch Forest Dr.  
The Woodlands  
Texas 77380  
(281) 719-6000

**Huntsman Advanced Technology  
Center**

8600 Gosling Rd.  
The Woodlands  
Texas 77381  
(281) 719-7400  
Website :  
[www.huntsman.com/advanced\\_materials](http://www.huntsman.com/advanced_materials)