




Ventistamp Zanatta Corevents

Description

Ventistamp Zanatta Corevents are very high-quality investment cast corevents designed for maximum durability and performance. These vents were developed to be used in high-production applications where standard screen or perforated vents would traditionally be utilized. Features and benefits for Ventistamp Zanatta Corevents include:



- **One piece construction** - *No screens or foils to break*
- **Manufactured from Brass Alloy (SAE-430-B)** - *Higher wear resistance than steel*
- **Manufactured with tapered slots (20°)** - *Less likely to clog with sand and binders*
- **Extremely flat head surface** - *Less imperfection in the core*
- **Outside diameter is .005" oversized in the middle of the vent** - *Provides tight installation to prevent movement*
- **Outside diameter at the top of the vent is .003" undersized** - *Prevents deformation of the slots*

Ordering Information

Part Number	Description	Head Thickness
034576	3/16" ZVP 30 Zanatta Vent	0.025"
034577	1/4" ZVP 30 Zanatta Vent	0.025"
034578	5/16" ZVP 30 Zanatta Vent	0.025"
034579	3/8" ZVP 30 Zanatta Vent	0.025"
034581	1/2" ZVP 30 Zanatta Vent	0.028"
034583	5/8" ZVP 30 Zanatta Vent	0.032"
034584	3/4" ZVP 30 Zanatta Vent	0.032"
054586	1" ZVP 30 Zanatta Vent	0.035"

- All vents are sold in 100 piece bags
- The slot width is .012" which is designed for sand grain fineness between 70 & 90 AFS
- All fractional vents are 5/16" tall

Please inquire for availability on other slot widths, metric diameters and other fractional diameters.

Freeman Mfg. & Supply Co.
1101 Moore Rd
Avon, OH 44011

Phone 800 321 8511
Fax 440 934 7200
www.freemansupply.com