

A Quality Product from Hawkeye Industries Inc.

Duratec® Polyester EZ Sanding Primer



An exceptionally easily sanded primer, versus the Duratec Surfacing Primer, which also polishes to a smooth, porosity-free surface.

Usage

For composites, metal, MDF, brick, concrete, various low-density foams, plaster, and clay.

Features

Builds rapidly and provides a very easily sanded, low porosity smooth surface.

Here's why you should choose Duratec Polyester EZ Sanding Primer—

Low Porosity—provides a super fine leveling and filling system on a variety of substrates with superior release properties.

Adhesion to most epoxies—with heat distortion level of 201°F, 94°C, it also adheres to fiberglass, properly prepared metal, wood, MDF, brick, concrete and polyurethane foam.

Rapid coat buildup—to 20 mils, 500 microns, wet on wet, on composite plugs and master mold surfaces; saves time and labor cost.

Very easy sanding—saves time and effort. An exceptional primer for polishing or topcoating with Duratec Surfacing Primers and Hi-Gloss Coatings, lacquers and polyurethane paints.

Duratec Polyester EZ Sanding Primer

707-061 Lt. Gray

702-061 Black

714-061 White

(Link to MSDS)



Hawkeye Industries Inc.

P O Box 415 Bloomington, CA 92316
Tel 909-546-1160; Toll Free 800-977-0060; Fax: 909-546-1161
Email productinfo@duratec1.com Web www.duratec1.com

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511



Liability/warranty statement: Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.

Duratec is a registered trademark of Dura Technologies Inc.



Product Nos. 707-061 Lt. Gray
702-061 Black
714-061 White

Data Sheet
Continued

Pg. 2

Duratec Polyester EZ Sanding Primer

Product Properties

All time calculations are based on temperatures of 77°F, 25°C

Viscosity

*As measured on a Brookfield Viscometer
Model RVF, Spindle #2 at 20 rpm*

2900 cps +/- 150 cps

Thixotropic Index

6.5

Gel Time

*Sample based on a 100 g mass
catalyzed at 2 percent with mekP*

22 min +/- 2 min

Weight per Gallon

11.8 lb., 5.36 kg

Coverage per Gallon

*10 mil thickness
250 micron thickness*

110-115 ft²

10.2-10.7 m²

Link to Application Guides for Duratec EZ Sanding Primer

- [Sealing, Fairing, Priming and Surfacing Application: Plugs, Patterns and Models](#)

Duratec Polyester EZ Sanding Primer is among the many fine Duratec products marketed worldwide by Hawkeye Industries Inc.

[📁 Contents/Literature CD](#) [📁 Trouble Shooting Guide](#)

Rev 06-30-12



Hawkeye Industries Inc.

P O Box 415 Bloomington, CA 92316
Tel 909-546-1160; Toll Free 800-977-0060; Fax: 909-546-1161
Email productinfo@duratec1.com Web www.duratec1.com

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511



Liability/warranty statement: Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.

Duratec is a registered trademark of Dura Technologies Inc.