



## RP 802 SEALER

**DESCRIPTION:** RP 802 is a green colored, lacquer-type sealing agent recommended for plaster and wood surfaces. It requires a release agent such as RP 803 to prevent bonding of tooling resins to the model or to the sealer.

RP 802 can be applied with a brush. However, best results are obtained with a spray application. Use lacquer thinner to dilute to a proper spray viscosity.

**DIRECTIONS:** Apply multiple coats. Let each coat dry to the touch before applying the next. When the entire surface dries to a high gloss finish, the surface is sealed. Several light coats will dry more quickly than a few heavy coats. Clean surfaces contaminated with dirt, oils, or release agents (as in the case of old models) before applying RP 802.

### STORAGE/HANDLING INFORMATION:

#### RP 802

Store at 60-100°F in a dry place. After use tightly reseal.

Work in a well ventilated area and use clean, dry tools for mixing and applying. For two component system, combine the resin and hardener according to mix ratio. Mix together thoroughly and use immediately after mixing. Material temperature should not be below 65°F (18°C) when mixing.

Stir well before use. This material will separate.

**SHELF LIFE:** Provided materials are stored under the recommended storage conditions in their original containers, they will remain in useable condition for at least one year from date of shipping.

**PACKAGING:** This product is available in the following package size(s):

6 quart package (11.4#)

Please call Customer Service (800-367-8793) for price and availability.

**SAFETY/HANDLING PRECAUTIONS:** Do not use or handle this product until the Material Safety Data Sheet has been read and understood.

**RP 802**

**DANGER!** FLAMMABLE. Causes skin and eye irritations.

Keep away from heat, sparks and flame.  
Avoid contact with eyes, skin, and clothing.  
Keep container closed  
Use with adequate ventilation.  
Wash thoroughly after handling.

**FIRST AID:** In case of contact with:

**Skin:** Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes.

**Eyes:** Immediately flush with water for at least 15 minutes. Call a physician.

**Ingestion:** If conscious, give plenty of water to drink. Do not induce vomiting. Call a physician.

**Inhalation:** Remove to fresh air. Administer oxygen or artificial respiration if necessary. Call a physician.

**Other:** Referral to physician is recommended if there is any question about the seriousness of any injury.

**IMPORTANT:** The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES AND CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential, or indirect damages for alleged negligence, breach of warranty, strict liability, tort, or contract arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled or lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.

Vantico A&T US, Inc.  
RenShape Solutions  
4917 Dawn Avenue  
East Lansing, MI 48823 USA

Tel 517 351 5900  
800 375 1363  
[www.tooling.vantico.com](http://www.tooling.vantico.com)

Customer Service Hotline: 800 367 8793  
Technical Inquiries: 800 759 7165  
Product Literature: 800 955 5509