

Safety Data Sheet Freeman Wax Release



Section 1 Identification

Product identifiers

Product name: Freeman Wax Release

HMIS H 1 F 2 R 0

Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Release of urethanes, epoxies, or polyester resins

PPE Sec.8.

Details of the supplier of the safety data sheet

Freeman Manufacturing & Supply Company 1101 Moore Road, Avon, OH 44011 Telephone (440) 934-1902

24 Hour emergency telephone number: CHEMTREC (800) 424-9300

Section 2 Hazards Identification

GHS Classification in accordance with 29 CFR 1910.1200 (OSHA HCS)

Flammable liquids, Category 3 Aspiration hazard, Category 1

Not classified as an environmental hazard.

GHS Label elements, including precautionary statements





Signal word Danger

Hazard statements

Flammable liquid and vapor. May be fatal if swallowed and enters airways.

Precautionary statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed. Ground/bond container and receiving equipment.

Wear protective gloves/ eye protection/ face protection.

Response

If swallowed: Immediately call poison center/doctor. Do NOT induce vomiting.

If on skin: Remove/take off immediately all contaminated clothing.

Rinse skin with water/shower. If skin irritation occurs: Get medical attention.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If exposed or concerned: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep cool.

Disposal

Dispose of contents and container to an appropriate waste site in accordance with regulations.



Freeman Wax Release

Section 2 Hazards Identification continued

Hazards not otherwise classified (HNOC) or not covered by GHS

Repeated exposure may cause skin dryness or cracking.

Section 3 Composition/Information on Ingredients

Component	CAS Number	Composition (%)
Petroleum Naphtha	64742-48-9	75 - 95

Section 4 First-Aid Measures

Description of first aid measures

If inhaled

Move person into fresh air and keep comfortable for breathing. If not breathing, give oxygen or artificial respiration. Get medical advice/attention if you feel unwell.

In case of skin contact

Remove/take off immediately all contaminated clothing.

Rinse skin with water/shower. Get medical attention if irritation occurs.

In case of eye contact

Immediately flush eyes thoroughly with water. If irritation persists, get medical assistance

If swallowed

Immediately call poison center/doctor. Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Aspiration may cause pulmonary edema and pneumonitis.

Direct contact with eyes may cause temporary irritation.

Indication of any immediate medical attention and special treatment needed

No data available.

Section 5 Fire-Fighting Measures

Suitable extinguishing media

Use water fog, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as it may spread the fire.

Special hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel a considerable distance to a source of ignition and flash back. Gases formed during combustion may be hazardous to health.

Special protective equipment and precautions for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Do not breathe fumes. Move containers away from fire area if safe to do so.

Section 6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapors. Eliminate all sources of ignition.

For personal protection see section 8.



Freeman Wax Release

Section 6 Accidental Release Measures continued

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Shovel into suitable containers for disposal. Clean surface thoroughly to remove residual contamination.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Section 7 Handling and Storage

Precautions for safe handling

Use normal precautions when handling flammable materials. Take precautionary measure against static discharges. All equipment used when handling this product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe fumes or vapor. Do not allow material to contact skin. Provide appropriate exhaust ventilation Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene.

Conditions for safe storage, including any incompatibilities

Store at ambient temperatures in tightly closed containers. Keep away from heat, sparks, and open flame. This material can catch fire if overheated. Do not heat this material above the flash point. Keep away from flame and open electrical coils. Protect material from direct sunlight. Keep away from incompatible materials (see Section 10 of the SDS).

Section 8 Exposure Controls/Personal Protection

Occupational exposure limits

No exposure limits noted.

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls.

Good general ventilation (typically ten air changes per hour) should be used.

Personal protective equipment

Eye/face protection

With product at ambient temperatures, use safety glasses equipped with side shields.

Hand Protection

With product at ambient temperatures, use disposable nitrile gloves.

Contaminated gloves should be replaced.

Body Protection

Prevent skin contact when handling material.

Respiratory Protection

The need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations are anticipated, a NIOSH-approved respirator with organic vapor cartridge and full face piece should be used.

Safety Stations

Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

General Hygienic Practices

Avoid breathing vapor. Avoid contamination of food, beverages, or smoking materials. Wash thoroughly after handling, and before eating, drinking or smoking. Remove contaminated clothing promptly and clean thoroughly before reuse.



Freeman Wax Release

Section 9 Physical and Chemical Properties

AppearanceWhite to amber pasteOdorSlight petroleum odorOdor ThresholdNo data available

pH No data available Freezing Point -60°C (-76°F) VOC Content 5.3 lb./gal

Initial boiling point & boiling range
Flash Point(COC)

Evaporation rate
Flammability (solid, gas)
Upper/lower flammability
Vapor Pressure
Vapor density

No data available

Relative density (g/cc) 0.80 ± 0.05 Water Solubility Negligible

Coefficient: n-octanol/ water Auto-ignition temperatureNo data available
No data available

Viscosity Paste at room temperature

Explosive PropertiesNoneOxidizing PropertiesNone% Volatile87%

Section 10 Stability and Reactivity

Reactivity: Non-reactive under normal conditions of use, storage and transport.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: None

Conditions to avoid: Heat, open flames, sparks and other ignition sources. Avoid temperatures

exceeding the flash point. Avoid contact with incompatible materials.

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: Thermal oxidative decomposition can produce carbon

monoxide and carbon dioxide.

Section 11 Toxicological Information

Information on likely routes

Inhalation Harmful if inhaled.

Skin contact Eye contactNo adverse effects due to skin contact are expected.

Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of product aspirated into the lungs through ingestion or

vomiting may cause a serious chemical pneumonia.

Symptoms related to physical, chemical, and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Acute inhalation toxicity Harmful if inhaled.

Skin corrosion/irritation Prolonged exposure may cause temporary irritation.



Freeman Wax Release

Section 11 Toxicological Information continued

Serious eye damage/eye irritation Direct contact may cause temporary irritation.

Respiratory or skin sensitization Not a respiratory sensitizer.

Not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components

present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen.

NTP: No component of this product present at levels greater than or equal to

0.1% is identified as a known or anticipated carcinogen

OSHA: No component of this product present at levels greater than or equal to

0.1% is identified as a carcinogen or potential carcinogen.

Reproductive toxicityNot expected to be a reproductive or

developmental hazard.

Specific target organ toxicity -

single exposure

Specific target organ toxicity -

repeated exposure Aspiration hazard Not expected to be a hazard

Not expected to be a hazard

May be fatal if swallowed or enters airways.

Section 12 Ecological Information

ToxicityNo data availablePersistence and degradabilityNo data availableBioaccumulative potentialNo data availableMobility in soilNo data availableResults of PBT & vPvB assessmentNo data available

Section 13 Disposal Considerations

Use safety containers for disposal. Contact a licensed contractor for detailed recommendations. Dispose of in accordance with all applicable Federal, state, and local regulations.

Section 14 Transport Information

DOT UN Number: UN1268

Proper shipping name: Petroleum Distillates, N.O.S. (Petroleum Naphtha)

Hazard Class: 3 Packing Group: III ERG number: 128



Freeman Wax Release

Section 15 Regulatory Information

EPCRA - Emergency Planning and Community Right-to-Know

SARA 304: This material does not contain any components with a section 304 EHS RQ. SARA 302: This material does not contain any components with a section 302 EHS TPO.

SARA 311/312: Flammable, Aspiration hazard

SARA 313: No components are subject to reporting levels established by SARA Title III

TSCA Inventory Status

All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

California Prop 65

▲ WARNING: This product can expose you to chemicals including ethylbenzene, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

Component	CAS Number	Composition (%)	NSRL (μg/day)
Ethylbenzene	100-41-4	< 0.03	41 (ingestion) 54 (inhalation)

Section 16 Other Information

Disclaimer

The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.