



## Chemlease® MPP 117

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

### SECTION 1. IDENTIFICATION

Product name : Chemlease® MPP 117

#### Manufacturer or supplier's details

Company name of supplier : Chem-Trend LP  
1445 W McPherson Park Dr  
PO Box 860, Howell MI 48844-0860  
United States  
+1 517 546 4520

E-mail address of person responsible for the SDS : SDS-NA@chemtrend.com

Emergency telephone number : +1 517 545 7070

#### Recommended use of the chemical and restrictions on use

Recommended use : Primers  
Sealing agent

Restrictions on use : For industrial use only.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2  
Acute toxicity (Oral) : Category 3  
Acute toxicity (Inhalation) : Category 3  
Acute toxicity (Dermal) : Category 3  
Skin irritation : Category 2  
Skin sensitisation : Category 1  
Reproductive toxicity : Category 1B  
Specific target organ toxicity - single exposure : Category 1

**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

Specific target organ toxicity : Category 3 (Central nervous system)  
- single exposure

Specific target organ toxicity : Category 2 (Central nervous system)  
- repeated exposure  
(Inhalation)

Aspiration hazard : Category 1

**GHS label elements**

Hazard pictograms :    

Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.  
Toxic if swallowed, in contact with skin or if inhaled.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause an allergic skin reaction.  
May cause drowsiness or dizziness.  
May damage fertility or the unborn child.  
Causes damage to organs.  
May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Precautionary statements : **Prevention:**  
Obtain special instructions before use.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not breathe vapours.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
Rinse mouth.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water.  
IF exposed or concerned: Call a POISON CENTER/ doctor.  
Do NOT induce vomiting.  
In case of fire: Use alcohol-resistant foam, carbon dioxide or water mist to extinguish.

**Storage:**  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Methanol	67-56-1	Trade secret ( $\geq 30 - < 60$ )
Toluene	108-88-3	Trade secret ( $\geq 10 - < 30$ )
Light aliphatic naphtha	64742-49-0	Trade secret ( $\geq 10 - < 30$ )
3-butoxypropan-2-ol	5131-66-8	Trade secret ( $\geq 1 - < 5$ )
dibutyltin dilaurate	77-58-7	Trade secret ( $\geq 0.1 - < 1$ )

Actual concentration is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- If inhaled : Take victim immediately to hospital.  
Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
Get medical attention immediately.
- If swallowed : Move the victim to fresh air.

**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

If accidentally swallowed obtain immediate medical attention. If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Rinse mouth with water.  
Never give anything by mouth to an unconscious person.  
Aspiration hazard if swallowed - can enter lungs and cause damage.

Most important symptoms and effects, both acute and delayed : Central nervous system depression  
Dangerous amounts can be absorbed through the skin.  
Can be absorbed through skin.  
Risk of product entering the lungs on vomiting after ingestion.  
Health injuries may be delayed.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Aspiration may cause pulmonary oedema and pneumonitis.  
Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema

Notes to physician : Treat symptomatically.

---

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not let product enter drains.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides  
Metal oxides

Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.



**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Do not allow contact with soil, surface or ground water. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Non-sparking tools should be used.

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : Keep away from heat and sources of ignition.

Advice on safe handling : Use only in an area containing explosion proof equipment. Do not use in areas without adequate ventilation. Do not breathe vapours or spray mist. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the application area. Wash hands and face before breaks and immediately after handling the product. Ensure all equipment is electrically grounded before beginning transfer operations. Do not get in eyes or mouth or on skin. Do not get on skin or clothing.

**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

Do not ingest.  
Do not use sparking tools.  
Do not enter areas where used or stored until adequately ventilated.  
Do not repack.  
Do not re-use empty containers.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Keep container closed when not in use.

Conditions for safe storage : Store in original container.  
Keep container closed when not in use.  
Keep in a cool place away from oxidizing agents.  
Keep in a dry, cool and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store in accordance with the particular national regulations.  
Keep in properly labelled containers.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH (2013-03-01)
		STEL	250 ppm	ACGIH (2013-03-01)
		ST	250 ppm 325 mg/m3	NIOSH REL (2013-10-08)
		TWA	200 ppm 260 mg/m3	NIOSH REL (2013-10-08)
		TWA	200 ppm 260 mg/m3	OSHA Z-1 (1997-08-04)
Toluene	108-88-3	TWA	20 ppm	ACGIH (2022-01-01)
		TWA	100 ppm 375 mg/m3	NIOSH REL (2013-10-08)
		ST	150 ppm 560 mg/m3	NIOSH REL (2013-10-08)
		TWA	200 ppm	OSHA Z-2 (2012-07-01)
		CEIL	300 ppm	OSHA Z-2 (2012-07-01)
		Peak	500 ppm (10 minutes)	OSHA Z-2 (2012-07-01)

**Chemlease® MPP 117**

Version 2.0      Revision Date: 07/15/2024      Date of last issue: 02/28/2023      Date of first issue: 02/28/2023      Print Date: 07/24/2024

Light aliphatic naphtha	64742-49-0	TWA	500 ppm 2,000 mg/m3	OSHA Z-1 (2007-01-01)
		TWA (Mist)	5 mg/m3	OSHA Z-1 (2018-03-15)
		TWA (Mist)	5 mg/m3	NIOSH REL (2019-10-04)
		ST (Mist)	10 mg/m3	NIOSH REL (2019-10-04)
dibutyltin dilaurate	77-58-7	TWA	0.1 mg/m3 (Tin)	OSHA Z-1 (1997-08-04)
		TWA	0.1 mg/m3 (Tin)	ACGIH (2013-03-01)
		STEL	0.2 mg/m3 (Tin)	ACGIH (2013-03-01)
		TWA	0.1 mg/m3 (Tin)	NIOSH REL (2013-10-08)

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI (2007-01-01)
Toluene	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI (2010-03-01)
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI (2010-03-01)
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI (2010-03-01)

**Engineering measures** : Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).



**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Protective gloves The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : yellow

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/range : No data available

Boiling point/boiling range : 150.8 °F / 66.0 °C



# SAFETY DATA SHEET

- US



DISTRIBUTED BY  
Freeman Mfg. & Supply Co.  
www.FreemanSupply.com



## Chemlease® MPP 117

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

Flash point : 39 °F / 4 °C  
Method: Tag closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 128.0 hPa (68 °F / 20 °C)  
(for a component of this mixture)

Relative vapour density : No data available

Relative density : 0.84 (68 °F / 20 °C)  
Reference substance: Water  
The value is calculated

Bulk density : No data available

Solubility(ies)  
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20.5 mm<sup>2</sup>/s (104 °F / 40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available



**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

**SECTION 10. STABILITY AND REACTIVITY**

- Reactivity : No hazards to be specially mentioned.
- Chemical stability : Stable under normal conditions.
- Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.
- Conditions to avoid : Heat, flames and sparks.  
Strong sunlight for prolonged periods.
- Incompatible materials : Oxidizing agents
- Hazardous decomposition products : No decomposition if stored and applied as directed.

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

**Product:**

- Acute oral toxicity : Symptoms: Central nervous system depression  
  
Acute toxicity estimate: 236.65 mg/kg  
Method: Calculation method  
  
Remarks: Effects due to ingestion may include:  
Toxic if swallowed.
- Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.  
Toxic by inhalation.  
  
Symptoms: Inhalation may provoke the following symptoms: ,  
Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central  
nervous system depression  
  
Acute toxicity estimate: 6.69 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method
- Acute dermal toxicity : Remarks: Toxic in contact with skin.  
  
Symptoms: Redness, Local irritation  
  
Acute toxicity estimate: 710.86 mg/kg  
Method: Calculation method



**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

**Components:**

**|| Methanol:**

- Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.
- Acute inhalation toxicity : LC50 (Rat): 131.25 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The component/mixture is toxic after short term inhalation.
- Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.

**|| Toluene:**

- Acute oral toxicity : LD50 (Rat): 5,580 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
- Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**|| Light aliphatic naphtha:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**|| 3-butoxypropan-2-ol:**

- Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

**|| dibutyltin dilaurate:**

- Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg
- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

**Skin corrosion/irritation**

**Product:**

- Remarks : Irritating to skin.

**Components:**

**|| Toluene:**

- Species : Rabbit
- Assessment : Irritating to skin.
- Method : OECD Test Guideline 404



**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

Result : Irritating to skin.

**Light aliphatic naphtha:**

Result : Skin irritation

**3-butoxypropan-2-ol:**

Result : Skin irritation

**Serious eye damage/eye irritation**

**Product:**

Remarks : Irritating to eyes.

**Components:**

**Toluene:**

Species : Rabbit  
Result : No eye irritation  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
GLP : yes

**3-butoxypropan-2-ol:**

Result : Eye irritation

**dibutyltin dilaurate:**

Result : Eye irritation

**Respiratory or skin sensitisation**

**Product:**

Remarks : This information is not available.

**Components:**

**Toluene:**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : Directive 67/548/EEC, Annex V, B.6.  
Result : Does not cause skin sensitisation.  
GLP : yes

**dibutyltin dilaurate:**

Result : May cause sensitisation by skin contact.

**Chemlease® MPP 117**

Version 2.0	Revision Date: 07/15/2024	Date of last issue: 02/28/2023 Date of first issue: 02/28/2023	Print Date: 07/24/2024
----------------	------------------------------	---	---------------------------

**Germ cell mutagenicity**

**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Components:**

**|| Toluene:**

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

**|| dibutyltin dilaurate:**

Germ cell mutagenicity - Assessment : In vitro tests showed mutagenic effects

**Carcinogenicity**

**Product:**

Remarks : No data available

**Components:**

**|| Toluene:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**IARC OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available



**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

**Components:**



**Toluene:**

Reproductive toxicity - Assessment : - Teratogenicity -  
Some evidence of adverse effects on development, based on animal experiments.



**dibutyltin dilaurate:**

Reproductive toxicity - Assessment : - Fertility -  
Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

**STOT - single exposure**

**Product:**

Remarks : No data available

**Components:**



**Methanol:**

Assessment : Causes damage to organs.



**Toluene:**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.



**Light aliphatic naphtha:**

Assessment : May cause drowsiness or dizziness.



**dibutyltin dilaurate:**

Assessment : Causes damage to organs.

**STOT - repeated exposure**

**Product:**

Remarks : No data available

**Components:**



**Toluene:**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Assessment : The substance or mixture is classified as specific target organ



**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

toxicant, repeated exposure, category 2.

**dibutyltin dilaurate:**

Exposure routes : Inhalation  
Assessment : Causes damage to organs through prolonged or repeated exposure.

**Repeated dose toxicity**

**Product:**

Remarks : This information is not available.

**Aspiration toxicity**

**Product:**

May be fatal if swallowed and enters airways.

**Components:**

**Toluene:**

May be fatal if swallowed and enters airways.

**Light aliphatic naphtha:**

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.  
Danger of very serious irreversible effects.

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

Toxicity to fish :  
Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates :  
Remarks: No data available



**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

**Components:**

**|| Toluene:**

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l  
Exposure time: 96 h  
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 11.5 mg/l  
Exposure time: 48 h  
Test Type: Immobilization

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 433 mg/l  
Exposure time: 96 h  
Test Type: Growth inhibition

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 4 mg/l  
Exposure time: 32 d  
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1 mg/l  
Exposure time: 21 d  
Test Type: Reproduction Test

**|| Light aliphatic naphtha:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**|| dibutyltin dilaurate:**

M-Factor (Acute aquatic toxicity) : 1





**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

**Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

**Persistence and degradability**

**Product:**

Biodegradability : Remarks: No data available

Physico-chemical  
removability : Remarks: No data available

**Components:**



**Methanol:**

Biodegradability : Result: Readily biodegradable.



**Toluene:**

Biodegradability : Primary biodegradation  
Result: rapidly biodegradable  
Biodegradation: > 80 %  
Method: OECD Test Guideline 301F



**Light aliphatic naphtha:**

Biodegradability : Remarks: No data available



**3-butoxypropan-2-ol:**

Biodegradability : Result: Readily biodegradable.



**dibutyltin dilaurate:**

Biodegradability : Result: Not readily biodegradable.

**Bioaccumulative potential**

**Product:**

Bioaccumulation : Remarks: No data available



**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

**Components:**



**Methanol:**

Bioaccumulation : Bioconcentration factor (BCF): 1.0



**Toluene:**

Bioaccumulation : Bioconcentration factor (BCF): 90



**Light aliphatic naphtha:**

Bioaccumulation : Bioconcentration factor (BCF): 10 - 2,500



**3-butoxypropan-2-ol:**

Bioaccumulation : Bioconcentration factor (BCF): < 100

Partition coefficient: n-octanol/water : log Pow: 1.2



**dibutyltin dilaurate:**

Bioaccumulation : Bioconcentration factor (BCF): 31

Partition coefficient: n-octanol/water : Pow: ca. 3

**Mobility in soil**

**Product:**

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

**Other adverse effects**

**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological : Toxic to aquatic life with long lasting effects.

**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

information

**Components:**



**Toluene:**

Results of PBT and vPvB assessment : Non-classified PBT substance Non-classified vPvB substance

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Dispose of waste product or used containers according to local regulations.

---

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**UNRTDG**

UN number : UN 1992  
Proper shipping name : FLAMMABLE LIQUID, TOXIC, N.O.S.  
(methanol, toluene)  
Class : 3  
Subsidiary risk : 6.1  
Packing group : II  
Labels : 3 (6.1)

**IATA-DGR**

UN/ID No. : UN 1992  
Proper shipping name : Flammable liquid, toxic, n.o.s.  
(methanol, toluene)  
Class : 3  
Subsidiary risk : 6.1  
Packing group : II  
Labels : Flammable Liquids, Toxic  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 352

**Chemlease® MPP 117**

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

**IMDG-Code**

UN number : UN 1992  
Proper shipping name : FLAMMABLE LIQUID, TOXIC, N.O.S.  
(methanol, toluene)  
Class : 3  
Subsidiary risk : 6.1  
Packing group : II  
Labels : 3 (6.1)  
EmS Code : F-E, S-D  
Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**

**49 CFR**

UN/ID/NA number : UN 1992  
Proper shipping name : Flammable liquids, toxic, n.o.s.  
(methanol, toluene)  
Class : 3  
Subsidiary risk : 6.1  
Packing group : II  
Labels : FLAMMABLE LIQUID, POISON  
ERG Code : 131  
Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION**

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Acute toxicity (any route of exposure)  
Respiratory or skin sensitisation  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard  
Skin corrosion or irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Methanol	67-56-1	>= 30 - < 50 %
----------	---------	----------------

**Chemlease® MPP 117**

Version 2.0	Revision Date: 07/15/2024	Date of last issue: 02/28/2023 Date of first issue: 02/28/2023	Print Date: 07/24/2024
----------------	------------------------------	---	---------------------------

Toluene	108-88-3	>= 20 - < 30 %
ETHYLBENZENE	100-41-4	< 0.1 %
Toluene	108-88-3	< 0.1 %

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Methanol	67-56-1	>= 30 - < 50 %
Toluene	108-88-3	>= 20 - < 30 %

**California Prop. 65**

WARNING: This product can expose you to chemicals including Benzene, ETHYLBENZENE, naphthalene, Cumene, which is/are known to the State of California to cause cancer, and Methanol, Toluene, Benzene, Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**

TSCA : All substances listed as active on the TSCA inventory

**TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

**SECTION 16. OTHER INFORMATION**

**Further information**

**Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	: 8-hour time weighted average

# SAFETY DATA SHEET

- US



## Chemlease® MPP 117

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

OSHA Z-2 / TWA : 8-hour time weighted average  
OSHA Z-2 / CEIL : Acceptable ceiling concentration  
OSHA Z-2 / Peak : Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/15/2024

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have

# SAFETY DATA SHEET

- US



DISTRIBUTED BY  
Freeman Mfg. & Supply Co.  
www.FreemanSupply.com



## Chemlease® MPP 117

Version	Revision Date:	Date of last issue: 02/28/2023	Print Date:
2.0	07/15/2024	Date of first issue: 02/28/2023	07/24/2024

---

been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.