

SAFETY DATA SHEET

- US

Distributed By
Freeman Manufacturing & Supply Co.
www.freemansupply.com 800-321-8511 **FREEMAN**



Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

SECTION 1. IDENTIFICATION

Product name : Chemlease® R&B EZ

Manufacturer or supplier's details

Company name of supplier : Chem-Trend LP
1445 W McPherson Park Dr
PO Box 860, Howell MI 48844-0860
United States
+1 517 546 4520

E-mail address of person responsible for the SDS : SDS-NA@chemtrend.com
Emergency telephone number : +1 517 545 7070

Recommended use of the chemical and restrictions on use

Recommended use : Release agent
Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2
Skin irritation : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :   

Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.

Chemlease® R&B EZ

Version 1.0	Revision Date: 01/23/2023	Date of last issue: - Date of first issue: 01/23/2023	Print Date: 03/14/2023
----------------	------------------------------	--	---------------------------

May cause drowsiness or dizziness.

Precautionary statements :

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting.
In case of fire: Use alcohol-resistant foam, carbon dioxide or water mist to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Light aliphatic naphtha	64742-49-0	Trade secret ($\geq 30 - < 60$)
Distillates (petroleum), hydrotreated light	64742-47-8	Trade secret ($\geq 10 - < 30$)
Light aliphatic naphtha	64742-49-0	Trade secret ($\geq 10 - < 30$)
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Trade secret ($\geq 10 - < 30$)
Naphtha (petroleum), light alkylate	64741-66-8	Trade secret ($\geq 5 - < 10$)

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled :

Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

- If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Never give anything by mouth to an unconscious person.
Aspiration hazard if swallowed - can enter lungs and cause damage.
- Most important symptoms and effects, both acute and delayed : Central nervous system depression
Can be absorbed through skin.
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Causes skin irritation.
Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema
Aspiration may cause pulmonary oedema and pneumonitis.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

- Specific hazards during firefighting : Do not let product enter drains.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Hazardous combustion products : Carbon oxides
Metal oxides
- Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
Exposure to decomposition products may be a hazard to health.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Non-sparking tools should be used.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Keep away from heat and sources of ignition.
- Advice on safe handling : Use only in an area containing explosion proof equipment.
Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory

Chemlease® R&B EZ

Version 1.0	Revision Date: 01/23/2023	Date of last issue: - Date of first issue: 01/23/2023	Print Date: 03/14/2023
----------------	------------------------------	--	---------------------------

equipment.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Keep away from fire, sparks and heated surfaces.
 Smoking, eating and drinking should be prohibited in the application area.
 Wash hands and face before breaks and immediately after handling the product.
 Ensure all equipment is electrically grounded before beginning transfer operations.
 Do not get in eyes or mouth or on skin.
 Do not get on skin or clothing.
 Do not ingest.
 Do not use sparking tools.
 Do not enter areas where used or stored until adequately ventilated.
 Do not repack.
 Do not re-use empty containers.
 These safety instructions also apply to empty packaging which may still contain product residues.
 Keep container closed when not in use.

Conditions for safe storage : Store in original container.
 Keep container closed when not in use.
 Keep in a cool place away from oxidizing agents.
 Keep in a dry, cool and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Store in accordance with the particular national regulations.
 Keep in properly labelled containers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Light aliphatic naphtha	64742-49-0	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1 (2007-01-01)
		TWA	400 ppm 1,600 mg/m ³	OSHA P0 (1989-01-19)
		TWA (Mist)	5 mg/m ³	OSHA Z-1 (2018-03-15)
		TWA (Mist)	5 mg/m ³	OSHA P0 (1989-01-19)
		TWA (Mist)	5 mg/m ³	NIOSH REL (2019-10-04)
		ST (Mist)	10 mg/m ³	NIOSH REL

Chemlease® R&B EZ

Version 1.0 Revision Date: 01/23/2023 Date of last issue: - Date of first issue: 01/23/2023 Print Date: 03/14/2023

				(2019-10-04)
Distillates (petroleum), hydrotreated light	64742-47-8	TWA (Mist)	5 mg/m3	OSHA Z-1 (2011-07-01)
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH (2010-03-01)
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH (2010-03-01)
		TWA (Mist)	5 mg/m3	OSHA P0 (1989-01-19)
		TWA (Mist)	5 mg/m3	NIOSH REL (2013-10-08)
		TWA (Mist)	5 mg/m3	OSHA Z-1 (2018-03-15)
		ST (Mist)	10 mg/m3	NIOSH REL (2013-10-08)
		TWA (Mist)	5 mg/m3	OSHA P0 (1989-01-19)
		TWA (Mist)	5 mg/m3	NIOSH REL (2019-10-04)
		ST (Mist)	10 mg/m3	NIOSH REL (2019-10-04)
Light aliphatic naphtha	64742-49-0	TWA	500 ppm 2,000 mg/m3	OSHA Z-1 (2007-01-01)
		TWA	400 ppm 1,600 mg/m3	OSHA P0 (1989-01-19)
		TWA (Mist)	5 mg/m3	OSHA Z-1 (2018-03-15)
		TWA (Mist)	5 mg/m3	OSHA P0 (1989-01-19)
		TWA (Mist)	5 mg/m3	NIOSH REL (2019-10-04)
		ST (Mist)	10 mg/m3	NIOSH REL (2019-10-04)
Naphtha (petroleum), hydrotreated heavy	64742-48-9	TWA	500 ppm 2,000 mg/m3	OSHA Z-1 (2007-01-01)
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1 (2007-01-01)
		TWA	400 ppm 1,600 mg/m3	OSHA P0 (1989-01-19)
		TWA	400 ppm 1,600 mg/m3	OSHA P0 (1989-01-19)
Naphtha (petroleum), light alkylate	64741-66-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1 (2007-01-01)
		TWA	400 ppm 1,600 mg/m3	OSHA P0 (1989-01-19)
		TWA (Mist)	5 mg/m3	OSHA Z-1 (2018-03-15)
		TWA (Mist)	5 mg/m3	OSHA P0

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

				(1989-01-19)
		TWA (Mist)	5 mg/m3	NIOSH REL (2019-10-04)
		ST (Mist)	10 mg/m3	NIOSH REL (2019-10-04)

Engineering measures : Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Protective gloves The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : amine-like

Odour Threshold : No data available

Chemlease® R&B EZ

Version 1.0	Revision Date: 01/23/2023	Date of last issue: - Date of first issue: 01/23/2023	Print Date: 03/14/2023
----------------	------------------------------	--	---------------------------

pH : No data available

Melting point/range : No data available

Boiling point/boiling range : 280.0 °F / 137.8 °C

Flash point : 27.0 °F / -2.8 °C
Method: Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 45 hPa (68 °F / 20 °C)

Relative vapour density : No data available

Relative density : 0.73 (68 °F / 20 °C)
Reference substance: Water
The value is calculated

Bulk density : No data available

Solubility(ies)
Water solubility : insoluble
Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : < 20.5 mm²/s (104 °F / 40 °C)

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:
Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.
Irritating to respiratory system.
Symptoms: Inhalation may provoke the following symptoms:,
Local irritation, Respiratory disorders, Dizziness, Drowsiness,
Vomiting, Fatigue, Vertigo, Central nervous system
depression

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method
Symptoms: Redness, Local irritation

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

Components:

Light aliphatic naphtha:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Light aliphatic naphtha:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Naphtha (petroleum), hydrotreated heavy:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Naphtha (petroleum), light alkylate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Light aliphatic naphtha:

Species : Rabbit
Result : Skin irritation

Light aliphatic naphtha:

Result : Skin irritation

Naphtha (petroleum), hydrotreated heavy:

Result : Repeated exposure may cause skin dryness or cracking.

Naphtha (petroleum), light alkylate:

Result : Skin irritation

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks : No data available

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

IARC OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

Components:

Light aliphatic naphtha:

Assessment : May cause drowsiness or dizziness.

Distillates (petroleum), hydrotreated light:

Exposure routes : Inhalation

Assessment : May cause drowsiness or dizziness.

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

Light aliphatic naphtha:

Assessment : May cause drowsiness or dizziness.

Naphtha (petroleum), light alkylate:

Assessment : May cause drowsiness or dizziness.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

Light aliphatic naphtha:

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Light aliphatic naphtha:

May be fatal if swallowed and enters airways.

Naphtha (petroleum), hydrotreated heavy:

May be fatal if swallowed and enters airways.

Naphtha (petroleum), light alkylate:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Light aliphatic naphtha:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Distillates (petroleum), hydrotreated light:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Light aliphatic naphtha:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

Naphtha (petroleum), hydrotreated heavy:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Naphtha (petroleum), light alkylate:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.4 mg/l
Exposure time: 48 h

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

Light aliphatic naphtha:

Biodegradability : Remarks: No data available

Distillates (petroleum), hydrotreated light:

Biodegradability : Result: rapidly biodegradable

Light aliphatic naphtha:

Biodegradability : Remarks: No data available

Naphtha (petroleum), hydrotreated heavy:

Biodegradability : Result: Readily biodegradable.

Naphtha (petroleum), light alkylate:

Biodegradability : Result: Not readily biodegradable.

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

Light aliphatic naphtha:

Bioaccumulation : Bioconcentration factor (BCF): 10 - 2,500

Partition coefficient: n-octanol/water : log Pow: 2.2 - 5.2

Distillates (petroleum), hydrotreated light:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

Light aliphatic naphtha:

Bioaccumulation : Bioconcentration factor (BCF): 10 - 2,500

Naphtha (petroleum), hydrotreated heavy:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

Naphtha (petroleum), light alkylate:

Bioaccumulation : Bioconcentration factor (BCF): 105

Partition coefficient: n-octanol/water : log Pow: 3.52

Mobility in soil

Product:

Mobility : Remarks: No data available

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

Distribution among environmental compartments : Remarks: No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of waste product or used containers according to local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1866
Proper shipping name : RESIN SOLUTION
(Light aliphatic naphtha)
Class : 3
Packing group : II
Labels : 3

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution
(Light aliphatic naphtha)

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1866
Proper shipping name : RESIN SOLUTION
(Light aliphatic naphtha)
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1866
Proper shipping name : Resin solution
(Light aliphatic naphtha)
Class : 3
Packing group : II
Labels : FLAMMABLE LIQUID
ERG Code : 127
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

WARNING: This product can expose you to chemicals including ETHYLBENZENE, which is/are known to the State of California to cause cancer, and Toluene, n-hexane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -

Chemlease® R&B EZ

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	01/23/2023	Date of first issue: 01/23/2023	03/14/2023

Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 01/23/2023

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.