

according to WHMIS 2015 and ANSI Z400.1-2010

Aircast 3700A, Aircast 3600A

Material number 1032

Revision date: 15/5/2019 Version: 15 en-CA,US Language: Date of first version: 13/8/2008

Page:

1 of 9

1. Product and company identification

### **Product identifier**

Trade name:

## Aircast 3700A, Aircast 3600A

## Relevant identified uses of the substance or mixture and uses advised against

RTV high temperature casting compound. Reserved for industrial and professional use.

## Details of the supplier of the safety data sheet

Company name:

General use:

Airtech International, Inc. 5700 Skylab Road Huntington Beach, CA 92647 E-mail: airtech@airtechintl.com Website: www.airtechonline.com Telephone: +1 714.899.8100 Dept. responsible for information: Telephone: +1 714.899.8100 E-mail: airtech@airtechintl.com

Tygavac Advanced Materials Ltd. The Causeway **Broadway Business Park** Chadderton, Oldham OL9 9XD United Kingdom Website: www.tygavac.co.uk Telephone: +44 161.947.1610 Dept. responsible for information: Telephone: +44 161.947.1610 E-mail: sales@tygavac.co.uk

Airtech Europe Sarl Zone industrielle Haneboesch L-4562 Differdange Luxembourg Website: www.airtech.lu Telephone: +352 582.282 Dept. responsible for information: Telephone: +352 582.282 E-mail: sales@airtech.lu

Airtech Asia Ltd. No. 161 of Anyuan Rd **Chagugang County** Wuqing District 301721, Tianjin, P.R. China Website: www.airtech.asia Telephone: +86 22 8862 9800 Telefax:: +86 22 8862 9900 Dept. responsible for information: Telephone: +86 22 8862 9800 E-mail: airtech.asia@airtechasia.com.cn

## **Emergency phone number**

CHEMTREC EMERGENCY PHONE: International: +1 703-741-5970

## 2. Hazards identification

## **Emergency overview**

Appearance:	Physical state at 20 °C and 101.3 kPa: solid Form: pasty Color: brown
Odor:	weak
Classification:	Reproductive toxicity 2;
Hazard symbols:	



Warning Suspected of damaging fertility or the unborn child.







Revision date: 15/5/2019 Version: 15 en-CA,US Language: Date of first version: 13/8/2008

2 of 9

Page:

Aircast 3700A, Aircast 3600A

Material number 1032

Precautionary statements:

Obtain special instructions before use.

Use personal protective equipment as required. IF exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents/container to hazardous or special waste collection point.

## **Regulatory status**

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

### Hazards not otherwise classified

Special danger of slipping by leaking/spilling product. see section 11: Toxicological information

## 3. Composition / Information on ingredients

Chemical characterisation:

A mixture of organopolysiloxane mixture and silicon dioxide.

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 541-02-6	Decamethylcyclopentasiloxane	< 0.5 %	not applicable
CAS 540-97-6	Dodecamethylcyclohexasiloxane	< 0.5 %	not applicable
CAS 556-67-2	Octamethylcyclotetrasiloxane	< 0.5 %	Flammable Liquid 3. Reproductive toxicity 2. Aquatic toxicity - chronic 4.

Additional information: The maximum workplace exposure limits are, where necessary, listed in section 8. Contains: Silicon dioxide (Quartz (SiO2))

	4. First aid measures	
In case of inhalation:	Provide fresh air. Seek medical treatment in case of troubles.	
Following skin contact:	Remove mechanically with cloth or paper. Thoroughly wash skin with soap and water. Change contaminated clothing. In case of skin reactions, consult a physician.	
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. In case of troubles or persistent symptoms, consult an opthalmologist.	
After swallowing:	Seek medical attention. Rinse mouth. Do not induce vomiting without medical assistance.	
Most important symptoms and effects, both acute and delayed		
	Suspected of damaging fertility or the unborn child. Product can cause slight irritation.	

### Information to physician

Treat symptomatically.



w.freemansupply.com



according to WHMIS 2015 and ANSI Z400.1-2010

Revision date:15/5/2019Version:15Language:en-CA,USDate of first version:13/8/2008

Aircast 3700A, Aircast 3600A

Material number 1032

3 of 9

Page:

5. Fire fighting measures

Flash point/flash point range:  $250 \ ^{\circ}C \ (o.c.)$ 

Auto-ignition temperature:

No data available

Suitable extinguishing media:

Carbon dioxide, extinguishing powder, alcohol resistant foam.

Extinguishing media which must not be used for safety reasons:

full water jet

## Specific hazards arising from the chemical

	Combustible. Emits toxic fumes under fire conditions. In case of fire may be liberated: Silicon dioxide, traces of incompletely burned carbon compounds, formaldehyde, carbon monoxide and carbon dioxide.	
Protective equipment and precautions for firefighters:		
	Wear a self-contained breathing apparatus and chemical protective clothing.	
Additional information:	Cool endangered containers with water spray and, if possible, remove from danger zone. Use a water fog to control vapors. Do not breathe fumes. Do not allow fire water to penetrate into surface or ground water.	

6. Accidental release measures	
--------------------------------	--

Personal precautions:	Avoid contact with the substance. Wear suitable protective clothing. Provide adequate ventilation. Do not breathe vapor or spray. Keep unprotected people away.
Environmental precautio	ins:
	Do not allow to penetrate into soil, waterbodies or drains. If necessary notify appropriate authorities.
Methods for clean-up:	Plug leak if safely possible. Take up mechanically, placing in appropriate containers for disposal.
Additional information:	Special danger of slipping by leaking/spilling product.

## 7. Handling and storage

## Handling

Advices on safe handling: Do not breathe vapor or spray. Obtain special instructions before use. Provide adequate ventilation, and local exhaust as needed. Avoid contact with skin and eyes. Wear suitable gloves. When using do not eat, drink or smoke.

Precautions against fire and explosion:

Keep away from heat sources, sparks and open flames. Take standard precautions to prevent fire.

## Storage

Requirements for storerooms and containers: Keep only in the original container. Keep container tightly closed in a cool, well-ventilated place. Do not drop, drag or bang the container. Protect from frost and exposure to sun. Hints on joint storage: Keep away from food and drinks.





Material number 1032

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date:15/5/2019Version:15Language:en-CA,USDate of first version:13/8/2008

Page:

4 of 9

# 8. Exposure controls / personal protection

Aircast 3700A, Aircast 3600A

## **Exposure guidelines**

Occupational exposure limit values:

CAS No.	Designation	Туре	Limit value
14808-60-7	Silicon dioxide (Quartz (SiO2))	Canada, Alberta: OEL 8 hour	0.025 mg/m³
		Canada, BC: OEL TWA	0.025 mg/m <sup>3</sup>
		Canada, Ontario: OEL TWA	0.1 mg/m <sup>3</sup> (respirable fraction)
		Canada, Québec: VEMP	0.1 mg/m <sup>3</sup> (respirable fraction)
		USA: ACGIH: TWA	0.025 mg/m <sup>3</sup> (respirable fraction)
		USA: NIOSH: TWA	0.05 mg/m <sup>3</sup> (respirable fraction)
		USA: OSHA: TWA	10 mg/m³/% SiO2+ 2 (respirable fraction)
		USA: OSHA: TWA	250 mppcf/%SiO2+5 (fine dust)
		USA: OSHA: TWA	30 mg/m³/% SiO2+ 2 (inhalable fraction)
7631-86-9	Silicon dioxide	USA: NIOSH: TWA	6 mg/m³
		USA: OSHA: TWA	20 mppcf
		USA: OSHA: TWA	80 mg/m³ (total dust)

Additional information: Silicon dioxide, Quartz (SiO2) are embedded in the product and therefore no dust is present.

## **Engineering controls**

Provide adequate ventilation, and local exhaust as needed. See also information in chapter 7, section storage.

## Personal protection equipment (PPE)

Eye/face protection	Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.	
Skin protection	Wear suitable protective clothing.	
	Protective gloves according to OSHA Standard - 29 CFR: 1910.138. Glove material: Plastic or Rubber. Observe glove manufacturer's instructions concerning penetrability and breakthrough time.	
Respiratory protection:	Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. When vapors form, use respiratory protection. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.	
General hygiene considerations:		
	Do not breathe vapor or spray. Avoid contact with skin, eyes, and clothing. Change contaminated clothing. Eye wash facility must be provided. Wash hands before breaks and after work. When using do not eat, drink or smoke.	

## 9. Physical and chemical properties

## Information on basic physical and chemical properties

Appearance:

Physical state at 20 °C and 101.3 kPa: solid Form: pasty Color: brown





according to WHMIS 2015 and ANSI Z400.1-2010

Revision date:	15/5/2019
Version:	15
Language:	en-CA,US
Date of first version:	13/8/2008

5 of 9

Page:

Aircast 3700A, Aircast 3600A

Material number 1032

Odor:	weak
Odor threshold:	No data available
pH value:	not applicable
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	250 °C (o.c.)
Evaporation rate:	No data available
Flammability:	No data available
Explosion limits:	No data available
Vapor pressure:	No data available
Vapor density:	No data available
Density:	at 25 °C: 1.25 g/cm <sup>3</sup>
Solubility: Water solubility:	miscible with organic solvents insoluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Thermal decomposition:	No data available
Viscosity, dynamic:	180000 mPa*s

10. Stability and reactivity	
Reactivity:	Refer to section: Possibility of hazardous reactions.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous reactions No hazardous reactions known.	
Conditions to avoid:	Keep away from heat.
Incompatible materials:	Strong bases, strong oxidizing agents, strong acids

Hazardous decomposition products:

Thermal breakdown of this product during fire or very high heat condition may evolve the following hazardous decomposition products: Silicon dioxide, traces of incompletely burned carbon compounds, formaldehyde, carbon monoxide and carbon dioxide.

Thermal decomposition: No data available





according to WHMIS 2015 and ANSI Z400.1-2010

 Revision date:
 15/5/2019

 Version:
 15

 Language:
 en-CA,US

 Date of first version:
 13/8/2008

Page:

6 of 9

Aircast 3700A, Aircast 3600A

Material number 1032

11. Toxicological information

Toxicological	rests
Toxicological effects:	Acute toxicity (oral): Lack of data.
	Acute toxicity (dermal): Lack of data.
	Acute toxicity (inhalative): Lack of data.
	Skin corrosion/irritation: Lack of data.
	Serious eye damage/irritation: Lack of data.
	Sensitisation to the respiratory tract: Lack of data.
	Skin sensitisation: Lack of data.
	Germ cell mutagenicity/Genotoxicity: Lack of data.
	Carcinogenicity: Lack of data.
	Reproductive toxicity: Reproductive toxicity 2 = Suspected of damaging fertility or the unborn child.
	Effects on or via lactation: Lack of data.
	Specific target organ toxicity (single exposure): Lack of data.
	Specific target organ toxicity (repeated exposure): Lack of data.
	Aspiration hazard: Lack of data.
Other information:	Information about Silicon dioxide (Quartz (SiO2)): Carcinogen Status: IARC Rating: Group 1 OSHA Carcinogen: not listed NTP Rating: listed NIOSH Recommendations: Occupational Health Guideline: 0553 Silicon dioxide: Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0552
Symptoms	
	In case of inhalation: Overheating released mist or vapors can irritate the respiratory tracts. Can damage your health.

In case of ingestion: Gastrointestinal irritation.

- After contact with skin:
- Frequently or prolonged contact with skin may cause dermal irritation.

After eye contact: Product can cause slight irritation.

## **12. Ecological information**

## Ecotoxicity

Further details:

No data available





Aircast 3700A, Aircast 3600A

Material number 1032

Revision date:15/5/2019Version:15Language:en-CA,USDate of first version:13/8/2008

Page:

7 of 9

## Mobility in soil

No data available

## Persistence and degradability

Further details: No data available

## Additional ecological information

General information: Do not allow to penetrate into soil, waterbodies or drains.

## **13. Disposal considerations**

#### Product

Recommendation: Special waste. Dispose of waste according to applicable legislation.

### Contaminated packaging

Recommendation:

Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled. Do not remove label until container is thoroughly cleaned.

## 14. Transport information

### **USA:** Department of Transportation (DOT)

Proper shipping name: Not restricted

### Canada: Transportation of Dangerous Goods (TDG)

Shipping name:

Not restricted

### Sea transport (IMDG)

Proper shipping name: Not restricted Marine pollutant: No

### Air transport (IATA)

Proper shipping name:

Not restricted

### Further information

No dangerous good in sense of these transport regulations.

## 15. Regulatory information

### National regulations - Canada

No data available





according to WHMIS 2015 and ANSI Z400.1-2010

Revision date:15/5/2019Version:15Language:en-CA,USDate of first version:13/8/2008

8 of 9

Page:

Aircast 3700A, Aircast 3600A

Material number 1032

### National regulations - U.S. Federal Regulations

Silicon dioxide (Quartz (SiO2)):	TSCA Inventory: listed TSCA HPVC: not listed Carcinogen Status: IARC Rating: Group 1 OSHA Carcinogen: not listed NTP Rating: listed NIOSH Recommendations: Occupational Health Guideline: 0553
Silicon dioxide:	TSCA Inventory: listed TSCA HPVC: not listed Carcinogen Status: IARC Rating: Group 3 OSHA Carcinogen: not listed NTP Rating: not listed NIOSH Recommendations: Occupational Health Guideline: 0552
Decamethylcyclopentasiloxane:	TSCA Inventory: listed TSCA HPVC: not listed
Dodecamethylcyclohexasiloxane:	TSCA Inventory: listed TSCA HPVC: not listed
Octamethylcyclotetrasiloxane:	TSCA Inventory: listed TSCA HPVC: not listed

## National regulations - U.S. State Regulations

Silicon dioxide (Quartz (SiO2)): California Proposition 65: cancer

## National regulations - EC member states

Further regulations, limitations and legal requirements:

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: Decamethylcyclopentasiloxane (PBT, vPvB), Dodecamethylcyclohexasiloxane (PBT, vPvB), Octamethylcyclotetrasiloxane (PBT, vPvB)

	16. Other information		
Text for labeling:	Contains < 0.5 % Decamethylcyclopentasiloxane, < 0.5 % Dodecamethylcyclohexasiloxane, < 0.5 % Octamethylcyclotetrasiloxa sheet available on request.	ane. Safety data	
Hazard rating systems:	NFPA Hazard Rating: Health: 2 (Moderate) Fire: 1 (Slight) Reactivity: 0 (Minimal)		
	HMIS Version III Rating: Health: 2 (Moderate) - Chronic effects Flammability: 1 (Slight) Physical Hazard: 0 (Minimal) Personal Protection: X = Consult your supervisor	HEALTH <b>*</b> FLAMMABILITY PHYSICAL HAZARD	2 1 0 X
Reason of change: <b>Department issu</b>	Changes in section 1: Identification of the substance or mixture ing data sheet		
Contact person:	see section 1. Dent responsible for information		

Contact person: see section 1: Dept. responsible for information





Material number 1032

according to WHMIS 2015 and ANSI Z400.1-2010

Revision date:15/5/2019Version:15Language:en-CA,USDate of first version:13/8/2008

9 of 9

Page:

This data sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, and which additional precautions may be necessary. All health and safety information contained in this data sheet should be provided to your employees and customers. It is your responsibility to develop appropriate workplace instructions and training programs for employees.

Aircast 3700A, Aircast 3600A

As the conditions and methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. All statements or suggestions are made without warranty, expressed or implied, regarding accuracy of information, the hazards connected with the use of the product or the results to be obtained from the use thereof.







according to WHMIS 2015 and ANSI Z400.1-2010

Revision date:15/5/2019Version:11Language:en-CA,USDate of first version:12/8/2008

Page:

1 of 7

Aircast 3700B, Aircast 3600B

Material number 1033

## 1. Product and company identification

### **Product identifier**

Trade name: Ai

### Aircast 3700B, Aircast 3600B

## Relevant identified uses of the substance or mixture and uses advised against

Curing agent for RTV casting resin. Reserved for industrial and professional use.

## Details of the supplier of the safety data sheet

Company name:

General use:

Airtech International, Inc. 5700 Skylab Road Huntington Beach, CA 92647 E-mail: airtech@airtechintl.com Website: www.airtechonline.com Telephone: +1 714.899.8100 Dept. responsible for information: Telephone: +1 714.899.8100 E-mail: airtech@airtechintl.com

Tygavac Advanced Materials Ltd. The Causeway Broadway Business Park Chadderton, Oldham OL9 9XD United Kingdom Website: www.tygavac.co.uk Telephone: +44 161.947.1610 Dept. responsible for information: Telephone: +44 161.947.1610 E-mail: sales@tygavac.co.uk

Airtech Europe Sarl Zone industrielle Haneboesch L-4562 Differdange Luxembourg Website: www.airtech.lu Telephone: +352 582.282 Dept. responsible for information: Telephone: +352 582.282 E-mail: sales@airtech.lu

Airtech Asia Ltd. No. 161 of Anyuan Rd Chagugang County Wuqing District 301721, Tianjin, P.R. China Website: www.airtech.asia Telephone: +86 22 8862 9800 Telefax:: +86 22 8862 9900 Dept. responsible for information: Telephone: +86 22 8862 9800 E-mail: airtech.asia@airtechasia.com.cn

## **Emergency phone number**

CHEMTREC EMERGENCY PHONE: International: +1 703-741-5970

## 2. Hazards identification

## **Emergency overview**

Appearance:	Form: liquid Color: blue
Odor:	odorless
Classification:	Reproductive toxicity 2;
Hazard symbols:	



Signal word: Hazard statements:

**Warning** Suspected of damaging fertility or the unborn child.





 Revision date:
 15/5/2019

 Version:
 11

 Language:
 en-CA,US

 Date of first version:
 12/8/2008

Page:

Aircast 3700B, Aircast 3600B

Material number 1033

Precautionary statements:

Obtain special instructions before use.

Use personal protective equipment as required. IF exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents/container to hazardous or special waste collection point.

## **Regulatory status**

This material is considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

## Hazards not otherwise classified

Product may separate hydrogen. Danger of explosion!

Direct contact may cause skin and eyes reddening and irritation. Overheating released mist or vapors can irritate the respiratory tracts. In case of ingestion gastrointestinal irritation.

see section 11: Toxicological information

## 3. Composition / Information on ingredients

Chemical characterisation:

A mixture of Vinyldimethyl terminated Polydimethylsiloxane (CAS 68083-19-2) and Polymethylhydrosiloxane (CAS 63148-57-2).

Relevant ingredients:

CAS No.	Designation	Content	Classification
CAS 556-67-2	Octamethylcyclotetrasiloxane	< 1 %	Flammable Liquid 3. Reproductive toxicity 2. Aquatic toxicity - chronic 4.

4. First aid measures	
In case of inhalation:	Provide fresh air. Seek medical treatment in case of troubles.
Following skin contact:	Remove mechanically with cloth or paper. Change contaminated clothing. Thoroughly wash skin with soap and water. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. In case of troubles or persistent symptoms, consult an opthalmologist.
After swallowing:	Seek medical attention. Rinse mouth immediately and drink plenty of water. Do not induce vomiting without medical assistance.
Most important	t symptoms and effects, both acute and delayed
	Suspected of damaging fertility or the unborn child.

Product can cause slight irritation.

## Information to physician

Treat symptomatically.

## 5. Fire fighting measures

Flash point/flash point range:

Auto-ignition temperature:

94 °C (o.c.)

No data available

printed by Airtech Advanced Materials Group



with Qualisys SUMDAT

2 of 7



according to WHMIS 2015 and ANSI Z400.1-2010

 Revision date:
 15/5/2019

 Version:
 11

 Language:
 en-CA,US

 Date of first version:
 12/8/2008

3 of 7

Page:

Aircast 3700B, Aircast 3600B

Material number 1033

Suitable extinguishing media:

Carbon dioxide, extinguishing powder, foam.

Extinguishing media which must not be used for safety reasons:

Full water jet.

## Specific hazards arising from the chemical

Emits toxic fumes under fire conditions.

In case of fire may be liberated: Silicon dioxide, traces of incompletely burned carbon compounds, formaldehyde, carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information: Cool endangered containers with water spray and, if possible, remove from danger zone. Use a water fog to control vapors. Do not breathe fumes. Do not allow fire water to penetrate into surface or ground water.

6. Accidental release measures

Personal precautions: Product may separate hydrogen. Remove all sources of ignition. Provide adequate ventilation. Wear suitable protective clothing. Avoid contact with the substance.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains.

Methods for clean-up: Soak up with absorbent materials such as sand, siliceus earth, acid- or universal binder. Store in special closed containers and dispose of according to ordinance.

## 7. Handling and storage

## Handling

Advices on safe handling: Obtain special instructions before use. Provide adequate ventilation, and local exhaust as needed. Avoid contact with skin and eyes. Do not breathe vapor or spray. Wear suitable gloves.

Precautions against fire and explosion:

Keep away from heat sources, sparks and open flames.

## Storage

Requirements for storerooms and containers:

Keep in a cool place. Keep container tightly closed and in a well-ventilated place. Protect from frost and exposure to sun.

Hints on joint storage: Keep away from strongly acidic and alkaline materials as well as oxidizers. Keep away from food and drinks.

## 8. Exposure controls / personal protection

## **Engineering controls**

Provide good ventilation and/or an exhaust system in the work area. See also information in chapter 7, section storage.

## Personal protection equipment (PPE)

Eye/face protection Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.

Skin protection Wear suitable protective clothing.





Revision date:15/5/2019Version:11Language:en-CA,USDate of first version:12/8/2008

Aircast 3700B, Aircast 3600B Material number 1033

Page:

4 of 7

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.<br/>Glove material: Plastic or rubber<br/>Observe glove manufacturer's instructions concerning penetrability and breakthrough time.Respiratory protection:When vapors form, use respiratory protection. The filter class must be suitable for the<br/>maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise<br/>when handling the product. If the concentration is exceeded, self-contained breathing<br/>apparatus must be used.<br/>Recommended: Use filter type A (= against vapors of organic substances) according to<br/>OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.General hygiene considerations:<br/>Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Eye wash<br/>feaility must be provided. When hende before breake and offere work. When weine do not<br/>

Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Eye wash facility must be provided. Wash hands before breaks and after work. When using do not eat, drink or smoke.

9. Physical and chemical properties

## Information on basic physical and chemical properties

Appearance: Odor: Odor threshold:	Form: liquid Color: blue odorless No data available
pH value:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	94 °C (o.c.)
Evaporation rate:	No data available
Flammability:	This material is combustible, but will not ignite readily.
Explosion limits:	No data available
Vapor pressure:	No data available
Vapor density:	No data available
Density:	No data available
Solubility:	No data available
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Thermal decomposition:	No data available
Additional information:	No data available

## 10. Stability and reactivity

Reactivity:	Refer to section: Possibility of hazardous reactions.
Chemical stability:	Stable under recommended storage conditions.
Possibility of hazardous	<sup>reactions</sup> Hazardous polymerisation: May occur. Polymerization along with heat production. Product may separate hydrogen. Danger of explosion!
Conditions to avoid:	Keep away from heat sources, sparks and open flames.
Incompatible materials:	Strong acid or bases as well as oxidizing agents.



according to WHMIS 2015 and ANSI Z400.1-2010

Revision date: 15/5/2019 Version: en-CA,US Language: Date of first version: 12/8/2008

5 of 7

Page:

Aircast 3700B, Aircast 3600B

Material number 1033

Hazardous decompositio	n products:
	Product may release hydrogen gas.
	In case of fire may be liberated: Silicon dioxide, traces of incompletely burned carbon
	compounds, formaldehyde, carbon monoxide and carbon dioxide.
Thermal decomposition:	No data available

## 11. Toxicological information

## **Toxicological tests**

Lack of data. Acute toxicity (dermal): Lack of data. Acute toxicity (inhalative): Lack of data. Skin corrosion/irritation: Lack of data. Serious eye damage/irritation: Lack of data. Sensitisation to the respiratory tract: Lack of data. Skin sensitisation: Lack of data. Germ cell mutagenicity/Genotoxicity: Lack of data. Carcinogenicity: Lack of data. Reproductive toxicity: Reproductive toxicity 2 = Suspected of damaging fertility or the unborn child. Effects on or via lactation: Lack of data. Specific target organ toxicity (single exposure): Lack of data. Specific target organ toxicity (repeated exposure): Lack of data. Aspiration hazard: Lack of data. In case of inhalation:

### Symptoms

Overheating released mist or vapors can irritate the respiratory tracts. In case of ingestion: Gastrointestinal irritation. After contact with skin: Frequently or prolonged contact with skin may cause dermal irritation. After eye contact: Product can cause slight irritation.

## 12. Ecological information

### **Ecotoxicity**

Further details: No data available

### Mobility in soil

No data available

## Persistence and degradability

Further details: No data available

## Additional ecological information

General information: Do not allow to penetrate into soil, waterbodies or drains.

printed by Airtech Advanced Materials Group





according to WHMIS 2015 and ANSI Z400.1-2010

Revision date:15/5/2019Version:11Language:en-CA,USDate of first version:12/8/2008

Page:

Aircast 3700B, Aircast 3600B

Material number 1033

6 of 7

## 13. Disposal considerations

### Product

Recommendation:

Special waste. Dispose of waste according to applicable legislation.

## Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled. Do not remove label until container is thoroughly cleaned.

## **14. Transport information**

## USA: Department of Transportation (DOT)

Proper shipping name: Not restricted

### Canada: Transportation of Dangerous Goods (TDG)

Not restricted

Shipping name:

### Sea transport (IMDG)

Proper shipping name:	Not restricted
Marine pollutant:	no

### Air transport (IATA)

Proper shipping name: Not restricted

## **Further information**

No dangerous good in sense of these transport regulations.

## 15. Regulatory information

## National regulations - Canada

### No data available

## National regulations - U.S. Federal Regulations

 Vinyldimethyl terminated Polydimethylsiloxane:
 TSCA Inventory: listed; UVCB; EPA flags XU

 Polymethylhydrosiloxane:
 TSCA HPVC: not listed;

 TSCA HPVC: not listed;
 UVCB; EPA flags XU

 TSCA HPVC: not listed;
 TSCA HPVC: not listed;

Octamethylcyclotetrasiloxane:

TSCA HPVC: not listed TSCA Inventory: listed TSCA HPVC: not listed

## National regulations - EC member states

Further regulations, limitations and legal requirements:

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: Octamethylcyclotetrasiloxane (PBT, vPvB)

## 16. Other information

Text for labeling:

Contains < 1 % Octamethylcyclotetrasiloxane. Safety data sheet available on request.





Hazard rating systems: NFPA Hazard Rating:

## SAFETY DATA SHEET

according to WHMIS 2015 and ANSI Z400.1-2010

 Revision date:
 15/5/2019

 Version:
 11

 Language:
 en-CA,US

 Date of first version:
 12/8/2008

7 of 7

Page:

Aircast 3700B, Aircast 3600B

Material number 1033

HEALTH *	2
FLAMMABILITY	1
PHYSICAL HAZARD	0

Reason of change: Changes in section 1: Identification of the substance or mixture

Personal Protection: X = Consult your supervisor

Health: 2 (Moderate) - Chronic effects

### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

Health: 2 (Moderate) Fire: 1 (Slight)

Reactivity: 0 (Minimal) HMIS Version III Rating:

Flammability: 1 (Slight) Physical Hazard: 0 (Minimal)

This data sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, and which additional precautions may be necessary. All health and safety information contained in this data sheet should be provided to your employees and customers. It is your responsibility to develop appropriate workplace instructions and training programs for employees.

As the conditions and methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. All statements or suggestions are made without warranty, expressed or implied, regarding accuracy of information, the hazards connected with the use of the product or the results to be obtained from the use thereof.

