





Dynacast Black Part A

DATE PREPARED: 4/20/2005

LAST REVISION: 1/5/2010

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: Kindt-Collins Company LLC INFORMATION PHONE: (216) 252-4122

12651 Elmwood Ave EMERGENCY PHONE: (800) 424-9300

Cleveland, OH 44111 (Chemtrec)

PRODUCT NAME: Dynacast Black Part A PRODUCT NUMBER:

UPC NUMBER:

SYNONYMS:

PREPARED BY Kathy Louney-Bilski

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient %	OSHA PEL	ACGIH TLV
Polymethylene polyphenyl Isocyanate	9016-87-9	15- 25%		
Hydrocarcon Naphta	64742-47-8	2- 10%		
Amorphous Silica	112945-52-5	.03- .08%		
BARIUM SULFATE	7727437	5- 15%	PEL = Total dust 15 mg/M3 Respirable fraction 5mg/M3	TLV = 10mg/M3 TOTAL DUST CONTAINING NO ASBESTOS AND LESS THA
BOROSILATE	65997173	45- 55%		10 mg/m³
4,4' Diphenylmethanc Diisocyanate	101-68-8	5- 19%		

N/A Not Available

3. HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW:

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Eye contact may result in conjunctival irritation.

INHALATION: Exposure exceeding the PEL may result in chemical bronchitis, headache or pulmonary edema.

INGESTION: Gastrointestinal symptoms include nausea, vomiting and abdominal pain

SKIN CONTACT: Skin contact may result in dermatitis, either irritative or allergic.

SIGNS AND SYMPTOMS OF EXPOSURE:

Eye, skin, or respiratory imitation.

4. FIRST AID MEASURES

Dynacast Black Part A Page 1 of 5

EYE CONTACT: Flush with Copious Amounts of water for 15 minutes; Contact Physician

INHALATION: Remove victim to uncontaminated area, administer oxygen if necessary. Seek medical attention.

INGESTION: DO NOT induce vomiting. Never give fluids or induce vomiting if victim is unconscious or having

convulsions. Seek medical attention.

SKIN CONTACT: Remove contaminated clothes and wash affected areas with soap and water. Seek medical

attention.

AGGRAVATED MEDICAL CONDITIONS:

Chronic overexposure to isocyanates may cause sensitization in some individuals, resulting in wheezing, shortness of breath and difficulty in breathing. Subsequent reactions may occur below the PEL and TLV. Asthma caused by polyisocyanates may persist in some individuals after removal of the polyisocyanate. Long-term overexposure has been reported to cause lung damage including reduced lung function.

SUPPLEMENTAL HEALTH INFORMATION:

Individuals who are sensitized to isocyanates and those with pre-existing lung diseases or conditions, including asthma, pulmonary sensitization, recurrent eczema must avoid all exposure to isocyanates.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: 141°F FLASH POINT METHOD USED: TOC

AUTOIGNITION: Not Determined LEL: N/A UEL: N/A

EXTINGUISHING MEDIA:

Carbon Dioxide, dry chemical, chemical foam, water spray

SPECIAL FIRE FIGHTING PROCEDURES:

Fire fighters must wear self-contained breathing apparatus to protect against toxic and irritating vapors. Full protective clothing should also be worn.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None Known

COMBUSTION PRODUCTS:

Carbon Dioxide, Carbon Monoxide

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

Remove spillage by absorbing in sand, vermiculite, sawdust, or absorbent sweeping compound. For small spills, rubbing alcohol may be used. Dike to prevent entry into water system.

7. HANLDING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Should be stored in a ventilated storage area between 70-80°F. Avoid excessive temperatures. Storage must be in tightly sealed containers to protect from moisture.

OTHER PRECAUTIONS:

N/A

8. EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

If the PEL is exceeded, wear a NIOSH approved air supplied respirator.

Dynacast Black Part A Page 2 of 5

VENTILATION: Use local exhaust to maintain concentration below the PEL.

PROTECTIVE GLOVES: Wear resistant gloves, (Consult your safety supplier for appropriate gloves).

EYE PROTECTION: Fitted chemical goggles, face shield or safety glasses.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Boots and rubber apron to avoid skin contact. Contaminated

clothing or equipment should be cleaned or disposed of after

use

WORK / HYGENIC PRACTICES:

Educate and train employees on safe use of product. Shower and eye wash station should be available.

ENGINEERING CONTROLS: Good ventilation should be sufficient to control airborne levels.

EXPOSURE GUIDELINES: CAS#64742-47-8 PEL 100 ppm TLV 100 ppm CAS#101-68-8 TLV .005 ppm

9. PHYSICAL AND CHEMICAL PROPERTIES

SOLUABILITY IN WATER: Slight APPEARANCE AND ODOR: Oxide yellow liquid, slight odor

BOILING POINT: >300°F FREEZING POINT: N/A

VAPOR PRESSURE N/A PERCENT VOLATILE: N/A

EVAPORATION: N/A PH: N/A

POUNDS PER GALLON: N/A MOLECULAR WEIGHT: N/A

SPECIFIC GRAVITY: 1.8-1.9 VAPOR DENSITY: N/A

MELTING POINT: N/A OTHER PROPERTIES: N/A

10. STABILITY AND REACTIVITY

STABLE: Stable INCOMPATIBILITY: Strong oxidizing materials.

HAZARDOUS DECOMPOSITION Carbon dioxide (Carbon monoxide with incomplete combustion)

OR BY PRODUCTS:

HAZARDOUS Will Not Occur

POLYMERIZATION:

11. TOXICOLOGY INFORMATION

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Use approved incineration in accordance with federal, state and local environmental regulations. Material must be disposed of in approved land fill.

14. TRANSPORTATION INFORMATION

DOT CLASS: Liquid Plastic, N.O.I., Non regulated

HAZARD CLASS: N/A
UN NUMBER: N/A
PACKING: N/A
GUIDE NUMBER: N/A

PROPER SHIPPING NAME: Liquid Plastic, N.O.I., Non regulated

Dynacast Black Part A Page 3 of 5

15. REGULATORY INFORMATION

EC Classification: No information available.

SARA Title III Section 302 : Extremely Hazardous (If Section is blank - then it is N/A (not applicable))

Chemical Name CAS number Wt. %

per 40 CFR 372.45(f) toxic chemicals if so listed here in the mixture do not exceed the specified upper bound concentration value listed as Wt%

Section 311-312: Hazardous Catergorization (If Section is blank - then it is N/A (not applicable))

Chemical Name CAS number Wt. % BARIUM SULFATE 7727437 5-15%

Section 313: Toxic Chemical (If Section is blank - then it is N/A (not applicable))

Chemical Name CAS number Wt. %

WHIMIS (If Section is blank - then it is N/A (not applicable))
Chemical name CAS number Wt. %

Proposition 65 (If Section is blank - then it is N/A (not applicable))

Chemical name CAS number Wt. %

Dynacast Black Part A Page 4 of 5

16. OTHER INFORMATON

HMIS INFORMATION: HEALTH: 3 FLAMMABILITY: 2 REACTIVITY: 1 PROTECTIVE: H

DISCLAIMER

The information contained herein is based on the data available to The Kindt-Collins LLC and is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. We assume no responsibilities for injury from the use of this product desribed herein.

We only warrant to you, but no other persons, that the product herein shall conform to our Quality Assurance specifications on the date of shipment to you. Any technical advise, information, or recommendations given to you is given gratis without any warranty, expressed or implied.

Dynacast Black Part A Page 5 of 5



Dynacast Black Part B

DATE PREPARED: 4/20/2005

LAST REVISION: 1/5/2010

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: Kindt-Collins Company LLC

INFORMATION PHONE:

(216) 252-4122

12651 Elmwood Ave

EMERGENCY PHONE:

(800) 424-9300

Cleveland, OH 44111

(Chemtrec)

PRODUCT NUMBER:

PRODUCT NAME:

Dynacast Black Part B

UPC NUMBER:

SYNONYMS:

PREPARED BY

Kathy Louney-Bilski

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name CAS # Ingredient % OSHA PEL ACGIH TLV

 Polyether Polyol
 9051-49-4

 Nitrogen Based Polyether
 102-60-3

 Hydrocarbon Naphtha
 64742-47-8

 Amorphous Silica
 112945-52-5

 Barium Sulphate
 7727-43-7

 Glass Oxide
 65997-17-3

 Blue Pigment
 000147-14-8

N/A Not Available

3. HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW:

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Eye contact may result in conjunctival irritation.

INHALATION: Exposure exceeding the PEL may result in chemical bronchitis, headache or pulmonary edema.

INGESTION: Gastrointestinal symptoms include nausea, vomiting and abdominal pain

SKIN CONTACT: Skin contact may result in dermatitis, either irritative or allergic.

SIGNS AND SYMPTOMS OF EXPOSURE:

Eye, skin, or respiratory irritation.

4. FIRST AID MEASURES

EYE CONTACT: Flush with Copious Amounts of water for 15 minutes; Contact Physician

INHALATION: Remove victim to uncontaminated area, administer oxygen if necessary. Seek medical attention.

Dynacast Black Part B Page 1 of 5

INGESTION: DO NOT induce vomiting. Never give fluids or induce vomiting if victim is unconscious or having

convulsions. Seek medical attention.

SKIN CONTACT: Remove contaminated clothes and wash affected areas with soap and water. Seek medical

attention.

AGGRAVATED MEDICAL CONDITIONS:

Chronic overexposure to isocyanates may cause sensitization in some individuals, resulting in wheezing, shortness of breath and difficulty in breathing. Subsequent reactions may occur below the PEL and TLV. Asthma caused by polyisocyanates may persist in some individuals after removal of the polyisocyanate. Long-term overexposure has been reported to cause lung damage including reduced lung function.

SUPPLEMENTAL HEALTH INFORMATION:

Individuals who are sensitized to isocyanates and those with pre-existing lung diseases or conditions, including asthma, pulmonary sensitization, recurrent eczema must avoid all exposure to isocyanates.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: 142°F FLASH POINT METHOD USED: TOC

AUTOIGNITION: Not Determined LEL: N/A UEL: N/A

EXTINGUISHING MEDIA:

Carbon Dioxide, dry chemical, chemical foam, water spray

SPECIAL FIRE FIGHTING PROCEDURES:

Fire fighters must wear self-contained breathing apparatus to protect against toxic and irritating vapors. Full protective clothing should also be worn.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None Known

COMBUSTION PRODUCTS:

Carbon Dioxide, Carbon Monoxide

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

Remove spillage by absorbing in sand, vermiculite, sawdust, or absorbent sweeping compound. For small spills, rubbing alcohol may be used. Dike to prevent entry into water system.

7. HANLDING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Should be stored in a ventilated storage area between 70-80°F. Avoid excessive temperatures. Storage must be in tightly sealed containers to protect from moisture.

OTHER PRECAUTIONS:

N/A

8. EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

If the PEL is exceeded, wear a NIOSH approved air supplied respirator.

VENTILATION: Use local exhaust to maintain concentration below the PEL.

PROTECTIVE GLOVES: Wear resistant gloves. (Consult your safety supplier for appropriate gloves).

Dynacast Black Part B Page 2 of 5

EYE PROTECTION: Fitted chemical goggles, face shield or safety glasses.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Boots and rubber apron to avoid skin contact. Contaminated

clothing or equipment should be cleaned or disposed of after

use

WORK / HYGENIC PRACTICES:

Educate and train employees on safe use of product. Shower and eye wash station should be available.

ENGINEERING CONTROLS: Good ventilation should be sufficient to control airborne levels.

EXPOSURE GUIDELINES: CAS#64742-47-8 PEL 100 ppm TLV 100 ppm

9. PHYSICAL AND CHEMICAL PROPERTIES

SOLUABILITY IN WATER: Slight APPEARANCE AND ODOR: Black liquid, slight odor

BOILING POINT: >300°F FREEZING POINT: N/A **VAPOR PRESSURE** N/A **PERCENT VOLATILE:** N/A **EVAPORATION:** N/A PH: N/A **POUNDS PER GALLON:** N/A **MOLECULAR WEIGHT:** N/A **SPECIFIC GRAVITY:** 1.8-1.9 VAPOR DENSITY: N/A **MELTING POINT:** N/A **OTHER PROPERTIES:** N/A

10. STABILITY AND REACTIVITY

STABLE: Stable INCOMPATIBILITY: Moisture and isocyanates

HAZARDOUS DECOMPOSITION Carbon dioxide and carbon monoxide

OR BY PRODUCTS:

HAZARDOUS Will Not Occur

POLYMERIZATION:

11. TOXICOLOGY INFORMATION

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Use approved incineration in accordance with federal, state and local environmental regulations. Material must be disposed of in approved land fill.

14. TRANSPORTATION INFORMATION

DOT CLASS: Liquid Plastic, N.O.I., Non regulated

HAZARD CLASS: N/A
UN NUMBER: N/A
PACKING: N/A
GUIDE NUMBER: N/A

PROPER SHIPPING NAME: Liquid Plastic, N.O.I., Non regulated

Dynacast Black Part B Page 3 of 5

15. REGULATORY INFORMATION

EC Classification: No information available.

SARA Title III Section 302 : Extremely Hazardous (If Section is blank - then it is N/A (not applicable))

Chemical Name CAS number Wt. %

per 40 CFR 372.45(f) toxic chemicals if so listed here in the mixture do not exceed the specified upper bound concentration value listed as Wt%

Section 311-312: Hazardous Catergorization (If Section is blank - then it is N/A (not applicable))

Chemical Name CAS number Wt. %

Section 313: Toxic Chemical (If Section Is blank - then it is N/A (not applicable))

Chemical Name CAS number Wt. %

WHIMIS (If Section is blank - then it is N/A (not applicable))

Chemical name CAS number Wt. %

Proposition 65 (If Section is blank - then it is N/A (not applicable))

Chemical name CAS number Wt. %

Dynacast Black Part B Page 4 of 5

16. OTHER INFORMATON

HMIS INFORMATION: HEALTH: 1 FLAMMABILITY: 2 REACTIVITY: 0 PROTECTIVE: H

DISCLAIMER

The information contained herein is based on the data available to The Kindt-Collins LLC and is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. We assume no responsibilities for injury from the use of this product desribed herein.

We only warrant to you, but no other persons, that the product herein shall conform to our Quality Assurance specifications on the date of shipment to you. Any technical advise, information, or recommendations given to you is given gratis without any warranty, expressed or implied.

Dynacast Black Part B Page 5 of 5