

SAFETY DATA SHEET



1. Identification

Product identifier DEVCON® Aluminum Liquid (F-2) Resin

Other means of identification

0103 SKU#

Recommended use Not available. Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name **ITW Performance Polymers**

30 Endicott Street **Address**

Danvers, MA 01923

United States

Telephone Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available. **Contact person EHS** Department

Chemtrec 800-424-9300 **Emergency phone number**

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

> Serious eye damage/eye irritation Category 2A Sensitization, skin Category 1

Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. **Hazard statement**

Precautionary statement

Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated Prevention

work clothing must not be allowed out of the workplace. Wear eye protection/face protection.

Wear protective gloves.

If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Response

Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take

off contaminated clothing and wash it before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Material name: DEVCON® Aluminum Liquid (F-2) Resin 1/7

0103 Version #: 01 Issue date: 05-29-2019

Chemical name	Common name and synonyms	CAS number	%
Aluminum Flake		7429-90-5	30 - 60
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)		25068-38-6	30 - 60
Calcium Carbonate		1317-65-3	10 - 30
Alkyl Glycidyl Ether		68609-97-2	1 - 5
Other components below reportable le	evels		1 - <3

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

General information

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Use water spray to cool unopened containers.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
Aluminum Flake (CAS 7429-90-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Calcium Carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFF	•		_
Components	Туре	Value	Form
Aluminum Flake (CAS 7429-90-5)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Aluminum Flake (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Aluminum Flake (CAS 7429-90-5)	TWA	5 mg/m3	Welding fume or pyrophoric powder.
		5 mg/m3	Respirable.
		10 mg/m3	Total
Calcium Carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
ogical limit values	No biological exposure limits noted for	or the ingredient(s).	
ropriate engineering trols	Good general ventilation should be u applicable, use process enclosures, maintain airborne levels below recon	local exhaust ventilation, or ot	her engineering controls t

established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Face shield is recommended. Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Thermal hazards

Wear appropriate chemical resistant gloves. Hand protection

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

In case of insufficient ventilation, wear suitable respiratory equipment.

Respiratory protection

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

Material name: DEVCON® Aluminum Liquid (F-2) Resin 0103 Version #: 01 Issue date: 05-29-2019

9. Physical and chemical properties

Appearance Paste. Solid. Physical state **Form** Paste. Color Grev. Odor Slight.

Odor threshold Not available. Not available. pН Melting point/freezing point Not available.

608 °F (320 °C) estimated Initial boiling point and boiling

range

> 399.9 °F (> 204.4 °C) Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) Not available. Vapor pressure Not available. Vapor density Not available. Relative density

Solubility(ies)

Solubility (water) Not available. Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **Viscosity**

Other information

Density 2.17 g/cm3 estimated

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing. 0.11 % estimated Percent volatile Specific gravity 2.17 estimated

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. **Skin contact** Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

No data is available on the degradability of any ingredients in the mixture.

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

Mobility in soil

No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Aluminum Flake (CAS 7429-90-5)

% 1.0

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Aluminum Flake (CAS 7429-90-5) Listed.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard categories

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

SARA 313 (TRI reporting)

Chemical name **CAS** number % by wt. Aluminum Flake 30 - 60 7429-90-5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to Quartz, which is known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Aluminum Flake (CAS 7429-90-5)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Vorce	Eviating Chamicals List (ECL)	Vaa

KoreaExisting Chemicals List (ECL)YesNew ZealandNew Zealand InventoryYes

Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

16. Other information, including date of preparation or last revision

Issue date 05-29-2019

Version # 01

HMIS® ratings Health: 2

Flammability: 1

Physical hazard: 0

NFPA ratings Health: 2

Flammability: 1 Instability: 0

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® Aluminum Liquid (F-2) Resin 0103 Version #: 01 Issue date: 05-29-2019

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SAFETY DATA SHEET



1. Identification

Product identifier Aluminum Liquid (F-2) Hardener

Other means of identification

SKU# 5331

Recommended use Not available. Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

ITW Performance Polymers Company name

30 Endicott Street **Address**

Danvers, MA 01923

United States

978-777-1100 **Telephone Customer Service**

Website www.itwperformancepolymers.com

E-mail Not available. **Contact person EHS** Department

Chemtrec 800-424-9300 **Emergency phone number**

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

> Acute toxicity, dermal Category 4 Skin corrosion/irritation Category 1 Serious eye damage/eye irritation Category 1 Sensitization, skin Category 1

Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements



Danger Signal word

Hazard statement Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage.

May cause an allergic skin reaction. Causes serious eye damage.

Precautionary statement

Prevention Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when

using this product. Contaminated work clothing must not be allowed out of the workplace. Wear

protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all Response

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor. If skin irritation or rash occurs: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Ingestion

Chemical name	Common name and synonyms	CAS number	%
Benzyl Alcohol		100-51-6	10 - 30
TRIETHYLENETETRAMINE		112-24-3	10 - 30
Other components below repor	table levels		50

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician

or poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

General information

media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting

Specific methods

equipment/instructions

General fire hazards

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Use water spray to reduce vapors or divert vapor cloud drift. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not breathe mist/vapors. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Туре	Value	
Benzyl Alcohol (CAS 100-51-6)	TWA	44.2 mg/m3	
		10 ppm	
TRIETHYLENETETRAMIN E (CAS 112-24-3)	TWA	6 mg/m3	
		1 nnm	

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Exposure guidelines

US WEEL Guides: Skin designation

TRIETHYLENETETRAMINE (CAS 112-24-3)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield. Face shield is

recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

. .

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Amber.
Odor Amine-like.
Odor threshold Not available.
pH Not available.

Melting point/freezing point 4.64 °F (-15.2 °C) estimated initial boiling point and boiling 420.8 °F (216 °C) estimated

range

Flash point 199.9 °F (93.3 °C) estimated

Evaporation rate Not available.

Material name: Aluminum Liquid (F-2) Hardener 5331 Version #: 01 Issue date: 05-29-2019

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Not available.

Flammability limit - upper

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 5.73 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 640 °F (337.78 °C) estimated

Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 0.97 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Combustible IIIB estimated

Oxidizing properties Not oxidizing.

Specific gravity 0.97 estimated

VOC 100 % SOLIDS

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stabilityMaterial is stable under normal conditions.Possibility of hazardousHazardous polymerization does not occur.

reactions

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Peroxides. Phenols.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contactCauses severe skin burns. Harmful in contact with skin. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

Acute toxicity Harmful in contact with skin. Harmful if swallowed.

Components Species Test Results

Benzyl Alcohol (CAS 100-51-6)

Acute Dermal

LD50 Rabbit 2000 mg/kg

Components Species Test Results

Inhalation

LC50 Rat 1000 mg/l, 8 Hours

Oral

LD50 Rat 1230 - 3100 mg/kg

TRIETHYLENETETRAMINE (CAS 112-24-3)

Acute Dermal

LD50 Rat 1465 mg/kg

Oral *Liquid*

LD50 Rat 1716 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Benzyl Alcohol 1.1

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN2735

UN proper shipping name Amines, liquid, corrosive, n.o.s, or Polyamines, liquid, corrosive, n.o.s.

(TRIETHYLENETETRAMINE, Aliphatic Amines), Limited Quantity

Transport hazard class(es)

Class 8 Subsidiary risk 8 Label(s) Packing group Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B2, IB2, T11, TP1, TP27

Packaging exceptions 154 202 Packaging non bulk 242 Packaging bulk

IATA

UN2735 **UN number**

UN proper shipping name Transport hazard class(es) Amines, liquid, corrosive, n.o.s. (TRIETHYLENETETRAMINE, Aliphatic Amines), Limited Quantity

8 Class Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 8L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

IMDG

UN number UN2735

AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. **UN proper shipping name**

(TRIETHYLENETETRAMINE, Aliphatic Amines), Limited Quantity

Transport hazard class(es)

Class 8 Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant No. F-A, S-B **EmS**


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

DOT; IMDG





General information

IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

categories

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes

Country(s) or region On inventory (yes/no)* Inventory name Europe European List of Notified Chemical Substances (ELINCS) Inventory of Existing and New Chemical Substances (ENCS) Yes Japan Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

TaiwanTaiwan Chemical Substance Inventory (TCSI)YesUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

16. Other information, including date of preparation or last revision

Issue date 05-29-2019

Version # 01

HMIS® ratings Health: 3

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 1 Instability: 0

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material

designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Material name: Aluminum Liquid (F-2) Hardener 5331 Version #: 01 Issue date: 05-29-2019

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).