

Safety Data Sheet

Freeman 165PL Regular Sheet Wax

Section 1 Chemical Product and Company Identification

1.1 Product identifiers

Freeman 165PL Regular Sheet Wax (Plain back)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Specialty Tooling Wax. For professional/industrial use only.

1.3 Details of the supplier of the safety data sheet

Freeman Manufacturing & Supply Company 1101 Moore Road, Avon, OH 44011-4043 USA Telephone: +1 (440) 934-1902

Email: contactus@freemansupply.com

1.4 Emergency telephone number

CHEMTREC (800) 424-9300

Section 2 Hazards Identification

2.1 Classification of the substance or mixture

Not classified according to OSHA 29 CFR 1910.1200 HCS

2.2 GHS Label elements, including precautionary statements

No label element(s) required

2.3 Hazards not otherwise classified

Molten product can cause serious burns.

Section 3 Composition/Information on Ingredients

3.1 Mixture of Substances

Proprietary mixture of synthetic waxes, resin(s), and additive(s).

No components need to be disclosed according to the applicable regulations.

Section 4 First Aid Measures

4.1 Description of first aid measures

Inhalation Get medical assistance if irritation develops or persists. If breathing is difficult,

move the person to fresh air. Give artificial respiration if person is not breathing.

Skin contact For thermal burns, flush or submerge effected area in cold water to dissipate heat.

Cover with clean bandage material. Do not peel material from skin. Get medical attention.

For contact at ambient temperatures, wash with soap and water.

Eye contact Immediately flush with plenty of water for at least 15 minutes.

If irritation persists, get medical attention immediately, preferably an ophthalmologist.

Ingestion If swallowed, rinse mouth with water. Never give anything by mouth to an unconscious person.

Do NOT induce vomiting. Consult a physician if necessary.

Section 5 Fire Fighting Measures

5.1 Extinguishing media

Suitable extinguishing media: Water fog, dry chemical, foam, carbon dioxide.

Unsuitable extinguishing media: Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards: Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. See Section 10 for possible products of hazardous combustion.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Date of Preparation: March 26, 2025 Page 1 of 4

Freeman 165PL Regular Sheet Wax

Section 6 Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Wear appropriate personal protective equipment, see Section 8.

6.2 Environmental precautions

Should not be released into the environment. Prevent product from entering drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage and use clean non-sparking tools to collect material.

Shovel spillage into suitable container for disposal.

Section 7 Handling and Storage

7.1 Precautions for safe handling

Wear appropriate personal protective equipment, see Section 8. Avoid contact with skin and eyes. Wash thoroughly with soap and water after handling. Do not use in areas without adequate ventilation. Avoid breathing fumes.

Avoid contact with molten material.

7.2 Conditions for safe storage, including any incompatibilities

Store at ambient temperatures. Keep in closed container when not in use. Keep away from ignition sources, heat, open flames, and direct sunlight. Do not store with incompatible materials, see Section 10.

Section 8 Exposure Controls/Personal Protection

8.1 Control parameters

Substance Name	Exposure Limit / Standard	Source
Wax fumes	2 mg/m ³ TWA	ACGIH

8.2 Exposure controls

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation may be needed in special circumstances, such as poorly ventilated spaces, very hot processing, mechanical generation of dusts, etc.

8.3 Personal protective equipment

Eye/Face

Wear safety glasses equipped with side shields, or safety goggles.

Hands

Chemical protective gloves should not be needed when handling this material. Use gloves to protect from mechanical injury. Use gloves with insulation for thermal protection when needed.

Skin/Body

No precautions other than clean body-covering clothing should be needed.

Respiratory

The need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, or when adverse effects such as respiratory irritation has been experienced, or where indicated by your risk assessment process, then use an approved air-purifying respirator. Use an approved air-purifying respirator with organic vapor cartridge and particulate pre-filter when vapors are generated at increased temperatures.

Safety Stations

Make emergency eyewash stations and washing facilities available in work area.

General Hygienic Practices

Wash thoroughly after handling, and before eating, drinking or smoking. Remove contaminated clothing promptly and clean thoroughly before reuse. Avoid contamination of food, beverages, or smoking

Freeman 165PL Regular Sheet Wax

Section 9 Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Physical State & Color Pale yellow solid

Odor Mild

Odor ThresholdNo data availablepHNo data availableMelting Point>165°F (74°C)

VOC Content 0

Boiling Point No data available **Flash Point** 465°F (240°C) **Evaporation rate** No data available Flammability (solid, gas) No data available Upper/lower flammability No data available **Vapor Pressure** No data available **Vapor Density** No data available Relative Density (g/cc) 0.9 ± 0.05

Water Solubility
Coefficient: n-octanol/ water
Auto-Ignition Temperature

No data available
No data available

Viscosity Solid at room temperature

Explosive Properties None **Oxidizing Properties** None

Section 10 Stability and Reactivity

10.1 Reactivity: No dangerous reaction known under conditions of normal use.

10.2 Chemical stability:Stable under recommended storage conditions. **10.3 Possibility of hazardous reactions:**Hazardous polymerization does not occur.

10.4 Conditions to avoid:Heat, sparks, open flame. **10.5 Incompatible materials:**Strong oxidizing agents.

10.6 Hazardous decomposition productsMay include: carbon monoxide, carbon dioxide

Section 11 Toxicological Information

11.1 Information on likely routes of exposure:

Ingestion Very low toxicity if swallowed. Harmful effects not

anticipated from swallowing small amounts.

Skin contactNo adverse effects anticipated from skin absorption. **Inhalation**Vapors released during thermal processing may cause

respiratory irritation.

Eye contact No data available

Skin Corrosion/IrritationClassification criteria not metSerious Eye Damage/Eye IrritationClassification criteria not metRespiratory or Skin SensitizationClassification criteria not metGerm Cell MutagenicityClassification criteria not met

Carcinogenicity No component of this product present at levels greater than

or equal to 0.1% is identified as an anticipated, potential, probable, possible, known, or confirmed carcinogen.

Reproductive Toxicity Classification criteria not met

Aspiration Hazard Not relevant

Specific Target Organ Toxicity (STOT)Not expected for Single Exposure or Repeated Exposures

Freeman 165PL Regular Sheet Wax

Section 12 Ecological Information

12.1 Toxicity Not expected to be harmful to aquatic organisms

12.2 Persistence and degradabilityNo data available12.3 Bioaccumulative potentialNo data available12.4 Mobility in soilNo data available12.5 Results of PBT & vPvB assessmentNo data available

Section 13 Disposal Considerations

13.1 Disposal Follow applicable Federal, State, and local regulations.

Section 14 Transport Information

14.1 DOT/TDG, IMO/IMDG, IATA/ICOA: Not regulated for transport

Section 15 Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the product

Inventories: This product complies with the following inventories: Canada DSL/NDSL, USA TSCA

SARA 311/312 Hazards Classifications: None

SARA 313 Components: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

RCRA: In the form delivered, this product is not considered as hazardous waste, and is not subject to reporting under the Resource Conservation and Recovery Act.

California Proposition 65: This product is not known to contain any components for which the State of California has found to cause cancer, birth defects or other reproductive harm.

Section 16 Other Information

16.1 Disclaimer

The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.

Initial issue date: June 1, 2015

Previous revision date: June 20, 2022 Current revision date: March 26, 2025