

SAFETY DATA SHEET



H.B. Fuller® TORQUE 62 TL

Version 1.3 Revision Date 12/09/2022

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : H.B. Fuller® TORQUE 62 TL
Product code : 100000007001

Manufacturer or supplier's details

Company : H.B. Fuller Engineering Adhesives
Address : 9001 W Fey Drive
Frankfort, IL, 60423
Telephone : 1-815-464-5606

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Anaerobic Cure Adhesive
Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION


Emergency Overview

Appearance	liquid
Color	red
Odor	characteristic

GHS Classification

Skin irritation : Category 2
Eye irritation : Category 2A
Skin sensitization : Category 1
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements:

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

SAFETY DATA SHEET

H.B. Fuller® TORQUE 62 TL

Version 1.3

Revision Date 12/09/2022

Precautionary Statements:

Prevention: P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection.

Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:

IARC	Group 2B: Possibly carcinogenic to humans cumene 98-82-8
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	Reasonably anticipated to be a human carcinogen cumene 98-82-8

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
2-phenoxyethyl methacrylate	10595-06-9	30 - 50
Poly(oxy-1,2-ethanediyl), .alpha.-(2-methyl-1-oxo-2-propenyl)-.omega.-[(2-methyl-1-oxo-2-propenyl)oxy]-	25852-47-5	30 - 50
methacrylic acid, monoester with propane-1,2-diol	27813-02-1	30 - 50
α,α-dimethylbenzyl hydroperoxide	80-15-9	0.1 - 1
cumene	98-82-8	0.1 - 1
2'-phenylacetohydrazide	114-83-0	0.1 - 1
maleic acid	110-16-7	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Show this material safety data sheet to the doctor in attendance.

SAFETY DATA SHEET

H.B. Fuller® TORQUE 62 TL

Version 1.3

Revision Date 12/09/2022

If inhaled	: Move to fresh air. Keep patient warm and at rest. Consult a physician after significant exposure.
In case of skin contact	: Wash off immediately with soap and plenty of water. Call a physician if irritation develops or persists.
In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids. Seek medical advice.
If swallowed	: If swallowed, call a poison control center or doctor immediately. Do not induce vomiting without medical advice.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	: Water spray jet
Hazardous combustion products	: Nitrogen oxides (NO _x) Sulfur oxides
Specific extinguishing methods	:
Further information	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for fire-fighters	: Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Refer to protective measures listed in sections 7 and 8. Ensure adequate ventilation.
Environmental precautions	: Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.
Methods and materials for containment and cleaning up	: Ventilate the area. Soak up with inert absorbent material. Shovel or sweep up.

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation	: Use only with adequate ventilation.
-------------------------	---------------------------------------

SAFETY DATA SHEET

H.B. Fuller® TORQUE 62 TL

Version 1.3

Revision Date 12/09/2022

- Advice on safe handling : Wear personal protective equipment.
Do not get on skin or clothing.
Keep away from heat and flame.
- Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated place.
Store in original container.
- Materials to avoid : Do not store together with oxidizing and self-igniting products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
cumene	98-82-8	TWA	5 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0
		PEL	50 ppm 245 mg/m3	CAL PEL

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Combined particulates and organic vapor type
- Hand protection
Material : Neoprene gloves
Nitrile rubber
butyl-rubber
- Eye protection : Tightly fitting safety goggles
Ensure that eyewash stations and safety showers are close to the workstation location.
- Skin and body protection : Long sleeved clothing
Preventive skin protection

SAFETY DATA SHEET**H.B. Fuller® TORQUE 62 TL**

Version 1.3

Revision Date 12/09/2022

Protective measures : Avoid contact with skin.
Hygiene measures : Avoid contact with skin, eyes and clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Color : red
Odor : characteristic
Odor Threshold : no data available
pH : is not determined
Melting point/freezing point : is not determined
Boiling point/boiling range : is not determined
Flash point : Not applicable
Evaporation rate : is not determined
Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : Upper flammability limit
is not determined
Lower explosion limit : Lower flammability limit
is not determined
Vapor pressure : is not determined
Density : 1.06 g/cm³
Solubility(ies)
Water solubility : is not determined
Partition coefficient: n-
octanol/water : no data available
Autoignition temperature : is not determined

Viscosity
Viscosity, kinematic : is not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.
Hazardous decomposition products : Nitrogen oxides (NO_x)
Sulfur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

SAFETY DATA SHEET

H.B. Fuller® TORQUE 62 TL

Version 1.3

Revision Date 12/09/2022

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:

α,α -dimethylbenzyl hydroperoxide:

Acute oral toxicity : LD50 Oral Rat: 382 mg/kg

Acute inhalation toxicity : LC50 Rat: 220 ppm
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal Rat: 500 mg/kg

cumene:

Acute oral toxicity : LD50 Oral Rat: 1,400 mg/kg

maleic acid:

Acute oral toxicity : LD50 Oral Rat: 708 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: 1,560 mg/kg

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

SAFETY DATA SHEET

H.B. Fuller® TORQUE 62 TL

Version 1.3

Revision Date 12/09/2022

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

methacrylic acid, monoester with propane-1,2-diol :

Toxicity to fish : LC50 (Fish): 493 mg/l
Exposure time: 48 h
Test Method: static test

α,α -dimethylbenzyl hydroperoxide :

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3.9 mg/l
Exposure time: 96 h
Test Method: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 7 mg/l
Exposure time: 24 h
Test Method: static test

cumene :

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.7 mg/l
Exposure time: 96 h
Test Method: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.6 mg/l
Exposure time: 48 h
Test Method: static test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (microalgae)): 2.6 mg/l
Exposure time: 72 h
Test Type: flow-through test

maleic acid :

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5 mg/l
Exposure time: 96 h
Test Method: static test

Persistence and degradability

No data available

Bioaccumulative potential

SAFETY DATA SHEET

H.B. Fuller® TORQUE 62 TL

Version 1.3

Revision Date 12/09/2022

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of together with household waste.
Do not dispose of waste into sewer.
To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Respiratory or skin sensitization
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SAFETY DATA SHEET

H.B. Fuller® TORQUE 62 TL

Version 1.3

Revision Date 12/09/2022

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

2-phenoxyethyl methacrylate	10595-06-9
1,2-benzisothiazol-3(2H)-one 1,1-dioxide	81-07-2
cumene	98-82-8

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

2-phenoxyethyl methacrylate	10595-06-9
cumene	98-82-8

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TSCA All substances listed as active on the TSCA inventory

IECSC On the inventory, or in compliance with the inventory
Inventories Legend TSCA (USA), DSL (Canada), REACH(Europe), AIIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

SAFETY DATA SHEET


H.B. Fuller® TORQUE 62 TL

Version 1.3

Revision Date 12/09/2022

Further information

NFPA:



HMIS III:

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.