according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

SECTION 1. IDENTIFICATION

Telephone

Product name : ARALDITE® 2011 GB RESIN

Manufacturer or supplier's details

Company name of supplier : Huntsman Advanced Materials Americas LLC

Address : P.O. Box 4980

The Woodlands, TX 77387

United States of America (USA)
: Non-Emergency: (800) 257-5547

E-mail address : Global Product EHS AdMat@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

: Category 2

GHS label elements

Hazard pictograms :





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Precautionary statements

: Prevention:

P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

Storage:

Not available

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international

regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	70 - 90
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	9003-36-5	5 - 10
bisphenol A - epoxy resins, number average MW >700 - <1100	25068-38-6	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms

and effects, both acute and

delayed

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

Specific hazards during

media

Exercise caution when using a high volume water jet as it may

scatter and spread fire

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

firefighting

: Carbon oxides

Phenolics

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.

Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation

and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this

product.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Keep in properly labelled containers.

For in a supportible marketicle interest in the Co

Materials to avoid : For incompatible materials please refer to Section 10 of this

SDS.

Recommended storage

temperature

Further information on

storage stability

: 36 - 104 °F / 2 - 40 °C

Stable under normal conditions.

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

Version Revision Date: SDS Number: Date of last issue: 12/10/2020 2.1 12/28/2023 400001015903 Date of first issue: 09/13/2017

Print Date 10/21/2025

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : butyl-rubber Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)

Material : Nitrile rubber
Break through time : 10 - 480 min
Material : Neoprene gloves

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste
Colour : transparent
Odour : slight

Odour Threshold : No data is available on the product itself.

ca. 6 (68 °F / 20 °C) Concentration: 500 g/l

pΗ

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Melting point/freezing point : No data available

Boiling point : $> 392 \, ^{\circ}\text{F} / > 200 \, ^{\circ}\text{C}$

Flash point : 410 °F / 210 °C

Method: Pensky-Martens closed cup

500 °F / 260 °C

Method: Cleveland open cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Vapour pressure : < 0.001 hPa (68 °F / 20 °C)

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

Density : 1.15 g/cm3 (77 °F / 25 °C)

Solubility(ies)

Water solubility : practically insoluble (68 °F / 20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 392 °F / > 200 °C

Self-Accelerating

decomposition temperature

(SADT) Viscosity No data is available on the product itself.

Viscosity, dynamic : 30,000 - 50,000 mPa.s (77 °F / 25 °C)

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

Molecular weight : No data available

Particle size : No data is available on the product itself.

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

Version Revision Date: SDS Number: Date of last issue: 12/10/2020 12/28/2023 400001015903 Date of first issue: 09/13/2017 2.1

Print Date 10/21/2025

SECTION 10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability Stable under normal conditions. No hazards to be specially mentioned.

Possibility of hazardous

Conditions to avoid

reactions

None known.

Incompatible materials Strong acids Strong bases

Strong oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

LD50 (Rat, female): > 2,000 mg/kg Acute oral toxicity

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral

toxicity

Remarks: No mortality observed at this dose.

: LD50 (Rat, male and female): > 2,000 mg/kg Acute dermal toxicity

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Method: OECD Test Guideline 401

: LD50 (Rat, male and female): > 2,000 mg/kg Acute dermal toxicity

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

bisphenol A - epoxy resins, number average MW >700 - <1100:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral

toxicity

: LD50 (Rat, male and female): > 2,000 mg/kg Acute dermal toxicity

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Skin corrosion/irritation

Causes skin irritation.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rabbit Exposure time : 4 h

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Irritating to skin.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Irritating to skin.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Method : OECD Test Guideline 404

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rabbit

Result : Irritating to eyes. Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species : Rabbit
Result : Eye irritation

Method : OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin Species : Mouse

Method : OECD Test Guideline 429

Result : The product is a skin sensitiser, sub-category 1B.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Exposure routes : Skin Species : Mouse

Method : OECD Test Guideline 429

Result : May cause sensitisation by skin contact.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Exposure routes : Skin Species : Guinea pig

Method : OECD Test Guideline 406

Result : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: without metabolic activation

Result: positive

Test Type: reverse mutation assay
Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse

mutation assay) Result: negative

Genotoxicity in vivo : Test Type: in vivo assay

Species: Mouse (male)

Cell type: Germ Application Route: Oral Dose: 3333, 10000 mg/kg

Result: negative

Test Type: gene mutation test

Species: Rat (male) Cell type: Somatic Application Route: Oral

Dose: 50,250,500,1000 mg/kg bw/day Method: OECD Test Guideline 488

Result: negative

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

Version Revision Date: SDS Number: Date of last issue: 12/10/2020 2.1 12/28/2023 400001015903 Date of first issue: 09/13/2017

Print Date 10/21/2025

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive

Genotoxicity in vivo : Cell type: Somatic

Application Route: Oral Exposure time: 48 h Dose: 2000 mg/kg

Method: OECD Test Guideline 474

Result: negative

Cell type: Somatic Application Route: Oral Dose: 2000 mg/kg

Method: OECD Test Guideline 486

Result: negative

bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: Positive results were obtained in some in vitro tests.

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Cell type: Germ

Application Route: Oral

Method: OECD Test Guideline 478

Result: negative

Cell type: Somatic Application Route: Oral Dose: 0 - 5000 mg/kg Method: OPPTS 870.5395

Result: negative

Carcinogenicity

Not classified due to lack of data.

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rat, male Application Route : Oral

Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week
NOAEL : 15 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Mouse, male
Application Route : Dermal
Exposure time : 24 month(s)

Dose : 0, 0.1, 10, 100 mg/kg bw/day

Frequency of Treatment : 3 days/week

NOEL : 0.1 mg/kg body weight
Method : OECD Test Guideline 453

Result : negative Target Organs : Digestive organs

Species : Rat, female
Application Route : Dermal
Exposure time : 24 month(s)

Dose : 0.1, 100, 1000 mg/kg bw/day

Frequency of Treatment : 5 days/week

NOEL : 100 mg/kg body weight
Method : OECD Test Guideline 453

Result : negative

Species : Rat, female
Application Route : Oral
Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week

NOAEL : 100 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

Species : Rat, females

Application Route : Oral Exposure time : 24 month(s)

Dose : 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment : 7 days/week
NOEL : 2 mg/kg bw/day

Method : OECD Test Guideline 453

Result : negative

Target Organs : Digestive organs

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species : Rat, male and female

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Application Route : Oral

Exposure time : 24 month(s)

Dose : 15 mg/kg

Frequency of Treatment : 7 daily

Method : OECD Test Guideline 453

Result : negative

IARC No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified due to lack of data.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 180, 540 or 750 milligram per kilogram

Duration of Single Treatment: 238 d Frequency of Treatment: 1 daily

General Toxicity - Parent: NOEL: 540 mg/kg body weight General Toxicity F1: NOEL: 750 mg/kg body weight

Symptoms: No adverse effects Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

Effects on foetal : Species: Rabbit, female development : Application Route: Dermal

Dose: 0, 30, 100 or 300 milligram per kilogram

Duration of Single Treatment: 28 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 300 mg/kg body weight

Method: Other guidelines Result: No teratogenic effects

Test Type: Pre-natal Species: Rabbit, female Application Route: Oral

Dose: 0, 20, 60 or 180 milligram per kilogram

Duration of Single Treatment: 13 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 60 mg/kg body weight Developmental Toxicity: NOAEL: 180 mg/kg body weight

Method: OECD Test Guideline 414

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Result: No teratogenic effects

Test Type: Pre-natal Species: Rat, female Application Route: Oral

Dose: 0, 60, 180 and 540 milligram per kilogram

Duration of Single Treatment: 10 d Frequency of Treatment: 1 daily

General Toxicity Maternal: NOAEL: 180 mg/kg body weight Developmental Toxicity: NOAEL: > 540 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Effects on fertility : Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

Effects on foetal : Species: Rabbit, female development : Application Route: Dermal

General Toxicity Maternal: NOAEL: 30 mg/kg body weight

Result: No teratogenic effects

bisphenol A - epoxy resins, number average MW >700 - <1100:

Effects on fertility : Species: Rat, male and female

Application Route: Oral

General Toxicity - Parent: NOEL: 750 mg/kg body weight General Toxicity F1: NOEL: 750 mg/kg body weight

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

Effects on foetal development

Species: Rabbit, female Application Route: Dermal

General Toxicity Maternal: NOAEL: 30 mg/kg body weight

Method: Other guidelines Result: No teratogenic effects

Species: Rabbit, female Application Route: Oral

General Toxicity Maternal: NOAEL: 60 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Species: Rat, female Application Route: Oral

General Toxicity Maternal: NOAEL: 180 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

Version Revision Date: SDS Number: Date of last issue: 12/10/2020 2.1 12/28/2023 400001015903 Date of first issue: 09/13/2017

Print Date 10/21/2025

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rat, male and female

NOAEL : 50 mg/kg
Application Route : oral (gavage)
Exposure time : 14 Weeks

Number of exposures : 7 d

Dose : 0, 50, 250, 1000 mg/kg/day Method : OECD Test Guideline 408

Species : Rat, male and female

NOAEL : >= 10 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks

Number of exposures : 5 d

Dose : 0, 10, 100, 1000 mg/kg/day Method : OECD Test Guideline 411

Species: Mouse, maleNOAEL: 100 mg/kgApplication Route: Skin contactExposure time: 13 Weeks

Number of exposures : 3 d

Dose : 0, 1, 10, 100 mg/kg/day Method : OECD Test Guideline 411

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species : Rat, male and female

NOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Number of exposures : 7 d

Method : Subchronic toxicity

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species : Rat, male and female

NOAEL : 50 mg/kg Application Route : Ingestion Exposure time : 14 Weeks

Number of exposures : 7 d

Method : Subchronic toxicity

Species : Rat, male and female

NOEL : 10 mg/kg
Application Route : Skin contact

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Exposure time : 13 Weeks

Number of exposures : 5 d

Method : Subchronic toxicity

Aspiration toxicity

Not classified due to lack of data.

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1.8 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50: 11 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: EPA-660/3-75-009

NOEC: 4.2 mg/l Exposure time: 72 h Test Type: static test

Test substance: Fresh water Method: EPA-660/3-75-009

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 0.3 mg/l

Exposure time: 21 d
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Exposure time: 3 h
Test Type: static test

Test substance: Fresh water

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Toxicity to fish : LC50 (Fish): 2.54 mg/l

Exposure time: 96 h

Method: Calculation method

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 2.55 mg/l

Exposure time: 48 h

Method: Calculation method

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): 1.8 mg/l

Exposure time: 72 h Test Type: static test

Test substance: Fresh water

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 0.3 mg/l

Exposure time: 21 d
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l

Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

bisphenol A - epoxy resins, number average MW >700 - <1100:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EgC50 (Selenastrum capricornutum (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : aerobic

Inoculum: activated sludge, non-adapted

Concentration: 20 mg/l

Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C) pH: 4

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C) pH: 9

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C) pH: 7

Method: OECD Test Guideline 111

Remarks: Fresh water

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Biodegradability : Inoculum: activated sludge

Concentration: 3 mg/l Result: Not biodegradable Biodegradation: ca. 0 % Exposure time: 28 d

Method: Directive 67/548/EEC Annex V, C.4.E.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Biodegradability : aerobic

Inoculum: Sewage (STP effluent)

Concentration: 20 mg/l Result: Not biodegradable Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C) pH: 4

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C) pH: 9

Method: OECD Test Guideline 111

Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C) pH: 7

Method: OECD Test Guideline 111

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Remarks: Fresh water

Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31

Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 3.242 (77 °F / 25 °C)

octanol/water pH: 7.1

Method: OECD Test Guideline 117

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 150 Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 2.7 - 3.6

octanol/water Method: OECD Test Guideline 117

bisphenol A - epoxy resins, number average MW >700 - <1100:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 31 Remarks: Does not bioaccumulate.

Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among : Koc: 445

environmental compartments

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Distribution among : Koc: 4460

environmental compartments Method: OECD Test Guideline 121

bisphenol A - epoxy resins, number average MW >700 - <1100:

Distribution among : Koc: 445

environmental compartments

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

Version Revision Date: SDS Number: Date of last issue: 12/10/2020 2.1 12/28/2023 400001015903 Date of first issue: 09/13/2017

Print Date 10/21/2025

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues Dispose of contents and container in accordance with all local.

regional, national and international regulations.

Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

Class 9 Ш Packing group Labels 9 Environmentally hazardous yes

IATA-DGR

UN/ID No. UN 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

Class 9 Packing group Ш

Labels Miscellaneous

Packing instruction (cargo 964

aircraft)

Packing instruction 964

(passenger aircraft)

Environmentally hazardous

IMDG-Code

UN number UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

yes

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

Class 9 Ш Packing group

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY

RESIN)

Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : yes

Remarks : Shipment by ground under DOT is non-regulated; however it

may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

Remarks : 49CFR: no dangerous good in non-bulk packaging

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 311/312 Hazards : Respiratory or skin sensitisation

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP) >=0.1%, as defined by the U.S. Clean Air Act Section 112 (40 CFR 61

California Prop. 65

WARNING: This product can expose you to chemicals including 4,4'-isopropylidenediphenol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/10/2020

 2.1
 12/28/2023
 400001015903
 Date of first issue: 09/13/2017

Print Date 10/21/2025

AllC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.


US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Revision Date : 12/28/2023

according to the OSHA Hazard Communication Standard





ARALDITE® 2011 GB RESIN

Version Revision Date: SDS Number: Date of last issue: 12/10/2020 2.1 12/28/2023 400001015903 Date of first issue: 09/13/2017

Print Date 10/21/2025

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY. EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.



DISTRIBUTED BY WWW.Freeman Mg. & Supply Co. E® 2011 GB HARDENER

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

SECTION 1. IDENTIFICATION

Product name : ARALDITE® 2011 GB HARDENER

Manufacturer or supplier's details

Company name of supplier

: Huntsman Advanced Materials Americas LLC

Address

P.O. Box 4980 The Woodlands,

TX 77387

United States of America (USA) Non-Emergency: (800) 257-5547

Telephone

E-mail address of person responsible for the SDS

: Global Product EHS AdMat@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Hardener

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion : Category 1C

Serious eye damage : Category 1

Skin sensitisation : Category 1

Short-term (acute) aquatic

hazard

: Category 3

GHS label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H402 Harmful to aquatic life.

Precautionary statements : **Prevention:**

P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of



DISTRIBUTED BY WWW.Freeman Mg. & Supply Co. E® 2011 GB HARDENER

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON

CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international

regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
N'-(3-aminopropyl)-N,N-dimethylpropane-	10563-29-8	5 - 9.65
1,3-diamine		
trientine	112-24-3	2.5 - 3
N-[2-(1-piperazinyl)ethyl]ethylenediamine	24028-46-4	0.1 - 1
N,N-bis(2-aminoethyl)ethylenediamine	4097-89-6	0.25 - 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.



DISTRIBUTED BY Freeman Mig. 8 Supply Co. E® 2011 GB HARDENER

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

Get medical attention if symptoms occur.

In case of skin contact : Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with

difficulty.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Notes to physician

None known.

: Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Ammonia

Carbon oxides Nitrogen oxides (NOx)

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment : We

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.

Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.



DISTRIBUTED BY Freeman Mg a Supply Co. E® 2011 GB HARDENER

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage :

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Keep in properly labelled containers.

Materials to avoid : For incompatible materials please refer to Section 10 of this

SDS.

Recommended storage

temperature

: 36 - 104 °F / 2 - 40 °C

Further information on

storage stability

: No decomposition if stored and applied as directed.

Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Triethylenetetramine	112-24-3	TWA	1 ppm	US WEEL

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and



DISTRIBUTE BY WWW.FreemanSupply.co. E® 2011 GB HARDENER

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled

release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : butyl-rubber Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)

Material : Nitrile rubber Break through time : 10 - 480 min

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : light yellow
Odour : slight

Odour Threshold : No data is available on the product itself.

pH : No data is available on the product itself.

Melting point : No data available

Boiling point : $> 392 \, ^{\circ}\text{F} / > 200 \, ^{\circ}\text{C}$

Flash point : 230 °F / 110 °C

Method: Pensky-Martens closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Vapour pressure : 0.04 hPa (68 °F / 20 °C)



DISTRIBUTED BY FREEMAN (M.). & Supply Co. E® 2011 GB HARDENER www.Freeman Supply.com

Revision Date: SDS Number: Date of last issue: 11/20/2020 Version 400001015904 1.2 12/10/2020 Date of first issue: 09/19/2017

Print Date 10/21/2025

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

: 0.95 g/cm3 (77 °F / 25 °C) Density

Solubility(ies)

: practically insoluble (68 °F / 20 °C) Water solubility

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

: No data is available on the product itself. Auto-ignition temperature

: > 392 °F / > 200 °C Decomposition temperature

Self-Accelerating

decomposition temperature

(SADT) Viscosity

Viscosity, dynamic

: 20,000 - 35,000 mPa.s (77 °F / 25 °C)

No data is available on the product itself.

Explosive properties No data is available on the product itself.

Oxidizing properties No data is available on the product itself.

Molecular weight No data available

Particle size No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

No dangerous reaction known under conditions of normal use. Reactivity

Stable under normal conditions.

Chemical stability No hazards to be specially mentioned.

Possibility of hazardous

reactions

Conditions to avoid None known. Incompatible materials None known.

Hazardous decomposition

products

ammonia, anhydrous

Aldehydes

Nitrogen oxides (NOx) carbon monoxide carbon dioxide Ketones

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : No data is available on the product itself.

exposure

Acute toxicity



FISHBLUTED BY FOR THE PROPERTY OF THE PROPERTY

Revision Date: SDS Number: Date of last issue: 11/20/2020 Version 400001015904 1.2 12/10/2020 Date of first issue: 09/19/2017

Print Date 10/21/2025

Acute oral toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

: No data available Acute inhalation toxicity

Acute dermal toxicity -: Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method Product

Acute toxicity (other routes of : No data available

administration)

Skin corrosion/irritation

Product:

Result: Corrosive after 1 to 4 hours of exposure

Serious eye damage/eye irritation

Product:

Species: Rabbit Result: Corrosive Assessment: Corrosive

Respiratory or skin sensitisation

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Test Type: Maximisation Test

Exposure routes: Skin Species: Guinea pig

Method: OECD Test Guideline 406

Result: The product is a skin sensitiser, sub-category 1B.

GLP: yes

trientine:

Exposure routes: Skin Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

Exposure routes: Skin Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

N-[2-(1-piperazinyl)ethyl]ethylenediamine: Result: May cause sensitisation by skin contact.

No data available Assessment:

Germ cell mutagenicity

Components:



JETRIBUTE STRIBUTE ST

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Genotoxicity in vitro : Test Type: in vitro assay

Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

GLP: yes

Test Type: reverse mutation assay Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative GLP: yes

Test Type: reverse mutation assay

Test system: Salmonella tryphimurium and E. coli

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

trientine:

Genotoxicity in vitro : Concentration: 0 - 200 µg/L

Metabolic activation: negative Method: OECD Test Guideline 482

Result: negative

Components:

trientine:

Genotoxicity in vivo : Application Route: Intraperitoneal injection

Dose: 0 - 600 mg/kg

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity-

Assessment

: No data available

Carcinogenicity

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Species: Mouse, male Application Route: Dermal Exposure time: 20 month(s) Dose: 1.25/56.3 mg/animal Frequency of Treatment: 3 daily NOAEL: >= 56.3 mg/kg body weight

Result: negative



DISTRIBUTED BY WWW.Freeman Mg. & Supply Co. E® 2011 GB HARDENER

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

Remarks: Information given is based on data obtained from similar substances.

trientine:

Species: Mouse, male Application Route: Dermal

Dose: 42 mg/kg

Frequency of Treatment: 3 days/week Method: OECD Test Guideline 451

Result: negative

Species: Mouse, male Application Route: Dermal Exposure time: 104 weeks

Dose: 16.8 mg/kg

Frequency of Treatment: 3 days/week Method: OECD Test Guideline 451

Carcinogenicity - : No data available

Assessment

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Effects on fertility : Test Type: Combined Repeated Dose Toxicity Study with the

Reproduction / Developmental Toxicity Screening Test

Species: Rat, male and female

Application Route: Oral

Dose: 5, 15 and 50 mg/kg bw/d

General Toxicity - Parent: No observed adverse effect level:

15 mg/kg body weight

General Toxicity F1: No observed adverse effect level: 15

mg/kg body weight

Method: OECD Test Guideline 422

Result: Animal testing did not show any effects on fertility.

GLP: yes

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Effects on foetal : Species: Rat, male and female



JIER DISTRIBUTED BY FREEMAN MIS & SUpply Co. E® 2011 GB HARDENER

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

development Application Route: Oral

Dose: 5, 15 and 50 mg/kg bw/d

General Toxicity Maternal: No observed adverse effect level:

15 mg/kg body weight

Method: OECD Test Guideline 422

Result: Not classified

GLP: yes

trientine:

Species: Rat

Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

> 750 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Species: Rabbit

Application Route: Dermal

General Toxicity Maternal: No observed adverse effect level:

125 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Reproductive toxicity - : No evidence of adverse effects on sexual function and fertility,

Assessment or on development, based on animal experiments.

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Species: Rat, male and female

NOEC: 550 mg/m3

Application Route: Inhalation Test atmosphere: vapour Exposure time: 3 w 6 h Number of exposures: 5 d/w

Dose: 550 mg/m3

Method: Subchronic toxicity

Remarks: Based on data from similar materials

Species: Mouse, male NOAEL: >= 56.3 mg/kg/d Application Route: Skin contact Number of exposures: 3 d Method: Chronic toxicity

Remarks: Based on data from similar materials



DISTRIBUTED BY Freeman Mrg. 8. Supply Co. E® 2011 GB HARDENER

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

Species: Rat, male and female

NOAEL: 1000 ppm Application Route: Oral Exposure time: 90 d

Method: OECD Test Guideline 408

Remarks: Based on data from similar materials

trientine:

Species: Rat, male and female

NOAEL: 50 mg/kg/d

Application Route: Ingestion Exposure time: 26 Weeks Number of exposures: 7 d Method: Subchronic toxicity

Repeated dose toxicity -

: No data available

Assessment

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available





Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l

Exposure time: 96 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 203

GLP: yes

trientine:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 330 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: Fish Acute Toxicity Test

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 9.2 mg/l

aquatic invertebrates Exposure time: 48 h

Test Type: static test Analytical monitoring: no Test substance: Fresh water Method: OECD Test Guideline 202

GLP: yes

trientine:

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 31.1 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water

Method: Directive 67/548/EEC, Annex V, C.2.

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Toxicity to algae/aquatic : ErC50 (Selenastrum capricornutum (green algae)): 21 mg/l

plants

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

NOEC (Selenastrum capricornutum (green algae)): 5.7 mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201



DISTRIBUTE BY WWW.FreemanSupply.co. E® 2011 GB HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11/20/2020

 1.2
 12/10/2020
 400001015904
 Date of first issue: 09/19/2017

Print Date 10/21/2025

GLP: yes

trientine:

Toxicity to algae/aquatic

plants

: ErC50 (Selenastrum capricornutum (green algae)): 20 mg/l

Exposure time: 72 h

Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 201

M-Factor (Acute aquatic

toxicity)

: No data available

Toxicity to fish (Chronic

toxicity)

: No data available

Components:

trientine:

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: EC10 (Daphnia magna (Water flea)): 1.9 mg/l

Exposure time: 21 d
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 202

M-Factor (Chronic aquatic

toxicity)

: No data available

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Toxicity to microorganisms : E

: EC50 (Pseudomonas putida): 181 mg/l

Exposure time: 16 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: DIN 38 412 Part 8

GLP: no

trientine:

Toxicity to microorganisms : EC50 (activated sludge): 800 mg/l

Exposure time: 0.5 h Test Type: static test

Test substance: Fresh water

Toxicity to soil dwelling

organisms

: No data available

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial

organisms

: No data available

Ecotoxicology Assessment

Acute aquatic toxicity : No data available



Julie Freeman Mg. & Supply Co. E® 2011 GB HARDENER

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

Components:

N,N-bis(2-aminoethyl)ethylenediamine:

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Toxicity Data on Soil : No data available

Other organisms relevant to

the environment

: No data available

Persistence and degradability

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine: Biodegradability: Test Type: aerobic

Result: Readily biodegradable.

Biodegradation: 100 % (Dissolved organic carbon (DOC))

Exposure time: 28 d

Method: OECD Test Guideline 301A

GLP: yes

trientine:

Biodegradability : Inoculum: activated sludge

Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 162 d

Method: OECD Test Guideline 301D

Inoculum: activated sludge Result: Not readily biodegradable.

Biodegradation: 20 % Exposure time: 84 d

Method: Inherent Biodegradability: Modified SCAS Test

Biochemical Oxygen

Demand (BOD)

: No data available

Chemical Oxygen Demand

(COD)

: No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon

(DOC)

: No data available

Physico-chemical

removability

: No data available

Stability in water : No data available

Photodegradation : No data available

Impact on Sewage : No data available



DISTRIBUTE BY WWW.FreemanSupply.co. E® 2011 GB HARDENER

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

Treatment

Bioaccumulative potential

Bioaccumulation : No data available

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Partition coefficient: n- : log Pow: -0.56 (77 °F / 25 °C)

octanol/water pH: 11.6

Method: OECD Test Guideline 107

trientine:

Partition coefficient: n- : log Pow: -2.65 (68 °F / 20 °C) octanol/water : Method: OECD Test Guideline 117

Mobility in soil

Mobility : No data available

Components:

trientine:

Distribution among : Koc: 1584.9 - 5012

environmental compartments Method: OECD Test Guideline 106

Stability in soil : No data available

Other adverse effects

Environmental fate and

pathways

: No data available

Results of PBT and vPvB

assessment

: No data available

Endocrine disrupting

potential

: No data available

Adsorbed organic bound

halogens (AOX)

: No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

Additional ecological information - Product

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.

Global warming potential : No data available



DISTRIBUTED BY WWW.FreemanSupply.co. E® 2011 GB HARDENER

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

(GWP)

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

national regulations.

Dispose of contents/ container to an approved waste disposal

plant.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA

UN/ID No. : UN 2735

Proper shipping name : Polyamines, liquid, corrosive, n.o.s.

: 856

(DIMETHYL DIPROPYL TRIAMINE)

Class : 8 Packing group : III

Labels : Corrosive

Packing instruction (cargo

aircraft)

Packing instruction : 852

(passenger aircraft)

IMDG

UN number : UN 2735

Proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(DIMETHYL DIPROPYL TRIAMINE)

Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

DOT Classification



Julie Freeman Mg. & Supply Co. E® 2011 GB HARDENER

Version Revision Date: SDS Number: Date of last issue: 11/20/2020 1.2 12/10/2020 400001015904 Date of first issue: 09/19/2017

Print Date 10/21/2025

UN/ID/NA number : UN 2735

Proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(DIMETHYL DIPROPYL TRIAMINE)

Class : 8
Packing group : III

Labels : CORROSIVE

ERG Code : 153 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitisation

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components listed in the

Canadian NDSL.

AIIC : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory





DISTRIBUTED BY FREEMAN (Mg. 8 Supply Co. E® 2011 GB HARDENER www.Freeman Supply Com

Revision Date: SDS Number: Date of last issue: 11/20/2020 Version 400001015904 1.2 12/10/2020 Date of first issue: 09/19/2017

Print Date 10/21/2025

TSCA : All substances listed as active on the TSCA inventory

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.


US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Revision Date 12/10/2020

US WEEL USA. Workplace Environmental Exposure Levels (WEEL)

US WEEL / TWA 8-hr TWA

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.



DISTRIBUTED BY Freeman Mig. & Supply Co. E® 2011 GB HARDENER

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11/20/2020

 1.2
 12/10/2020
 400001015904
 Date of first issue: 09/19/2017

Print Date 10/21/2025

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.